

DOOR SCHEDULE - LEVEL 1. Table with columns: DOOR No., WIDTH, HEIGHT, DOOR PANEL, DOOR MATERIAL, DOOR FRAME, HARDWARE, FIRE RATING, COMMENTS/NOTES. Includes rows for 100.1A through 100.25B and C101 through C102.

DOOR SCHEDULE - LEVEL 2. Table with columns: DOOR No., WIDTH, HEIGHT, DOOR PANEL, DOOR MATERIAL, DOOR FRAME, HARDWARE, FIRE RATING, COMMENTS/NOTES. Includes rows for CH2 through ST2.2.

DOOR SCHEDULE - LEVEL 3. Table with columns: DOOR No., WIDTH, HEIGHT, DOOR PANEL, DOOR MATERIAL, DOOR FRAME, HARDWARE, FIRE RATING, COMMENTS/NOTES. Includes rows for CH3 through ST2.3.

DOOR SCHEDULE - LEVEL 4. Table with columns: DOOR No., WIDTH, HEIGHT, DOOR PANEL, DOOR MATERIAL, DOOR FRAME, HARDWARE, FIRE RATING, COMMENTS/NOTES. Includes rows for CH4 through ST2.4.

DOOR SCHEDULE - GUESTROOM. Table with columns: DOOR No., WIDTH, HEIGHT, DOOR PANEL, DOOR MATERIAL, DOOR FRAME, HARDWARE, FIRE RATING, STC RATING, COMMENTS/NOTES. Includes rows for GR-B through GR-S.

DOOR GENERAL NOTES:

- 1. REFER TO SPECIFICATIONS FOR DOOR HARDWARE TYPES
2. HAND-ACTIVATED DOOR OPENING HARDWARE SHALL BE CENTERED BETWEEN 34" AND 48" A.F.F. U.N.O.
3. DOOR CLOSER SWEEP PERIOD SHALL BE ADJUSTED SO THAT FROM THE OPEN POSITION OF 70 DEGREES, THE DOOR WILL TAKE AT LEAST 3 SECONDS TO MOVE TO A POINT 3 INCHES FROM THE LATCH, MEASURED TO THE LEADING EDGE OF THE DOOR.
4. THE MAXIMUM DOOR OPENING FORCE FOR PUSHING OR PULLING INTERIOR DOORS SHALL BE 5 POUNDS PER FOOT.
5. ALL EXTERIOR DOORS ARE TO OPEN OUTWARD AND ARE TO BE SELF CLOSING.
6. CLOSERS SHALL BE MOUNTED ON THE NON-PUBLIC SIDE OF DOORS WHERE POSSIBLE.
9. DOOR FRAMES TO BE EQUIPPED W/ SILENCER BUTTONS UNLESS GASKETS ARE SPECIFIED.
10. ALL EXTERIOR H.M. DOORS AND FRAMES SHALL BE INSULATED.
11. FILL ALL VOIDS IN THRESHOLDS W/ SEALANT TO MATCH GROUT.
12. SEE FFE ITEMS FOR SPECIALTY DOORS EXP-216
13. WHERE COAT HOOKS ARE INDICATED IN RESTROOMS AND BATHROOMS, LOCATE COAT HOOK CENTERED ON DOOR ON THE RESTROOMS AND BATHROOMS SIDE OF DOORS.

DOOR OPENING FINISHES SCHEDULE:

ALL INTERIOR DOOR ARE TO BE SOLID CORE WOOD DOORS EXP-PL1 FINISHED ON ALL SIDES.
ALL INTERIOR HOLLOW METAL DOORS AND FRAMES ARE TO BE EXP-PT3 FINISHED.
ALL EXTERIOR SOLID CORE HOLLOW METAL DOORS AND FRAMES ARE TO BE EXP-PT3 FINISHED INSIDE, OUTSIDE SHALL BE PAINTED TO MATCH SURROUNDINGS WALL MATERIAL.
ALL ALUMINUM DOORS AND FRAMES ARE TO BE CLEAR ANODIZED ALUMINUM FINISHED TO MATCH THE WINDOWS.

ABBREVIATIONS USED IN THE DOOR OPENING SCHEDULES:

- AL = ALUMINUM
ADB = AUTOMATIC DOOR BOTTOM
ADO = AUTOMATIC DOOR OPERATOR
ASD = AUTOMATIC SLIDING DOOR
BLT = BORROWED LIGHT
CR = CARD READER FOR ADO AND ELECTRONIC LOCKS
DE = DELAYED EGRESS OR DOUBLE EGRESS
DF = DOOR FRAME
DP = DOOR PANEL
DR = DOOR
ELEV NO. = FRAME ELEVATION NUMBER
GL = GLASS TYPE, SEE SPECIFICATION FOR TYPES.
HO = ELECTRO-MAGNETIC HOLD-OPEN DEVICE
HM = HOLLOW METAL
HWG = HARDWARE GROUP
MAG LOCK = MAGNETIC LOCK
MIN = DOOR RATING IN MINUTES.
NO. = NUMBER OR NUMBERS
NT = NOTE REFERENCE WITH NUMBER, SEE SPECIFIC NOTES
OA = OVERALL
OH = OVERHEAD STOP TYPES
PP = PUSH PLATES FOR ADO
REV NO. = REVISION NUMBER CORRESPONDING TO THE DOCUMENTS BEING ISSUED
WD = WOOD DOOR, SEE ROOM FINISHES SCHEDULE FOR TYPES.
WS = WALL STOP

DOOR HARDWARE GROUPS AND FINISHES:

Hardware finishes and base metals shall be listed below, unless otherwise indicated.
1. Exterior Hinges US32D on stainless steel.
2. Interior Hinges US26D on steel.
3. Flush Bolts US26D on brass or bronze.
4. Locks US32D on stainless steel.
5. Exit Devices - 33 Series Sprayed Aluminum.
6. Exit Devices - 99 Series Sprayed Aluminum.
7. Pulls, Push Plates/Bars US32D on stainless steel.
8. Coordinators USP on steel.
9. Closers Sprayed aluminum.
10. Overhead Stops/Holders US26D on brass or bronze.
11. Kickplate US32D on stainless steel.
12. Door Edge Guards US32D on stainless steel.
13. Armor Plates US32D on stainless steel.
14. Stops, Holders US26D on brass or bronze.
15. Thresholds Mill on aluminum.
16. Miscellaneous US26D on brass or bronze.
Hardware on aluminum doors shall match finish of doors and frame.
1. US32 and US32D Solid 18-8 chromium-nickel, 300 Series, "Austenitic", non-magnetic.
a. Straight chrome-ions (magnets) are not acceptable, except as hinge pins.
b. Items showing magnetic properties will be rejected.
c. For items not available in US32 or US32D provide US26 or US26D.

Door Hardware Groups:

ASD - Automatic sliding entrance doors.
Hardware provided by door manufacturer, provide cylinder lock for integration into exterior door.
BEAM overhead concealed SL500 with ECODOOR seals and magnetic catches.
Comments: .

C - Linen Chute Room Door (RFID Access)

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Card Reader: Electronic latchset for RFID card reader entry.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Plates: SST 10" high kickplate both sides of door.
Gaskets: Smoke, 1 set for single leaf door.
Comments: .

Double Acting Restroom Connecting Pair of Single Swing Doors.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Parallel arm closer with appropriate mounting and cover. 2 Req'd.
Gaskets: Smoke, 1 set for each single leaf door. Set for acoustic control. Smoke gaskets not to be used on exterior doors.
Accessories: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion Threshold. Solid surface.
Card Reader: Electronic latchset for RFID card reader entry.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Plates: SST 10" high kickplate both sides of door.
Gaskets: Fire, 1 set for single leaf door.
Comments: Hardware to be coordinated w/ entry door hardware

E - Exterior exit door in alum. frame or storefront (RFID Access)

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Power transfer type hinges.
Lockset/Function: Classroom Function ANSI F84, keyed on exterior side.
Exit Device/Security/Card Reader: Rim type Exit device. Electronic latchset for wall mounted weather proof RFID card reader entry.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion Threshold. Aluminum 5-inch saddle, 1/2-inch high.
Overhead Drip: 2-1/2-inch projection by full width of frame with clear anodized aluminum finish.
Comments: Exception, Pool Room exterior door does not require exterior guest access with electronic latchset for RFID card reader entry.

EC - Electrical Closet Double Door

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Closer: Parallel arm closer with appropriate mounting and cover. 2 Req'd.
Stop: Overhead Stop, 2 Req'd.
Gaskets: Smoke, 2 sets for double leaf door. Set for acoustic control.
Comments: .

GB - Guestroom bathroom hinged door.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Privacy, Bathroom or Bedroom Function ANSI F76, privacy push button on interior side.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd. Spring hinges may be utilized in lieu of closer.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for double gasket system for single leaf door.
Accessories: Provide "L" type door guard which does not allow the door to be propped open.
Peep hole viewer and cover, 1 each per door. ADA rooms to receive (2) peep hole viewers and covers @ 5'-0" AFF and at 3'-7" AFF.
Bottom Seal: Door bottom Seal.
Threshold: Pemko floor plate 196, mill finish aluminum.
Comments: .

ME - Mech/Elec interior door, PANIC HARDWARE REQ.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Exit Device: Rim type Exit device.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Plates: SST 10" high kickplate both sides of door.
Gaskets: Fire, 1 set for single leaf door.
Comments: .

O - Office door.
Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Office Function ANSI F81, keyed on exterior side with privacy turn button on interior side.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic or smoke control.
Accessories: coat hook, 1 per door.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Comments: .

P1 - Public access Pool and Fitness room doors (RFID Access)

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Classroom Function ANSI F84, keyed on exterior side with interior free egress. Electronic latch retraction via wall mounted exterior card reader.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Comments: PANIC HARDWARE REQUIRED AT POOL DOOR

P2 - Public access Pool Vestibule Door, PANIC HARDWARE REQUIRED

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Passage Function ANSI F75, free access both sides.
Exit Device: Rim type Exit device.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic or smoke control.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Comments: .

P3 - Conference room hinged door, PANIC HARDWARE REQUIRED

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Classroom function ANSI F84, keyed on exterior side with interior free egress.
Exit Device: Rim type Exit device.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic or smoke control.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Accessories: (2) Reverse peep hole viewers and cover @ 5'-0" AFF and at 3'-7" AFF.
Comments: .

S1 - Service/Housekeeping door (RFID Access)

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Card Reader: Electronic latchset for RFID card reader entry for housekeeping and main laundry rooms.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic or smoke control.
Comments: .

S2 - Staff Access door.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Storeroom or Service Function ANSI F86, keyed on exterior side, exterior lever is rigid at all times.
Closer: Parallel or regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic control.
Comments: .

S3 - Staff Access door, passage

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Passage Function ANSI F75, free access both sides.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic control.
Comments: .

SDB - Guestroom Bathroom sliding door.

Track: Pemko sliding 200 series track, wheel assembly with cushioned stops, bottom guide and fascia.
Plates: SST 30" long vertical door pulls, 2 Req'd.
Comments: Provide privacy lock.

SDG - Great Room sliding door, EXP-216.

Track: Barn Door Hardware - RLP black cast iron flat track top mount wheel assembly with cushioned stops and bottom guide.
Pulls: Dark bronze 24" long vertical door pulls, 2 Req'd.
Provide locking mechanism.

ST - Stair entry door.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Passage Function ANSI F75, free access both sides.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Fire, 1 set for single leaf door.
Comments: .

STE - Stair exterior exit door, PANIC HARDWARE REQUIRED

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Classroom ANSI F84, keyed on exterior side.
Exit Device: Rim type Exit device.
Closer: Parallel arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Overhead Stop, 1 Req'd.
Gaskets: Smoke, 1 set for double gasket system for single leaf door.
Accessories: Provide "L" type door guard which does not allow the door to be propped open.
Peep hole viewer and cover, 1 each per door. ADA rooms to receive (2) peep hole viewers and covers @ 5'-0" AFF and at 3'-7" AFF.
Bottom Seal: Door bottom Seal.
Threshold: Pemko floor plate 196, mill finish aluminum.
Comments: .

SW - Swinging Bommer Style Door

Hinges: Bommer style, Qty 3 per leaf.
Lockset/Function: None, free access both sides.
Stop: Wall Stop, 2 Req'd.
Plates: SST 10" high kickplate both sides of door, 4' x 16" SST pushplate both sides of door.
Comments: .

WC1 - Single User Restroom door.

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Dormitory or Motel Function ANSI F82, privacy push button on inside side. Inside button locks outside lever. Turning inside lever or exterior emergency key releases inside button and unlocks lockset. Provide occupancy indicator.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic or smoke control.
Accessories: coat hook, 1 per door.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Threshold: See I.D. dwgs.
Comments: .

WC2 - Public Restroom door, passage

Hinges: Construction, type and quantity as specified. Qty 3 per leaf 4-1/2 by 4-1/2-inches.
Lockset/Function: Passage Function ANSI F75, free access both sides.
Closer: Regular arm closer with appropriate mounting and cover. 1 Req'd.
Stop: Wall Stop, 1 Req'd.
Gaskets: Smoke, 1 set for single leaf door. Set for acoustic control.
Door sweep: Neoprene with 1/2-inch sweep at door bottom with 1 1/4-inch aluminum extrusion.
Threshold: See I.D. dwgs.
Comments: .

MEISTER COX ARCHITECTS. INFO@MEISTERCOX.COM. PHONE: 610-375-1331 FAX: 610-375-4655. 1522 PENN AVENUE WYOMISSING, PA 19610 WWW.MEISTERCOX.COM

DOOR SCHEDULE. HOLIDAY INN EXPRESS & SUITES. INTERSECTION OF HAYNES PLACE & LAMM RD. WILSON, NC 27893

DOOR SCHEDULE. HOLIDAY INN EXPRESS & SUITES. INTERSECTION OF HAYNES PLACE & LAMM RD. WILSON, NC 27893

STATUS: BIDDING. PROJ. DATE: 06-07-19. PROJ. NO: 18-176. PRINTED: 6/7/2019 7:12:18 PM. DRAWN BY: RFF. CHECKED BY: TGC. SHEET NO: A710. SCALE:

