



ADA SHEET BASED ON ANSI A117.1-2009; REVISED APRIL 2016

**NOTES:**

- THIS SHEET IS NOT PROJECT SPECIFIC. APPLY THE GUIDELINES SHOWN TO THE AREAS INCLUDED IN THE PROJECT.
- EXISTING BUILDING MAY HAVE IBC CHAPTER 34 CODE REQUIREMENTS THAT SUPERCEDE SOME REQUIREMENTS ON THIS PAGE.
- THIS SHEET CONTAINS SOME INFORMATION RELATED TO THE AMERICAN NATIONAL STANDARD FOR ACCESSIBLE AND USABLE BUILDING AND FACILITIES AS PER AMERICAN NATIONAL STANDARD ICC/ANSI A117.1-2009.
- THE ITEMS FOUND ON THIS DRAWING ARE TO HELP THE CONTRACTOR DURING CONSTRUCTION AND ARE NOT INTENDED TO BE A COMPLETE GRAPHIC DISPLAY OF THE UNIVERSAL ACCESSIBILITY STANDARDS. FOR COMPLETE INFORMATION SEE THE FOLLOWING:
  - THE 2009 INTERNATIONAL BUILDING CODE
  - THE 2012 INTERNATIONAL BUILDING CODE (CHAPTER 11 AND APPENDIX E ONLY)
  - THE AMERICAN NATIONAL STANDARD ICC/ANSI A117.1-2009
- VERIFY W/ LOCAL CODE ENFORCEMENT OFFICIAL WHICH VERSION OF THE ICC/ANSI A117.1 IS BEING ENFORCED.
- ASSISTIVE LISTENING SYSTEMS (IF REQUIRED BY IBC - CHAPTER 11): THE CONTRACTOR SHALL INSTALL THE SOUND SYSTEM AND HEARING AIDS SERVICES A LOCATION. THE SUBCONTRACTOR SHALL BE RESPONSIBLE FOR THE SYSTEM UNDER SUB CONTRACTS.

**SIGNAGE:**

- SIGNAGE SHALL BE PLACED THROUGHOUT THE BUILDING TO IDENTIFY LOCATIONS OF LIFE SAFETY AND EVACUATION ROUTES. EXITS, AREAS OF REFUGE, FIRE ALARM PANELS, FIRE EXTINGUISHERS, SPRINKLER SYSTEM DEVICES, AND FIRE ALARM CONTROL PANELS AND VISION LOCATION WITHIN THE BUILDING. PROVIDE AND INSTALL SIGNAGE IN ACCORDANCE WITH IBC-CHAPTER 11.
- IBC CHAPTER 11) REQUIRED ACCESSIBLE ELEMENTS SHALL BE IDENTIFIED BY THE INTERNATIONAL SYMBOL OF ACCESSIBILITY AT THE FOLLOWING LOCATIONS:
  - ACCESSIBLE PARKING SPACES REQUIRED BY SECTION 1106.1 EXCEPT WHERE TOTAL NUMBER OF PARKING SPACES PROVIDED IS FOUR OR LESS.
  - ACCESSIBLE PASSENGER LOADING ZONES.
  - ACCESSIBLE ROOMS WHERE MULTIPLE SINGLE-USER TOILET OR BATHING ROOMS ARE CLUSTERED AT A SINGLE LOCATION.
  - ACCESSIBLE ENTRANCES WHERE NOT ALL ENTRANCES ARE ACCESSIBLE.
  - ACCESSIBLE CHECK-OUT AISLES WHERE NOT ALL AISLES ARE ACCESSIBLE. THE SIGN SHALL BE ABOVE THE CHECK-OUT AISLE IN THE SAME LOCATION AS THE CHECK-OUT AISLE NUMBER OR TYPE OF CHECK-UP IDENTIFICATION.
  - UNisex TOILET AND BATHING ROOMS.
  - ACCESSIBLE DRESSING, FITTING AND LOCKER ROOMS WHERE NOT ALL SUCH ROOMS ARE ACCESSIBLE.
  - EXTERIOR AREAS FOR ASSISTED RESCUE IN ACCORDANCE W/ IBC SECTION 1007.9
- DIRECTIONAL SIGNAGE: SIGNAGE INDICATING THE ROUTE TO THE NEAREST LIFE ACCESSIBLE ELEMENT SHALL BE PROVIDED AT THE FOLLOWING LOCATIONS. THESE DIRECTIONAL SIGNS SHALL INCLUDE THE INTERNATIONAL SYMBOL OF ACCESSIBILITY.
  - INACCESSIBLE BUILDINGS ENTRANCES.
  - INACCESSIBLE PUBLIC TOILETS AND BATHING FACILITIES.
  - ELEVATORS NOT SERVING AN ACCESSIBLE ROUTE.
  - AT EACH SEPARATE SEX TOILET AND BATHING ROOM INDICATING THE LOCATION OF THE NEAREST FAMILY OR ASSISTED USE TOILET OR BATH ROOM WHERE PROVIDED IN ACCORDANCE W/ IBC-CHAPTER 11.
  - AT EXITS AND EXIT STAIRWAYS SERVING A REQUIRED ACCESSIBLE SPACE, BUT NOT PROVIDING AN APPROVED ACCESSIBLE MEANS OF EGRESS, SIGNAGE SHALL BE PROVIDED IN ACCORDANCE W/ IBC-CHAPTER 11.
- ASSISTIVE LISTENING SYSTEMS SIGNAGE: EACH ASSEMBLY AREA REQUIRED TO COMPLY W/ IBC CHAPTER 11, SHALL PROVIDE A SIGN NOTIFYING PATRONS OF THE AVAILABILITY OF ASSISTIVE LISTENING SYSTEMS. EXCEPT WHERE TICKET OFFICES OR WINDOW ARE PROVIDED, SIGNS ARE NOT REQUIRED AT EACH ASSEMBLY AREA PROVIDED THAT SIGNS ARE DISPLAYED AT EACH TICKET OFFICE OR WINDOW INFORMING PATRONS OF THE AVAILABILITY OF ASSISTIVE LISTENING SYSTEMS.
- EXIT SIGNAGE: AT EACH DOOR TO EGRESS STAIRWAY, EXIT PASSAGEWAY AND EXIT DISCHARGE, SIGNAGE SHALL BE PROVIDED IN ACCORDANCE W/ IBC-CHAPTER 11.
- AREA OF REFUGE SIGNAGE:
  - DIRECTIONS TO FIND OTHER MEANS OF EGRESS.
  - PERSONS ABLE TO USE THE EXIT STAIRWAY DO SO AS SOON AS POSSIBLE, UNLESS THEY ARE ASSISTING OTHERS.
  - INFORMATION ON AVAILABILITY OF ASSISTANCE IN THE USE OF STAIRS OR SUPERVISED OPERATIONS OF ELEVATORS AND HOW TO SUMMON SUCH ASSISTANCE
  - DIRECTIONS FOR USE OF EMERGENCY COMMUNICATIONS SYSTEM
- SECTION 1007.5.4 OF 2009 INTERNATIONAL FIRE CODE. INSTRUCTIONS SHALL BE POSTED IN AREAS OF REFUGE CONTAINING A TWO WAY EMERGENCY COMMUNICATION SYSTEM. INSTRUCTIONS SHALL INCLUDE:
  - DIRECTIONS TO FIND OTHER MEANS OF EGRESS.
  - PERSONS ABLE TO USE THE EXIT STAIRWAY DO SO AS SOON AS POSSIBLE, UNLESS THEY ARE ASSISTING OTHERS.
  - INFORMATION ON AVAILABILITY OF ASSISTANCE IN THE USE OF STAIRS OR SUPERVISED OPERATIONS OF ELEVATORS AND HOW TO SUMMON SUCH ASSISTANCE
  - DIRECTIONS FOR USE OF EMERGENCY COMMUNICATIONS SYSTEM
- SECTION 1007.5.5 OF 2009 INTERNATIONAL FIRE CODE. EACH DOOR PROVIDING ACCESS TO AN AREA OF REFUGE FROM THE ADJACENT FLOOR AREA SHALL BE IDENTIFIED BY A SIGN COMPLYING W/ ICC A117.1, STATING "AREA OF REFUGE," AND INCLUDING THE INTERNATIONAL SYMBOL OF ACCESSIBILITY. WHERE EXIT SIGN ILLUMINATION IS REQUIRED BY IBC - SECTION 1011, THE AREA OF REFUGE SIGN SHALL BE ILLUMINATED. ADDITIONALLY, TACTILE SIGNAGE COMPLYING W/ ICC A117.1 SHALL BE LOCATED AT EACH DOOR TO AN AREA OF REFUGE.
- TACTILE SIGNAGE:
  - PROVIDE AND INSTALL TACTILE EXIT SIGNAGE AT EXIT LOCATIONS. TACTILE SIGNAGE SHALL BE POSTED FOR THE MECHANICAL ROOM AND TOILET ROOMS. TACTILE SIGNAGE SHALL COMPLY W/ SECTIONS 703.3.1, 703.3.2 OF ICC/ANSI A117.1-2009, AND VISUAL CHARACTERS SHALL COMPLY W/ SECTION 703.4 OF ICC/ANSI A117.1-2009
  - SECTION 703.3.1 LOCATION - WHERE A TACTILE SIGN IS PROVIDED AT A DOOR, THE SIGN SHALL BE ALONGSIDE THE DOOR AT THE LATCH SIDE, WHERE A TACTILE SIGN IS PROVIDED AT DOUBLE DOORS OR ONE ACTIVE LEAF, THE SIGN SHALL BE LOCATED ON THE ACTIVE LEAF, WHERE A TACTILE SIGN IS PROVIDED AT DOUBLE DOORS W/ TWO ACTIVE LEAVES, THE SIGN SHALL BE TO THE RIGHT OF THE RIGHT-HAND DOOR, WHERE THERE IS NO WALL SPACE ON THE LATCH SIDE OF A SINGLE DOOR, OR TO THE RIGHT SIDE OF DOUBLE DOORS. SIGNS SHALL BE ON THE NEAREST ADJACENT WALL SIGNS CONTAINING TACTILE CHARACTERS SHALL BE LOCATED SO THAT A CLEAR FLOOR AREA 18" MIN BY 18" MIN, CENTERED ON THE TACTILE CHARACTERS IS PROVIDED BETWEEN THE ARC OF ANY DOOR SWING BETWEEN THE CLOSED POSITION AND 45 DEGREE OPEN POSITION. EXCEPTION SIGNS W/ TACTILE CHARACTERS SHALL BE PERMITTED ON THE PUSH SIDE OF DOORS W/ CLOSERS AND WITHOUT HOLD-OPEN DEVICES.
  - PROVIDE AND INSTALL TACTILE SIGNAGE AT ELEVATORS MEETING ANSI A117.1-2009 FOR ELEVATORS
  - 703.4.5 MOUNT HEIGHT - BRAILLE SHALL BE 48" MIN. AND 60" MAX. ABOVE THE FLOOR, MEASURED TO THE BASELINE OF THE BRAILLE CELLS. EXCEPTION ELEVATOR CAR CONTROLS SHALL NOT BE REQUIRED TO COMPLY W/ SECTION 703.4.5

HEIGHT ABOVE FLOOR TO BASELINE OF CHARACTER	HORIZONTAL VIEWING DISTANCE	MINIMUM CHARACTER HEIGHT
48 INCHES TO LESS THAN OR EQUAL TO 60 INCHES	LESS THAN 6 FEET AND 0 INCHES	LESS THAN 18 FEET AND 0 INCHES
GREATER THAN 60 INCHES TO LESS THAN OR EQUAL TO 120 INCHES	LESS THAN 15 FEET AND 0 INCHES	LESS THAN 24 FEET AND 0 INCHES
GREATER THAN 120 INCHES	LESS THAN 24 FEET AND 0 INCHES	LESS THAN 24 FEET AND 0 INCHES

**MEISTER COX ARCHITECTS**

INFO@MEISTER-COX.COM  
 PHONE: 610-375-1531 FAX: 610-375-4655  
 1522 PENN AVENUE WYOMISSING, PA 19380  
 WWW.MEISTER-COX.COM

**ADA DETAILS**

HOLIDAY INN EXPRESS & SUITES  
 INTERSECTION OF HAYNES PLACE & LAMM RD.  
 WILSON, NC 27783

**STATUS:** BIDDING  
**PROJ. DATE:** 06-07-19  
**PROJ. NO.:** 18-176  
**PRINTED:** 6/7/2019 7:12:43 PM  
**DRAWN BY:** RFF  
**CHECKED BY:** TGC  
**SHEET NO.:** ADA  
**SCALE:** As indicated