

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
DL1	○	WAC	R-421-CL-WT	LED DOWNLIGHT RECESSED WITH WHITE TRIM WITH 450 LUMEN LED LAMP	1	LED	7	2700	85	RECESSED	120	PROVIDE IC RATED FIXTURE WHERE REQUIRED
DL2	⊙	WAC	R-435-WT	LED WALL WASH RECESSED WITH WHITE TRIM, BEAM ANGLE - 25, WITH 450 LUMEN LED LAMP	1	LED	7	2700	85	RECESSED	120	PROVIDE IC RATED FIXTURE WHERE REQUIRED
DL3	○	WAC	R-424-WT	LED DOWNLIGHT RECESSED WITH WHITE TRIM WITH 675 LUMEN LED LAMP	1	LED	10	2700	85	RECESSED	120	PROVIDE IC RATED FIXTURE WHERE REQUIRED
DL4	○	GOTHAM	EVO 30/15 6AR MD LSS CR190	LED RECESSED 1500 LUMEN DOWNLIGHT	1	LED	19	3000	90	RECESSED	120	PROVIDE IC RATED FIXTURE WHERE REQUIRED
DL5	○	GOTHAM	EVO VR 30/15 6AR LSS CGL MVOLT DWH	RECESSED DOWNLIGHT IN POOL AREA, LED BULB, NATATORIUM FINISH	1	LED	19	3000	90	RECESSED	120	PROVIDE IC RATED FIXTURE WHERE REQUIRED

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
LL1	▬	PEERLESS	RD4W4 LLP 4FT MSL4 80CRI 30K 800LMF120 SCT C032	WALL MOUNTED LINEAR LED	1	LED	61	3000	80	SURFACE	120	
LL2	▬	LITHONIA	WL4 20L LP830	1x4 SURFACE MOUNTED LED WITH ACRYLIC LENS	1	LED	19	3000	80	SURFACE	120	
LL3	▬	LITHONIA	VAP 4000LM PCL MD MVOLT 30K 90CRI WLFEND2	DAMP LOCATION 1x4 SURFACE MOUNTED WITH ACRYLIC LENS	1	LED	42	3000	90	SURFACE	120	
LL4	□	LITHONIA	2ALL2 33L LP830	2X2 LED LAY-IN WITH ACRYLIC LENS	1	LED	29	3000	80	RECESSED	120	PROVIDE HARD CEILING FLANGE WHERE INSTALLED IN DRYWALL CEILING. COORDINATE WITH ARCHITECTURAL RCP.
LL5	□	LITHONIA	2ALL4 40L LP830	2X4 LED LAY-IN WITH ACRYLIC LENS	1	LED	32	3000	80	SURFACE	120	

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
SM1	■	SISTEMALUX BLADE	0864-3000-120-XX	LED WALL SCONCE CLEAR TEMPERED GLASS	1	LED	5	3000	80	SURFACE	120	EXP-4
SM2	■	AS SELECTED BY OWNER	AS SELECTED BY OWNER	LED WALL SCONCE RESTROOM FIXTURE	1	LED	10	3000	80	SURFACE	120	
SM3	○	PHILIPS	FORCAST F608059	LED 3AR LIGHT SATIN ALUMINUM FINISH	1	LED	10	3000	80	SURFACE	120	
SM4	○	TECH LIGHTING	700CQ L S-LED	SURFACE CEILING MTD LIGHT, EXP-404, GLASS	1	LED	20	2700	90	SURFACE	120	

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
AL1	□	CON-TECH	RAN18L SERIES	RECESSED ACCENT LIGHT, (3) LED LAMPS, 18 WATTS	3	LED	18	3000	80	RECESSED	120	
AL2	—	WAC	LED-T24-P-X-WT	SURFACE COVE LED	1	LED	3 W/FT	3000	80	COVE	120	LED REMOTE DRIVER

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
PL1	○	PHILIPS	FORCAST	DECORATIVE PENDANT EXP-404, DIMMER IN COLOR	1	LED	4	3000	80	PENDANT	120	
TR1	—	CHALLENGE LIGHTING	HTK 13-BN/BK HEAD WITH TRACK	HTK LED TRACK HEAD WITH TRACK, BRUSHED NICKEL WITH BLACK TRACK ADAPTOR, 675 LUMENS	1	LED	11	2700	85	TRACK	120	

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
X1	□	LITHONIA	WST LED 1 10A700/30K SR3 MVOLT	EXTERIOR SURFACE MOUNTED LED WALL PACK	1	LED	24	3000	80	SURFACE	120	FINISH SELECTED BY ARCHITECT
X2	○	GOTHAM	EVO VR 35/30 BAR LSS CGL DWHG	3000 LUMEN LED EXTERIOR DOWNLIGHT	1	LED	30	3500	80	RECESSED	120	
X3	□	HALLMARK	BY OWNER	LED ACCENT LIGHT - SMALL	1	LED	32	BLUE		SURFACE	120	MOUNT PER ARCHITECTURAL ELEVATIONS IHG #EXP-1002
X4	□	LITHONIA	DSXF2 LED 3 A540/30K WFL MVOLT THK VG DDBKD	LED FLOOD LIGHT	1	LED	54	3000	80	GROUND	120	
X5	—	TTVOLI	ILT -1010-27-02-12+ ADNM-320-4-5-12-D	EXTERIOR LINEAR LED	1	LED	2 W / FT	2700	80	SURFACE	120	PROVIDE ALL MOUNTING HARDWARE, OUTDOOR END CAPS AND POWER SUPPLIES AS REQUIRED FOR INSTALLATION
X6	□	HALLMARK	BY OWNER	LED ACCENT LIGHT - LARGE	1	LED	32	BLUE		SURFACE	120	MOUNT PER ARCHITECTURAL ELEVATIONS IHG #EXP-1003
X7	□	SYSTEMALUX	S.5081-UNV-4 NARROW BEAM	LED STARBURST LIGHT	1	T4.5 MH	39	5000	85	SURFACE	120	MOUNT PER ARCHITECTURAL ELEVATIONS IHG #XLT

FIXTURE ID	FIXTURE SYMBOL	FIXTURE TYPE			LAMP					MOUNTING	FIXTURE VOLTAGE	REMARKS
		MANUFACTURER	EMERGENCY MODEL #	DESCRIPTION	LAMP QUANTITY	LAMP TYPE	LAMP WATTAGE	CCT	CRI			
EM1	●	LITHONIA	LQM 5 W 3 R 120/277 ELN SD	THERMOPLASTIC LED EMERGENCY SINGLE OR DOUBLE FACE AS INDICATED ON PLANS, NICKEL-CADMIUM BATTERY BACK-UP, SELF DIMMING OPTICS	1	LED	1.0	-	-	CEILING	120	ALL EXIT SIGNS SHALL HAVE LOW EXIT SIGN ADJACENT AND MOUNTED ON WALL.
EM2	●	LITHONIA	LQM 5 W 3 R 120/277 ELN SD	THERMOPLASTIC EXIT SIGN SINGLE OR DOUBLE INDICATED ON PLANS, NICKEL-CADMIUM BATTERY BACK-UP, SELF DIMMING OPTICS	1	LED	1.0	-	-	WALL	120	ALL EXIT SIGNS SHALL HAVE LOW EXIT SIGN ADJACENT AND MOUNTED ON WALL.
EM3	◁	LITHONIA	ELM2 LED HO SD	TWIN HEAD, ADJUSTABLE HOOP, THERMOPLASTIC, 12 VOLT, 5W KRYSTAL LAMP, NICKEL-CADMIUM BATTERY BACK-UP	2	LED	1.5	-	-	WALL	120	
EM4	◁	LITHONIA	ELR2 TWP M12	EXTERIOR REMOTE DUAL HEAD	2	LED	1	-	-	WALL	120	
EM5	◁	LITHONIA	ELR2 N181 TWP SD	CEILING MOUNTED DUAL HEAD, BATTERY BACK-UP	2	INC	18	-	-	CEILING	120	

LIGHTING FIXTURE SCHEDULES GENERAL NOTES

- FIXTURES, LAMPS, AND RELATED DEVICES FURNISHED UNDER THIS CONTRACT SHALL CARRY THE APPROVAL LABEL OF U.L. OR E.T.L. FOR THE SPECIFIC APPLICATION IN WHICH THEY ARE USED.
- L-1 UNLESS OTHERWISE INDICATED, ALL FLUORESCENT LAMP BALLASTS SHALL BE ELECTRONIC TYPE. ELECTRONIC BALLASTS FOR STRAIGHT AND U-BENT LAMPS SHALL BE RAPID-START TYPE AND SHALL BE ADVANCE STANDARD SERIES OR MAGNETEK TRIAD SERIES. ELECTRONIC BALLASTS FOR COMPACT FLUORESCENT LAMPS (TWIN TUBE, QUAD TUBE, AND TRIPLE TUBE) SHALL BE EQUIPPED WITH A PROTECTIVE SHUT DOWN CIRCUIT TO SHUT OFF THE BALLAST WHEN THE LAMP IS APPROACHING FAILURE.
 - L-3 UNLESS OTHERWISE NOTED, LAMP DESIGNATIONS ARE FOR LAMPS BY PHILIPS LIGHTING COMPANY. LAMPS OF EQUIVALENT CHARACTERISTICS WITH EQUAL OR GREATER PERFORMANCE FROM GENERAL ELECTRIC OR OSRAM/SYLVANIA ARE ACCEPTABLE ALTERNATIVES.
 - L-4 CONTRACTOR SHALL CONFIRM THAT FIXTURE VOLTAGE AND FIXTURE CEILING TRIMS ARE COMPATIBLE WITH THEIR APPLICATION PRIOR TO ORDERING FIXTURES.
 - L-5 CONTRACTOR SHALL SELECT, FURNISH, AND INSTALL THE CORRECT SIZE OF SECONDARY WIRING FROM REMOTE TRANSFORMERS AND/OR REMOTE BALLASTS AS REQUIRED TO KEEP VOLTAGE DROP IN THE SECONDARY WIRING BELOW 3% OF RATED VOLTAGE.
 - L-6 CONTRACTOR SHALL PROVIDE LABOR AND EQUIPMENT FOR FOCUSING OF ADJUSTABLE FIXTURES AND PRESETTING OF LIGHTING CONTROL SYSTEMS. FOCUSING AND PRESETTING SHALL BE DONE IN THE PRESENCE OF THE DESIGN PROFESSIONAL. CONTRACTOR SHALL FOCUS LIGHTING AFTER DARK IF DIRECTED BY THE OWNER/DESIGN PROFESSIONAL. THE CONTRACTOR SHALL PROVIDE A MINIMUM OF ONE SUCCESSFUL NIGHT-TIME AIMING SESSION WITH THE OWNER AND DESIGN PROFESSIONAL. CONTRACTOR SHALL PROVIDE AT LEAST ONE DAY OF A FACTORY-TRAINED AND CERTIFIED TECHNICIAN TO PROVIDE WARRANTY START-UP AND PROGRAMMING FOR ALL LIGHTING CONTROL SYSTEM AND PROGRAMMABLE LIGHTING FIXTURES.

MEISTER COX ARCHITECTS
 INFO@MEISTER-COX.COM
 PHONE: 610-375-1331 FAX: 610-375-4555
 1522 PENN AVENUE WYOMISSING, PA 19610
 WWW.MEISTER-COX.COM

SEAL: _____

**ELECTRICAL LIGHTING
 FIXTURE SCHEDULES**

HOLIDAY INN EXPRESS & SUITES
 INTERSECTION OF HAYNES PLACE & LAMMI RD.
 WILSON, NC 27883

STATUS: FOR BID

PROJ. DATE: 06/06/2019

PROJ. NO: 19-116

PRINTED: 06/06/2019

DRAWN BY: jlm/brm/jpk

CHECKED BY: brm

SHEET NO. **E5.1**

SCALE: AS NOTED

Order Plans @ WWW.IDLINE.COM

No.	Description	Date

DISCLAIMER: This document is provided by agreement with the client. It is not to be used for any other project without the express written consent of the provider. The provider shall not be held responsible for any errors or omissions in this document. The provider shall not be held responsible for any damages, claims, or losses resulting from the use of this document. The provider shall not be held responsible for any changes or modifications to this document. The provider shall not be held responsible for any delays or interruptions in the delivery of this document. The provider shall not be held responsible for any loss of data or information. The provider shall not be held responsible for any unauthorized use or distribution of this document. The provider shall not be held responsible for any legal action or litigation. The provider shall not be held responsible for any other matters. The provider shall not be held responsible for any other matters. The provider shall not be held responsible for any other matters.