

1 SECOND FLOOR - PARTIAL FRAMING PLAN G

SCALE: 1/8" = 1'-0"

STRUCTURAL KEY NOTES

1	20" DEEP FLOOR JOISTS AT 24" O.C. MAX. UNLESS DIMENSIONED OTHERWISE ON PLAN
2	TAPPERED BALCONY TRUSS. 18" DEEP TO 16" DEEP ON EXTERIOR SIDE SPACED @ 24" O.C. MAX.
3	LOAD BEARING HEADER. REFER TO HEADER SCHEDULE UNLESS NOTED OTHERWISE
4	NON-LOAD BEARING HEADER. REFER TO HEADER SCHEDULE UNLESS NOTED OTHERWISE
5	HATCHED AREA INDICATES LOAD BEARING WALL
6	PRESSURE TREATED 4x4 COLUMN POST OR (3) 2x4 P.T. STUDS W/ HD-3B HOLD DOWN FOR EXTERIOR WALLS AND BALCONIES ONLY. P.T. COLUMNS AND HOLDDOWNS ARE NOT REQUIRED IN INTERIOR CONDITIONS AT BALCONY AND STAIR.)
7	PRESSURE TREATED 4x6 COLUMN POST OR (4) 2x6 P.T. STUDS W/ HD-3B HOLD DOWN FOR EXTERIOR WALLS AND BALCONIES. PRESSURE TREATED COLUMNS ARE NOT REQUIRED IN INTERIOR CONDITIONS. USE CB-66 OR HD-3B CONNECTION AT BASE.
8	PRESSURE TREATED 6x6 COLUMN POST OR (4) 2x6 P.T. STUDS W/ HD-3B HOLD DOWN FOR EXTERIOR WALLS AND BALCONIES. PRESSURE TREATED COLUMNS ARE NOT REQUIRED IN INTERIOR CONDITIONS. USE CB-66 OR HD-3B CONNECTION AT BASE.
9	(3) 2x12 P.T. WITH (2) 1/2" PLYWOOD FLITCH. ALL BEAM SIZES TO BE VERIFIED BY TRUSS MANUFACTURER.
10	(2) 2X12 P.T. WITH (2) 1/2" PLYWOOD FLITCH. ALL BEAM SIZES TO BE VERIFIED BY TRUSS MANUFACTURER.
11	20" DEEP LADDER TRUSS AT ALL EXTERIOR NON-BEARING WALLS AS SHOWN.
12	(2) 2x12 LEDGER BEAM W/ 1/2" DIAMETER THRU-BOLT @ 16" O.C. STAGGERED MINIMUM 2" FROM TOP AND BOTTOM OF BEAM.
13	DOUBLE U-BLOCK BOND BEAM W/ (2) #5 BARS CONTINUOUS IN EACH COURSE. OCCURS AT EACH FLOOR LEVEL AND AT ROOF
14	3-1/2" x 18" LVL OR FLOOR TRUSS GIRDER (UPTURNED BEAM) SIZESS TO BE VERIFIED BY TRUSS MANUFACTURER.
15	CONCRETE LINTEL. REFER TO SCHEDULE ON SDT SHEETS
16	(2) 2x12 LEDGER BEAM W/ (2) 1/2" DIAMETER x 7" WEDGE ANCHORS @ 16" O.C. SET ANCHORS 2" MINIMUM FROM TOP AND BOTTOM OF BEAM. 3" MINIMUM EMBED INTO CMU.
17	12" DEEP FLOOR JOISTS AT 16" O.C. MAX UNLESS DIMENSIONED OTHERWISE ON PLAN
18	P.T. 2X12's @12" O.C.
19	20" DEEP FLOOR JOIST W/2" STEP DOWN AT CANTILEVERED END. SLOPE CANTILEVER ... AND ATTACH ONE P.T. 2X12 ON SIDE OF TRUSS. EQUAL
20	CROSS BRACING BETWEEN TRUSSES IN LINE WITH BEARING WALL ABOVE
21	5-1/4" x 18" LVL OR FLOOR TRUSS GRIDER (UPTURNED BEAM) SIZES TO BE VERIFIED BY TRUSS MANUFACTURER.
22	PRESSURE TREATED 8x8 COLUMN POST W/ (2) HD-3B HOLDDOWNS FOR EXTERIOR WALLS AND BALCONIES. PRESSURE TREATED COLUMNS ARE NOT REQUIRED IN INTERIOR CONDITIONS. USE (2) HD-3B CONNECTIONS @ BASE.
23	7-1/4" x 18" LVL OR FLOOR TRUSS GIRDER (UPTURNED BEAM) SIZES TO BE VERIFIED BY TRUSS MANUFACTURER.
24	PRESSURE TREATED 4x8 COLUMN POST OR (5) 2x4 P.T. STUDS W/ (2) HD-3B HOLDDOWNS FOR EXTERIOR WALLS AND BALCONIES ONLY. PRESSURE TREATED COLUMNS ARE NOT REQUIRED IN INTERIOR CONDITIONS. USE CB-48 OR (2) HD-3B CONNECTIONS @ BASE.
25	PRESSURE TREATED 6x8 COLUMN POST OR (5) 2x6 P.T. STUDS W/ (2) HD-3B HOLDDOWNS FOR EXTERIOR WALLS AND BALCONIES ONLY. PRESSURE TREATED COLUMNS ARE NOT REQUIRED IN INTERIOR CONDITIONS. USE CB-48 OR (2) HD-3B CONNECTIONS @ BASE.
26	W16x31 - CLUBHOUSE ONLY
27	W16x40 - CLUBHOUSE ONLY
28	6x6x1/2" THICK TUBE STEEL COLUMN - CLUBHOUSE ONLY
29	6x12x1/2" THICK TUBE STEEL COLUMN - CLUBHOUSE ONLY
30	W16x45 - CLUBHOUSE ONLY
31	4x4x5/16" THICK TUBE STEEL COLUMN - CLUBHOUSE ONLY
32	POINT LOAD FROM ABOVE - CLUBHOUSE ONLY

KEY PLAN



Lyric at Norton Commons

Prospect, Kentucky

Bristol Development Group
381 Mallory Station Rd, Suite 204
Franklin, TN 37067

NALIN H. JOSHI, P.E.
4321 MAYWOOD DRIVE
JACKSONVILLE, FL 32277
NALINJAYSHREE@AOL.COM
(904) 744-6133

cba
charlan • brock associates
architects • planners
1770 fennell street
maitland florida 32751-7208
407 660 8900 f:407 875 9948
www . cbaarchitects . com

SECOND FLOOR FRAMING PLAN

date: 06-04-2019
job no: 3789.15
drawn by: COOL
reviewed by: NHJ
issue history:
Δ Date
1 7-3-2019

REV1-07-03-2019

S1.12G

Order Plans @ WWW.LDIIinc.com