



GENERAL NOTES

- EXTERIOR WALL DIMENSIONS ARE FROM FACE OF PLYWOOD/CMU STEM WALL. INTERIOR WALL DIMENSIONS ARE FROM FACE OF STUD, UNLESS NOTED OTHERWISE.
- ALL WALLS BEHIND WALK-IN REFRIGERATORS AND FREEZERS SHALL BE 1/2" DUROCK CEMENT BOARD TO HEIGHT OF 11'-0" A.F.F. FASTEN BOARDS TO STUDS @ 8" O.C. EA. WAY W/ DUROCK FASTENERS. EMBED ALKALI-RESISTANT TAPE IN THINSET OVER JOINTS.
- STOREFRONT TO BE DRY SET.

FLOOR PLAN LEGEND

	8" MTL STUDS W/ R19 BATT INSUL. & STONE VENEER	V1	DOOR IDENTIFICATION. SEE DOOR SCHEDULE
	4" MTL STUDS W/ R11 BATT INSUL. FINISH AS SCHED.	1	BLOCKING IDENTIFICATION. SEE EQ BLOCKING NOTES
	3-5/8" MTL STUDS W/ 1/2" GWB, U.N.O.	EXIT	TACTILE BRaille SIGN. STATING "EXIT". COMPLYING WITH ICC/ANSI A117.1. SEE DETAIL 41A4
	6" MTL STUDS W/ 1/2" GWB, U.N.O.	WH	WATER HEATER
	INSULATED MTL PANELS BY REF. CO.		
	FIRE EXTINGUISHER		

EQUIPMENT BLOCKING

#	ITEM	MATL	ELEVATION	REMARKS
1	SHELVING @ 3 COMP. SINK	1/2" PLYWD	RE: ELEVATION	
2	MOP HOLDER	2" X 6"		
3	HAND DRYER	AS PER MFR		
5	HAND WASH SINK	6"	3'-5"	
6	JURNAL	6"		
7	GRAB BARS	2"	2'-10" AND VERTICAL	
10	TOILET PARTITIONS	2"		
11	COAT HOOKS	1/2"	3'-10"	
12	SECURITY SHELVING	4"	4'-0" & 5'-0" RE: DETAIL 10A11	
13	CLC	2" X 12"	5'-6"	
14	FLOOR TANK MONITOR	2" X 12"	5'-5"	
15	SURGE TANK SHELL	2" X 6"	8'-8" RE: DETAIL 5A11	
19	SECURITY SIGN	2" X 8"	9'-6" SEE 18A11.1	
21	FIRE EXTINGUISHER	2" X 6"	3'-6"	
22	CAR UNIT	5/8" PLYWD	IN LIEU OF GWB. FLR TO CLG	
23	FULL SERVICE CUBBIES	2" X 8" & 2" X 10"	SEE DETAIL 6A11.1	
28	COFFEE AREA CUBBIES	2" X 8" & 2" X 10"	SEE DETAIL 7A11.1	
30	KPS MONITOR	2X8 (VERT.)	2'-6" UP TO 4'-0"	
31	GOOSE LOGO SIGN	2" X 6"	8'-4" & 9'-8" RE: 7A8	
32	COMPARTMENT SINK	2" X 12"	2'-11" RE: ELEVATION	
33	TRASH RECEPTACLE	AS PER MFR		
34	AIR CURTAIN	2" X 12"	ABOVE DOOR. RE: 3A3	

EQUIPMENT BLOCKING NOTES:

- PROVIDE ADDITIONAL BLOCKING AT OTHER LOCATIONS AS REQUIRED.
- ALL HEIGHTS ARE CENTERED, UNLESS NOTED OTHERWISE.
- PROVIDE BLOCKING FOR ALL CABINET - 2X12 CENTERED ON CABINET TOP.

DOOR THRESHOLDS

DOOR PANEL TYPES

DOOR NOTES:

- DOOR #S SHOWN IN DOOR SCHEDULE ARE TYPICAL FOR WAWA STORES. VERIFY QUANTITIES AND WHICH DOORS ARE REQUIRED AS INDICATED IN FLOOR PLAN.
- SEE STOREFRONT MFR. SPECIFICATIONS FOR VESTIBULE DOORS. DOORS ARE TO BE KEYPAD ALIKE WITH THUMB LATCH AND CLOSER AT ALL DOORS.
- ALL EXTERIOR HOLLOW METAL DOORS SHALL BE INSULATED DOORS.
- RUN CONTINUOUS BEAD OF CLEAR SILICONE GASKET AROUND ALL DOOR FRAMES.
- EXIT DOOR LOCKS, IF PROVIDED ON EGRESS DOORS, SHALL NOT REQUIRE THE USE OF A KEY, A TOOL OR SPECIAL KNOWLEDGE OR EFFORT FOR OPERATION FROM THE EGRESS SIDE IN ACCORDANCE WITH IBC 2009 & 2012 - SECTION 1008.1.9 OR IBC 2015 1010.1.9 (AS APPLICABLE).
- A LATCH OR OTHER FASTENING DEVICE ON AN EGRESS DOOR SHALL BE PROVIDED WITH A KNOB, HANDLE, PANIC BAR, OR OTHER SIMPLE TYPE OF RELEASING DEVICE HAVING AN OBVIOUS METHOD OF OPERATION UNDER ALL LIGHTING CONDITIONS. DOORS SHALL BE OPERABLE WITH NO MORE THAN ONE RELEASING OPERATION PER IBC 2009 & 2012 - SECTION 1008.1.9.5 OR IBC 2015 1010.1.9.5 (AS APPLICABLE).
- REFER TO HARDWARE SCHEDULE IN THE SPECIFICATION MANUAL.
- ALL GLAZING IN DOORS & SIDELIGHTS SHALL MEET THE REQUIREMENTS FOR SAFETY GLAZING AS REQUIRED IN IBC 2009, 2012 & 2015 - SECTION 1008.
- HARDWARE HEIGHTS, HANDLES, PULLS, LATCHES, LOCKS, AND OTHER OPERATING DEVICES ON DOORS SHALL BE INSTALLED, 34" MINIMUM AND 48" MAXIMUM ABOVE THE FINISHED FLOOR.
- ACROVYN DOORS SHALL BE INSTALLED IN H.M. FRAMES PER SPECIFICATIONS. THE DOORS SHALL HAVE ACROVYN COVERING FACTORY APPLIED.
- ALL FRAMES FOR ACROVYN DOORS SHALL BE CECO DOOR PRODUCTS. NO SUBSTITUTIONS. H.M. FRAMES FOR ACROVYN DOORS SHALL BE ORDERED THRU WILLIAM MCAULIFFE. I.H. ACC. SEE SPECIFICATIONS. FRAMES SHALL HAVE ACROVYN COVERING FIELD APPLIED.
- THRESHOLD 'A' NOT TO EXCEED 1/2" HIGH INSTALLED.
- ALL DOORS, INTERIOR AND EXTERIOR SHOULD BE FULLY WELDED-NO K.D. FRAMES. ADD WOOD BLOCKING AROUND THE FRAMES. SEE DETAILS 9 AND 10A11.2.

DOOR SCHEDULE

#	HT	TH	TYPE	FRM	TH	HOW	REMARKS	PUSH	HW	PULL	KICK
AP1	2'-0"	2'-0"	STL	STL	-	NYSTROM HS					
AP3	2'-0"	3'-0"	STL	STL	-	BABCOCK DAVIS BNT - CUSTOM HARDWARE CONFIG					
C6	6'-8"	2'-8"	134"	B	WD	HM	C	HW14.8	SEE NOTES 10 AND 11. SEE DETAIL 9 & 18A11.2	LOCKSET	16"X34"
D1	7'-0"	4'-0"	134"	C	HM	HM	A	HW10	4"X25" SAFETY GLASS VISION PANEL. SEE DETAIL 15A8	PANIC BAR	36"X48"
EL	6'-8"	3'-0"	134"	C	HM	C	HW13.3	4"X25" SAFETY VISION PNL. SEE DETAIL 9 & 17A11.2	PANIC BAR		
ELS	7'-0"	3'-0"	134"	C	HM	HM	B	HW5.3	4"X25" SAFETY GLASS VISION PNL. SEE DETAIL 15A8	LOCKSET	
EL6	6'-9"	3'-0"	2"	REF	-	-	-	-	BY REFRIGERATION COMPANY		
EL7	6'-9"	3'-0"	4"	REF	-	-	-	-	BY REFRIGERATION COMPANY		
F1	6'-8"	3'-6"	-	-	-	-	-	-	CASED OPENING. RE: DETAIL 9A111.2. SEE NOTES 10 & 11		
OF	6'-8"	3'-0"	134"	C	WD	HM	-	HW12	4"X25" ONE WAY SAFETY GLASS VISION PNL. SEE DETAIL 9A111.2. PROVIDE 8" JAMB AT ASSOC. RM W/ EXTENSION ON RETAIL SIDE. SEE DETAIL 10A11.2	LOCKSET	16"X34" 16"X36"
PT	6'-8"	3'-0"	134"	B	WD	HM	-	HW7	SEE NOTES 10 & 11. SEE DETAIL 9A111.2	24"X24"	16"X34" 16"X36"
R2	6'-9"	4'-0"	2"	REF	-	-	-	-	BY REFRIGERATION COMPANY		
R3	6'-9"	3'-0"	2"	REF	-	-	-	-	BY REFRIGERATION COMPANY		
R4	6'-9"	3'-0"	2"	REF	-	-	-	-	BY REFRIG. CO. W/ KEYPAD COMINATION LOCK		
RU	7'-4"	5'-4"	2"	-	-	-	-	-	ROLL-UP DOOR. SEE DTL 4A8. HT & WIDTH ARE R.O. DIMS		
T5	7'-0"	3'-0"	134"	C	HM	HM	B	HW5.3	4"X25" SAFETY GLASS VISION PNL. SEE DETAIL 15A8	LOCKSET	
TC	7'-0"	3'-6"	134"	B	HM	HM	-	-	SEE DETAIL 9A111.2. PROVIDE 8" JAMB AT ASSOC. RM W/ EXTENSION ON RETAIL SIDE. SEE DETAIL 10A11.2		
V1	7'-0"	6'-0"	134"	A	ALLUM	ALLUM	C	-	NO HOLD OPENS (DBL DOOR). SEE SPECS FOR HDW	PUSH BAR	
V2	7'-0"	3'-0"	134"	A	ALLUM	ALLUM	C	-	NO HOLD OPENS (DBL DOOR). SEE SPECS FOR HDW	PUSH BAR	
V3	7'-0"	3'-0"	134"	A1	ALLUM	ALLUM	C	-	NO HOLD OPENS. PUSH ONLY. SEE SPECS FOR HDW	PUSH BAR	
V4	7'-0"	3'-0"	134"	A	ALLUM	ALLUM	C	-	NO HOLD OPENS. SEE SPECS FOR HDW	PUSH BAR	
W1	6'-8"	3'-0"	134"	C	WD	HM	-	HW3	4"X25" ONE WAY SAFETY GLASS VISION PNL. SEE NOTES 10 AND 11. SEE DETAIL 9A111.2	LOCKSET	16"X34" 16"X36"

Order Plans @ WWW.DIYLINC.COM

1925 Prospect Ave.
Orlando, FL 32814
P (407) 661-9100
F (407) 661-9101
www.c-p.com

Chiacri & Peterson
Architects Engineers Planners

CLIENT NAME
WAWA
280 W. BALTIMORE PIKE
WAWA, PA 19063

PROJECT NAME
W50FB-VA 2018-01-MA
STORE #6668-SUD
10091 DAVIDSON PLACE
MANASSAS, VA 20109

REVISION SCHEDULE

No.	Description	Date
1	PERMIT SET	01/04/2019
1	PERMIT COMMENTS	03/15/2019
	BID SET	06/27/2019

PROJECT NO.
2170584

DATE
01/04/2019

DRAWN
VL

CHECKED
C

A1