RECEIVED
MAR 21 2019
1736 E. SUNSHINE ST. SUITE 417
SPRINGFIELD, MO

STEEL SQUARE POLES

POLE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **5SQB5 S07G 24 S PLP SF DGP**

Pole Series	Material	Weight[2]	Mounting Configuration	Pole Finish	Options
Bolt-on Arm Mount - See pole selection guide for patterns and fixture matches. **4SQB3** - 3" Reduced drilling pattern **5SQB3** - 3" Reduced drilling pattern **4SQB5** - 5" Traditional drilling pattern **5SQB5** - 5" Traditional drilling pattern **6SQB5** - 5" Traditional drilling pattern	S11G – 11 Ga. Steel S07G – 07 Ga. Steel	14' 16' 18' 20' 22' 24' 26' 28' 30' 35' 39'	S – Single/Parallel D180° – Double D90° – Double DSQ90° – Double T120° – Triple TSQ90° – Triple Q90° – Quad QT90° – Quad N – Tenon Mount (Standard tenon size is 3-3/8" O.D.)	BRZ – Bronze BLK – Black PLP – Platinum Plus WHT – White SVG – Satin Verde Green GPT – Graphite MSV – Metallic Silver	GA – Galvanized Anchor Bolts SF – Single Flood[3] DF – Double Flood[3] DGP – DuraGrip® Plus LAB – Less Anchor Bolts DSCE – Pole Preparation for PMSS Occupancy Sensor[4]
Tenon Mount - Slip fitter selection guide for tenon and fixture bracket matches. **4SQN** **5SQN** **6SQN**	Consult Pole Selection Chart on opposite page				Standard SF and DF pole preparations are located 3/4 of the height of the pole from the base, unless otherwise specified.
No Mounting Holes - Use with: • BKA 4GB & BPA 5GB* • BKA AASP- & ERA XASP-					
Internal Slip-fitter*					
4SQB **5SQB**					

ACCESSORY ORDERING INFORMATION (Accessories are field installed)

Description	Order Number
DBC – 5" Square Base Cover	1ZBXBC1-5
DBC – 7" Square Base Cover	1ZBXBC1-7
DBC – 9" Square Base Cover	1ZBXBC1-9
EPS – Weatherproof Duplex Receptacle	1ZBXRE1-5
GFI – Ground Fault Circuit Interrupter	1ZBXRF1-5
RKW – Mounting Hole Weatherproof Cover for use with 2" knockout drill pattern	1ZBXRE
KWP – Mounting Hole Weatherproof Cover for use with 3" knockout drill pattern	1ZBXRE
Vibration Damper - 4" Square Pole (bolt-on mount only)	1YZ009
Vibration Damper - 5" Square Pole (bolt-on mount only)	1YZ010
Vibration Damper - 6" Square Pole (bolt-on mount only)	1YZ011
PMSS0393 - 120V Occupancy Sensor	518PMSS1-5
PMSS0394 - 208, 240V Occupancy Sensor	519PMSS1-5
PMSS0395 - 277V Occupancy Sensor	520PMSS1-5
PMSS4459 - 480V Occupancy Sensor	1347PMSS1-5

FOOTNOTES:
1 - See Area Lighting Brackets 5" Bolt-on Drill Pattern and Area Lighting Brackets - Bolt-on 5" Traditional Drill Pattern spec sheets for optional BSQ-style brackets.
2 - Pole heights will have +/- 5% tolerance.
3 - See Flood Lighting Brackets section for choice of EBQ brackets.
4 - Order PMSS0 assembly. Change "XX" to indicate height and site all pole location for pole preparation. EX: 15' SF indicates preparation is to be 15ft. up from pole base on side A. Optional distance from ground to sensor is 20ft.
5 - DSCE option required. Not for use with Metal Halide fixtures

BOLT CIRCLE



	B Slotted 8"-11" (203mm-279mm)	C Slotted 9"-11" (229mm-279mm)	D Slotted 9"-11" (229mm-279mm)	J Slotted 12" (305mm)
Bolt Circle				
Anchor Bolt Size	3/4" x 30" (19mm x 762mm)	3/4" x 30" (19mm x 762mm)	1" x 36" (25mm x 914mm)	1" x 36" (25mm x 914mm)
Anchor Bolt Projection	3-1/2" (89mm)	3-1/2" (89mm)	4" (102mm)	4" (102mm)
Base Plate Opening for Handhole Entry	2-5/8" (67mm)	2-3/8" (121mm)	4-1/2" (114mm)	5-3/8" (142mm)
Base Plate Dimensions	10-1/2" sq. x 3/4" thk. (267mm x 19mm)	10-1/2" sq. x 3/4" thk. (267mm x 19mm)	10-1/2" sq. x 1" thk. (267mm x 25mm)	12" sq. x 1-1/8" thk. (305mm x 29mm)

Note: Base plate thicknesses may change without notice. Do not use for setting anchor bolts. Consult factory for the base plate template.

Project Name _____ Fixture Type _____ 11/22/17
Catalog # _____ © 2017 LSI INDUSTRIES INC.

STEEL SQUARE POLES

DIMENSIONS



DRILLING LOCATIONS



Sides	A	B	C	D
Hand-hole	A			
Single	X			
D180°		X		X
D90°	X			X
DSQ90°	X	X		
T120°*	X			X
TSQ90°	X		X	
Q90°	X	X	X	X
Single PSQ	X			X
Double PSQ	X		X	

*Other two locations will be 120° to the left and right of Side A.

Note: Standard SF and DF pole preparations are located 3/4 of the height of the pole from the base, unless otherwise specified.

SHIPPING WEIGHTS - Steel Square Poles

4"(102mm) sq. 11 Ga. (approximately)	7.33 lbs/ft.
4"(102mm) sq. 07 Ga. (approximately)	10.66 lbs/ft.
5"(127mm) sq. 11 Ga. (approximately)	9.20 lbs/ft.
5"(127mm) sq. 07 Ga. (approximately)	12.20 lbs/ft.
6"(152mm) sq. 07 Ga. (approximately)	15.45 lbs/ft.
Anchor Bolts (3/4" x 30") (19mm x 762mm)	12 lbs. (5.4kg) ea.
Anchor Bolts (1" x 36") (25mm x 914mm)	23 lbs. (10.4kg) ea.

ARRA Funding Compliant

Project Name _____ Fixture Type _____ 11/22/17
Catalog # _____ © 2017 LSI INDUSTRIES INC.

POLE SHAFT - Pole shaft is electro-welded ASTM-A500 Grade C steel tubing with a minimum yield strength of 50,000 psi. On Tenon Mount steel poles, tenon is 2-3/8" O.D. high-strength pipe. Tenon is 4-3/4" in length. Straight poles are 4", 5", and 6" square.

HAND-HOLE - Standard hand-hole location is 12" above pole base. Poles 22' and above have a 3" x 5" reinforced handhole. Shorter poles have a 2" x 4" size reinforced hand-hole.

BASE - Pole base is ASTM-A36 hot-rolled steel plate with a minimum yield strength of 36,000 psi. Two-piece square base cover is optional.

ANCHOR BOLTS - Poles are furnished with anchor bolts featuring zinc-plated double nuts and washers. Galvanized anchor bolts are optional. Anchor bolts conform to ASTM F 1554-07a Grade 55 with a minimum yield strength of 55,000 psi.

GROUND LUG - Ground lug is standard.

DUPLEX RECEPTACLE - Weatherproof duplex receptacle is optional.

GROUND FAULT CIRCUIT INTERRUPTER - Self-testing ground fault circuit interrupter is optional.

FINISHES - Each pole is finished with DuraGrip®, LSI's baked-on polyester-powder finishing process which electrostatically applies and fuses a polyester powder to the pole. Provides an extremely smooth and uniform finish to withstand extreme weather changes without cracking or peeling, and features a five-year limited warranty. Optional DuraGrip® Plus features the added protection of a 3.0 to 5.0 mil thickness of polyester-powder finish plus an inner coating, as well as a seven-year limited warranty.

DETERMINING THE LUMINAIRE/POLE COMBINATION FOR YOUR APPLICATION:

- Select luminaire from luminaire ordering information
- Select bracket configuration if required
- Determine EPA value from luminaire/bracket EPA chart
- Select pole height
- Select MPH to match wind speed in the application area (See windspeed maps).
- Confirm pole EPA equal to or exceeding value from note above
- Consult factory for special wind load requirements and banner brackets

Project Name _____ Fixture Type _____ 11/22/17
Catalog # _____ © 2017 LSI INDUSTRIES INC.

Catalog # : | Project :
Prepared By : | Date :



Features & Specifications

Optical System

- State-of-the-Art one piece silicone optic sheet delivers industry leading optical control with an integrated gasket to provide IP66 rated sealed optical chamber in 1 component.
- Proprietary silicone refractor optics provide exceptional coverage and uniformity in IES Types 2, 3, SW, FT and FTA.
- Silicone optical material does not yellow or crack with age and provides a typical light transmittance of 93%.
- Zero uplight.
- Available in 5000K, 4000K, 3000K, and amber color temperatures per IESNA RP-8-00 & TM-15-07. Also available in Phosphor Converted Amber, consult factory for availability.
- Minimum CRI of 70 (additional 80 CRI available, consult factory for lead time.
- Integral Louver (IL) option available for improved back-light control without sacrificing street side performance. See page 5 for more details.

Electrical

- Multi-performance driver features over-voltage, under-voltage, short-circuit and over temperature protection.
- 0-10V dimming (10% - 100%) standard.
- Standard Universal Voltage (120-277 Vac) Input 50/60 Hz or optional High Voltage (347-480 Vac).
- L70 Calculated Life: >100k Hours (See Lumen Maintenance on Page 2)
- Total harmonic distortion: <20%
- Operating temperature: -40°C to +50°C (-40°F to +122°F). 42L lumen package rated to +40°C.
- Power factor: >.90
- Input power stays constant over life.
- Field replaceable surge protection device meets a minimum Category C Low operation (per ANSI/IEEE C62.41.2).
- High-efficacy LEDs mounted to metal-core circuit board to maximize heat dissipation
- Terminal block provided accepts up to 10ga wire.
- Components are fully encased in potting material for moisture resistance. Driver complies with FCC standards. Driver and key electronic components can easily be accessed.

IP66 RoHS COMPLIANT ARRA cULus LISTED USA

Product Dimensions



LSI Industries Inc. 10200 Alliance Rd. Cincinnati, OH 45242 • www.lsi-industries.com • (513) 372-3200 • ©LSI Industries Inc. All Rights Reserved

MIRADA WALL SCONCE (XWM)

LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **XWM FT LED 08L 50 UE WHT IMS**

Prefix	Distribution	Light Source	Output[4]	Color Temperature	Input Voltage	Finish	Optional Controls	Optional Sensor/Options
XWM - Mirada Wall Sconce	2 - Type 2 3 - Type 3 (Wide Throw) FT – Type 4 (Forward Throw)	LED	02L - 2,400 Lumens 04L - 4,600 Lumens 06L - 6,600 Lumens 08L - 8,000 Lumens	50 - 5000K 40 - 4000K 30 - 3000K	UE - Universal Voltage (120-277) HV - 347-480	BLK - Black BRZ - Bronze GPT - Graphite MSV - Metallic Silver PLP - Platinum Plus WHT - White	**Wireless Control Network**[1,2] (blank) - None PCM - Platinum Control System CCM - Gold Control System ICM - 5-Pin networking (required for stability fixtures) ALCS - Acuity Synapse Control System **Stand-Alone Control** (blank) - None DIM - 0-10 volt dimming[3] (from external signal)	**Sensor** IMS - Integral Motion Sensor[4,5] **Options** BB - Battery Back-up[5] CWBB - Cold Weather Battery Back-up[5] XPMA - Pole Mounting Bracket

ACCESSORY ORDERING INFORMATION[1] (Accessories are field installed)

Description	Order Number	Description	Order Number
XWM FIN BLK - Surface Mount Box (available in black only)	1SXWFIN-X	ERC105 - Double Fusing	DRC001
FK105 - Single Fusing	FK105	ERC106 - Double Fusing	DRC002
FK277 - Single Fusing	FK277	ERC107 - Double Fusing	DRC003
FK347 - Single Fusing	FK347	PMS-PC - Remote Control Tool[2]	3SPC01

FOOTNOTES:
1 - For luminaire controls information and accessories, see Controls Section
2 - Requires a Bluetooth-enabled and override system. Not compatible with battery back-up, IMS or HL Options.
3 - Not compatible with IMS Option
4 - Not compatible with ICM or Wireless Control System
5 - Not compatible with 347-480 Input Voltage Option
6 - Not compatible with Wireless Control System
7 - Not compatible with Battery Back-up, IMS or HL Options
8 - Not compatible with 347-480 Input Voltage Option

DIMENSIONS



Project Name _____ Fixture Type _____ 10/20/17
Catalog # _____ © 2017 LSI INDUSTRIES INC.

MIRADA WALL SCONCE (XWM)



DOE LIGHTING FACTS
Department of Energy has verified representative product test data and results in accordance with its Lighting Facts Program. Visit www.lightingfacts.com for specific catalog listings.

LIGHT OUTPUT - XWM - 3 5000K CCT

	Lumens	Wattage	LPW
02	3412	29	117
04	4417	40	111
06	6699	59	113
08	8610	82	105

LED Chips are frequently updated therefore values may increase.

COVERAGE DIAGRAM

SIDE VIEW



TOP VIEW



US & Int'l. patents pending

SMARTTEC™ - LSI drivers feature integral sensor which reduces drive current, when ambient temperatures exceed rated temperature

ENERGY SAVING CONTROL OPTIONS - DIM - 0-10 volt dimming enabled with LSI wireless controls.

OPTIONAL INTEGRAL MOTION SENSOR - Passive infrared motion sensor activates switching of luminaire light levels. High level light is activated when passersby enter target zone and increased to full bright in 1-2 seconds. Low light level (20% of maximum drive current) is activated when target zone is absent of motion activity for 5 minutes and to gradually ramped down (10 seconds) to low level. Sensor detection range 110° horizontal x 95° vertical x 10 meters maximum distance.

LEDS - Available with 5000K, 4000K or 3000K color temperatures, 70 CRI min.

OPTICS/DISTRIBUTIONS - Ultra-high efficiency reflectors provide three distributions. Choose from Type 2, Type 3 or Type FT.

HOUSING - Three-piece die-cast aluminum housing is smoothly contoured low-profile shape. Mounting hardware is stainless steel or electro-zinc plated steel. Housing and optical unit are sealed with extruded silicone gasket; supply conductors with molded EPDM bushing.

OPTICAL UNIT - Proprietary silicone refractor optics provide exceptional coverage and uniformity. Pressure stabilizing breather silicon super-tight protection while preventing cycling from building up internal pressures and vacuums that can stress optical unit seals

WALL MOUNTING - Galvanized-steel universal wall mounting plate easily mounts directly to 4" octagonal or square junction box. EPDM gasket is supplied to be installed between mounting plate and junction box, sealing junction box from entrance of water. Universal plate permits fixture to be mounted in uplighting (indoor only) or downlighting position. Optional pole-mounting bracket permits mounting to standard poles (XPMA).

ELECTRICAL - Two-stage surge protection (including separate surge protection built into electronic driver) meets IEEE C62.41.2-2002, Location Category C. Available with universal voltage power supply 120-277VAC (50/60Hz input) or 347-480VAC.

DRIVER - Drivers are dimming, standard. Components are fully encased in potting material for IP65 moisture resistance. Driver complies with IEC and FCC standards. Driver can be easily accessed.

EMERGENCY OPTIONS - Optional integral emergency battery-back-up options are available. BB option operates in 0°C to 69°C ambient temperature and CWBB operates in -20°C to 60°C ambient temperature. When primary AC power failure occurs, both options operate 10 LEDs for minimum of 90 minutes.

OPERATING TEMPERATURE - -10°C to +55°C (-40°F to +122°F)

FINISH - Fixtures are finished with LSI's DuraGrip® polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling.

WARRANTY - LSI LED fixtures carry a limited 5-year warranty.

PHOTOMETRICS - Please visit our web site at www.lsi-industries.com for detailed photometric data.

SHIPPING WEIGHT (in carton) - 30 lbs./13.6Kg

LISTING - UL listed to ANSI/UL1598, UL8750 and other U.S. and international safety standards. Suitable for wet locations in downlight position.

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.

RoHS COMPLIANT cULus wet location CE ARRA Performance IP65 FC

Project Name _____ Fixture Type _____ 10/20/17
Catalog # _____ © 2017 LSI INDUSTRIES INC.

Mirada Medium - MRM
Outdoor LED Area Light

Performance (Cont.)

All published luminaire photometric testing performed to IESNA LM-79 standards. ISO footcandle plots below demonstrate the Mirada (MRM) light patterns only. Not for total fixture output. For complete specifications and IES files, see website.



Ordering Guide

TYPICAL ORDER EXAMPLE: **MRM LED 36L SIL FTA UNV DIM 50 70CRI ALSCS04 BRZ IL**

Luminaire Prefix	Light Source	Lumen Package*	Light Output	Distribution	Orientation[1]	Voltage	Driver
MRM Mirada	LED	7L - 7,000 lms 9L - 9,000 lms 12L - 12,000 lms 18L - 18,000 lms 24L - 24,000 lms 30L - 30,000 lms 36L - 36,000 lms 42L - 42,000 lms *Consult factory for programmable wattages and lumens packages	SIL - Silicone	2 - Type 2 3 - Type 3 SW - Type 5 Wide FT - Forward Throw FTA - Forward Throw Automotive	(blank) - standard L - Optics rotated left 90 R - Optics rotated right 90	UNV - Universal Voltage (120-277V) HV - High Voltage (347-480V)	DIM - 0-10V Dimming (0-10%)

Color Temp	Color Rendering	Controls (Choose One)	Finish	Options
50 - 5,000 CCT 40 - 4,000 CCT 30 - 3,000 CCT 27 - 2,700 CCT AMB - Phosphor Converted Amber[2,3]	70CRI - 70 CRI 80CRI - 80 CRI	**(Blank) - None** **Wireless Controls System** ALSC - AirLink Synapse Control System [4] ALSCH - AirLink Synapse Control System Host / Satellite[4,5] ALSCS01 - AirLink Synapse Control System with 8-12' Motion Sensor [4] ALSCHS01 - AirLink Synapse Control System Host / Satellite with 8-12' Motion Sensor [4,5] ALSCS02 - AirLink Synapse Control System with 12-20' Motion Sensor[4] ALSCHS02 - AirLink Synapse Control System Host / Satellite with 12-20' Motion Sensor [4,5] ALSCS04 - AirLink Synapse Control System with 20-40' Motion Sensor [4] ALSCHS04 - AirLink Synapse Control System Host / Satellite with 20-40' Motion Sensor [4,5] **Stand-Alone Controls** EXT - 0-10v Dimming (from external signal) IMSS01 - Integral Motion Sensor 8-12' 120-277V [4] IMSS02 - Integral Motion Sensor 12-20' 120-277V [4] IMSS04 - Integral Motion Sensor 20-40' 120-277V [4] IMSS01HV - Integral Motion Sensor 8-12' 347-480V [4,6] IMSS02HV - Integral Motion Sensor 12-20' 347-480V [4,6] IMSS04HV - Integral Motion Sensor 20-40' 347-480V [4,6] CRTP - 7 Pin Control Receptacle ANSI C136.41 [7] **Button Type Photocells** PC120 - 120V PC208-277 - 208-277V PC347 - 347V	BRZ - Bronze BLK - Black GPT - Graphite MSV - Metallic Silver WHT - White PLP - Platinum Plus SVG - Satin Verde Green	**(Blank) - None** IL - Integral Louver HSS[1]

LSI Industries Inc. 10200 Alliance Rd. Cincinnati, OH 45242 • www.lsi-industries.com • (513) 372-3200 • ©LSI Industries Inc. All Rights Reserved. 08/13/18

Order Plans @ WWW.LDLine.com

Cameron K. Collins, P.E. #29387
3309 S. Jefferson Ave.
Springfield, Missouri 65804
phone 417.881.0020
fax 417.881.0055
mfec
Malone Finkle Eckhardt & Collins, Inc.
MORE CHOICES EVEN EMPLOYABLE BY ARCHITECTS AND ENGINEERS © 2000

Craig A. Schneider, AIA
ARCHITECT
1736 East Sunshine, Suite 417
Springfield, Missouri 65804
417.862.0656
Fax: 417.862.3265
e-mail: architect@esterlyschneider.com

PROJECT:
NEW O'REILLY AUTO PARTS STORE
N. MAIN STREET
WALNUT COVE, NC

SITE LIGHTING DETAILS

O'Reilly AUTO PARTS
CORPORATE OFFICES
233 SOUTH PATTERSON
SPRINGFIELD, MISSOURI 65802
(417) 862-2674 TELEPHONE

COMM #	4300
DATE:	3-22-19
REVISION DATE:	

SP2

H:_JOBS_07900_DWG\07900SP2 9 Mar 2019 - 5:36 pm