

WATER HEATER SCHEDULE				
TAG	DESCRIPTION	MBH INPUT	RECOVERY	MANUFACTURER/MODEL NO.
DWH-1	GAS-FIRED INSTANTANEOUS DOMESTIC WATER HEATER	15,200 - 199,000	3.8 GPM @ 100° RISE	RINNAI CU1991
DWH-2	GAS-FIRED INSTANTANEOUS DOMESTIC WATER HEATER	15,200 - 199,000	3.8 GPM @ 100° RISE	RINNAI CU1991

- COMMENTS:
- REFERENCE SPECIFICATIONS FOR ADDITIONAL INFORMATION
  - U.L. LISTED
  - PROVIDE REMOTE CONTROLLERS
  - SET HOT WATER SUPPLY TEMPERATURE TO 140 DEGREES F

GAS CONNECTED LOAD SCHEDULE				
TAG	EQUIPMENT	INLET CONNECTION	MIN. SUPPLY INLET PRESSURE (WC)	INPUT LOAD (CFH)
43	3-BANK DEEP FRYER	1"	3.5"	225
DWH-1	TANKLESS WATER HEATER	3/4"	5"	199
DWH-2	TANKLESS WATER HEATER	3/4"	5"	199
RTU-1	HVAC ROOFTOP UNIT	3/4"	5"	240
RTU-2	HVAC ROOFTOP UNIT	3/4"	5"	130
			TOTAL	993

KITCHEN EQUIPMENT PLUMBING SCHEDULE										
GENERAL INFORMATION					PLUMBING INFORMATION					
TAG	QTY	DESCRIPTION	PROVIDED BY	INSTALLED BY	DCW	FW	DHW	DRAIN	GAS	REMARKS
2	1	12-HEAD DRINK DISPENSER	OWNER	OWNER	-	BY SODA VENDOR	-	3/4" & 1/2"	-	3/4" DRAIN FROM BIN & 1/2" DRAIN FROM TOWER.
5	2	WALL MOUNTED HAND SINK	OWNER	GC	1/2"	-	1/2"	1-1/2"	-	G.C. TO RUN PLUMBING AND CONNECT
8	1	8-HEAD DRIVE-THRU DRINK DISPENSER W/ OVERHEAD ICE MAKER ABOVE (SEE #92)	OWNER	OWNER	-	BY SODA VENDOR	-	3/4" & 1/2"	-	3/4" DRAIN FROM ICE MAKER & 1/2" DRAIN FROM TOWER.
12	1	SHAKE MACHINE	OWNER	VENDOR	-	-	-	-	-	REQUIRES CO2 OR COMPRESSED AIR, REQUIRES A SERVER 3 PUMP RAIL FOR SYRUPS.
19	1	3 COMPARTMENT SINK	OWNER	GC	1/2"	-	1/2"	1-1/2" F.S.	-	16" AFF (DCW AND DHW), 8" AFF (DRAIN), G.C. TO RUN PLUMBING AND CONNECT. INCLUDES (1) B231 FAUCET WITH 12" SPOUT, (1) B1338 FAUCET W/ BACKSPASH MOUNT, (1) B-157 PRE-RINSE FAUCET AND (3) LEVER WASTES
22	1	DISHWASHER	OWNER	VENDOR	-	-	1/2"	2" F.S.	-	INDIRECT DRAIN TO FS-1 WITH AIR GAP. ATMOSPHERIC VACUUM BREAKER INTEGRAL WITH DISHWASHER. VERIFY VACUUM BREAKER IS INSTALLED AT LEAST 6" ABOVE SPILL LINE AND LOCATED ON THE DISCHARGE SIDE OF THE LAST CONTROL VALVE.
30	1	PREP TABLE 2/ BACKSPASH AND PREP SINK	OWNER	GC	1/2"	-	1/2"	1-1/2"	-	16" AFF (DCW AND DHW), 8" AFF (DRAIN), G.C. TO RUN PLUMBING AND CONNECT. INCLUDES (1) B231 FAUCET WITH 12" SPOUT, (1) B1338 FAUCET W/ BACKSPASH MOUNT, (1) B-157 PRE-RINSE FAUCET AND (3) LEVER WASTES
43	1	3 BANK, 6 BASKET FRYER W/ NATURAL GAS	OWNER	VENDOR	-	-	-	-	1"	(3) @ 75,000 BTU/H INPUT PER FRYPOT. FACTORY MANIFOLD TO (1) CONNECTION TOTAL 225,000 BTU/H, 1" CONNECTION AT 11.5" AFF. G.C. TO HOOK UP QUICK DISCONNECT (SUPPLIED BY KES). INCLUDE DORMONT GAS HOSE KIT #16100-41-48. ALSO INCLUDE DIVERTER KIT TO ALLOW HOOK-UP TO DARLING 1500 H UNIT.
49	1	COFFEE MAKER	OWNER	VENDOR	-	1/4"	-	-	-	PROVIDE A 1/2" X 1/4" LEAD-FREE CHROME PLATED BRASS 1/4-TURN BALL STOP, WATTS #SD-3 ASSE 1022 LISTED LISTED DUAL CHECK BACKFLOW PREVENTER W/ INLET STRAINER AND FOOD GRADE PLASTIC TUBING ON SUPPLY CONNECTION.
60	1	DRIVE THRU COUNTER W/ DROP-IN HAND SINK	OWNER	VENDOR	1/2"	1/2"	1/2"	1-1/2"	-	16" AFF (DCW AND DHW), 8" AFF (DRAIN), G.C. TO RUN PLUMBING AND CONNECT.
84	1	WATER BOOST MODULAR FILTER SYSTEM	OWNER	VENDOR	3/8"	3/8"	-	-	-	PROVIDE A 1/2" X 3/8" LEAD-FREE CHROME PLATED BRASS 1/4-TURN BALL STOP, WATTS #SD-3 ASSE 1022 LISTED LISTED DUAL CHECK BACKFLOW PREVENTER W/ INLET STRAINER AND FOOD GRADE PLASTIC TUBING ON SUPPLY CONNECTION.
92C	2	ICE MAKER	OWNER	VENDOR	1/2"	1/2"	-	-	-	PROVIDE A 1/2" X 3/8" LEAD-FREE CHROME PLATED BRASS 1/4-TURN BALL STOP, WATTS #SD-3 ASSE 1022 LISTED LISTED DUAL CHECK BACKFLOW PREVENTER W/ INLET STRAINER AND FOOD GRADE PLASTIC TUBING ON SUPPLY CONNECTION.

PLUMBING FIXTURE SCHEDULE											
FIXTURE				ACCESSORIES				DESCRIPTION			
TAG	ITEM	MANUFACTURER	MODEL	DCW	DHW	DRAIN	VENT	ITEM	MANUFACTURER	MODEL	DESCRIPTION
WC-1	WATER CLOSET	ZURN	Z5665-8WL-AM	1"	-	4"	2"	SEAT	ZURN	Z5955S-E	ADA COMPLIANT FLOOR MOUNTED WHITE VITREOUS CHINA TOILET, ELONGATED BOWL, 16-1/2" RIM HEIGHT, EXPOSED 1-1/2" TOP SPUD, 1.28 GPF. PROVIDE FLOOR BOLTS, WAX RING & BOLT COVERS. PROVIDE HEAVY-DUTY PLASTIC ELONGATED OPEN FRONT SEAT LESS COVER WITH STAINLESS STEEL SELF-SUSTAINING CHECK HINGES. PROVIDE CHROME PLATED BRASS 1.28 GPF HARD WIRED SENSOR ACTIVATED FLUSHMETER WITH MANUAL OVERRIDE FLUSH BUTTON. INSTALL FLUSH VALVE SO FLUSH LEVER IS LOCATED ON WIDE SIDE OF STALL.
LAV-1	LAVATORY	ZURN	Z5344	3/8"	3/8"	1-1/4"	1-1/2"	FLUSHMETER	ZURN	ZEM6000AV-HE	ADA COMPLIANT WALL MOUNTED WHITE VITREOUS CHINA LAVATORY, 4" CENTER FAUCET HOLES, OVERFLOW. PROVIDE CHROME PLATED BRASS 4" CENTERSET HARD WIRED SENSOR ACTIVATED FAUCET, 0.5 GPM VANDAL RESISTANT SPRAY HEAD. PROVIDE CHROME PLATED GRID STRAINER DRAIN WITH CHROME PLATED BRASS TAILPIECE. PROVIDE CHROME PLATED BRASS P-TRAP WITH CLEANOUT, WALL BEND AND WALL FLANGE. PROVIDE CHROME PLATED BRASS LOOSE KEY ANGLE BALL STOP WITH CHROME PLATED FLEXIBLE COPPER SUPPLY RISERS. PROVIDE CHROME FINISH ASSE 1070 LISTED UNDER-SINK THERMOSTATIC MIXING VALVE SET AT 108°F. PROVIDE MOLDED VINYL SAFETY COVERS FOR ALL EXPOSED SUPPLY AND DRAIN PIPING. PROVIDE RIGID IN-WALL CONCEALED ARM LAVATORY SUPPORT SYSTEM.
MS-1	MOP SINK	ZURN	Z1996-24	1/2"	1/2"	1-1/2"	1-1/2"	FAUCET	ZURN	Z6915-XL-WB-F	FLOOR MOUNTED ONE-PIECE MOLDED FIBERGLASS MOP SERVICE BASIN WITH INTEGRAL MOLDED-IN DRAIN AND REMOVABLE STAINLESS STEEL STRAINER. PROVIDE CHROME PLATED CAST BRASS SERVICE SINK FAUCET WITH COLOR-CODED METAL LEVER HANDLES, QUARTER-TURN CERAMIC DISC CARTRIDGES, INTEGRAL SERVICE STOPS, INTEGRAL CHECK STOPS, 6" CAST BRASS SPOUT WITH VACUUM BREAKER, 3/4" HOSE THREAD OUTLET, PAIL HOOK AND ADJUSTABLE WALL BRACE. PROVIDE HOSE AND STAINLESS STEEL HOSE HOLDER, STAINLESS STEEL MOP HANGER, STAINLESS STEEL BUMPER GUARDS, STAINLESS STEEL WALL GUARDS. INSTALL FAUCET AT 36" ABOVE FINISH FLOOR.

PLUMBING EQUIPMENT SCHEDULE				
TAG	ITEM	MANUFACTURER	MODEL NO.	COMMENTS
TP-1	TRAP PRIMER	PRECISION PLUMBING	PR-500	ALL BRASS BODY TRAP PRIMER VALVE, PRESSURE DROP OF 5 - 10 PSIG OPENS VALVE, OPERATING RANGE: 35 - 75 PSIG, 1/2" MALE NPT INLET CONNECTION, 1/2" FEMALE NPT OUTLET CONNECTION.
ET-1	EXPANSION TANK	ZURN	XT-18	THERMAL EXPANSION TANK, MOUNT ON WALL NEAR WATER HEATER. SEE PLANS FOR EXACT LOCATION. REFER TO DETAIL ON SHEET P4-20.
RP-1	RECEIVING PUMP	GRUNDFOS	ALPHA 15-55SF	ALL BRONZE CONSTRUCTION, LISTED FOR POTABLE WATER SERVICE AND 120 PSIG WORKING PRESSURE, 6.3 GPM AT 6 FEET OF HEAD, 115 VOLTS, 45 WATTS. SINGLE PHASE, 3250 RPM. MOUNT PUMP NEAR WATER HEATER IN ACCESSIBLE LOCATION. PUMP TO BE ON A TIMECLOCK. REFER TO ELECTRICAL DRAWINGS FOR ADDITIONAL INFORMATION.
B-1	EXTERIOR WALL HYDRANT	ZURN	Z1321-C-8FP	EXTERIOR FREEZE-PROOF WALL HYDRANT RECESSED IN LOCKABLE WALL BOX, AUTOMATIC DRAINING WITH INTEGRAL ASSE 1052 APPROVED DOUBLE CHECK BACKFLOW PREVENTER, LOOSE KEY, HARDENED STAINLESS STEEL OPERATING STEM AND ONE-PIECE VALVE PLUNGER TO CONTROL BOTH FLOW AND DRAIN FUNCTIONS. BRONZE SEAT AND SEAT WASHER, 3/4" INLET AND 3/4" HOSE OUTLET CONNECTION. CHROME FINISH, ANODIZED ALUMINUM WALL BOX AND DOOR WITH OPERATION KEY LOCK AND "WATER" STAMPED ON COVER. INSTALL UNIT AT 24" ABOVE FINISHED GRADE AND SECURE TO STRUCTURE.


DRAIN AND CLEANOUT SCHEDULE				
TAG	ITEM	MANUFACTURER	MODEL NO.	COMMENTS
FD-1	FLOOR DRAIN	ZURN	FR06NIC3N	LIGHT-DUTY PLASTIC FLOOR DRAIN WITH 6" DIA. NICKEL BRONZE STRAINER, MEMBRANE FLASHING CLAMP AND 1/2" TRAP PRIMER CONNECTION. PROVIDE OUTLET WITH P-TRAP. CLEAN AND POLISH ROUND STRAINER TOP AFTER INSTALLATION.
FD-2	FLOOR DRAIN	ZURN	FR06NIC3N-F	SAME AS FD-1, PROVIDE WITH 4" DIA. NICKEL BRONZE FUNNEL.
FS-1	FLOOR SINK INDIRECT WASTE RECEPTOR	ZURN	FD2370-PVC-DS-H-Y	PVC PLASTIC FLOOR RECEPTOR WITH 12" X 12" SQUARE TOP, 6" DEEP SUMP BODY, PVC BODY, PVC LOOSE SET 1/2 GRATE, STAINLESS STEEL DEBRIS BASKET AND ANCHOR FLANGE. PROVIDE OUTLET WITH P-TRAP. PROVIDE WITH FLASHING COLLAR WHERE REQUIRED.
RD-1	PRIMARY ROOF DRAIN	SIOUX CHIEF	866-1504	ROOF DRAIN WITH CAST IRON BODY, LARGE SUMP, ROOF/DECK RECEIVER PAN, CLAMPING COLLAR, DECK CLAMP. REMOVABLE 15" DIAMETER ROUND ALUMINUM DOME STRAINER, FLASHING/MEMBRANE CLAMP, GRAVEL STOP & BOTTOM NO-HUB OUTLET CONNECTION. FINISH WITH BODY EXTENSION (IF REQUIRED) FOR BUILT-UP ROOF CONSTRUCTION. PIPE SIZE AS INDICATED ON DRAWINGS.
CO	EXPOSED ACCESSIBLE CLEANOUT	ZURN	Z81470	COUNTER-SUNK TAPERED THREAD BRONZE PLUG.
CO-1	FINISHED AREA FLOOR CLEANOUT	ZURN	CR06NIC3N	LIGHT-DUTY CAST IRON CLEANOUT WITH GAS TIGHT POLYPROPYLENE PLUG, AND 6" DIA. ADJUSTABLE SCORRIATED NICKEL BRONZE TOP.
CO-2	FINISHED AREA WALL CLEANOUT	ZURN	Z1441	PROVIDE CLEANOUT TEE. PROVIDE COUNTERSINK ABS TAPERED THREAD PLUG AND ROUND SMOOTH STAINLESS STEEL WALL ACCESS COVER AND SECURING SCREW.
CO-3	EXTERIOR CLEANOUT	ZURN	ZN1400-HD	EXTRA HEAVY-DUTY ADJUSTABLE CLEANOUT, CAST IRON BODY WITH ANCHOR FLANGE AND ABS TAPERED THREAD PLUG. ROUND SCORRIATED EXTRA HEAVY-DUTY NICKEL-BRONZE VENEER CAST IRON COVER. SET TOP OF CASTING FLUSH WITH ADJACENT FINISHED PAVEMENT.

Order Plans @

WWW.DILLIN.COM

red  
architecture + planning  
174 east long street  
suite 300  
columbus, ohio 43215  
tel: 614.487.8770  
fax: 614.487.8777

PROFESSIONAL INFORMATION NOTICE  
THESE PROTOTYPICAL DOCUMENTS MAY BE SUBJECT TO CHANGE WITHOUT NOTICE. THE DESIGN CONCEPTS EMBODIED IN THESE DOCUMENTS ARE SPECIFICALLY FOR THIS PROJECT. INFORMATION CONTAINED HEREIN REMAINS THE SOLE PROPERTY OF ARBY'S RESTAURANT GROUP. IT IS CONFIDENTIAL AND PROPRIETARY AND IS NOT TO BE COPIED, REPRODUCED, DISCLOSED OR OTHERWISE TRANSMITTED TO OTHER PARTIES IN ANY FORM WHATSOEVER WITHOUT THE EXPRESS WRITTEN CONSENT OF ARBY'S RESTAURANT GROUP.



Copyright © 2019 by Arby's Restaurant Group

ARBY'S RESTAURANT  
INSPIRE WORKSMART 2400  
2385 LEN PATTERSON RD  
FORT MILL, SC 29708  
FOR  
BRUMIT RESTAURANT GROUP, LLC  
40 SEMINOLE STREET, ASHEVILLE, NC 28803

PROJECT NUMBER:  
ARF149

ISSUE DATE  
OWNER REVIEW AUG 7, 2019

SCHEDULES  
PLUMBING

SHEET:

P5.1

NOT FOR CONSTRUCTION, FOR REFERENCE ONLY