ACO DRAIN
KlassikDrain - K100 Galvanized steel edge rail channel system

One meter channel



Type K901G In line catch basin



Outlet flow rates

Outlet	Product	Outlet dia (Sch. 40)	Invert Depth	GPM	CFS
a	Bottom outlet - K60	4" round	3.94"	108	0.24
e	Bottom outlet - K40	4" round	11.81"	187	0.42
b	Bottom outlet - K60	6" oval	3.94"	177	0.39
b	Bottom outlet - K40	6" oval	11.81"	300	0.68
c	End outlet - K60	4" round	7.87"	132	0.29
c	End outlet - K40	4" round	11.81"	171	0.38
d	K1-3066 6" outlet cap	6" oval	9.84"	293	0.52
e	K1-4086 6" outlet cap	6" oval	11.81"	264	0.59
f	Type K1-901G	4" round	25.20"	236	0.52
g	Type K1-901G	4" round	25.57"	266	0.59
h	Type K1-901G	4" round	25.20"	263	0.59
i	Type K1-901G	4" round	18.16"	222	0.49
j	Type K1-901G	6" round	25.85"	586	1.30
k	Type K1-901G	4" round	26.43"	269	0.60
l	Type K1-901G	4" round	19.28"	227	0.51
m	Type K1-901G	6" round	27.36"	604	1.35
n	Type K1-901G	6" round	19.99"	505	1.12
o	Type K1-901G	4" round	26.43"	593	1.32
p	Type K1-901G	6" round	27.36"	1051	2.34
q	Type K1-901G	4" round	27.17"	273	0.61
r	Type K1-901G	4" round	25.68"	235	0.52
s	Type K1-901G	4" round	18.99"	224	0.50
t	Type K1-901G	4" round	27.17"	670	1.34

Note: These are the pipe flow rates at the specified outlet, NOT channel flow rates. Catch basin flow rates are without trash bucket - using trash bucket reduces flow.

End Cap



6" Oval inlet cap



6" Oval outlet cap

April 2018

www.ACODrain.us

ACO Specification Information

ACO DRAIN
KlassikDrain - K100 Galvanized steel edge rail channel system

Description	Part No.	Invert Outlet	Invert Inlet	Weight lbs/ft
K1-00 Neutral channel - 39.37" (1m)*	74041	3.94	100	28.1
K1-1 Sloped channel - 39.37" (1m)	74001	4.13	105	28.1
K1-2 Sloped channel - 39.37" (1m)	74002	4.33	110	29.9
K1-3 Sloped channel - 39.37" (1m)	74003	4.53	115	29.7
K1-4 Sloped channel - 39.37" (1m)	74004	4.72	120	30.3
K1-5 Sloped channel - 39.37" (1m)	74005	4.92	125	31.3
K1-6 Sloped channel - 39.37" (1m)	74006	5.12	130	32.1
K1-7 Sloped channel - 39.37" (1m)	74007	5.31	135	30.9
K1-8 Sloped channel - 39.37" (1m)	74008	5.51	140	33.7
K1-9 Sloped channel - 39.37" (1m)	74009	5.71	145	34.5
K1-10 Sloped channel - 39.37" (1m)*	74010	5.91	150	35.3
K1-010 Neutral channel - 39.37" (1m)*	74043	5.91	150	36.8
K1-0010 Neutral channel - 19.69" (0.5m)*	74044	5.91	150	17.0
K1-11 Sloped channel - 39.37" (1m)	74011	6.10	155	36.1
K1-12 Sloped channel - 39.37" (1m)	74012	6.30	160	36.9
K1-13 Sloped channel - 39.37" (1m)	74013	6.50	165	37.7
K1-14 Sloped channel - 39.37" (1m)	74014	6.69	170	38.5
K1-15 Sloped channel - 39.37" (1m)*	74015	6.89	175	39.3
K1-16 Sloped channel - 39.37" (1m)	74016	7.09	180	40.1
K1-17 Sloped channel - 39.37" (1m)	74017	7.28	185	40.9
K1-18 Sloped channel - 39.37" (1m)	74018	7.48	190	41.7
K1-19 Sloped channel - 39.37" (1m)	74019	7.68	195	42.5
K1-20 Sloped channel - 39.37" (1m)*	74020	7.87	200	43.4
K1-020 Neutral channel - 39.37" (1m)*	74045	7.87	200	43.4
K1-0020 Neutral channel - 19.69" (0.5m)*	74046	7.87	200	20.5
K1-21 Sloped channel - 39.37" (1m)	74021	8.07	205	44.2
K1-22 Sloped channel - 39.37" (1m)	74022	8.27	210	45.0
K1-23 Sloped channel - 39.37" (1m)	74023	8.46	215	45.8
K1-24 Sloped channel - 39.37" (1m)	74024	8.66	220	46.6
K1-25 Sloped channel - 39.37" (1m)*	74025	8.86	225	47.4
K1-26 Sloped channel - 39.37" (1m)	74026	9.06	230	48.2
K1-27 Sloped channel - 39.37" (1m)	74027	9.25	235	49.0

Description	Part No.	Invert Outlet	Invert Inlet	Weight lbs/ft
K1-28 Sloped channel - 39.37" (1m)	74028	9.45	240	49.8
K1-29 Sloped channel - 39.37" (1m)	74029	9.65	245	50.6
K1-30 Sloped channel - 39.37" (1m)*	74030	9.84	250	51.4
K1-030 Neutral channel - 39.37" (1m)*	74047	9.84	250	51.4
K1-0030 Neutral channel - 19.69" (0.5m)*	74048	9.84	250	24.0
K1-31 Sloped channel - 39.37" (1m)	74031	10.04	255	52.2
K1-32 Sloped channel - 39.37" (1m)	74032	10.24	260	53.0
K1-33 Sloped channel - 39.37" (1m)	74033	10.63	270	54.6
K1-34 Sloped channel - 39.37" (1m)	74034	10.63	270	54.6
K1-35 Sloped channel - 39.37" (1m)	74035	10.82	275	55.4
K1-36 Sloped channel - 39.37" (1m)	74036	11.02	280	56.2
K1-37 Sloped channel - 39.37" (1m)	74037	11.22	285	57.0
K1-38 Sloped channel - 39.37" (1m)	74038	11.42	290	57.9
K1-39 Sloped channel - 39.37" (1m)	74039	11.61	295	58.7
K1-40 Sloped channel - 39.37" (1m)*	74040	11.81	300	59.5
K1-040 Neutral channel - 39.37" (1m)*	74049	11.81	300	59.5
K1-0040 Neutral channel - 19.69" (0.5m)*	74050	11.81	300	27.5
K1-956 Chrome steel kerb - 19.69" (0.5m)*	94408	11.81	N/A	62.6
K1-4211 Catch basin - 19.69" (0.5m)*	94617	29.84	7322	55.8
K1-4213 Catch basin - 19.69" (0.5m)*	94631	40.84	8224	60.8
K-Series 600 Optional grate riser	99902			10.0
Anti-tilt clip - fits both 600 & 400 series bases	90854			1.2
K1-3066 6" Inlet Cap	96839	9.84	295	5.2
K1-3086 6" Outlet Cap	96840	9.84	295	5.0
K1-4046 6" Inlet Cap	96834	11.81	300	6.0
K1-4086 6" Outlet Cap	96836	11.81	300	5.8
Universal end cap	96622	11.81	300	0.4
Gutters drainfree for 6" bottom knockout	94608	11.81	N/A	0.2
4" Quil to 6" mount outlet adaptor	90140			1.1
KlickLok/Lok Brace	97477			3.6
Grate removal tool	01318			0.3
K1-Quicklok locking bar	02899			0.1

Notes:
1. This channel offers a bottom knockout feature, 4" round/6" oval.
2. Inverts shown are for the male end, for female invert (built out) add 0.5mm (~0.2") from the male invert (except for neutral channels), where it will be same as male invert to calculate the overall channel depth add 20mm (~0.8") to invert depth.
3. This catch basin kit includes a polymer concrete top, removable Quicklok locking bar, trash bucket and plastic base. Select an appropriate grate.
4. This catch basin kit includes a polymer concrete top, removable Quicklok locking bar, door, trash bucket, plastic riser and plastic base. Select an appropriate grate.

Specifications

General
The surface drainage system shall be ACO Drain KlassikDrain complete with gratings secured with "QuickLok" locking as manufactured by ACO, Inc. or approved equal.

Materials
The trench system bodies shall be manufactured from polyester polymer concrete with the minimum properties as follows:

Compressive strength:	18,000 psi
Flexural strength:	4,000 psi
Water absorption	0.07%
Frost proof	YES
Salt proof	YES
Oil & acid and alkali resistant	YES

The nominal clear opening shall be 4" (100mm) with overall width of 5.12" (130mm). Trim-end units shall be manufactured with 40% of an invert slope of 0.5% or with neutral invert and have a wall thickness of at least 1.52" (13mm). Each unit will feature a pre-bevelled radius in the trench bottom and a male to female interconnecting end detail. Units shall have horizontal cast in anchoring keys on the outside wall to ensure maximum interlock and bond to the surrounding bedding material and pavement surface. The galvanized steel edge rail will be integrally

Grates
Grates shall be specified. See separate ACO Slot Mat grates brochure for details. After removal of grates, use "QuickLok" bar (three shall be unintended) access to the trench to aid maintenance.

Installation
The trench drain system shall be installed in accordance with the manufacturer's instructions and recommendations.

cast in by the manufacturer to ensure maximum fine bonding between polymer concrete body and edge material. Each edge rail shall be cut 0.2" (5mm) short of the trench.

ACO, Inc.
Northeast Sales Office
9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230
Toll free: (800) 543-4764
Fax: (440) 639-7235

West Sales Office
825 W. Beechcroft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-0899

Southeast Sales Office
4211 Pheasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on
Electronic Contact:
info@ACODrain.us
www.ACODrain.us

© ACO 2018, ACO, Inc. This information is believed to be accurate but is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for its own use. ACO, Inc. reserves the right to change the product and specifications without notice.

SPEC INFO

April 2018

www.ACODrain.us

ACO Specification Information

LEVEL SPREADER (Lv)
NOT TO SCALE

1

ACO DRAIN
4" width - ductile iron longitudinal grate

Product Features

- Certified to EN 1433 Load Class F - 200,000 lbs - 4,182 psi
- Uses 'PowerLok' boltless locking system
- Suitable for use with S100K and H100K channels
- Manufactured from ductile iron to ASTM A 536-84 - Grade 304 65-45-12
- Anti-Shunt lugs



Specifications

General
The surface drainage system shall be ACO PowerDrain or SlotDrain, complete with ACO ductile iron longitudinal grate with 'PowerLok' locking as manufactured by ACO, Inc. or similar approved.

Materials
The covers shall be manufactured from ductile iron and have mechanical properties as follows:

- **Independently certified to meet Load Class F to EN 1433 - 200,000 lbs - 4,182 psi**
- **Ductile iron to ASTM 536-84 - Grade 60-45-12**
- **Intake capacity of 13.4 sq. cm per meter of grate**

The overall width of 5.43" (138mm) shall be made of 19 bars with a pitch of 0.98" (25mm) at a minimum depth of 1.38" (34mm).

Grates
Grates shall be ductile iron conforming to ASTM A536 Grade 65-45-12. After removal of grates, users shall be unobstructed access to the trench for ease maintenance.
Grates are not used for PowerDrain or SlotDrain.

Installation
The trench drain system shall be installed in accordance with the manufacturer's instructions and recommendations.

* device as appropriate

April 2018

www.ACODrain.us

ACO Specification Information

ACO DRAIN
4" width - ductile iron longitudinal grate

Plan view

Side elevation

Description		Length inches (mm)	Width inches (mm)	Weight lbs
PowerLok gr... ductile iron longitudinal grate	96096	19.68 (500)	5.43 (138)	13.0

PowerLok locking mechanism



ACO **PowerLok** is a patented boltless locking system. Grates are removed and replaced with minimum time and effort for ease of maintenance.

Lugs on the rail opposite the **PowerLok** device slots into recesses in the grate. The **PowerLok** device is used to engage the lug on the rail at two locations per grate to 'lock' the grate to the channel.

ACO, Inc.
Northeast Sales Office
9470 Pinecone Drive
Mentor, OH 44060
Tel: (440) 639-7230
Toll free: (800) 543-4764
Fax: (440) 639-7235

West Sales Office
825 W. Beechcroft St.
Casa Grande, AZ 85122
Tel: (520) 421-9988
Toll Free: (888) 490-9552
Fax: (520) 421-0899

Southeast Sales Office
4211 Pheasant Road
Fort Mill, SC 29708
Toll free: (800) 543-4764
Fax: (803) 802-1063

Follow us on
Electronic Contact:
info@ACODrain.us
www.ACODrain.us

© ACO 2018, ACO, Inc. This information is believed to be accurate but is not guaranteed to be so. We cannot assume liability for results that buyer obtains with our product since conditions of use are beyond the control of the company. It is the customer's responsibility to evaluate suitability and safety of product for its own use. ACO, Inc. reserves the right to change the product and specifications without notice.

SPEC INFO

April 2018

www.ACODrain.us

ACO Specification Information

TRENCH DRAIN DETAILS
NOT TO SCALE

2



NOTES:

1.) WEIR CONFIGURATION SHOWN FOR CONCEPTUAL PURPOSES ONLY

2.) THREADED END CAP WITH ORIFICE REQ'D FOR ORIFICE DIA. < 4".

3.) STONE FILTER SHALL BE #4 STONE OR SMALLER.

4.) FOR ROUND STRUCTURES PROVIDE 48" 3/4 ROUND PERFORATED WITH 0.5" DIA. HOLES. HINGED LID TO BE OF EXPANSED METAL WITH 0.75" x 0.5" OPENDINGS.

5.) ORIFICE & CORRESPONDING PIPE SIZES:

ORIFICE SIZE	PIPE SIZE
< 3"	6"
3" TO < 5"	8"
5" TO < 11"	12"

DETENTION OUTLET CONTROL STRUCTURE - FILTER RING DETAIL
NOT TO SCALE

3

NOTE: OCS RISER TO BE STANDARD 48" INSIDE DIMENSION PRECAST SQUARE MANHOLE.



FRONT VIEW



TRASH RACK
*TO BE PROVIDED AT EACH ORIFICE



PROFILE VIEW

ANTI-FLOATATION CALCULATION:	
BOUYANT FORCE (48" DIA.): (LB/VERT. FT OF OCS)	784.1 LB
CONCRETE: (CF PER V.F. TO PREVENT FLOATATION)	10.98 CF
HEIGHT OF OCS	3.5'
CONCRETE REQUIRED	= 38.43 CF
CONCRETE DEPTH = CONCRETE REQUIRED / AREA OF CONC. BASE (36 SF)	= 1.07 FT = 13"

DETENTION OUTLET CONTROL STRUCTURE DETAIL
NOT TO SCALE

4

PREPARED IN THE OFFICE OF:
LECRAW ENGINEERING

© 2019 LECRAW ENGINEERING, INC.

3475 CORPORATE WAY
SUITE A
DULUTH, GA 30096
PHONE - 678.546.8100
FAX - 678.546.8105
WWW.LECRAWENGINEERING.COM
COA - 4400

REV. #	DESCRIPTION	DATE	DRAWN BY	CHECKED BY
1	COUNTY & SCDOT COMMENTS	09/23/19	MAT	MSL

CLIENT
CAROLINA RE HOLDINGS, LLC
300 GALLERIA PARKWAY - ATLANTA, GA 30339

PROJECT
BURGER KING - BEECH ISLAND, SC
BEECH ISLAND AVENUE & ATOMIC DRIVE
AIKEN COUNTY, SOUTH CAROLINA

FOR INFORMATIONAL PURPOSES ONLY

DESIGN TEAM:

DRAWN BY:	MAT
DESIGNED BY:	MAT
REVIEWED BY:	MSL

811 Know what's below. Call before you dig.

DETAILS ARE NOT DRAWN TO SCALE

JOB #: 259004
DATE: JULY 18, 2019

CONSTRUCTION DETAILS - 6

C-7.5

Drawing name: L:\259004 - Carolina RE Holdings, LLC - Burger King - Beech Island_SC\CAD\CONSTR\259004 - 10 - DETAILS.dwg CONSTRUCTION DETAILS - 6 Aug 28, 2019 8:56am by michael.bodiker

This document, together with the concepts and designs presented herein, as an instrument of service, is intended only for the specific purpose and client for which it was prepared. Reuse of and improper reliance on this document without written authorization and adaptation by LeCraw Engineering, Inc. shall be without liability to LeCraw Engineering, Inc. Copyright LeCraw Engineering, Inc., 2019

Order Plans @ WWW.LDI.me.com