



5905 Shihon Road East, Suite 200
Alpharetta, Georgia 30005 | (770) 565-4508



08/30/2019

Item K03
1 Each **HOT FOOD SERVING COUNTER - 4 Wall**
DUKE Model TEHF-60SS or equal

- Thurmaduke Hot Food Unit, mobile, electric, 60"L, 32"W, 34"H,
- 4 Stainless steel hot wells with drains, copper manifolds, (1) valve, individual thermostats
- Recess top to hold 18" x 26" pans
- 20ga undershelf
- 5" swivel casters (2 with brakes)
- 208v/60/1-ph, 3600 watts, 17.3 amps, NEMA L6-30 plug, 10' cord
- Internal locking device, stainless steel pin & latch line up device under counter top, on both ends
- 12" wide stainless tray slide with rubbing rails, 16ga stainless steel, on (2) stainless steel hinged brackets, located on customer's side locking device on right end, 6 round out-outs for silver ware cylinders on left end of tray slide
- Thurmaduke™ Designer Sneeze Guard, model TS580-60-1SN customized, Full service style breath guard on the lower shelf over left two wells and self service style breath guard on the lower shelf over the right two wells, No breath guards on top shelf. Stainless steel top and frame, blue TBD painted ends, with LED lights

Item K02
1 each **MECHANICALLY ASSISTED NSF 7 COLD PAN**
Duke Model TCM-60SS-N7 or equal

- 60" W x 32"D x 34" H
- 16 gauge, 300 series stainless steel top, stainless steel frame, Laminate front panel TBD
- 8" deep stainless steel mechanical assist cold pan, 1" drain line & valve
- 120v/60/1-ph, 60 cycle, 1-ph, 1/4 HP, 4.8 amps, R134A, NEMA #5-15, 10' cord
- Internal locking device, stainless steel pin & latch line up device under counter top, on both ends
- 4 - 5" dia. gray poly swivel casters (2 with brakes)
- 12" wide stainless tray slide, rubbing rails, 18ga stainless steel, on (2) stainless steel hinged brackets, located on customer's side
- Thurmaduke™ Designer Sneeze Guard, model TS580-60-1SN, self-service style breath guard on the lower shelf and no breath guard on the upper shelf, TBD Blue painted ends, LED lights

Item K01
1 each - **UTILITY SERVING COUNTER**
Duke Manufacturing Model TST-32SS or equal

- 32"W x 32"D x 34"H
- 16 gauge, 300 series stainless steel top, stainless steel frame, Laminate front panel
- 4 - 5" dia. gray poly swivel casters (2 with brakes)
- 12" wide solid stainless tray slide with rubbing rails, 18ga stainless steel, on (2) stainless steel hinged brackets, tray slide locking device located on right end, located on customer's side
- Thurmaduke™ Designer Sneeze Guard, model TS590-32-1SN, without breath guards, TBD Blue painted ends, LED lights

4 K03 SPECIFICATION
SCALE: 12" = 1'-0"

3 K02 SPECIFICATION
SCALE: 12" = 1'-0"

2 K01 SPECIFICATION
SCALE: 12" = 1'-0"

BANDIT AIR SCREEN
MODEL # SCRFC (60" HIGH UNIT)

SPECIFICATIONS

The Bandit Air Screen SCRFC Series is a grid type air filter. The unit is designed for use in a recirculating air conditioning system. It features a built-in fan motor and controls, allowing you to engage or disengage the unit as needed. The unit is easy to clean and maintain. The unit is designed for use in a recirculating air conditioning system. It features a built-in fan motor and controls, allowing you to engage or disengage the unit as needed. The unit is easy to clean and maintain. The unit is designed for use in a recirculating air conditioning system. It features a built-in fan motor and controls, allowing you to engage or disengage the unit as needed. The unit is easy to clean and maintain.

Available lengths: 36" 48" 60" 72"

Available depths: 12" 24" 48"

Available heights: 60"

STANDARD FEATURES

- Self-Contained Refrigeration
- Motor Front Case Conversion with 6-Speed Compressor Air Split
- Motor Front Case Conversion with Easy Access to Compressor
- Stainless Steel Laminate Exterior
- 48" Top Edge Protection
- Brusher Abutment Inside Ends
- Stainless Steel Perforated Interior Back Panel
- LED Top Convoy Light
- Adjustable Stainless Steel Extra Deep Shelves for Maximum Capacity
- Removable Stainless Steel Shelf with Removable Edge to Control Spills
- Electronic Digital Control and Defrost Termination
- Removable Right Electric Operator if Conversion Responses Clearing
- Trayed Temperature Display for Zone Clearance
- Unique Indirect Drive Design for Compressor Noise Reduction
- Frame Air Intake with Top Rear Air Discharge for Zone Clearance
- Easy-Open Top Convoy Unit #4, #5 & #6 Working
- #7 Cover and Plug
- Complies to NSF 2-T, Type 2 Refrigeration
- Environmentally Safe Refrigerant
- 1 Year Parts and Labor Warranty
- 5 Year Compressor Warranty

OPTIONAL FEATURES

- Stainless Refrigeration
- Stainless Steel Exterior Finish with Standard T-Modeling
- 1 Year 1-800-839-2331
- Special Laminate
- Motor Housing (Brushed & Sealed)
- Microleakage Test
- Energy Efficient LED Lighting Reflector Shields
- Wire Shelves
- 1 Hinge 1 Trimble 1 Cabinet 1 Exhaust
- Aluminum Powder Coated Exterior (160 Finish)
- Ceiling (Maximum Height by 4")
- Adjustable Edge Convoy Pouch for Speed
- Polished Back with Black Air Split
- Quilting Steel Laminate Air Split
- Solid Insulation Panel (Shelving Cover)
- Roll Back 134A/12 1 Corrosion Coating
- Aluminum Powder Coated Interior (65 Finish)
- Removable Locking Safety Panels
- Energy Efficient LED Plug Down Night Station
- 1 Year 1-800-839-2331
- Transformer

CALL TOLL FREE: 800-825-3692 (666-714-2331)
FAX: 800-714-2331 www.rpiindustries.com
220 ROUTE 70, MEDFORD, NJ 08055

BANDIT AIR SCREEN
MODEL # SCRFC (60" HIGH UNIT)

SELF-CONTAINED

MODEL	E	D	H	NP	VOLTS	AMP	PLUG	WT	REFRIG.
SCRFC60H36	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H48	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H60	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H72	36	36	36	12	115	15.5	5:15P	55	134A

AMBIENT

MODEL	E	D	H	NP	VOLTS	AMP	PLUG	WT	REFRIG.
SCRFC60H36	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H48	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H60	36	36	36	12	115	15.5	5:15P	55	134A
SCRFC60H72	36	36	36	12	115	15.5	5:15P	55	134A

REMOTE - REFRIGERATED

MODEL	E	D	H	NP	VOLTS	AMP	PLUG	WT	REFRIG.
SCRFR60H36	36	36	36	12	115	15.5	5:15P	55	134A
SCRFR60H48	36	36	36	12	115	15.5	5:15P	55	134A
SCRFR60H60	36	36	36	12	115	15.5	5:15P	55	134A
SCRFR60H72	36	36	36	12	115	15.5	5:15P	55	134A

GLYCOL

MODEL	E	D	H	NP	VOLTS	AMP	PLUG	WT	REFRIG.
SCRGL60H36	36	36	36	12	115	15.5	5:15P	55	134A
SCRGL60H48	36	36	36	12	115	15.5	5:15P	55	134A
SCRGL60H60	36	36	36	12	115	15.5	5:15P	55	134A
SCRGL60H72	36	36	36	12	115	15.5	5:15P	55	134A

Electrical & Plumbing locations

- All Self-Contained, Remote and Glycol Units must be on a separate branch circuit of 15 amp branch circuit.
- Refrigeration System is designed so that the unit will be able to operate in a 115/60/1 phase system.
- The 60" unit is designed for use in a 115/60/1 phase system. The unit is designed to be used in a 115/60/1 phase system. The unit is designed to be used in a 115/60/1 phase system.

CALL TOLL FREE: 800-825-3692 (666-714-2331)
FAX: 800-714-2331 www.rpiindustries.com
220 ROUTE 70, MEDFORD, NJ 08055

6 K05 SPECIFICATION
SCALE: 12" = 1'-0"

5 K04 SPECIFICATION
SCALE: 12" = 1'-0"

BEVERAGE-AIR
3778 Champion Blvd., Winston Salem, NC 27106
1-800-845-8000 Fax 1-336-245-6433
http://www.beverage-air.com

SCHOOL MILK COOLERS DUAL ACCESS COLD WALL ST SERIES

Commercial Refrigeration Equipment General Specification

ST SERIES—DUAL ACCESS, COLD WALL
Dual access cold wall milk coolers designed to hold milk between 36° F to 38° F, unit ready to use. Produced in three sizes to hold 6, 12, and 18 milk cases (12" x 13" x 11") per unit.

CABINET CONSTRUCTION
Standard cabinet construction includes stainless steel exterior and powder coated interior. Balance of cabinet is made of 20 gauge stainless steel. Outside finish is a smooth, easy-to-clean stainless steel. Inside finish is a smooth, easy-to-clean stainless steel. Inside finish is a smooth, easy-to-clean stainless steel. Inside finish is a smooth, easy-to-clean stainless steel.

REFRIGERATION
Refrigeration system uses R404A refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

ELECTRICAL
Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.

SPECIAL FEATURES

- One-piece, reinforced stainless steel floor for maximum support of milk crates.
- ST34N & ST49N models have earned the ENERGY STAR®.
- Stainless options available.

Available From:

BEVERAGE-AIR CORPORATION
3778 Champion Blvd., Winston Salem, NC 27106 USA • (336) 245-6400 • Fax: (336) 245-6433 • (888) 646-8668 • www.beverage-air.com
Specifications are subject to change without prior notice. 08/16

Item K06
1 Each **CASH REGISTER STAND**

Duke Model TCS-30SS or equal

- 30"L, 32"W, 34"H
- 16ga stainless top, round cutout with raw edge - 2.75" dia. with plastic grommet
- 20ga stainless steel body & partial undershelf
- Veneer plastic laminate on left side of unit TBD by customer; Masoot logo decal TBD on laminate.
- Stainless steel tube foot rest
- Solid stainless steel trayslides with rubbing rails, on right side, 16ga stainless steel on (2) stainless steel hinged brackets, mounted 34" from floor
- 5" dia. gray poly swivel casters (2 with brakes)
- Electric outlet in base, J-box, receptacle & cover mounted & wired to a single point connection, 6 ft. cord & plug

7 K06 SPECIFICATION
SCALE: 12" = 1'-0"

DUNLEITH ELEMENTARY SCHOOL RENOVATIONS & MODIFICATIONS
120 SAINE DR., SW
MARIETTA, GA 30008 (781-0194)

FOOD SERVICE EQUIPMENT SPECIFICATIONS (K01-K06)

DATE 08/30/2019
PROJECT NO. 18122

FSE1.1

