

EROSION, SEDIMENTATION & POLLUTION CONTROL PLAN LEGEND

| | | |
|--|---|---|
| | CD CHECK DAM | SMALL, TEMPORARY BARRIER OR DAM CONSTRUCTED ACROSS A SWALE, DRAINAGE DITCH, OR AREA OF CONCENTRATED FLOW. |
| | Ce CONSTRUCTION EXIT | A STONE PAD AT THE SITE EXIT TO REMOVE MUD FROM TIRES. (STONE SIZE - 1 1/2" X 3 1/2" DIA., THICKNESS - 6", SEE DETAIL). |
| | Sb1-S TYPE B SEDIMENT BARRIER | SEDIMENT BARRIER SHALL HAVE SUPPORTS NO GREATER THAN 4" O.D. PIPES NO GREATER THAN 1/2" (GALVANIZED), TYPE-C SILT FENCE - SEE DETAIL). GSWOC - SENSITIVE AREA SILT FENCE. |
| | Sd2-T INLET SEDIMENT TRAP | TYPE C SILT FENCE SUPPORTED BY STEEL POSTS SHALL BE USED. THE STAKES SHALL BE SPACED EVENLY AROUND THE PERIMETER OF THE TRAP. A MAX. OF 5 FEET (LONG), AND SECURELY DRIVEN INTO THE GROUND. APPROX. 1" GSWOC. THE FABRIC SHALL BE SBTRENCHED 12" AND BACKFILLED WITH CRUSHED STONE OR COMPACTED SOIL. |
| | Sd2-P CURB INLET SEDIMENT TRAP | A CURB INLET FILTER AFTER PAVING HAS BEEN INSTALLED. METHOD SHALL BE "CRUSHED STONE" OR #10 STONE DRAINAGE BARS WRAPPED WITH FILTER FABRIC, WIRE, OR PLASTIC MESH. SEE DETAIL. |
| | Sd4-S SEDIMENT TRAP (STRAW BALE/SILT FENCE) | A SMALL, TEMPORARY POND THAT DRAINS A DISTURBED AREA OF UP TO 1 ACRE. THE SILT FENCE AND STRAW BALE OUTLET RELIES ON FILTERING THROUGH LAYERS OF AGGREGATE, RIPRAP TO DEWATER THE SEDIMENT TRAP. LIFE SPAN IS UP TO 1 YEAR. SEE DETAIL FOR Sd4-S. |
| | St STORM DRAIN OUTLET PROTECTION | PAVED AND/OR RIPRAPPED CHANNEL SECTIONS BELOW A STORM DRAIN OUTLET. THE LENGTH AND THE WIDTH OF THE APRON SHALL BE DETERMINED FROM DETAIL. |
| | Ds1 DISTURBED AREA STABILIZATION (TEMPORARY SEEDING) | SPREADING OF WOOD WASTE GRINDINGS, CHIPS, AND BARK AS PROTECTIVE PROTECTION FOR DISTURBED AREAS. WOOD WASTE CAN BE MULCHING (SEE DETAIL). SEEDING SHALL BE AT A RATE OF 8 TO 9 TON/ACRE. |
| | Ds2 DISTURBED AREA STABILIZATION (MULCH) | ANNUAL MULCH RATE 40 LBS/ACRE. FERTILIZE AT 500 LBS/ACRE, 10-10-10, 50% BROWN. |
| | Ds3 DISTURBED AREA STABILIZATION (GRASS) | SPREADING HULLED BERMAUDA SEED AT 10 LBS/ACRE AND 1500 LBS/ACRE 10-10-10 FERTILIZER, APPLY LINE AT A RATE OF 1 TON/ACRE. |
| | Ds4 DISTURBED AREA STABILIZATION (SODS) | A PERMANENT VEGETATIVE COVER USING SODS ON HIGHLY ERODIBLE OR CRITICALLY ERODED LANDS. |
| | Dc DUST CONTROL | CONTROLLING SURFACE AND AIR MOVEMENT OF DUST ON CONSTRUCTION SITES, ROADWAYS AND DEMOLITION SITES. |
| | Sa SLOPE STABILIZATION | REPCS - LONG TERM BLANKET CONSISTING OF 100% CURLED WOOD BLANKET ON SLOPES TO PREVENT EROSION AND SLOW WATER FLOW TO STABILIZE SOILS (EXCELSON EROSION CONTROL BLANKET). |
| | Flocc FLOCCULANTS AND COAGULANTS | FLOCCULANTS AND COAGULANTS ARE FORMULATED TO ASSIST IN THE SOLID-LIQUID SEPARATION OF SUSPENDED PARTICLES IN SOLUTION. APPLICATION RATES SHALL CONFORM TO MANUFACTURERS' GUIDELINES FOR APPLICATION. ONLY ANIONIC FORM OF P-20 SHALL BE USED. |
| | ML MONITORING LOCATION | SAMPLING LOCATION TO MONITOR THE STORM WATER FOR TURBIDITY. |

| RING | DISTANCE |
|------|----------|
| 30"E | 52.06' |
| 27"W | 80.27' |
| 24"W | 94.79' |


SITE BENCHMARK: 752.79
TOP OF BOLT IN MIDDLE OF "MUELLER"

"ANY DISTURBED AREA LEFT EXPOSED FOR A PERIOD GREATER THAN 14 DAYS SHALL BE STABILIZED WITH MULCH OR TEMPORARY SEEDING."
THE ESCAPE OF SEDIMENT FROM THE SITE SHALL BE PREVENTED BY THE INSTALLATION OF EROSION CONTROL MEASURES AND PRACTICES PRIOR TO, OR CONCURRENT WITH, LAND DISTURBING ACTIVITIES.
EROSION CONTROL MEASURES WILL BE MAINTAINED AT ALL TIMES. IF FULL IMPLEMENTATION OF THE APPROVED PLAN DOES NOT PROVIDE FOR EFFECTIVE EROSION CONTROL, ADDITIONAL EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IMPLEMENTED TO CONTROL OR TREAT THE SEDIMENT SOURCE

"THIS SHEET IS TO BE USED FOR SEDIMENT AND EROSION CONTROL ONLY"

CERTIFIED PERSON:
REBECCA R. KIRK, ASLA
LEVEL II CERTIFIED
DESIGN PROFESSIONAL
CERTIFICATION # 0000011106
ISSUED: 05/18/2018
EXPIRES: 05/18/2021

CAUTION:
THE UTILITIES SHOWN ARE SHOWN FOR THE CONTRACTORS CONVENIENCE ONLY. OTHER UTILITIES MAY BE PRESENT BUT NOT SHOWN ON THESE DRAWINGS. THE ARCHITECT & ENGINEER ASSUME NO RESPONSIBILITY FOR THE UTILITY LOCATIONS SHOWN, AND IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE THE EXACT LOCATIONS OF ALL UTILITIES WITHIN THE LIMITS OF THE WORK. ALL DAMAGE MADE TO THE EXISTING UTILITIES BY THE CONTRACTOR SHALL BE REPAIRED TO A "LIKE NEW" CONDITION. THE CONTRACTOR SHALL BEAR THE SOLE RESPONSIBILITY FOR ANY LOSSES THAT OCCUR FROM DAMAGES TO THE EXISTING UTILITIES.



| | |
|--|------------|
| SA&E PROJECT NUMBER | 01-615-056 |
| BID PACKAGE/PHASING | BP-1 |
| ISSUED FOR CONSTRUCTION | 10/15/2019 |
| REVISIONS | |
| R # | Doc # Date |
| 7951 Troon Circle Austell, Ga 30168 (770) 419-7777 architects & engineers I.L.C. | |

FACILITY CODE NUMBER: 674-0110
GYMNASIUM/AUDITORIUM FOR:
HEARD COUNTY SCHOOLS
545 MAIN STREET, FRANKLIN, GA 30217
HEARD COUNTY SCHOOL SYSTEM
FRANKLIN, GEORGIA

EROSION CONTROL PLAN PHASE II

DRAWING NUMBER
C207