2018 APPENDIX B
BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS
(EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)
(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: Garner, NC Firestone Complete Auto Care Facility
Address: 5845 NC Hwy 42, Garner, NC Zip Code 27529
Owner/Authorized Agent: Gregg Zuckerman Phone # 407.478.8220 E-Mail: gzuckerman@rockproperties.us
Owned By: Private
Code Enforcement Jurisdiction: County

CONTACT: Olivia Good, SGA Design Group

DESIGNER	FIRM	NAME	LICENSE #	TELEPHONE #	E-MAIL
Architectural	SGA Design Group	Mitchel R. Garrett	12330	(918)587-8600	mitchg@sgadesigngroup.com
Civil	BGE Inc.	Eric C. Hampton_C-4397		EHampton@bgeinc.com (980) 206-4871	
Electrical	Acertus Consulting Group	Randall A. Nelson	032801	(913) 322-5150	randynelson@acertusgroup.com
Fire Alarm	Deferred Submittal By Contractor				
Plumbing	Acertus Consulting Group	Randall A. Nelson	032801	(913) 322-5150	randynelson@acertusgroup.com
Mechanical	Acertus Consulting Group	Randall A. Nelson	032801	(913) 322-5150	randynelson@acertusgroup.com
Sprinkler -Standpipe	Deferred Submittal By Contractor				
Structural	Wallace Engineering	Carrie J. Johnson	033399	(918) 584-5858	cjohnson@wallaceeng.com

Retaining Walls >5' High N/A (.....) .....
Other (.....) .....
("Other" should include firms and individuals such as truss, precast, pre-engineered, interior designers, etc.)

2018 NC BUILDING CODE: New Building

2018 NC EXISTING BUILDING CODE: Select one Select one Select one
CONSTRUCTED: (date) _____ **CURRENT OCCUPANCY(S)** (Ch. 3): _____
RENOVATED: (date) _____ **PROPOSED OCCUPANCY(S)** (Ch. 3): _____

RISK CATEGORY (Table 1604.5): **Current:** Select one **Proposed:** II

BASIC BUILDING DATA
Construction Type: V-B
Sprinklers: No N/A
Standpipes: No
Primary Fire District: No **Flood Hazard Area:** No
Special Inspections Required: Yes (Contact the local inspection jurisdiction for additional procedures and requirements.)

Gross Building Area Table

FLOOR	EXISTING (SQ FT)	NEW (SQ FT)	SUB-TOTAL
3rd Floor	N/A	N/A	N/A
2nd Floor	N/A	N/A	N/A
Mezzanine	N/A	N/A	N/A
1st Floor	N/A	6,116 SF	6,116 SF
Basement	N/A	N/A	N/A
TOTAL	N/A	6,116 SF	6,116 SF

2018 NC Administrative Code and Policies

ALLOWABLE AREA

Primary Occupancy Classification(s): Mercantile Storage - S-1 Select one Select one Select one
Select one
Accessory Occupancy Classification(s): _____
Incidental Uses (Table 509): _____
Special Uses (Chapter 4 – List Code Sections): section 406 – motor-vehicle-related occupancies
Special Provisions: (Chapter 5 – List Code Sections): _____
Mixed Occupancy: Yes Separation: Select one Exception: non-separated use (508.3)

Select one
$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} \leq 1$
_____ + _____ + ... ≤ 1.00

STORY (NO.)	DESCRIPTION AND USE	(A) BLDG AREA PER STORY (SQ FT) [1]	(B) TABLE 506.2[2] AREA	(C) AREA FOR FRONTAGE INCREASE[3]	(D) ALLOWABLE AREA PER STORY OF OCCUPANCY[4]
1	Minor auto repair and mercantile	6,116	9,000	N/A	N/A

[1] Frontage area increases from Section 506.3 are computed thus:
a. Perimeter which fronts a public way or open space having 20 feet minimum width = _____ (F)
b. Total Building Perimeter = _____ (P)
c. Ratio (F/P) = _____ (F/P)
d. W = Minimum width of public way = _____ (W)
e. Percent of frontage increase I_f = 100(F/P - 0.25) x W/30 = _____ (%)
[2] Unlimited area applicable under conditions of Section 507.
[3] Maximum Building Area = total number of stories in the building x D (maximum 3 stories) (506.2).
[4] The maximum area of open parking garages must comply with Table 406.5.4.
[5] Frontage increase is based on the unsprinklered area value in Table 506.2.

ALLOWABLE HEIGHT

	ALLOWABLE	NEW BUILDING	EXISTING BUILDING
Building Height in Feet (Table 504.3) [2]	40'-0"	22'-10"	
Building Height in Stories (Table 504.4) [2]	1	1	

[1] Provide code reference if the "Shown on Plans" option is not used on Table 504.3 or 504.4.
[2] The maximum height of air traffic control towers must comply with Table 412.3.1.
[3] The maximum height of open parking garages must comply with Table 406.5.4.

2018 NC Administrative Code and Policies

FIRE PROTECTION REQUIREMENTS

BUILDING ELEMENT	FIRE SEPARATION DISTANCE (FEET)	RATING REQUIRED	RATING PROVIDED	DETAIL # AND SHEET #	DESIGN # FOR RATED ASSEMBLY	SHEET # FOR RATED PENETRATION	SHEET # FOR RATED JOINTS
Structural Frame, including columns, girders, trusses		N/A					
Bearing Walls		N/A					
Exterior		N/A					
North		N/A					
East		N/A					
West		N/A					
South		N/A					
Interior		N/A					
Nonbearing Walls and Partitions		N/A					
Exterior walls							
North		N/A					
East		N/A					
West		N/A					
South		N/A					
Interior walls and partitions		N/A					
Floor Construction, including supporting beams and joints		N/A					
Floor Ceiling Assembly		N/A					
Columns Supporting Floors		N/A					
Roof Construction, including supporting beams and joints		N/A					
Roof Ceiling Assembly		N/A					
Columns Supporting Roof		N/A					
Shaft Enclosures - Exit		N/A					
Shaft Enclosures - Other		N/A					
Corridor Separation		N/A					
Occupancy/Fire Barrier Separation			N/A				
Party/Fire Wall Separation		N/A					
Smoke Barrier Separation		N/A					
Smoke Partition		N/A					
Tenant/Dwelling Unit/Sleeping Unit Separation		N/A					
Incidental Use Separation		N/A					

* Indicate section number permitting reduction

PERCENTAGE OF WALL OPENING CALCULATIONS

FIRE SEPARATION DISTANCE (FEET) FROM PROPERTY LINES	DEGREE OF OPENING PROTECTION (TABLE 705.8)	ALLOWABLE AREA (%)	ACTUAL AREA OF WALL (%)
Greater than 30' on all sides	UP, S	No limit	Not required

LIFE SAFETY SYSTEM REQUIREMENTS

Emergency Lighting: Yes
Exit Signs: Yes
Fire Alarm: Yes
Smoke Detection Systems: No
Carbon Monoxide Detection: Yes

LIFE SAFETY PLAN REQUIREMENTS

Life Safety Plan Sheet #: LS1

- ☐ Fire and/or smoke rated wall locations (Chapter 7)
- ☐ Assumed and real property line locations (if not on the site plan)
- ☐ Exterior wall opening area with respect to distance to assumed property lines (705.8)
- ☒ Occupancy Use for each area as it relates to occupant load calculation (Table 1004.1.2)
- ☒ Occupant loads for each area
- ☒ Exit access travel distances (1017)
- ☒ Common path of travel distances (Tables 1006.2.1 & 1006.3.2(1))
- ☐ Dead end lengths (1020.4)
- ☒ Clear exit widths for each exit door
- ☒ Maximum calculated occupant load capacity each exit door can accommodate based on egress width (1005.3)
- ☒ Actual occupant load for each exit door
- ☐ A separate schematic plan indicating where the rated floor/ceiling and/or roof structure is provided for purposes of occupancy separation)
- ☐ Location of doors with panic hardware (1010.1.10)
- ☐ Location of doors with delayed egress locks and the amount of delay (1010.1.9.7)
- ☐ Location of doors with electromagnetic egress locks (1010.1.9.9)
- ☐ Location of doors equipped with hold-open devices
- ☐ Location of emergency escape windows (1030)
- ☐ The square footage of each fire area (202)
- ☐ The square footage of each smoke compartment for Occupancy Classification I-2 (407.5)
- ☐ Note any code exceptions or table notes that may have been utilized regarding the items above

2018 NC Administrative Code and Policies

ACCESSIBLE DWELLING UNITS
(SECTION 1107)

TOTAL UNITS	ACCESSIBLE UNITS REQUIRED	ACCESSIBLE UNITS PROVIDED	TYPE A UNITS REQUIRED	TYPE A UNITS PROVIDED	TYPE B UNITS REQUIRED	TYPE B UNITS PROVIDED	TOTAL ACCESSIBLE UNITS PROVIDED
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

ACCESSIBLE PARKING
(SECTION 1106)

ASSIGNED PARKING AREA	TOTAL # OF PARKING SPACES REQUIRED	TOTAL # OF PARKING SPACES PROVIDED	# SPACES ACCESSIBLE SPACES PROVIDED REGULAR (8') ACCESS AISLE	VAN SPACES WITH 132" ACCESS AISLE	VAN SPACES WITH 8' ACCESS AISLE	TOTAL # ACCESSIBLE SPACES PROVIDED
6,721sf	25	41			2	2
TOTAL		41				2

PLUMBING FIXTURE REQUIREMENTS
(TABLE 2902.1)

USE		WATER CLOSETS			LAVATORIES			SHOWERS	DRINKING FOUNTAINS	
		MALE	FEMALE	UNISEX	MALE	FEMALE	UNISEX		REGULAR	ACCESSIBLE
BASE	EXIST'G	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	NEW	N/A	N/A	2	N/A	N/A	2	N/A	2	1
	REQ'D	N/A	N/A	1	N/A	N/A	1	N/A	1	1

SPECIAL APPROVALS

Special approval: (Local Jurisdiction, Department of Insurance, OSC, DPI, DHHS, etc., describe below)

N/A

ENERGY SUMMARY

ENERGY REQUIREMENTS:
The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portion of the project information for the plans data sheet. If performance method, state the annual energy cost for the standard reference design vs. actual energy cost for the proposed design.

Existing building envelope complies with code: Select one

Exempt Building: Select one Provide code or statutory reference:

Climate Zone: 4A

Method of Compliance: Energy Code - Prescriptive
("Other" specify source here)

THERMAL ENVELOPE (Prescriptive method only)

Roof/Ceiling Assembly (each assembly)
Description of assembly: Metal building roof
U-Value of total assembly: 0.035
R-Value of insulation: 28.6
Skylights in each assembly: N/A
U-Value of skylight: N/A
total square footage of skylights in each assembly: N/A

Exterior Walls (each assembly)
Description of assembly: Metal building walls
U-Value of total assembly: 0.052
R-Value of insulation: 19.2
Openings (windows or doors with glazing)
U-Value of assembly: 0.5 (HM doors), 0.1 (sectional overhead doors), 0.45 (glazing)
Solar heat gain coefficient: 0.33
projection factor: 0.2
Door R-Values:

Walls below grade (each assembly)
Description of assembly: N/A
U-Value of total assembly: N/A
R-Value of insulation:

Floors over unconditioned space (each assembly)
Description of assembly: N/A
U-Value of total assembly: N/A
R-Value of insulation:

Floors slab on grade
Description of assembly: concrete slab on grade
U-Value of total assembly: N/A
R-Value of insulation: 15 per inch
Horizontal/vertical requirement: 2'
slab heated: N/A

2018 NC Administrative Code and Policies

2018 APPENDIX B
BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS
STRUCTURAL DESIGN
(PROVIDE ON THE STRUCTURAL SHEETS IF APPLICABLE)

DESIGN LOADS:

Importance Factors: Snow (I_S) 1.0
Seismic (I_E) 1.0

Live Loads: Roof 20 psf
Mezzanine N/A psf
Floor N/A psf

Ground Snow Load: 15 psf

Wind Load: Ultimate Wind Speed 115 mph (ASCE-7)
Exposure Category C

SEISMIC DESIGN CATEGORY: B
Provide the following Seismic Design Parameters:
Risk Category (Table 1604.5) II
Spectral Response Acceleration S_S 0.157 %g S_1 0.077 %g
Site Classification (ASCE 7) D
Data Source: Presumptive
Basic structural system Building Frame
Analysis Procedure: Equivalent Lateral Force
Architectural, Mechanical, Components anchored? No

LATERAL DESIGN CONTROL: Wind

SOIL BEARING CAPACITIES:
Field Test (provide copy of test report) 3000 psf
If no, size, type and depth of ftg. _____

2018 APPENDIX B
BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS
MECHANICAL DESIGN
(PROVIDE ON THE MECHANICAL SHEETS IF APPLICABLE)

MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Thermal Zone
winter dry bulb: 19.6°F
summer dry bulb: 94.8°F

Interior design conditions
winter dry bulb: 70.0°F
summer dry bulb: 75.0°F
relative humidity: 50%

Building heating load: 65.9 MBH
Building cooling load: 55.4 MBH

Mechanical Spacing Conditioning System
Unitary
description of unit: refer to sheet M3
heating efficiency: refer to sheet M3
cooling efficiency refer to sheet M3
size category of unit: refer to sheet M3
Boiler
Size category. If oversized, state reason.. N/A
Chiller
Size category. If oversized, state reason.: N/A

List equipment efficiencies: refer to sheet M3

2018 APPENDIX B
BUILDING CODE SUMMARY FOR ALL COMMERCIAL PROJECTS
ELECTRICAL DESIGN
(PROVIDE ON THE ELECTRICAL SHEETS IF APPLICABLE)

ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance: Energy Code - Prescriptive

Lighting schedule (each fixture type)
lamp type required in fixture **PLEASE SEE LIGHT FIXTURE SCHEDULE ON SHEET E3 FOR ALL**
number of lamps in fixture
ballast type used in the fixture
number of ballasts in fixture
total wattage per fixture
total interior wattage specified vs. allowed (whole building or space by space) **8,186W**
total exterior wattage specified vs. allowed **4,546W**

Additional Efficiency Package Options
(When using the 2018 NCECC; not required for ASHRAE 90.1)
- ☐ C406.2 More Efficient HVAC Equipment Performance
- ☒ C406.3 Reduced Lighting Power Density
- ☐ C406.4 Enhanced Digital Lighting Controls
- ☐ C406.5 On-Site Renewable Energy
- ☐ C406.6 Dedicated Outdoor Air System
- ☐ C406.7 Reduced Energy Use in Service Water Heating

Order Plans @ WWW.LDILine.com

SGA Design Group, P.C.
1437 South Boulder, Suite 550
Tulsa, Oklahoma 74119-3609
p: 918.587.8600
f: 918.587.8601
www.sgadesigngroup.com

Firestone COMPLETE AUTO CARE

THIS DRAWING IS THE PROPERTY OF BRIDGESTONE RETAIL OPERATIONS, LLC AND IS LOANED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED IN WHOLE OR IN PART FOR ANY PURPOSE WHATSOEVER EXCEPT WITH THE WRITTEN PERMISSION AND THE ACCEPTANCE OF THE DRAWING WILL BE CONSTRUED AS AN ACCEPTANCE OF THE FOREGOING CONDITION AND AS AN AGREEMENT TO RETURN THE DRAWING ON DEMAND. ALL RIGHTS RESERVED. THIS DRAWING IS SUBJECT TO COPYRIGHT PROTECTION AS AN "ARCHITECTURAL WORK" UNDER SECTIONS 102 AND 120 OF THE COPYRIGHT ACT, AS AMENDED DECEMBER 1990. ANY USE OR DISTRIBUTION OF THIS DRAWING WITHOUT THE EXPRESS PERMISSION OF BRIDGESTONE RETAIL OPERATIONS, LLC OR ITS AUTHORIZED AGENTS IS STRICTLY PROHIBITED. THE RECEIPT OR POSSESSION OF THIS DRAWING DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, USE OR ALLOW OTHERS TO REPRODUCE OR USE THE DESIGN OR ANY PART THEREOF WITHOUT THE EXPRESS PERMISSION OF BRIDGESTONE RETAIL OPERATIONS, LLC. ANY REPRODUCTION OR UNAUTHORIZED USE OF THE DESIGN WITHOUT SUCH PERMISSION IS A VIOLATION OF THE COPYRIGHT LAWS OF THE UNITED STATES AND WILL SUBJECT THE VIOLATOR TO LEGAL ACTION. ADMISSION TO THE EXCLUSIVE OWNERSHIP IN AND TO THE DRAWING BY BRIDGESTONE RETAIL OPERATIONS, LLC.

STIPULATION OF RELIEF
THIS DRAWING IS PREPARED FOR USE ON A SPECIFIC SITE AT GARNER, NC. CONTEMPORANEOUSLY WITH ITS ISSUE DATE (NOTED BELOW) AND IT IS NOT SUITABLE FOR USE ON A DIFFERENT PROJECT SITE OR AT A LATER DATE. ANY REUSE OF THIS OR REFERENCE OR EXAMPLE ON ANOTHER PROJECT REQUIRES THE SERVICES OF PROPERLY LICENSED ARCHITECTS AND ENGINEERS. REPRODUCTION OF THIS DRAWING FOR USE ON ANOTHER PROJECT IS NOT AUTHORIZED AND MAY BE CONTRARY TO THE LAW.

NEW FCAC STORE
2019 - JANUARY -SMALL ER
5845 NC HWY 42
GARNER, NC

SGA DESIGN GROUP, P.C.
Registered Architectural Corporation
51720
North Carolina
TULSA, OK

MITCHEL R. GARRETT
REGISTERED ARCHITECT
12330
NORTH CAROLINA
TULSA, OK

Digitally signed by Mitchel R Garrett
Date: 2019.07.26 15:02:22
07/26/2019

ISSUE BLOCK

PROPERTY NO.: 160017
6 DIGIT NO.: 903065
4 DIGIT NO.: 015P
AOR PROJECT NUMBER: 1955B01
TO PERMIT: DATE: 07/26/19
TO BID: DATE: ##-##-##
#8

SHEET TITLE:
APPENDIX B

SHEET NUMBER:
APPB