SWITCHBOARD "SSA" — MAIN DEVICE: TYPE: BOLTED SW; SIZE: 3000A

FP VOLT: 480 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: PAD MOUNTED

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	1995	SEE RISER	PANEL HX	F	94725	21	1995		SPACE		
2	1563	SEE RISER	PANEL HXE	F	86106	23	1254		SPACE		
3	663	SEE RISER	PANEL H1	F	38308	25	1863		SPACE		
4	1863	SEE RISER	PANEL HM	F	105230	26	1995		SPACE		
5	663	SEE RISER	PANEL H3	F	37285						
6	663	SEE RISER	PANEL H4	F	3946						
7	2313	SEE RISER	PNL HDP1	F	95446						
8	2235	SEE RISER	PANEL HK	F	125729						
9	2063	SEE RISER	PANEL LXP	F	125470						
10	920	SEE RISER	PANEL HMP	F	285190						
11	405	SEE RISER	PANEL H2	F	8248						
12	4863	SEE RISER	PANEL HMS	F	286170						
13	663	SEE RISER	PANEL H5	F	34893						
14	4863	SEE RISER	PANEL HMS	F	286170						
15	663	SEE RISER	PANEL H7	F	31408						
16	4863	SEE RISER	PANEL HMS	F	286170						
17	663	SEE RISER	PANEL H8	F	31486						
18	4863	SEE RISER	PANEL HMS	F	278960						
19	805	SEE RISER	PANEL H9	F	37429						
20	2995	SEE PLANS	ELEVATOR	M	80500						

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	214400
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	0
COOL	1	0
MOTOR	1	80560
OTHER	1	0
SPARE	1	16169

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
214400
0
0
0
80560
0
16169

	CONNLOAD	AMP		DEMLOAD	AMP
	224969	269		224969	269

NOTES: SWITCHBOARD SHALL BE SERVICE ENTRY RATED.
PROVIDE SWITCHBOARD WITH TVSS UNIT PER SPECIFICATIONS.

PNL BRD "HX" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 225A

FP VOLT: 480 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/3	8	3/4"	EMERLTG	L	1200	2	20/3	10	1/2"	EMERLTG	L	900
3	20/3	8	3/4"	EMERLTG	L	1200	4	20/3	10	1/2"	EMERLTG	L	1200
5	20/1	10	1/2"	EMERLTG	L	600	6	20/1	10	1/2"	EMERLTG	L	1200
7	20/1	10	1/2"	EMERLTG	L	1200	8	20/1	12	1/2"	EMERLTG	L	600
9	20/1	10	1/2"	EMERLTG	L	1200	10	20/1	12	1/2"	EMERLTG	L	780
11	20/1	10	1/2"	EXITLTG	L	780	12	20/1	12	1/2"	EMERLTG	L	600
13	20/1	10	1/2"	EXITLTG	L	780	14	20/1	12	1/2"	EMERLTG	L	480
15	20/1	10	1/2"	EXITLTG	L	780	16	20/1	12	1/2"	EMERLTG	L	600
17	20/1	10	1/2"	EMERLTG	L	600	18	20/1	12	1/2"	EMERLTG	L	780
19	20/1	10	1/2"	EMERLTG	L	600	20	20/1	12	1/2"	EMERLTG	L	780
21	20/1			SPARE			22	20/1			SPARE		
23	20/1			SPARE			24	20/1			SPARE		
25	20/1			SPARE			26	20/1			SPARE		
27	20/1			SPARE			28	20/1			SPARE		
29	20/1			SPARE			30	20/1			SPARE		
31	20/1			SPACE			32	20/1			SPACE		
33	20/1			SPACE			34	20/1			SPACE		
35	20/1			SPACE			36	20/1			SPACE		
37	20/1			SPACE			38	1995	SEE RISER		PANEL LN	F	80560
39	20/1			SPACE			40	---	---	---	---	---	---
41	20/1			SPACE			42	---	---	---	---	---	---

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	80560
RECEPT.	0.5	0
LIGHT	1.25	20125
HEAT	1	0
COOL	1	0
MOTOR	1	0
OTHER	1	0
SPARE	1	3220

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
80560
0
20125
0
0
0
0
3220

	CONNLOAD	AMP		DEMLOAD	AMP
	182366	96		84228	101

NOTES:

PNL BRD "LX" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MCB; SIZE: 225A

FP VOLT: 208 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/1	10	1/2"	RECEPT	R	900	2	20/1	8	3/4"	EMERLTG	L	1200
3	20/1	8	3/4"	RECEPT	R	900	4	20/1	10	1/2"	EMERLTG	L	1200
5	20/1	8	3/4"	RECEPT	R	900	6	20/1	10	1/2"	EMERLTG	L	1200
7	20/1	8	3/4"	RECEPT	R	900	8	20/1	10	1/2"	EMERLTG	L	1200
9	20/1	8	3/4"	RECEPT	R	900	10	20/1	10	1/2"	EMERLTG	L	1200
11	20/1	8	3/4"	RECEPT	R	900	12	20/1	10	1/2"	EMERLTG	L	1200
13	20/1	10	1/2"	DATARACK	R	1200	14	20/1	8	3/4"	EMERLTG	L	1200
15	20/1	10	1/2"	DATARACK	R	1200	16	20/1	8	3/4"	DATARACK	R	1200
17	20/1	10	1/2"	DATARACK	R	1200	18	20/1	10	1/2"	DATARACK	R	1200
19	20/1	10	1/2"	DATARACK	R	1200	20	20/1	10	1/2"	DATARACK	R	1200
21	20/1	8	3/4"	DATARACK	R	1200	22	20/1	8	3/4"	DATARACK	R	1200
23	20/1	10	1/2"	ICRACK	R	1800	24	20/1	8	3/4"	ICRACK	R	1800
25	20/1	8	3/4"	ICRACK	R	1800	26	20/1	8	3/4"	ICRACK	R	1800
27	20/1	8	3/4"	EXP	O	1600	28	20/1	10	1/2"	ICRACK	R	1800
29	20/1	8	3/4"	GEN MONUN	O	900	30	20/1	8	3/4"	ICRACK	R	1800
31	20/1	8	3/4"	TELEPHONE	O	1200	32	20/1	12	1/2"	GEN CNTRLS	O	1500
33	20/1	12	1/2"	GEN BATT	O	900	34	20/1	12	1/2"	GEN HEATER	H	1500
35	20/1			SPARE			36	20/1			SPARE		
37	20/1			SPARE			38	20/1			SPARE		
39	20/1			SPARE			40	20/1			SPARE		
41	20/1			SPACE			42	20/1			SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	52400
RECEPT.	0.5	27400
LIGHT	1.25	3200
HEAT	1	1500
COOL	1	0
MOTOR	2	0
OTHER	1	4800
SPARE	1	6960

VOLTAGE:	208
PHASE%	3
SPARE %	0.2

DEMAND
52400
13700
1500
1500
0
0
4800
6960

	CONNLOAD	AMP		DEMLOAD	AMP
	74260	206		46800	168

NOTES: PROVIDE FEED THROUGH LUGS TO SERVE PANEL "LX1"

PNL BRD "LX1" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 225A

FP VOLT: 208 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/1	8	3/4"	HEATTAPE	H	1500	2	20/1	8	3/4"	ELEVCAB	L	1200
3	20/1	12	1/2"	HEATTAPE	H	1500	4	20/1	8	3/4"	RECEPT	R	900
5	40/2	3	1.25"	DISC-3	C	5280	6	40/2	3	1.25"	DISC-3	C	5280
7	---	---	---	---	---	---	8	---	---	---	---	---	---
9	20/2	8	3/4"	DISC-15	C	2880	10	20/2	8	3/4"	DISC-15	C	2880
11	---	---	---	---	---	---	12	---	---	---	---	---	---
13	20/2	10	1/2"	DISC-7	C	2090	14	20/1			SPARE		
15	---	---	---	---	---	---	16	20/1			SPARE		
17	20/1			SPARE			18	20/1			SPARE		
19	20/1			SPARE			20	20/1			SPARE		
21	20/1			SPARE			22	20/1			SPARE		
23	20/1			SPARE			24	20/1			SPARE		
25	20/1			SPARE			26	20/1			SPARE		
27	20/1			SPARE			28	20/1			SPARE		
29	20/1			SPACE			30	20/1			SPACE		
31	20/1			SPACE			32	20/1			SPACE		
33	20/1			SPACE			34	20/1			SPACE		
35	20/1			SPACE			36	20/1			SPACE		
37	20/1			SPACE			38	20/1			SPACE		
39	20/1			SPACE			40	20/1			SPACE		
41	20/1			SPACE			42	20/1			SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	0
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	0
COOL	1	0
MOTOR	1	0
OTHER	1	0
SPARE	1	540

VOLTAGE:	208
PHASE%	3
SPARE %	0.2

DEMAND
0
0
0
0
0
0
0
540

	CONNLOAD	AMP		DEMLOAD	AMP
	5040	14		540	2

NOTES: PROVIDE SEPARATE ISOLATED GROUND BUS AND INTEGRAL TVSS DEVICE.

PNL BRD "HXK" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 225A

FP VOLT: 480 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/1			SPARE			2	20/1			SPARE		
3	20/1			SPARE			4	20/1			SPARE		
5	20/1			SPARE			6	20/1			SPACE		
7	20/1			SPACE			8	20/1			SPACE		
9	20/1			SPACE			10	20/1			SPACE		
11	---	---	---	---	---	---	12	---	---	---	---	---	---
13	---	---	---	---	---	---	14	20/1			SPARE		
15	20/1			SPACE			16	20/1			SPARE		
17	20/1			SPACE			18	20/1			SPACE		
19	20/1			SPACE			20	20/1			SPACE		
21	20/1			SPACE			22	20/1			SPACE		
23	20/1			SPACE			24	20/1			SPACE		
25	20/1			SPACE			26	20/1			SPACE		
27	20/1			SPACE			28	20/1			SPACE		
29	20/1			SPACE			30	20/1			SPACE		
31	20/1			SPACE			32	20/1			SPACE		
33	20/1			SPACE			34	20/1			SPACE		
35	20/1			SPACE			36	20/1			SPACE		
37	20/1			SPACE			38	1995	SEE RISER		PANEL LX	F	94360
39	20/1			SPACE			40	---	---	---	---	---	---
41	20/1			SPACE			42	---	---	---	---	---	---

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	80560
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	0
COOL	1	0
MOTOR	1	0
OTHER	1	0
SPARE	1	0

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
80560
0
0
0
0
0
0
0

	CONNLOAD	AMP		DEMLOAD	AMP
	80560	96		80560	96

NOTES:

PNL BRD "LXK" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MCB; SIZE: 150A

FP VOLT: 208 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/3	10	1/2"	FREEZECUT	C	4000	2	20/3	12	1/2"	COOLSCUT	C	4000
3	---	---	---	---	---	---	4	---	---	---	---	---	---
5	---	---	---	---	---	---	6	---	---	---	---	---	---
7	20/2	10	1/2"	FREEVAP	C	1680	8	20/1	12	1/2"	CLRLIGHTS	L	1200
9	---	---	---	---	---	---	10	20/1	12	1/2"	HIGHLIGHTS	L	1200
11	20/1	12	1/2"	CLRVAP	C	1200	12	20/1			SPARE		
13	20/1			SPARE			14	20/1			SPARE		
15	20/1			SPARE			16	20/1			SPARE		
17	20/1			SPARE			18	20/1			SPARE		
19	20/1			SPARE			20	20/1			SPARE		
21	20/1			SPARE			22	20/1			SPARE		
23	20/1			SPARE			24	20/1			SPACE		
25	20/1			SPACE			26	20/1			SPACE		
27	20/1			SPACE			28	20/1			SPACE		
29	20/1			SPACE			30	20/1			SPACE		
31	20/1			SPACE			32	20/1			SPACE		
33	20/1			SPACE			34	20/1			SPACE		
35	20/1			SPACE			36	20/1			SPACE		
37	20/1			SPACE			38	20/1			SPACE		
39	20/1			SPACE			40	20/1			SPACE		
41	20/1			SPACE			42	20/1			SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	94460
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	10800
COOL	1	0
MOTOR	1	68700
OTHER	1	0
SPARE	1	15760

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
94460
0
0
10800
0
68700
0
15760

	CONNLOAD	AMP		DEMLOAD	AMP
	94460	114		94460	114

NOTES: * PUMP IS REDUNDANT.

DISTRIBUTION PANEL "HDP1" — MAIN DEVICE: TYPE: MLO; SIZE: 225A

FP VOLT: 480 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/3	12	1/2"	CTFAN	M	9000
2	20/3	12	1/2"	CTFAN	M	9000
3	20/3	12	1/2"	BARNHTR	H	7000
4	20/3	12	1/2"	BARNHTR	H	9000
5	30/3	10	1/2"	PUMP P-1	M	11700
6	30/3	10	1/2"	PUMP P-1-S	M	0*
7	50/3	3	1.25"	PUMP P-2	M	53200
8	30/3	3	1.25"	PUMP P-2	M	0*
9	20/3	12	1/2"	PUMP P-3	M	9000
10	20/3	12	1/2"	PUMP P-3	M	7000
11	100/3			SPACE		
12	60/3			SPACE		
13	60/3			SPACE		
14	30/3			SPACE		
15	30/3			SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	0
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	10800
COOL	1	0
MOTOR	1	68700
OTHER	1	0
SPARE	1	15760

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
0
0
0
10800
0
68700
0
15760

	CONNLOAD	AMP		DEMLOAD	AMP
	94460	114		94460	114

NOTES: * PUMP IS REDUNDANT.

PNL BRD "LST" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 225A

FP VOLT: 208 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/1	12	1/2"	RECEPT	R	900	2	20/1	12	1/2"	RECEPT	R	900
3	20/1	12	1/2"	RECEPT	R	900	4	20/1	12	1/2"	RECEPT	R	900
5	20/1	12	1/2"	RECEPT	R	900	6	20/1	12	1/2"	RECEPT	R	900
7	20/1	12	1/2"	TVR	R	1200	8	20/1	12	1/2"	EWD	R	1200
9	20/1	12	1/2"	TVR	R	1200	10	20/1	12	1/2"	STAGELTG	L	1500
11	20/1	12	1/2"	LTG	L	1500	12	20/1	12	1/2"	STAGELTG	L	1500
13	20/1	12	1/2"	STAGELTG	L	1500	14	20/1	12	1/2"	STAGELTG	L	1500
15	20/1			SPARE			16	20/1			SPARE		
17	20/1			SPARE			18	20/1			SPARE		
19	20/1			SPARE			20	20/1			SPARE		
21	20/1			SPARE			22	20/1			SPARE		
23	20/1			SPARE			24	20/1			SPARE		
25	20/1			SPARE			26	20/1			SPARE		
27	20/1			SPARE			28	20/1			SPARE		
29	20/1			SPACE			30	20/1			SPACE		
31	20/1			SPACE			32	20/1			SPACE		
33	20/1			SPACE			34	20/1			SPACE		
35	20/1			SPACE			36	20/1			SPACE		
37	20/1			SPACE			38	20/1			SPACE		
39	20/1			SPACE			40	20/1			SPACE		
41	20/1			SPACE			42	20/1			SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	0
RECEPT.	0.5	5580
LIGHT	1.25	7500
HEAT	1	0
COOL	1	0
MOTOR	1	500
OTHER	1	0
SPARE	1	2760

VOLTAGE:	208
PHASE%	3
SPARE %	0.2

DEMAND
0
5580
7500
0
0
500
0
2760

	CONNLOAD	AMP		DEMLOAD	AMP
	16940	46		15835	43

NOTES:

PNL BRD "HK" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 400A

FP VOLT: 480 | AIC RATING: 22,000 (NOTE 1) | NO. PH: 3 | CABINET: FLUSH

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/3	12	1/2"	VCM	M	6780	2	60/3	5	1.25"	BOOSTER	R	34200
3	---	---	---	---	---	---	4	---	---	---	---	---	---
5	---	---	---	---	---	---	6	---	---	---	---	---	---
7	30/3	10	1/2"	DW DRIER	M	14000	8	80/3	3	1.25"	DISH WASHER	H	45000
9	---	---	---	---	---	---	10	---	---	---	---	---	---
11	---	---	---	---	---	---	12	---	---	---	---	---	---
13	20/1			SPARE			14	5639*	12	1/2"	KH-1	M	8460
15	20/1			SPARE			16	---	---	---	---	---	---
17	20/1			SPARE			18	---	---	---	---	---	---
19	20/1			SPARE			20	---	---	---	MOUNT TRIP SPACE		
21				SPACE			22				SPACE		
23				SPACE			24				SPACE		
25				SPACE			26				SPACE		
27				SPACE			28				SPACE		
29				SPACE			30				SPACE		
31				SPACE			32				SPACE		
33				SPACE			34				SPACE		
35				SPACE			36				SPACE		
37				SPACE			38				SPACE		
39				SPACE			40				SPACE		
41				SPACE			42				SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	0
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	74080
COOL	1	0
MOTOR	1	29100
OTHER	1	0
SPARE	1	20620

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
0
0
0
74080
0
29100
0
20620

	CONNLOAD	AMP		DEMLOAD	AMP
	223720	149		123720	149

NOTES: 1 - PANEL SHALL BE SERIES RATED WITH THE UPSTREAM DEVICE
* PROVIDE SHUNT TRIP BREAKER CONTROLLED BY THE HOOD SUPPRESSION SYSTEM.

PNL BRD "HMP" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 400A

FP VOLT: 480 | AIC RATING: 65,000 | NO. PH: 3 | CABINET: SURFACE

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/3	6	1"	RTU-6	C	36800	2	30/3	6	1"	FEED	C	30800
3	---	---	---	---	---	---	4	20/3	10	1/2"	LIGHTING	L	2880
5	---	---	---	---	---	---	6	20/3	10	1/2"	LIGHTING	L	3360
7	60/3	4	1.25"	MAU-5	C	31700	8	20/3	10	1/2"	LIGHTING	L	1780
9	---	---	---	---	---	---	10	20/1			SPARE		
11	---	---	---	---	---	---	12	20/1			SPARE		
13	20/1			SPARE			14	20/1			SPARE		
15	20/1			SPACE			16	20/1			SPACE		
17	20/1			SPACE			18	20/1			SPACE		
19	20/1			SPACE			20	20/1			SPACE		
21	20/1			SPACE			22	20/1			SPACE		
23	20/1			SPACE			24	20/1			SPACE		
25				SPACE			26				SPACE		
27				SPACE			28				SPACE		
29				SPACE			30				SPACE		
31				SPACE			32				SPACE		
33				SPACE			34				SPACE		
35				SPACE			36				SPACE		
37				SPACE			38				SPACE		
39				SPACE			40				SPACE		
41				SPACE			42				SPACE		

DESCRIPT.	DF	LOAD
OTH. PNLS.	1	0
RECEPT.	0.5	0
LIGHT	1.25	0
HEAT	1	74080
COOL	1	0
MOTOR	1	29100
OTHER	0.65	0
SPARE	1	20620

VOLTAGE:	480
PHASE%	3
SPARE %	0.2

DEMAND
0
0
0
74080
0
29100
0
20620

	CONNLOAD	AMP		DEMLOAD	AMP
	223720	149		123720	149

NOTES: 1 - PANEL SHALL BE SERIES RATED WITH THE UPSTREAM DEVICE
* PROVIDE SHUNT TRIP BREAKER CONTROLLED BY THE HOOD SUPPRESSION SYSTEM.

PNL BRD "LK1" — NO. OF CKT. SPACES: 42 — MAIN DEVICE: TYPE: MLO; SIZE: 400A

FP VOLT: 208 | AIC RATING: 22,000 (NOTE 1) | NO. PH: 3 | CABINET: FLUSH

NO.	TA	WS	COND	DESCRIPT	TL	LOAD	NO.	TA	WS	COND	DESCRIPT	TL	LOAD
1	20/1	12	1/2"	EXCPT	R	1968	2	20/1	12	1/2"	WSR HTR	O	1200
3	20/1	12	1/2"	RECPT	R	1200	4	20/1	12	1/2"	WSR HTR	O	1200
5	20/1	12	1/2"	HEATER	M	666	6	20/1	12	1/2"	WSR HTR	O	1200
7	20/1	12	1/2"	HEATER	M	666	8	20/1	12	1/2"	CHS PUMP	M	696
9	20/1	10	1/2"	HEATER	M	666	10	20/1	12	1/2"	TRAP PRIME	O	552
11	20/1	12	1/2"	HEATER	M	666	12	20/1	12	1/2"	WALL FAN	M	696
13	20/1	12	1/2"	WARMER	R	1200	14	20/1	12	1/2"	WALL FAN	M	696
15	20/1	12	1/2"	DRYER	H	5988	16	20/1	12	1/2"	WALL FAN	M	696
17	---	---	---	---	---	---	18	20/1	12	1/2"	EF-3	M	696
19	20/1	12	1/2"	EXH FAN	M	696	20	20/1	12	1/2"	EF-4	M	696
21	20/1			SPARE			22	20/1			SPARE		
23	20/1			SPARE			24	20/1			SPARE		
25	20/1			SPARE			26	20/1			SPARE		
27	20/1			SPARE			28	20/1			SPARE		
29	20/1			SPARE			30	20/1			SPARE