PNL BRD "H4" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: NOTE 1
FP VOLT: 480 A/C RATING: 27,000
NO PH: 3 CABINET: SURFACE SIZE: 60A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	18	1/2" LIGHTING L		1380	2	20/1	18	1/2" LIGHTING L		2898
3	20/1	18	1/2" LIGHTING L		2898	4	20/1	18	1/2" LIGHTING L		2898
5	20/1	18	1/2" LIGHTING L		2898	6	20/1	18	1/2" LIGHTING L		2898
7	20/1	18	1/2" LIGHTING L		2898	8	20/1	18	1/2" LIGHTING L		2898
9	20/1	18	1/2" LIGHTING L		2898	10	20/1	18	1/2" LIGHTING L		2898
11	20/1		SPARE			12	20/1	17	1/2" LIGHTING L		1656
13	20/1		SPARE			14	20/1		SPARE		
15	20/1		SPARE			16	20/1		SPARE		
17	20/1		SPARE			18	20/1		SPARE		
19	20/1		SPACE			20	20/1		SPACE		
21			SPACE			22			SPACE		
23			SPACE			24			SPACE		
25			SPACE			26			SPACE		
27			SPACE			28			SPACE		
29			SPACE			30			SPACE		
31			SPACE			32			SPACE		
33			SPACE			34			SPACE		
35			SPACE			36			SPACE		
37			SPACE			38			SPACE		
39			SPACE			40			SPACE		
41			SPACE			42			SPACE		

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	480	0
RECEPT.	0.5	0	PHASE%	3	0
LIGHT	1.25	22665	SPARE %	0.2	28306
HEAT	1	0			0
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	4480			4480
		CONNLOAD	AMP		DEMLOAD AMP
		26986	32		32486 80

NOTES: 1 - PROVIDE MAIN CONTACTOR WITH COVER MOUNTED H-O-A SWITCH

PNL BRD "L5" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 200A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" RECEPT	R	1200	2	20/1	12	1/2" RECEPT	R	900
3	20/1	12	1/2" RECEPT	R	720	4	20/1	12	1/2" RECEPT	R	1080
5	20/1	12	1/2" RECEPT	R	900	6	20/1	12	1/2" RECEPT	R	900
7	20/1	12	1/2" RECEPT	R	900	8	20/1	12	1/2" RECEPT	R	900
9	20/1	12	1/2" RECEPT	R	900	10	20/1	12	1/2" RECEPT	R	900
11	20/1	12	1/2" RECEPT	R	900	12	20/1	12	1/2" RECEPT	R	1080
13	20/1	12	1/2" RECEPT	R	900	14	20/1	12	1/2" RECEPT	R	900
15	20/1	12	1/2" RECEPT	R	900	16	20/1	12	1/2" RECEPT	R	900
17	20/1	12	1/2" RECEPT	R	900	18	20/1	12	1/2" RECEPT	R	900
19	20/1	12	1/2" RECEPT	R	900	20	20/1	12	1/2" RECEPT	R	1080
21	20/1	12	1/2" RECEPT	R	900	22	20/1	12	1/2" RECEPT	R	900
23	20/1	12	1/2" RECEPT	R	900	24	20/1	12	1/2" RECEPT	R	900
25	20/1	12	1/2" RECEPT	R	900	26	20/1	12	1/2" RECEPT	R	900
27	20/1	12	1/2" RECEPT	R	900	28	20/1	12	1/2" RECEPT	R	900
29	20/1	12	1/2" RECEPT	R	900	30	20/1	12	1/2" RECEPT	R	900
31	20/1	12	1/2" RECEPT	R	900	32	20/1	12	1/2" RECEPT	R	900
33	20/1	12	1/2" RECEPT	R	900	34	20/1	12	1/2" RECEPT	R	900
35	20/1	12	1/2" RECEPT	R	900	36	20/1	12	1/2" RECEPT	R	900
37	20/1	12	1/2" RECEPT	R	900	38	20/1	12	1/2" RECEPT	R	900
39	20/1	12	1/2" RECEPT	R	900	40	20/1	12	1/2" RECEPT	R	900
41	20/1	12	1/2" RECEPT	R	900	42	20/1	12	1/2" RECEPT	R	900

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	22000	PHASE%	3	13200
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	13200			13200
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	3960			3960
		CONNLOAD	AMP		DEMLOAD AMP
		26400	73		30360 83

NOTES:

PNL BRD "L5A" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 400A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	30/3	10	1/2" HAND DRY	H	1500	2	---	---	---	---	---
3	---	---	---	---	---	4	---	---	---	---	---
5	20/1	13	1/2" RECEPT	R	936	6	20/1	12	1/2" RECEPT	R	900
7	20/1	12	1/2" RECEPT	R	900	8	20/1	12	1/2" RECEPT	R	900
9	20/1	12	1/2" RECEPT	R	900	10	20/1	12	1/2" RECEPT	R	900
11	20/1	12	1/2" RECEPT	R	900	12	20/1	12	1/2" RECEPT	R	900
13	20/1	12	1/2" RECEPT	R	900	14	20/1	12	1/2" RECEPT	R	900
15	20/1	12	1/2" RECEPT	R	900	16	20/1	12	1/2" RECEPT	R	900
17	20/1	12	1/2" RECEPT	R	900	18	20/1	12	1/2" RECEPT	R	900
19	20/1	12	1/2" RECEPT	R	900	20	20/1	12	1/2" RECEPT	R	900
21	20/1	12	1/2" RECEPT	R	900	22	20/1	12	1/2" RECEPT	R	900
23	20/1	12	1/2" RECEPT	R	900	24	20/1	12	1/2" RECEPT	R	900
25	20/1	12	1/2" RECEPT	R	900	26	20/1	12	1/2" RECEPT	R	900
27	20/1	12	1/2" RECEPT	R	900	28	20/1	12	1/2" RECEPT	R	900
29	20/1	12	1/2" RECEPT	R	900	30	20/1	12	1/2" RECEPT	R	900
31	20/1	12	1/2" RECEPT	R	900	32	20/1	12	1/2" RECEPT	R	900
33	20/1	12	1/2" RECEPT	R	900	34	20/1	12	1/2" RECEPT	R	900
35	20/1	12	1/2" RECEPT	R	900	36	20/1	12	1/2" RECEPT	R	900
37	20/1	12	1/2" RECEPT	R	900	38	20/1	12	1/2" RECEPT	R	900
39	20/1	12	1/2" RECEPT	R	900	40	20/1	12	1/2" RECEPT	R	900
41	20/1	12	1/2" RECEPT	R	900	42	20/1	12	1/2" RECEPT	R	900

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	18200	PHASE%	3	2500
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	3640			3640
		CONNLOAD	AMP		DEMLOAD AMP
		45680	110		23480 90

NOTES: PROVIDE SEPARATE ISOLATED GROUND BUS AND INTEGRAL TVSS UNIT.
PROVIDE FEED THROUGH LUGS TO SERVE PANEL "RG5A".

PNL BRD "RG5" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MCB
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 150A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" RECEPT	R	900	2	20/1	12	1/2" HAND DRY	H	2300
3	20/1	12	1/2" RECEPT	R	900	4	20/1	12	1/2" RECEPT	R	900
5	20/1	12	1/2" RECEPT	R	900	6	20/1	12	1/2" RECEPT	R	900
7	20/1	12	1/2" RECEPT	R	900	8	20/1	12	1/2" RECEPT	R	900
9	20/1	12	1/2" RECEPT	R	900	10	20/1	12	1/2" RECEPT	R	900
11	20/1	12	1/2" RECEPT	R	900	12	20/1	12	1/2" RECEPT	R	900
13	20/1	12	1/2" RECEPT	R	900	14	20/1	12	1/2" RECEPT	R	900
15	20/1	12	1/2" RECEPT	R	900	16	20/1	12	1/2" RECEPT	R	900
17	20/1	12	1/2" RECEPT	R	900	18	20/1	12	1/2" RECEPT	R	900
19	20/1	12	1/2" RECEPT	R	900	20	20/1	12	1/2" RECEPT	R	1080
21	20/1	12	1/2" RECEPT	R	900	22	20/1	12	1/2" RECEPT	R	900
23	20/1	12	1/2" RECEPT	R	900	24	20/1	12	1/2" RECEPT	R	900
25	20/1	12	1/2" RECEPT	R	900	26	20/1	12	1/2" RECEPT	R	900
27	20/1	12	1/2" RECEPT	R	900	28	20/1	12	1/2" RECEPT	R	900
29	20/1	12	1/2" RECEPT	R	900	30	20/1	12	1/2" RECEPT	R	900
31	20/1	12	1/2" RECEPT	R	900	32	20/1	12	1/2" RECEPT	R	900
33	20/1	12	1/2" RECEPT	R	900	34	20/1	12	1/2" RECEPT	R	900
35	20/1	12	1/2" RECEPT	R	900	36	20/1	12	1/2" RECEPT	R	900
37	20/1	12	1/2" RECEPT	R	900	38	20/1	12	1/2" RECEPT	R	900
39	20/1	12	1/2" RECEPT	R	900	40	20/1	12	1/2" RECEPT	R	900
41	20/1	12	1/2" RECEPT	R	900	42	20/1	12	1/2" RECEPT	R	900

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	7800	PHASE%	3	3900
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	1529			1529
		CONNLOAD	AMP		DEMLOAD AMP
		9329	25		5329 15

NOTES:

PNL BRD "RG5A" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 225A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" RECEPT	R	900	2	20/1	12	1/2" RECEPT	R	1080
3	20/1	12	1/2" RECEPT	R	900	4	20/1	12	1/2" RECEPT	R	900
5	20/1	12	1/2" RECEPT	R	900	6	20/1	12	1/2" RECEPT	R	900
7	20/1	12	1/2" RECEPT	R	900	8	20/1	12	1/2" RECEPT	R	900
9	20/1	12	1/2" RECEPT	R	900	10	20/1	12	1/2" RECEPT	R	1080
11	20/1	12	1/2" RECEPT	R	900	12	20/1	12	1/2" RECEPT	R	900
13	20/1	12	1/2" RECEPT	R	900	14	20/1	12	1/2" RECEPT	R	900
15	20/1	12	1/2" RECEPT	R	900	16	20/1	12	1/2" RECEPT	R	900
17	20/1	12	1/2" RECEPT	R	900	18	20/1	12	1/2" RECEPT	R	900
19	20/1	12	1/2" RECEPT	R	900	20	20/1	12	1/2" RECEPT	R	900
21	20/1	12	1/2" RECEPT	R	900	22	20/1	12	1/2" RECEPT	R	900
23	20/1	12	1/2" RECEPT	R	900	24	20/1	12	1/2" RECEPT	R	900
25	20/1	12	1/2" RECEPT	R	900	26	20/1	12	1/2" RECEPT	R	900
27	20/1	12	1/2" RECEPT	R	900	28	20/1	12	1/2" RECEPT	R	900
29	20/1	12	1/2" RECEPT	R	900	30	20/1	12	1/2" RECEPT	R	900
31	20/1	12	1/2" RECEPT	R	900	32	20/1	12	1/2" RECEPT	R	900
33	20/1	12	1/2" RECEPT	R	900	34	20/1	12	1/2" RECEPT	R	900
35	20/1	12	1/2" RECEPT	R	900	36	20/1	12	1/2" RECEPT	R	900
37	20/1	12	1/2" RECEPT	R	900	38	20/1	12	1/2" RECEPT	R	900
39	20/1	12	1/2" RECEPT	R	900	40	20/1	12	1/2" RECEPT	R	900
41	20/1	12	1/2" RECEPT	R	900	42	20/1	12	1/2" RECEPT	R	900

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	32700	PHASE%	3	7800
LIGHT	1.25	0	SPARE %	0.2	1256
HEAT	1	4600			4600
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	4240			4240
		CONNLOAD	AMP		DEMLOAD AMP
		55140	161		59596 140

NOTES: PROVIDE FEED THROUGH LUGS TO SERVE PANEL "L-A"

PNL BRD "L6" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 100A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" RECEPT	R	900	2	20/1	12	1/2" RECEPT	R	900
3	20/1	12	1/2" RECEPT	R	900	4	20/1	12	1/2" RECEPT	R	900
5	20/1	12	1/2" RECEPT	R	900	6	20/1	12	1/2" RECEPT	R	900
7	20/1	12	1/2" RECEPT	R	900	8	20/1	12	1/2" RECEPT	R	900
9	20/1	19	1/2" RECEPT	R	900	10	20/1	19	1/2" RECEPT	R	900
11	20/1	19	1/2" RECEPT	R	900	12	20/1	19	1/2" RECEPT	R	900
13	20/1	12	1/2" RECEPT	R	900	14	20/1	12	1/2" RECEPT	R	900
15	20/1	12	1/2" RECEPT	R	900	16	20/1	12	1/2" RECEPT	R	1260
17	20/1	12	1/2" RECEPT	R	900	18	20/1	12	1/2" RECEPT	R	900
19	20/1	12	1/2" HAND DRY	H	2300	20	---	---	---	---	---
21	---	---	---	---	---	22	---	---	---	---	---
23	---	---	---	---	---	24	---	---	---	---	---
25	---	---	---	---	---	26	---	---	---	---	---
27	---	---	---	---	---	28	---	---	---	---	---
29	---	---	---	---	---	30	---	---	---	---	---
31	---	---	---	---	---	32	---	---	---	---	---
33	---	---	---	---	---	34	---	---	---	---	---
35	---	---	---	---	---	36	---	---	---	---	---
37	---	---	---	---	---	38	---	---	---	---	---
39	---	---	---	---	---	40	---	---	---	---	---
41	---	---	---	---	---	42	---	---	---	---	---

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	2700	PHASE%	3	1350
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	6060			6060
MOTOR	1	0			0
OTHER	1	800			800
SPARE	1	2160			2160
		CONNLOAD	AMP		DEMLOAD AMP
		11548	58		12510 34

NOTES:

PNL BRD "IG7" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 100A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" 20 RECEPT	R	900	2	20/1	12	1/2" 20 RECEPT	R	900
3	20/1	12	1/2" 20 RECEPT	R	900	4	20/1	12	1/2" 20 RECEPT	R	900
5	20/1	12	1/2" 20 RECEPT	R	900	6	20/1	12	1/2" 20 RECEPT	R	900
7	20/1	12	1/2" 20 RECEPT	R	900	8	20/1	12	1/2" 20 RECEPT	R	900
9	20/1	12	1/2" 20 RECEPT	R	1080	10	20/1	12	1/2" 20 RECEPT	R	900
11	20/1	12	1/2" 20 RECEPT	R	900	12	20/1	12	1/2" 20 RECEPT	R	900
13	20/1	12	1/2" 20 RECEPT	R	900	14	20/1	12	1/2" 20 RECEPT	R	900
15	20/1	12	1/2" 20 RECEPT	R	900	16	20/1	12	1/2" 20 RECEPT	R	900
17	20/1	12	1/2" 20 RECEPT	R	900	18	20/1	12	1/2" 20 RECEPT	R	1080
19	20/1	12	1/2" 20 RECEPT	R	900	20	20/1	12	1/2" 20 RECEPT	R	900
21	20/1	12	1/2" 20 RECEPT	R	900	22	20/1	12	1/2" 20 RECEPT	R	900
23	20/1	12	1/2" 20 RECEPT	R	900	24	20/1	12	1/2" 20 RECEPT	R	900
25	20/1	12	1/2" 20 RECEPT	R	900	26	20/1	12	1/2" 20 RECEPT	R	900
27	20/1	12	1/2" 20 RECEPT	R	900	28	20/1	12	1/2" 20 RECEPT	R	900
29	20/1	12	1/2" 20 RECEPT	R	900	30	20/1	12	1/2" 20 RECEPT	R	900
31	20/1	12	1/2" 20 RECEPT	R	900	32	20/1	12	1/2" 20 RECEPT	R	900
33	20/1	12	1/2" 20 RECEPT	R	900	34	20/1	12	1/2" 20 RECEPT	R	900
35	20/1	12	1/2" 20 RECEPT	R	900	36	20/1	12	1/2" 20 RECEPT	R	900
37	20/1	12	1/2" 20 RECEPT	R	900	38	20/1	12	1/2" 20 RECEPT	R	900
39	20/1	12	1/2" 20 RECEPT	R	900	40	20/1	12	1/2" 20 RECEPT	R	900
41	20/1	12	1/2" 20 RECEPT	R	900	42	20/1	12	1/2" 20 RECEPT	R	900

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	208	0
RECEPT.	0.5	22500	PHASE%	3	11250
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	3600			3600
		CONNLOAD	AMP		DEMLOAD AMP
		26400	73		14850 43

NOTES:

PNL BRD "IG7A" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 208 A/C RATING: 22,000
NO PH: 3 CABINET: SURFACE SIZE: 225A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	20/1	12	1/2" 20 RECEPT	R	1080	2	20/1	12	1/2" 20 RECEPT	R	900
3	20/1	12	1/2" 20 RECEPT	R	1080	4	20/1	12	1/2" 20 RECEPT	R	1080
5	20/1	19	1/2" 20 RECEPT	R	1080	6	20/1	12	1/2" 20 RECEPT	R	1080
7	20/1	19	1/2" 20 RECEPT	R	1080	8	20/1	19	1/2" 20 RECEPT	R	1080
9	20/1		SPARE			10	20/1	19	1/2" 20 RECEPT	R	1080
11	20/1		SPARE			12	20/1		SPARE		
13	20/1		SPARE			14	20/1		SPARE		
15	20/1		SPARE			16	20/1		SPARE		
17	20/1		SPACE			18	20/1		SPARE		
19			SPACE			20			SPACE		
21			SPACE			22			SPACE		
23			SPACE			24			SPACE		
25			SPACE			26			SPACE		
27			SPACE			28			SPACE		
29			SPACE			30			SPACE		
31			SPACE			32			SPACE		
33			SPACE			34			SPACE		
35			SPACE			36			SPACE		
37			SPACE			38			SPACE		
39			SPACE			40			SPACE		
41			SPACE			42			SPACE		

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	6	VOLTAGE:	208	0
RECEPT.	0.5	9000	PHASE%	3	4500
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	0			0
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	1800			1800
		CONNLOAD	AMP		DEMLOAD AMP
		18900	50		6300 17

NOTES:

PNL BRD "HM5" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MLO
FP VOLT: 480 A/C RATING: 42,000
NO PH: 3 CABINET: SURFACE SIZE: 400A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	30/3	18	1/2" WSHP	C	16650	2	30/3	19	1/2" WSHP	C	18760
3	---	---	---	---	---	4	---	---	---	---	---
5	---	---	---	---	---	6	---	---	---	---	---
7	30/3	18	1/2" WSHP	C	16650	8	30/3	19	1/2" WSHP	C	18760
9	---	---	---	---	---	10	---	---	---	---	---
11	---	---	---	---	---	12	---	---	---	---	---
13	20/1		SPARE			14	20/1		SPARE		
15	20/1		SPARE			16	20/1		SPARE		
17	20/1		SPARE			18	20/1		SPARE		
19			SPACE			20			SPACE		
21			SPACE			22			SPACE		
23			SPACE			24			SPACE		
25			SPACE			26			SPACE		
27			SPACE			28			SPACE		
29			SPACE			30			SPACE		
31	60/3	4	1.25" EHU-C1	C	35705	32			SPACE		
33	---	---	---	---	---	34			SPACE		
35	---	---	---	---	---	36			SPACE		
37	60/3	4	1.25" EHU-C2	C	35705	38	100/3	SEE RISER		P	39590
39	---	---	---	---	---	40			SPACE		
41	---	---	---	---	---	42			SPACE		

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	937500	VOLTAGE:	480	937500
RECEPT.	0.5	0	PHASE%	3	0
LIGHT	1.25	0	SPARE %	0.2	0
HEAT	1	0			0
COOL	1	150000			150000
MOTOR	1	0			0
OTHER	1	0			0
SPARE	1	279720			279720
		CONNLOAD	AMP		DEMLOAD AMP
		369736	314		1367220 814

NOTES: PROVIDE FEED THROUGH LUGS TO SERVE PANEL "HM5A"

PNL BRD "HM5A" NO OF CKT SPACES: 42 — MAIN DEVICE: TYPE: MCB
FP VOLT: 480 A/C RATING: 47,000
NO PH: 3 CABINET: SURFACE SIZE: 400A

NO.	TA	WS	COND DESCRIPT	TL	LOAD	NO.	TA	WS	COND DESCRIPT	TL	LOAD
1	30/3	19	1/2" WSHP	C	18760	2	20/1		SPARE		
3	---	---	---	---	---	4	---	---	---	---	---
5	---	---	---	---	---	6	---	---	---	---	---
7	20/1		SPARE			8	30/1	12	1/2" WSHP	C	3480
9	20/1		SPARE			10	30/1	12	1/2" WSHP	C	3480
11	20/1		SPARE			12	---	---	---	---	---
13	20/1		SPARE			14	20/1		SPARE		
15	20/1		SPARE			16	20/1		SPARE		
17	20/1		SPARE			18	20/1		SPARE		
19			SPACE			20			SPACE		
21			SPACE			22			SPACE		
23			SPACE			24			SPACE		
25			SPACE			26			SPACE		
27			SPACE			28			SPACE		
29			SPACE			30			SPACE		
31			SPACE			32			SPACE		
33			SPACE			34			SPACE		
35			SPACE			36			SPACE		
37			SPACE			38			SPACE		
39			SPACE			40			SPACE		
41			SPACE			42			SPACE		

DESCRIPT.	DF	LOAD			DEMAND
OTH. PNLS.	1	0	VOLTAGE:	480	0
RECEPT.	0.5	17890	PHASE%	3	8995