



HARDWARE SCHEDULE

HARDWARE SET	DESCRIPTION	QTY.
1	NOTE: FIELD VERIFY EXISTING DOOR CONDITIONS AND REUSE IF ALLOWABLE THUMBTURN LOCK WITH INDICATOR SIGN - THESE DOORS TO REMAIN UNLOCKED WHILE BUSINESS IS OCCUPIED CLOSER HINGES THRESHOLD PUSH/PULL BAR WITH PADDLE HANDLE	1 EA 1 EA 1 SET 1 EA 1 EA
2	DOUBLE ACTION KITCHEN HINGES REFER TO DETAIL 1/A4.0	1 SET
3	NOTE: FIELD VERIFY EXISTING DOOR CONDITIONS AND REUSE IF ALLOWABLE LOCKSET W/ LEVER HAND OR REPLACE CYLINDER EXTERIOR STRIKE GUARD PLATE VIEWER CLOSER THRESHOLD 36" HIGH 14 GA STEEL DIAMOND PLATE KICK PLATE ON INTERIOR SIDE	1 EA 1 EA 1 EA 1 EA 1 EA 1 EA
4	HINGES PASSAGE SET LEVER HANDSET CLOSER DOOR STOP 8" HIGH KICK PLATE (BRUSHED SS FINISH) ONE ON EACH SIDE	1 SET 1 EA 1 EA 1 EA 1 EA
5	HINGES PRIVACY LOCK SET LEVER HANDLE CLOSER SIGN "MEN" / "WOMEN" (DECOR BY OWNER) ACCESSIBLE SIGN "MEN" / "WOMEN" (BY CONTRACTOR) DOOR / WALL STOP - REFER TO A1.0 8" HIGH KICK PLATE (BRUSHED SS FINISH) ONE ON EACH SIDE	1 SET 1 EA 1 EA 1 EA 1 EA

HARDWARE NOTES

- ALL HARDWARE NEW AND EXISTING SHALL BE IN ACCORDANCE WITH LOCAL AND STATE ACCESSIBILITY STANDARDS, AND AMERICANS WITH DISABILITY STANDARDS.
- A READILY VISIBLE, DURABLE SIGN IS POSTED ON THE EGRESS SIDE OR ADJACENT TO THE DOOR STATING, "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED".
- EGRESS DOORS TO BE READILY OPENABLE FROM THE EGRESS SIDE WITHOUT THE USE OF A KEY OR ANY REQUIRED SPECIAL KNOWLEDGE OR EFFORT.
- EGRESS DOOR LOCK AND LATCHES SHALL COMPLY WITH ALL LOCAL AND STATE CODE REQUIREMENTS.

DOOR SCHEDULE

MARK	SIZE	DESCRIPTION	FRAME	NOTES	RATING	HARDWARE
1	EXISTING	EXISTING ALUMINUM AND GLASS STOREFRONT	ALUM	FIELD VERIFY EXISTING CONDITIONS USE EXISTING HARDWARE IF POSSIBLE	N/A	NUMBER 1
2	CUSTOM	SALES COUNTER MILLWORK GATE	WOOD	SUPPLIED BY OWNER, INSTALLED BY G.C.	N/A	NUMBER 2
3	3'-0" x 7'-0" x 1 3/4"	NEW SOLID CORE WOOD (PAINT GRADE)	METAL	KNOCK-DOWN PRIMER GRADE FRAME PAINTED P4 ALL SIDES	N/A	NUMBER 5
4	3'-0" x 7'-0" x 1 3/4"	NEW SOLID CORE WOOD (PAINT GRADE)	METAL	KNOCK-DOWN PRIMER GRADE FRAME PAINTED P4 ALL SIDES	N/A	NUMBER 5
5	3'-0" x 7'-0" x 1 3/4"	NEW SOLID CORE WOOD (PAINT GRADE)	METAL	KNOCK-DOWN PRIMER GRADE FRAME PAINTED P5 ON PREP SIDE, P4 ON HALLWAY SIDE G.C. TO VFY.	N/A	NUMBER 4
6	CUSTOM	WALK-IN COOLER DOOR	-	G.C. TO VFY.	N/A	-
7	CUSTOM	WALK-IN FREEZER DOOR	-	G.C. TO VFY.	N/A	-
8	EXISTING	HOLLOW METAL (PAINTED)	METAL	FIELD VERIFY EXISTING CONDITIONS & USE EXISTING HARDWARE IF POSSIBLE (PAINT INTERIOR P5)	N/A	NUMBER 3

ROOM FINISH SCHEDULE

ROOM #	ROOM NAME	FLOOR	BASE	WALLS	CEILING	REMARKS
101	ORDER	F1	F5	W6, W7, W9, W10	C1	-
102	SEATING	F1	F5	W1, W6, W7, W9, W10, W11, W12	C1	-
103	HALLWAY	F1	F5	W6, W9, W10	C1	-
104	SALES	F2	F2	W7, W11	C2	REFER TO SHEET E02 FOR WALL TILE LOCATION
105	COOKING	F2	F2	W2, W8	C2	-
106	PREP	F2	F2	W2	C2	-
107	JANITOR	F2	F2	W2	C2	-
108	WALK-IN COOLER	F2	F2	REFER TO WALK-IN SPECIFICATIONS ON SHEET E01	-	EXTERIOR WALLS HAVE F2 AS BASE
109	WALK-IN FREEZER	-	-	REFER TO WALK-IN SPECIFICATIONS ON SHEET E01	-	EXTERIOR WALLS HAVE F2 AS BASE
110	MEN	F6	F3	W4, W6	C2	REFER TO SHEET A3.0 FOR FINISH LOCATIONS
111	WOMEN	F6	F3	W4, W6	C2	REFER TO SHEET A3.0 FOR FINISH LOCATIONS
112	OFFICE	F2	F2	W2	C2	-

ROOM FINISH SCHEDULE NOTES

- REFER TO SHEET A2.0 FOR CEILING HEIGHTS
- REFER TO SHEETS A1.1 FOR ADDITIONAL FLOOR FINISH NOTES
- REFER TO SHEETS A3.0 AND A3.2 FOR PAINT AND FINISH MATERIAL LOCATIONS

FINISH TYPES

- FLOORS**
- EXISTING CONCRETE SLAB TO BE DYED. COLOR: DRIFTWOOD #1395
 - ALTERNATE: 20" CMC ANTWERP BROWN, W/ MAPEI ULTRACOLOR PLUS FA, 07 CHOCOLATE GROUT. TILE LAID DIAGONAL
 - QUARRY TILE (HARD, SMOOTH UNDER ALL EQUIPMENT AND ABRASIVE IN WALL WALKWAYS, NON ABSORBENT) CMC RED QUARRY TILE COVE BASE. CMC RED SMOOTH 6X6X1/2" QUARRY TILE. CMC RED ABRASIVE 6X6X1/2" QUARRY TILE. W/ MAPEI KERAPOXY IEG (INDUSTRIAL EPOXY GROUT), 47 CHARCOAL GROUT
 - CMC ANTWERP BROWN 6X12 COVE BASE. W/ MAPEI ULTRACOLOR PLUS FA 07 CHOCOLATE GROUT
 - CMC RETRO BLACK 6X8 COVE BASE. W/ MAPEI ULTRACOLOR PLUS FA 07 CHOCOLATE GROUT
 - 1X4 WOOD BASE - PAINT P4
 - 20"X20" CMC ANTWERP BROWN, W/ MAPEI ULTRACOLOR PLUS FA, 07 CHOCOLATE GROUT. TILE LAID DIAGONAL
- WALLS**
- 1X6 BC SOUTHERN YELLOW PINE 10'-12' LONG BOARDS - SANDED UP TO 220 GRIT. (1) COAT (SHERWIN-WILLIAMS WOOD CLASSICS - SEMI TRANSPARENT STAIN FRUITWOOD #3118) - (2) COATS OF MINWAX FAST DRYING POLYURETHANE CLEAR SATIN - PROVIDED & INSTALLED BY CONTRACTOR
 - SATIN - PROVIDED & INSTALLED BY CONTRACTOR
 - SEE BELOW FOR CALIFORNIA STAIN SPECS
 - F.R.P. (FIBERGLASS REINFORCED PANELING) PEBBLED FINISH - #P199, COLOR: WHITE
 - PLASTIC LAMINATE, MATTE SURFACE- #ES2003T, COLOR: SIENNA ESSENCE
 - 20x20 CMC ANTWERP BROWN - W/ MAPEI ULTRACOLOR PLUS FA, 07 CHOCOLATE GROUT
 - NOT USED
 - WALL SURFACE FINISH- LEVEL 03 TEXTURED FINISH- ORANGE PEEL
 - WALL SURFACE FINISH- LEVEL 04 SMOOTH FINISH- SMOOTH SURFACE W/ NO TEXTURE
 - STAINLESS STEEL WALL PANEL- CUSTOM PANEL- SMOOTH SURFACE. REFER TO SHEET E02 FOR LOCATION - PROVIDED BY HOOD VENDOR
 - CORRUGATED METAL, 1 1/4" X 1 1/4" PANEL PROFILE
 - 1X CHAIR RAIL- CUSTOM
 - CMC MEZCALAS GREEN 1X1 GLOSSY MOSAIC, W/ MAPEI ULTRACOLOR PLUS FA, 93 WARM GRAY GROUT
 - SCHLUTER STRIP: QUAD-EC-AE. STAINLESS STEEL 304, BRUSHED
- CEILING**
- 2X2 LAY-IN CEILING TILES W/ PRELUDE GRID SYSTEM- FINE FISSURED #1728 COLOR: BLACK W/ BLACK GRID
 - 2X4 LAY-IN CEILING TILES W/ PRELUDE PLUS GRID SYSTEM- CLEAN ROOM VL #870, COLOR: WHITE
- PAINT SCHEDULE**
- COLOR: CRAFTSMAN BROWN, COLOR NO: SW 2835, PROMAR 200 ZERO VOC SEMI-GLOSS
 - COLOR: WINGSTOP BRICK RED, COLOR NO: CUSTOM, PROMAR 200 ZERO VOC SEMI-GLOSS
 - COLOR: PAVILION BEIGE, COLOR NO: SW 7512, PROMAR 200 ZERO VOC SEMI-GLOSS
 - COLOR: 2016 WINGSTOP GREEN, PROMAR 200 ZERO VOC SEMI-GLOSS
 - COLOR: EXTRA WHITE, COLOR NO: SW 7006, PROMAR 200 ZERO VOC SEMI-GLOSS
- ADDITIONAL MATERIAL FINISH NOTES:**
- ALL FINISH MATERIALS TO COMPLY W/ THE FLAME SPREAD CLASSIFICATION RATING AS SPECIFIED IN THE BUILDING CODES INDICATED ON THE COVER SHEET, A0.0
- ADDITIONAL CONCRETE FLOOR FINISH NOTES:**
- THE G.C. SHALL INSPECT THE EXIST. FLOOR PRIOR TO ANY INSTALLATION PROCEDURES & NOTIFY WINGSTOP OF ANY SERIOUS DEFECTS W/ THE EXIST. FLOOR THAT WOULD WARRANT THE INSTALLATION OF A FLOOR LEVELING COMPOUND. THE LEVELING COMPOUND SHALL BE NOTED AS AN ALTERNATE BID TO THE CONSTRUCTION CONTRACTOR.
 - MECHANICALLY SHOTBLAST FLOOR, GRIND EDGES, PREP & INSTALL EPOXY BROADCAST PRIMER.
 - MECHANICALLY GRIND FLOOR & EDGES W/ 50-HYBRID DIAMONDS TO BEGIN PROCESS OF PROFILING THE CONC.
 - CLEAN & PATCH FLOOR.
 - MECHANICALLY GRIND FLOOR & EDGES W/ 100-HYBRID DIAMONDS TO BEGIN THE PROCESS OF PROFILING THE CONC.
 - MASK OFF WALLS AND APPLY SCOFIELD FORMULA ONE LIQUID DYE CONCENTRATE TO FLOOR.
 - APPLY SCOFIELD FORMULA ONE LITHIUM DENSIFIER TO FLOOR.
 - MECHANICALLY GRIND FLOOR & EDGES W/ 400/800-HYBRID DIAMONDS TO BEGIN PROCESS OF POLISHING THE CONC.
 - APPLY (1) ONE COAT OF SCOFIELD CONCRETE GUARD - BURNISH FLOOR W/ 1500 GRIT DIAMOND PADS.
 - APPLY SECOND COAT OF SCOFIELD FORMULA ONE GUARD & BURNISH W/ 3000 GRIT DIAMOND PADS.
- ADDITIONAL QUARRY TILE FINISH NOTES:**
- EDGE PROFILE @ QUARRY TILE - REFER TO DETAIL 5/A1.1

MATERIAL INFORMATION

- FLOOR DYE**
SCOFIELD CONCRETE PRODUCTS / 1-800-800-9800 FORMULA ONE LIQUID DYE CONCENTRATE SEALED WITH FINISH HARDENER FORMULA ONE LITHIUM DENSIFIER. A CERTIFIED SCOFIELD INSTALLER IS RECOMMENDED. CONTACT CUSTOMER SERVICE FOR LOCAL INSTALLER AT THE NUMBER SPECIFIED ABOVE * REFER TO THE ADDITIONAL CONCRETE FLOOR FINISH NOTES.
- QUARRY TILE, WALL TILE, TILE COVE BASE & SETTING MATERIAL**
CREATIVE MATERIALS CORPORATION (CMC)
MAPEI or equal
AMY BURKE / 518-713-5386
ABURKE@CREATIVEMATERIALSCORP.COM
- WOOD BASE TRIM**
LIGHTLY SAND W/ 220 GRIT SANDPAPER & PAINT 'P4'
- FRP**
MARLITE / 330-343-6621
FRP SHALL BE PROVIDED ON ALL WALLS AT FULL HEIGHT IN THE SALES, COOKING, PREPARATION, SKULLERY & JANITOR AREAS. (ALSO IN OFFICE AREA IF APPLICABLE)
- WINDOW SHADES**
ROLL-A-SHADE / 951.245.5077 x 119
jsmall@rollashade.com
WWW.ROLLASHADE.COM
SHEER WEAVE 2390 (5%) V20 PEARL GRAY WITH DIGITALLY PRINTED WINGSTOP LOGO
- CORRUGATED METAL PANELS**
BRIDGER STEEL
11835 QUAA RD.
BLACK HAWK, SD 57718
PH: 605-716-9003
FAX: 605-716-9034
PANELS ARE TESTED FOR UL 790 CLASS A FIRE RESISTANCE RATING AND UL 2218 CLASS 4 HAIL IMPACT RESISTANCE.
- CEILING TILE**
ARMSTRONG PRODUCTS / 877-276-7876
- PAINT**
SHERWIN WILLIAMS / 214-728-6696. REFERENCE PARENT CODE #3729
REFER TO SHEET A3.0 FOR LOCATIONS
- WRI LIGHTING**
MELETO LIGHTING
JIM ELLIS
JELLIS@METELO.COM
PH: 214-352-3900
- GREASE INTERCEPTOR - NATIONAL ACCOUNT INFORMATION**
SCHIER NATIONAL STRATEGIC PRICING AGREEMENT #001078
PLEASE CONTACT:
SEAN MOLEN - NATIONAL ACCOUNTS MANAGER
SEAN.MOLEN@SCHIERPRODUCTS.COM
PH: 816-506-3203

WARNER ARCHITECTURAL ASSOCIATES
109 ANDERSON STREET SE, SUITE 105
MARIETTA, GA 30060
PH: 678.290.9200
EMAIL: INFO@WARNERARCHASSOC.COM



WING-STOP
10125 ULMERTON RD.
LARGO, FL 33771
STORE # V050

DRAWN BY: RDL
CHECKED BY: WLW
DATE:
PROJECT: WS1813
REVISION:
REVISION:

SCHEDULES & DETAILS
DRAWING NUMBER
A4.0