


Order Plans @

WWW.LDILine.com

PLUMBING FIXTURE SCHEDULE									
TAG	DESCRIPTION	WASTE	VENT	HOT WATER	COLD WATER	FIXTURE	FAUCET OR FLUSH VALVE	ADDITIONAL COMMENTS	
F-1	WATER CLOSET, FLUSH VALVE, WALL MOUNTED, ELECTRONIC FLUSH VALVE.	4"	2"	-	1-1/4"	BASIS OF DESIGN: AMERICAN STANDARD AFWALL FLOWISE, 1.28 GPF, MODEL 3355.128. WATER CLOSET SEAT SHALL BE WHITE, SOLID PLASTIC WITH CHECK HINGE. CHURCH 9900-C, OLSONITE 1050, BENEKE 525 CH, BEMIS 1655C, CENTOCO 500.	EXPOSED FLUSH VALVE SHALL BE A SLOAN 8111, SOLAR POWERED, 1.28 GPF, POLISHED CHROME FINISH, VACUUM BREAKER.	N/A	
F-2	WATER CLOSET, FLUSH VALVE, ADA, WALL MOUNTED, ELECTRONIC FLUSH VALVE.	4"	2"	-	1-1/4"	BASIS OF DESIGN: AMERICAN STANDARD AFWALL FLOWISE, 1.28 GPF, MODEL 3355.128. WATER CLOSET SEAT SHALL BE WHITE, SOLID PLASTIC WITH CHECK HINGE. CHURCH 9900-C, OLSONITE 1050, BENEKE 525 CH, BEMIS 1655C, CENTOCO 500.	EXPOSED FLUSH VALVE SHALL BE A SLOAN 8111, SOLAR POWERED, 1.28 GPF, POLISHED CHROME FINISH, VACUUM BREAKER, DUAL SEAL DIAPHRAGM, SUITABLE FOR ADA COMPLIANCE.	N/A	
F-3	WATER CLOSET, FLUSH VALVE, ADA, FLOOR MOUNTED, ELECTRONIC FLUSH VALVE.	4"	2"	-	1-1/4"	BASIS OF DESIGN: AMERICAN STANDARD MADERA FLOWISE, 1.28 GPF, MODEL 3461.128. WATER CLOSET SEAT SHALL BE WHITE, SOLID PLASTIC WITH CHECK HINGE. CHURCH 9900-C, OLSONITE 1050, BENEKE 525 CH, BEMIS 1655C, CENTOCO 500.	EXPOSED FLUSH VALVE SHALL BE A SLOAN 8111, SOLAR POWERED, 1.28 GPF, POLISHED CHROME FINISH, VACUUM BREAKER, DUAL SEAL DIAPHRAGM, SUITABLE FOR ADA COMPLIANCE.	N/A	
F-4	URINAL, FLUSH VALVE, ADA, WALL MOUNTED, ELECTRONIC FLUSH VALVE.	2"	2"	-	3/4"	BASIS OF DESIGN: AMERICAN STANDARD WASHBROOK FLOWISE, 0.125 GPF, MODEL 0590.125, TOP SPUD, ELONGATED RIM (14"), THE CONTRACTOR SHALL PROVIDE BLOCKING FOR WALL-MOUNTED CARRIERS FOR URINALS. MOUNT WITH RIM 24" ABOVE FINISHED FLOOR.	EXPOSED FLUSH VALVE SHALL BE SLOAN WEUS-1000.1201-0.13, SOLAR POWERED, 0.125 GPF, POLISHED CHROME FINISH, VACUUM BREAKER, DUAL SEAL DIAPHRAGM, SUITABLE FOR ADA COMPLIANCE.	N/A	
F-5	LAVATORY, ADA, UNDER-COUNTER MOUNTED, ELECTRONIC FAUCET.	2"	1-1/4"	1/2"	1/2"	BASIS OF DESIGN: AMERICAN STANDARD OVALYN, MODEL 0496.221.	FAUCET SHALL BE A SLOAN SOLIS, EAF-275-ISM, SENSOR OPERATED, 0.5 GPM, POLISHED CHROME FINISH WITH INTEGRAL SPOUT TEMPERATURE MIXER.	PROVIDE 1-1/4" OFFSET GRID DRAIN ASSEMBLY.	
F-6	MOP SINK, FLOOR MOUNTED TERRAZZO TYPE.	3"	2"	3/4"	3/4"	BASIS OF DESIGN: FIAT TSB-100, 24"x24"x12". PROVIDE WITH STAINLESS STEEL CAPS ON ALL CURBS.	FAUCET SHALL BE FIAT IS0-AA WITH IS2-AA HOSE AND BRACKET.	PROVIDE FIAT MSG-2424 STAINLESS STEEL WALL GUARD.	
F-7	ELECTRIC WATER COOLER, ADA, BLEVEL UNIT WITH ELECTRONIC BOTTLE FILLER.	2"	1-1/4"	----	1/2"	BASIS OF DESIGN: OASIS PGR8EBFSL WITH STAINLESS STEEL FINISH.	NA	NA	
F-8	ELECTRIC WATER COOLER, ADA, BLEVEL UNIT.	2"	1-1/4"	----	1/2"	BASIS OF DESIGN: OASIS PRACSL WITH STAINLESS STEEL FINISH.	NA	NA	
F-9	STAINLESS STEEL SECURITY FIXTURE, COMBINATION WATER CLOSET AND LAVATORY.	4"x1-1/4"	2"	1/2"	1-1/4"	BASIS OF DESIGN: ACORN 1420LRB-28P-04-FV-1.28-LW1-C01-PC.	N/A	N/A	
F-10	SHOWER (FITTINGS ONLY)	3"	2"	1/2"	1/2"	BASIS OF DESIGN: SYMMONS TEMPTR0L C-96-1, PROVIDED WITH 1.5 GPM SHOWER HEAD.	N/A	NA	
F-11	SHOWER (FITTINGS ONLY) ADA	3"	2"	1/2"	1/2"	BASIS OF DESIGN: SYMMONS TEMPTR0L C-96-300-B30-V-X, PROVIDED WITH 1.5 GPM SHOWER HEAD.	N/A	NA	
F-12	WASHING MACHINE BOX	2"	2"	1/2"	1/2"	BASIS OF DESIGN: WATER-TITE 85708 WITH WATER HAMMER ARRESTORS.	N/A	NA	
F-13	VALVE BOX	N/A	N/A	N/A	1/2"	BASIS OF DESIGN: WATER-TITE 87978 WITH WATER HAMMER ARRESTOR.	N/A	NA	
F-14	SINGLE COMPARTMENT STAINLESS STEEL SINK (BREAKROOM)	2"	1-1/2"	1/2"	1/2"	BASIS OF DESIGN: ELKAY LRAD3122	FAUCET SHALL BE AN ELKAY LK3001CR, 1.5 GPM WITH SINGLE LEVER HANDLE AND HOSE SPRAY	NA	
F-15	SINGLE COMPARTMENT STAINLESS STEEL SINK (TESTING LAB)	2"	1-1/2"	1/2"	1/2"	BASIS OF DESIGN: ELKAY LRAD251	FAUCET SHALL BE A CHICAGO 895-317GNZAF0CP GOOSENECK TYPE, 4" CENTERS, WRISTBLADE HANDLES AND 1.6 GPM LAMINAR FLOW CONTROL.	NA	
FD-1	FLOOR DRAIN, LIGHT DUTY, 8"x8" ROUND NICKEL-BRONZE TOP WITH VANDAL PROOF GRATE.	VARIES	---	---	---	BASIS OF DESIGN: J.R. SMITH 2055	NA	NA	
FD-2	FLOOR DRAIN, MEDIUM DUTY WITH 8" ROUND DUCTILE IRON TOP AND SEDIMENT BUCKET.	VARIES	---	---	---	BASIS OF DESIGN: J.R. SMITH 2055-MB	NA	NA	

PUMP SCHEDULE								
TAG	TYPE	ELECTRICAL				FLOW RATE	HEAD PRESSURE	BASIS OF DESIGN
		HP	WATTS	VOLT.	PH.			
RCP-1	DOMESTIC HOT WATER CIRCULATING	--	8	120	1	4 GPM	4 FEET	BELL & GOSSETT 63-4VBTPRC




THIS DRAWING IS AN INSTRUMENT OF SERVICE AND SHALL REMAIN THE PROPERTY OF THE ARCHITECT. NO PART OF THIS DOCUMENT SHALL BE REPRODUCED OR TRANSMITTED IN ANY FORM, ELECTRONICALLY OR MECHANICALLY, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF THE ARCHITECT.

PLUMBING SCHEDULES

PROJECT # 19160MONRpo
 DATE: Issue Date
 DRAWN BY: JAA
 CHECKED BY: DC

P501

SCALE: NTS



PERMIT SET