RECEIVED
APR 04 2019
1736 E. SUNSHINE ST. SUITE 417
SPRINGFIELD, MO

Catalog # : MRM LED 36L SIL FT UNV DIM 50 80CRI BRZ IL	Project : O'Reilly Auto Parts
Prepared By : Greybar	Date : 8/24/2018

Mirada Medium - MRM
Outdoor LED Area Light

The Mirada's sleek design makes it perfectly suitable for architectural & commercial applications while its cost-effective die-cast aluminum housing makes its acquisition cost very competitive. The Mirada starts high performance factory installed, and the optics & standard CCTs (4,000K) delivered lumens, and is available with integral Airlink™ Wireless Controls.

Features & Specifications

Optical System
- State-of-the-Art one piece silicone optic sheet delivers industry leading optical control with an integrated gasket to provide IP66 rated sealed optical chamber in 1 component.
- Proprietary silicone refractor optics provide exceptional coverage and uniformity in IES Types 2, 3, SW, FT and FTA.
- Silicone optical material does not yellow or crack with age and provides a typical light transmittance of 93%.
- Zero uplight.
- Available in 5000K, 4000K, 3000K, and 2700K color temperatures per ANSI C78.377. Also available in Phosphor Converted Amber, consult factory for availability.
- Minimum CRI of 70. Optional 80 CRI available, consult factory for lead time.
- Integral Louver (IL) option available for improved back-light control without sacrificing street side performance. See page 5 for more details.

Electrical
- High-performance driver features over-voltage, under-voltage, short-circuit and over temperature protection.
- 0-10V dimming (10% - 100%) standard.
- Standard Universal Voltage (120-277 Vac) Input 50/60 Hz or optional High Voltage (347-480 Vac).
- L80 Calculated Life: >100k Hours (See Lumen Maintenance on Page 3)
- Total harmonic distortion: <20%
- Operating temperature: -40°C to +50°C (-40°F to +122°F). 42L lumen package rated to +40°C.
- Power factor: >.90
- Input power stays constant over life.
- Field replaceable surge protection device meets a minimum Category C Low operation (per ANSI/IEEE C62.41.2).
- High-efficacy LEDs mounted to metal-core circuit board to maximize heat dissipation
- Terminal block provided accepts up to 10ga wire.
- Components are fully encased in potting material for moisture resistance. Driver complies with FCC standards. Driver and key electronic components can easily be accessed.

IP66 · RoHS COMPLIANT · ARRA Funding Compliant · cULus LISTED · USA

Product Dimensions



LSI Industries Inc. 10000 Alliance Rd. Cincinnati, OH 45242 • www.lsi-industries.com • (513) 372-3200 • ©LSIIndustries Inc. All Rights Reserved.

Mirada Medium - MRM
Outdoor LED Area Light

Features & Specifications (Cont.)

Construction
- Rugged die-cast aluminum housing contains factory prewired driver and optical unit. Cast aluminum wiring access door located underneath.
- Designed to mount to square or round poles.
- Luminaire is proudly manufactured in the U.S.of U.S. and imported parts.
- IP66 rated luminaire protects integral components from harsh environments.
- 3G rated for ANSI C136.31 high vibration applications
- Fixtures are finished with LSI's DuraSnap® polyester powder coat finishing process. The DuraSnap finish withstands extreme weather changes without cracking or peeling. Other standard LSI finishes available. Consult factory.
- Shipping weight: 30 lbs is carton.

Controls
Wireless Controls System
To make this fixture AirLink ready, simply order one of the following options:
a. The integrated Wireless Lighting Controller: ALSC or ALSCH (see ordering guide) as the controls option, or
b. Integrated Wireless Controller option (above) with integrated motion sensor: ALSCS (ordering guide for mounting heights) or
c. The 7-Pin Photoelectric Control Receptacle: CRFP as the controls option; and either the 5-Pin or 7-Pin Twist Lock Controller: ALSC UNV TLS or ALSC UNV TLT as an accessory

To see how the components of AirLink system work together, reference the diagram in the controls section of this specsheet. For more information on our AirLink products, visit our website: www.lsi-airlink.com/airlink-overview/

Stand-Alone Controls
- The integral passive infrared motion sensor (IMS) activates switching of luminaire light levels (see the controls section for more details).
- The 7-pin ANSI C136.41-2013 photocontrol receptacle option (CRFP) is available for twist lock photocontrols or wireless control modules.
- The Button Type Photocells (PC) are capable of switching luminaires ON/OFF in response to the amount of available daylight.

Installation
- A single fastener secures the hinged door, underneath the housing and provides quick & easy access to the electrical compartment for installing/servicing.
- Included terminal block provides quick and easy on-site wiring.
- Utilizes LSI's traditional 3" drill pattern for easy fastening of LSI products. (See drawing on page 1)

Warranty
- LSI LED Fixtures carry a 5-year warranty.

Listings
- Listed to UL 1598 and UL 8750.
- RoHS Compliant.
- American Recovery and Reinvestment Act Funding Compliant.
- IDA compliant; with 3000K color temperature selection.
- Title 24 Compliant; see local ordinance for qualification information.
- Suitable For wet Locations.
- IP66 rated Luminaire. IP66 rated optical chamber.
- 3G rated for ANSI C136.31 high vibration applications

Performance

ELECTRICAL DATA (AMPS)*

Lumens	Watts	120V	208V	240V	277V	347V	480V
7L	53	0.4A	0.3A	0.3A	0.2A	0.2A	0.1A
9L	68	0.6A	0.3A	0.3A	0.2A	0.2A	0.1A
12L	94	0.8A	0.5A	0.4A	0.3A	0.3A	0.2A
16L	130	1.2A	0.7A	0.6A	0.5A	0.4A	0.3A
23L	190*	1.6A	0.9A	0.8A	0.7A	0.6A	0.4A
30L	240	2.1A	1.3A	1.0A	0.9A	0.7A	0.5A
36L	317	2.8A	1.8A	1.5A	1.1A	0.9A	0.7A
42L	390	3.2A	1.9A	1.6A	1.4A	1.1A	0.8A

*Electrical data at 25C (77F). Actual wattage may differ by +/-10%.

ELECTRICAL DATA - PHOSPHOR CONVERTED AMBER (AMPS)*

Lumens	Watts	120V	208V	240V	277V	347V	480V
9L	74.3	0.6A	0.4A	0.3A	0.2A	0.2A	0.2A
12L	102.8	0.9A	0.5A	0.4A	0.4A	0.3A	0.2A

*Electrical data at 25C (77F). Actual wattage may differ by +/-10%.

RECOMMENDED LUMEN MAINTENANCE(Y24-42L)

Ambient	$L_{85}B_{50}$	25 $k h^2$	50 $k h^2$	75 $k h^2$	100 $k h^2$
0-40°C	100%	100%	97%	94%	92%

RECOMMENDED LUMEN MAINTENANCE(Y-18L)

Ambient	$L_{85}B_{50}$	25 $k h^2$	50 $k h^2$	75 $k h^2$	100 $k h^2$
0-50°C	100%	96%	92%	89%	84%

DELIVERED LUMENS*

Lumen Package	Distribution	Lm	2700K CCT Delivered Lumens	2700K CCT Efficacy	3000K CCT Delivered Lumens	3000K CCT Efficacy	4000K CCT Delivered Lumens	4000K CCT Efficacy	5000K CCT Delivered Lumens	5000K CCT Efficacy	Wattage
7L	2	1000	1000	89	1000	89	1000	89	1000	89	53
	2-5	1000	1000	89	1000	89	1000	89	1000	89	
	3	1000	1000	89	1000	89	1000	89	1000	89	
	3-5	1000	1000	89	1000	89	1000	89	1000	89	
	5	1000	1000	89	1000	89	1000	89	1000	89	
	FT	1000	1000	89	1000	89	1000	89	1000	89	
	FT-5	1000	1000	89	1000	89	1000	89	1000	89	
	FTA	1000	1000	89	1000	89	1000	89	1000	89	
	FTA-5	1000	1000	89	1000	89	1000	89	1000	89	
9L	2	1300	1300	89	1300	89	1300	89	1300	89	68
	2-5	1300	1300	89	1300	89	1300	89	1300	89	
	3	1300	1300	89	1300	89	1300	89	1300	89	
	3-5	1300	1300	89	1300	89	1300	89	1300	89	
	5	1300	1300	89	1300	89	1300	89	1300	89	
	FT	1300	1300	89	1300	89	1300	89	1300	89	
	FT-5	1300	1300	89	1300	89	1300	89	1300	89	
	FTA	1300	1300	89	1300	89	1300	89	1300	89	
	FTA-5	1300	1300	89	1300	89	1300	89	1300	89	
12L	2	1600	1600	89	1600	89	1600	89	1600	89	94
	2-5	1600	1600	89	1600	89	1600	89	1600	89	
	3	1600	1600	89	1600	89	1600	89	1600	89	
	3-5	1600	1600	89	1600	89	1600	89	1600	89	
	5	1600	1600	89	1600	89	1600	89	1600	89	
	FT	1600	1600	89	1600	89	1600	89	1600	89	
	FT-5	1600	1600	89	1600	89	1600	89	1600	89	
	FTA	1600	1600	89	1600	89	1600	89	1600	89	
	FTA-5	1600	1600	89	1600	89	1600	89	1600	89	
16L	2	2000	2000	89	2000	89	2000	89	2000	89	130
	2-5	2000	2000	89	2000	89	2000	89	2000	89	
	3	2000	2000	89	2000	89	2000	89	2000	89	
	3-5	2000	2000	89	2000	89	2000	89	2000	89	
	5	2000	2000	89	2000	89	2000	89	2000	89	
	FT	2000	2000	89	2000	89	2000	89	2000	89	
	FT-5	2000	2000	89	2000	89	2000	89	2000	89	
	FTA	2000	2000	89	2000	89	2000	89	2000	89	
	FTA-5	2000	2000	89	2000	89	2000	89	2000	89	
23L	2	2800	2800	89	2800	89	2800	89	2800	89	190
	2-5	2800	2800	89	2800	89	2800	89	2800	89	
	3	2800	2800	89	2800	89	2800	89	2800	89	
	3-5	2800	2800	89	2800	89	2800	89	2800	89	
	5	2800	2800	89	2800	89	2800	89	2800	89	
	FT	2800	2800	89	2800	89	2800	89	2800	89	
	FT-5	2800	2800	89	2800	89	2800	89	2800	89	
	FTA	2800	2800	89	2800	89	2800	89	2800	89	
	FTA-5	2800	2800	89	2800	89	2800	89	2800	89	
30L	2	3600	3600	89	3600	89	3600	89	3600	89	240
	2-5	3600	3600	89	3600	89	3600	89	3600	89	
	3	3600	3600	89	3600	89	3600	89	3600	89	
	3-5	3600	3600	89	3600	89	3600	89	3600	89	
	5	3600	3600	89	3600	89	3600	89	3600	89	
	FT	3600	3600	89	3600	89	3600	89	3600	89	
	FT-5	3600	3600	89	3600	89	3600	89	3600	89	
	FTA	3600	3600	89	3600	89	3600	89	3600	89	
	FTA-5	3600	3600	89	3600	89	3600	89	3600	89	
36L	2	4000	4000	89	4000	89	4000	89	4000	89	317
	2-5	4000	4000	89	4000	89	4000	89	4000	89	
	3	4000	4000	89	4000	89	4000	89	4000	89	
	3-5	4000	4000	89	4000	89	4000	89	4000	89	
	5	4000	4000	89	4000	89	4000	89	4000	89	
	FT	4000	4000	89	4000	89	4000	89	4000	89	
	FT-5	4000	4000	89	4000	89	4000	89	4000	89	
	FTA	4000	4000	89	4000	89	4000	89	4000	89	
	FTA-5	4000	4000	89	4000	89	4000	89	4000	89	
42L	2	4600	4600	89	4600	89	4600	89	4600	89	390
	2-5	4600	4600	89	4600	89	4600	89	4600	89	
	3	4600	4600	89	4600	89	4600	89	4600	89	
	3-5	4600	4600	89	4600	89	4600	89	4600	89	
	5	4600	4600	89	4600	89	4600	89	4600	89	
	FT	4600	4600	89	4600	89	4600	89	4600	89	
	FT-5	4600	4600	89	4600	89	4600	89	4600	89	
	FTA	4600	4600	89	4600	89	4600	89	4600	89	
	FTA-5	4600	4600	89	4600	89	4600	89	4600	89	

*LED Chips are frequently updated therefore values are nominal

LUMINAIRE EPA CHART - MRM

	Single	0.8
	D-D	1.1
	T	0.9
	T-T	1.9
	1x1	1.9
	2x2	2.1

Luminaires and dimensions are subject to change without notice.
LSI Industries Inc. 10000 Alliance Rd. Cincinnati, OH 45242 • www.lsi-industries.com • (513) 372-3200 • ©LSI Industries Inc. All Rights Reserved.
08/21/18

Mirada Medium - MRM
Outdoor LED Area Light

Performance (Cont.)

All published luminaire photometric testing performed to IESNA LM-79 standards. ISO footcandle plots below demonstrate the Mirada (MRM) light patterns only. Not for total fixture output. For complete specifications and IES files, see website.



Ordering Guide

TYPICAL ORDER EXAMPLE: **MRM LED 36L SIL FTA UNV DIM 50 70CRI ALSCS04 BRZ IL**

Luminaire Prefix	Light Source	Lumen Package*	Light Output	Distribution	Orientation*	Voltage	Driver
MRM2 Mirada	LED	7L - 7,000 lms 9L - 9,000 lms 12L - 12,000 lms 16L - 16,000 lms 23L - 23,000 lms 30L - 30,000 lms 42L - 42,000 lms *Consult factory for programmable wattages and lumen packages	SIL - SIRIUS	2 - Type 2 3 - Type 3 SW - Type 5 Wide FT - Forward Throw FTA - Forward Throw Automotive	(blank) - Standard L - Optics rotated left 90 R - Optics rotated right 90	UNV - Universal Voltage (120-277V) HVU - High Voltage (347-480V)	DIM - 0-10V Dimming (2-wire)

Color Temp	Color Rendering	Controls (Choose One)	Finish	Options
50 - 5,000 CCT 40 - 4,000 CCT 30 - 3,000 CCT* 27 - 2,700 CCT* AMB - Phosphor Converted Amber**	70CRI - 70 CRI 80CRI - 80 CRI*	(Blank) - None Wireless Controls System ALSC - AirLink Dynalite Control System * ALSCH - AirLink Synapse Control System with 5-12' Motion Sensor * ALSCHSM1 - AirLink Synapse Control System Head / Isolator with 8-12' Motion Sensor ** ALSCHSD - AirLink Synapse Control System with 13-23' Motion Sensor * ALSCHSD2 - AirLink Synapse Control System Head / Isolator with 13-23' Motion Sensor ** ALSCHSH - AirLink Synapse Control System with 23-42' Motion Sensor * ALSCHSH4 - AirLink Synapse Control System Head / Isolator with 23-42' Motion Sensor ** Stand-Alone Controls EXT - 0-10V Dimming (Field Installed) SHS0501 - Integral Motion Sensor 8-12' 120-277V ** SHS2040 - Integral Motion Sensor 13-23' 120-277V ** SHS4064 - Integral Motion Sensor 23-42' 120-277V ** SHS7HVF - Integral Motion Sensor 8-12' 347-480V ** SHS0501HV - Integral Motion Sensor 13-23' 347-480V ** SHS2040H - Integral Motion Sensor 23-42' 347-480V ** CRFP - 7 Pin Control Receptacle ANSI C136.41 *	BRZ - Bronze BLK - Black GPT - Granite MSV - Metallic Silver WHT - White PLP - Platinum Plus SVG - Satin Verde Green	(Blank) - None IL - Integral Louver, 90°*

Fixture Type Photometric
PCR26 - 120V
PCR26-277 - 208-277V
PCR347 - 347V

LSI Industries Inc. 10000 Alliance Rd. Cincinnati, OH 45242 • www.lsi-industries.com • (513) 372-3200 • ©LSI Industries Inc. All Rights Reserved. 03/21/18

MIRADA WALL SCONCE (XWM)



DOE LIGHTING FACTS
Department of Energy has verified representative product test data and results in accordance with its Lighting Facts Program. Visit www.lightingfacts.com for specific catalog strings.

LIGHT OUTPUT - XWM - 3 5000K CCT

Lumens	Wattage	LPW
03	9418	29
04	4417	43
05	6539	59
09	5810	82

LED Chips are frequently updated therefore values may increase.

COVERAGE DIAGRAM

SIDE VIEW



TOP VIEW



US & Int'l. patents pending

SMARTTEC™ - LSI drivers feature integral sensor which reduces drive current, when ambient temperatures exceed rated temperature

ENERGY SAVING CONTROL OPTIONS - DIM - 0-10 volt dimming enabled with LSI wireless controls.

OPTIONAL INTEGRAL MOTION SENSOR - Passive infrared motion sensor activates switching of luminaire light levels. High level light is activated when passersby enter target zone and increased to full bright in 1-2 seconds. Low light level (60% of maximum drive current) is activated when target zone is absent of motion activity for 5 minutes and is gradually ramped down (10 seconds) to low level. Sensor detection range 110° horizontal x 93° vertical x 10 meters maximum distance.

LEDS - Available with 6000K, 4000K or 3000K color temperature, 70 CRI min.

OPTICS/DISTRIBUTIONS - Ultra-high efficiency reflectors provide three distributions. Choose from Type 2, Type 3 or Type FT.

HOUSING - Three-piece die-cast aluminum housing is smoothly contoured low-profile shape. Mounting hardware is stainless steel or electro-zinc plated steel. Housing and optical unit are sealed with extruded silicone gasket; supply conductors with molded EPDM bushing.

OPTICAL UNIT - Proprietary silicone refractor optics provide exceptional coverage and uniformity. Pressure stabilizing breather allows super-tight protection while preventing cycling from building up internal pressures and vacuums that can damage optical unit seals

WALL MOUNTING - Galvanized-steel universal wall mounting plate easily mounts directly to 4" octagonal or square junction box. EPDM gasket is molded to be installed between mounting plate and junction box, sealing junction box from entry of moisture. Universal plate permits fixture to be mounted in up to four (4) directly) or downright position. Optional pole-mounting bracket permits mounting to standard poles (XPMA).

ELECTRICAL - Two-stage surge protection (separating secondary surge protector built into electronic driver) meets ANSI C136.41.2-2002 Location Category C. Available with universal voltage power supply (120-277 Vac, 50/60Hz) or 347 VAC.

DRIVER - Drivers are fully potted. Components are fully encased in potting material for moisture resistance. Driver complies with FCC and FCC standards. Driver can be easily accessed.

EMERGENCY OPTIONS - Optional integral emergency battery-back-up options are available. EM8 option operates in 0°C to 40°C ambient temperature and CWEB operates in -20°C to 60°C ambient temperature. When primary AC power failure occurs, both options operate 10 LEDs for minimum of 90 minutes.

OPERATING TEMPERATURE - -40°C to +50°C (-40°F to +122°F)

FINISH - Fixtures are finished with LSI's DuraSnap® polyester powder coat finishing process. The DuraCrip finish withstands extreme weather changes without cracking or peeling.

WARRANTY - LSI LED fixtures carry a limited 5-year warranty.

PHOTOMETRICS - Please visit our web site at www.lsi-industries.com for detailed photometric data.

SHIPPING WEIGHT (in carton) - 30 lbs./13.6Kg

LISTING - UL listed to ANSI/UL1598, UL8750 and other U.S. and international safety standards. Suitable for wet locations in downlight position.

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.

RoHS COMPLIANT · cULus WET LOCATIONS · CE · ARRA FUNDING COMPLIANT · IP65 · FC

Project Name _____ Fixture Type _____
Catalog # _____
10/20/17
© 2017 LSI INDUSTRIES INC.

MIRADA WALL SCONCE (XWM)

LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **XWM 04 LED 09L 50K UE WHT IMS**

Prefix	Generation	Performance	Color Temperature	Input Voltage	Finish	Optional Controls	Optional Accessories/Options
XWM - Mirada Wall Sconce	04 - Gen 4 (Current)	FT - Forward Throw (Forward)	50 - 5000K 40 - 4000K 30 - 3000K	UE - Universal 120/277 (120-277)	BLK - Black BRZ - Bronze MSV - Metallic Silver PLP - Platinum Plus WHT - White	(Blank) - None SMARTTEC™ - LSI Drivers feature integral sensor which reduces drive current, when ambient temperatures exceed rated temperature IMS - Integral Motion Sensor[1,2]	Sensor IMS - Integral Motion Sensor[1,2] Options EB - Battery Back-up[3] CWEB - Cold Weather Battery Back-up[3] XPMA - Pole Mounting Bracket

ACCESSORY ORDERING INFORMATION[1] (Accessories are field installed)

Order Description	Color Matched	Description	Order Number
XJBOX3-SQ-X - Surface Wiring Box (available in black only)	Specify color	SPD120 - Diode Fusing	SPD120
XJB3 - Square Housing	WHT	SPD240 - Diode Fusing	SPD240
XJB3T - Round Housing	WHT	SPD277 - Diode Fusing	SPD277
XJB3V - Round Housing	WHT	RMSPC Remote Compartment Box	SPD277

FOOTNOTES:
1 - Field installed (refer to instruction sheet).
2 - Requires a 5-pin Molded Twist Lock Receptacle (ANSI C136.41-2013) (Ordered separately).
3 - Not compatible with IMS Option.
4 - Not compatible with IMS or Wireless Control System.
5 - Not compatible with Wireless Control System.
6 - Not available with SQ, CWEB, 347 Volts or Wireless Control System.
7 - IMS is the Watchfyre Dual Sensor Daylight & Motion which is field adjustable, via a handheld remote configurator tool.
8 - Output base range & options are not available under conditions via IES files for exact delivered lumens.

DIMENSIONS



Project Name _____ Fixture Type _____
Catalog # _____
10/20/17
© 2017 LSI INDUSTRIES INC.

Order Plans @ WWW.

COMMONWEALTH OF VIRGINIA
NORMAN E. GOTH
Lic.No. 0402 038814
PROFESSIONAL ENGINEER
04/03/19

DRAWN BY: JTH

CRAIG A. SCHNEIDER, AIA
ARCHITECT
1736 East Sunshine, Suite 417
Springfield, Missouri 65804
417.862.9558
FAX: 417.862.3245
e-mail: architect@cfschneider.com

PROJECT:
NEW O'REILLY AUTO PARTS STORE
290 DEACON ROAD 03-25-19
FREDERICKSBURG, VA #4

SITE LIGHTING DETAILS

O'Reilly AUTO PARTS
CORPORATE OFFICES
233 SOUTH PATTERSON
SPRINGFIELD, MISSOURI 65802
(417) 862-2674 TELEPHONE

COMM #	4251
DATE:	11-02-18
REVISION DATE:	3-25-19

© COPYRIGHT 2019-2020 - DESIGNS, DRAWINGS AND SPECIFICATIONS ARE INSTRUMENTS OF SERVICE AND ARE THE PROPERTY OF THE DESIGN PROFESSIONAL. REPRODUCTION PROHIBITED WITHOUT THE EXPRESSED WRITTEN CONSENT OF THE DESIGN PROFESSIONAL.

SGE
SMITH-GOTH ENGINEERS, INC.
3855 S. JEFFERSON AVE. SPRINGFIELD, MO 65807
P: 417-882-2200
F: 417-882-1198
WWW.SMITHGOTH.COM