

OPMD 0.0.01

Normal Impact: FRAMING, DRYVIT ADHESIVE IN VERTICAL NOTCHED TROWEL CONFIGURATION APPLIED TO BACK OF EPS, EPS INSULATION BOARD, APPROVED SUBSTRATE, DRYVIT AIRWATER-RESISTIVE BARRIER COATING, DRYVIT BASE COAT, DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT, DRYVIT FINISH, DRYVIT DRAINAGE STRIP ADHERED WITH DAP OF DRYVIT AP ADHESIVE (SEE NOTES 2 AND 3).

High Impact: FRAMING, DRYVIT ADHESIVE IN VERTICAL NOTCHED TROWEL CONFIGURATION APPLIED TO BACK OF EPS, EPS INSULATION BOARD, APPROVED SUBSTRATE, DRYVIT AIRWATER-RESISTIVE BARRIER COATING, DRYVIT BASE COAT, DRYVIT PANZER REINFORCING MESH, DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT, DRYVIT FINISH, DRYVIT DRAINAGE STRIP ADHERED WITH DAP OF DRYVIT AP ADHESIVE (SEE NOTES 2 AND 3).

Outsulation® Plus MD System®

NOTE:
 1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH LOCATION OR HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
 2. AS AN OPTION DRYVIT DRAINAGE TRACK™ CAN BE USED AT SYSTEM TERMINATION AT GABLE, INFER TO OPMD 0.0.04 FOR CONFIGURATION.
 3. DRYVIT DRAINAGE TRACK SHALL ONLY BE USED AT GRADE LEVEL TERMINATIONS.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.02

FRAMING, APPROVED SUBSTRATE, DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT GRID TAPE™, DRYVIT AIRWATER-RESISTIVE BARRIER COATING.

Outsulation® Plus MD System®

AVWRB Application

NOTE:
 1. HIGH ADDITIONAL AIRWATER-RESISTIVE BARRIER DETAILS. REFER TO DRYVIT PUBLICATION DS84.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.03

STEP #1: APPLY DRYVIT AQUAFLASH SYSTEM AT ANGLE (SEE NOTES 1 AND 2).
STEP #2: INSTALL DIAGONAL STRIP OF DRYVIT AQUAFLASH MESH AT CORNERS AND EMBED IN AQUAFLASH LIQUID (SEE NOTES 1, 2).
STEP #3: INSTALL DRYVIT AQUAFLASH SYSTEM AT ANGLE (SEE NOTES 1 AND 2).
STEP #4: INSTALL DRYVIT AQUAFLASH SYSTEM AT HEADS (SEE NOTES 1, 2).

Outsulation® Plus MD System®

Opening Preparation - AquaFlash® System Option

NOTE:
 1. DRYVIT AQUAFLASH SHALL EXTEND TO INTERIOR FACE OF OPENING.
 2. REFER TO HEAD, SILL AND JAMB DETAILS FOR FLASHING INTEGRATION.
 3. DRYVIT FLASHING TAPE SURFACE COMPLETION™ AND DRYVIT FLASHING TAPE™ MAY BE USED IN LIEU OF DRYVIT AQUAFLASH SYSTEM.
 4. INSTALL WINDOW UNIT AND ASSOCIATED FLASHING PER MANUFACTURER'S RECOMMENDATIONS, CODE REQUIREMENTS AND PROJECT DOCUMENTS.
 5. AQUAFLASH SYSTEM CONSISTS OF AQUAFLASH MESH AND AQUAFLASH LIQUID.
 6. ADDITIONAL AIRWATER-RESISTIVE BARRIER DETAILS. REFER TO DRYVIT PUBLICATION DS84.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.04

STEP #1: APPLY DRYVIT GRID TAPE™ (SEE NOTES 1 AND 2).
STEP #2: TROWEL APPLY DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT GRID TAPE ALL THE WAY TO INSIDE FACE OF OPENING. ALL JOINTS MUST BE FILLER. MULTIPLE PASSES MAY BE REQUIRED. AS AN OPTION, DRYVIT GRID TAPE AND DRYVIT BACKSTOP-NT TEXTURE MAY ALSO BE APPLIED AT THE SILL PRIOR TO DRYVIT AQUAFLASH SYSTEM OR FLASHING TAPE APPLICATION.
STEP #3: APPLY DRYVIT AQUAFLASH SYSTEM (SEE NOTES 2, 3 AND 4).
STEP #4: TROWEL APPLY DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT AQUAFLASH SYSTEM (SEE NOTE 2).

Outsulation® Plus MD System®

Opening Preparation - Backstop-NT Option

NOTE:
 1. APPLY DRYVIT GRID TAPE ON HEAD, JAMB AND CORNERS OF OPENINGS AND SHEATHING JOINTS. RECOMMENDATIONS, CODE REQUIREMENTS AND PROJECT DOCUMENTS.
 2. TROWEL APPLY DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT GRID TAPE ALL THE WAY TO INSIDE FACE OF OPENING. ALL JOINTS MUST BE FILLER. MULTIPLE PASSES MAY BE REQUIRED. AS AN OPTION, DRYVIT GRID TAPE AND DRYVIT BACKSTOP-NT TEXTURE MAY ALSO BE APPLIED AT THE SILL PRIOR TO DRYVIT AQUAFLASH SYSTEM OR FLASHING TAPE APPLICATION.
 3. DRYVIT FLASHING TAPE SURFACE COMPLETION™ AND DRYVIT FLASHING TAPE™ MAY BE USED IN LIEU OF DRYVIT AQUAFLASH SYSTEM AT SILL, INCLUDING CORNER STRIPS.
 4. INSTALL WINDOW UNIT AND ASSOCIATED FLASHING PER MANUFACTURER'S RECOMMENDATIONS, CODE REQUIREMENTS AND PROJECT DOCUMENTS.
 5. REFER TO HEAD, SILL AND JAMB DETAILS FOR FLASHING INTEGRATION.
 6. FOR ADDITIONAL AIRWATER-RESISTIVE BARRIER DETAILS, REFER TO DRYVIT PUBLICATION DS84.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.05

STEP #1: REFER TO OPMD 0.0.02 AND OPMD 0.0.04 FOR PREPARATION OF OPENING PRIOR TO FLASHING INSTALLATION.
STEP #2: APPLY DRYVIT AQUAFLASH SYSTEM SPICES FLASHING OVER LIP OF SILL FLASHING. (SEE NOTES 1 AND 2).
STEP #3: INSTALL WINDOW UNIT AND ASSOCIATED FLASHING PER MANUFACTURER'S RECOMMENDATIONS, CODE REQUIREMENTS AND PROJECT DOCUMENTS.

Outsulation® Plus MD System®

Opening Flashing Integration

NOTE:
 1. REFER TO OPMD 0.0.12 AND OPMD 0.0.13 FOR INTEGRATION OF FLASHING.
 2. DRYVIT FLASHING TAPE SURFACE COMPLETION™ AND DRYVIT FLASHING TAPE™ MAY BE USED IN LIEU OF DRYVIT AQUAFLASH SYSTEM.
 3. FOR ADDITIONAL AIRWATER-RESISTIVE BARRIER DETAILS, REFER TO DRYVIT PUBLICATION DS84.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.06

APPROVED SUBSTRATE, DRYVIT AIRWATER-RESISTIVE BARRIER COATING, EPS INSULATION, DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT, DRYVIT FINISH.

Outsulation® Plus MD System®

Inside/Outside Corners

NOTE:
 1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH LOCATION OR HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
 2. DOUBLE WRAP OUTSIDE CORNERS WITH REINFORCING MESH OR USE CORNER MESH.
 3. USE MESH OR REINFORCING MESH WITHIN 300 MM (12") OF A CORNER.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.07

APPROVED SUBSTRATE, DRYVIT AIRWATER-RESISTIVE BARRIER COATING, EPS INSULATION, DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT GRID TAPE™, DRYVIT BASE COAT, DRYVIT PANZER REINFORCING MESH, DRYVIT CORNER MESH™, DRYVIT FINISH.

Outsulation® Plus MD System®

Outside Corner - High Impact

NOTE:
 1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH LOCATION OR HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
 2. OUTSIDE INSULATION BOARD EDGES SHALL BE OFFSET.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

OPMD 0.0.08

DRYVIT AIRWATER-RESISTIVE BARRIER COATING, DRYVIT ADHESIVE IN VERTICAL NOTCHED TROWEL CONFIGURATION APPLIED TO BACK OF EPS, APPROVED SUBSTRATE, EPS INSULATION, DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT, DRYVIT AQUAFLASH SYSTEM (SEE NOTE 4), DRYVIT BACKSTOP-NT TEXTURE OVER DRYVIT GRID TAPE™, DRYVIT DRAINAGE STRIP™ ADHERED WITH DAP OF DRYVIT AP ADHESIVE (SEE NOTE 3), DRYVIT BASE COAT FROM FOUNDATION WALL.

Outsulation® Plus MD System®

Grade Termination with Drainage Strip

NOTE:
 1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH LOCATION OR HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
 2. EXPANSION JOINT IS REQUIRED ALONG TOP OF FOUNDATION IF 910 MM (36") DIMENSION IS EXCEEDED.
 3. ENSURE BOTTOM EDGE OF DRAINAGE STRIP IS LEFT FREE TO DRAIN.
 4. DRYVIT FLASHING TAPE SURFACE COMPLETION™ AND DRYVIT FLASHING TAPE™ MAY BE USED IN LIEU OF DRYVIT AQUAFLASH SYSTEM.
 The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

dryvit®

NRD Project # 18228

NRD national restaurant architects & engineers

3008 CHARLTON HILL BLVD., SUITE 105
 MORRISVILLE, NORTH CAROLINA 27560
 PH: 919 544 7251 FAX: 919 544 9399
 A Division of LMAT Associates

FOR REFERENCE ONLY

Star-Hordee

BONE WOOD PROTOTYPE REVERSE
 LARGE DINING ROOM EN 2016 LDR
 DEERFIELD, VA 22922

BODDE-NOELL ENTERPRISES, INC.
 P.O. BOX 8008
 ROCKY MOUNT, NC 27802-8008
 (252) 887-2800

OWNER

BN

NO.	REVISIONS	DATE
	DESCRIPTION <td> </td>	

DRAWN BY: _____ CHECKED BY: _____

E.I.F.S. DETAILS

DATE: 9-4-2019

SHEET NUMBER: REF-1