2012 APPENDIX B
BUILDING CODE SUMMARY
FOR ALL COMMERCIAL PROJECTS
(EXCEPT 1 AND 2-FAMILY DWELLINGS AND TOWNHOUSES)
(Reproduce the following data on the building plans sheet 1 or 2)

Name of Project: Northern Tool and Equipment
Address: 9401 Statesville Road Zip Code 28269
Proposed Use: Mercantile
Owner/Authorized Agent: Rod Bennett Phone # (216) 223 - 3231 E-Mail rbennett@onyxcreative.com
Owned By: Northern Tool & Equipment ☐ City/County: Burnsville, MN X Private ☐ State
Code Enforcement Jurisdiction: ☐ City X County Mecklenburg ☐ State

LEAD DESIGN PROFESSIONAL:

DESIGNER	FIRM	NAME	LICENSE #	TELEPHONE #	E-MAIL
Architectural	Onyx Creative	Michael D. Crislip	11996	(216)223-3200	mcrislip@onyxcreative.com
Civil	n/a			( )	
Electrical	Bluestreak Consulting	Peter J Fitzgerald	034151	(216)223-3200	pfitzgerald@bluestreakconsulting
Fire Alarm	n/a			( )	
Plumbing	Bluestreak Consulting	Brian Rice	047478	(216)223-3200	brice@bluestreatconsulting.com
Mechanical	Bluestreak Consulting	Brian Rice	047478	(216)223-3200	brice@bluestreatconsulting.com
Sprinkler-Standpipe	n/a			( )	
Structural	Bluestreat Consulting	Terry S Francis	040087	(216)223-3200	tfrancis@bluestreatconsulting.com
Retaining Walls >5' High				( )	
Other				( )	

2012 EDITION OF NC CODE FOR: ☐ New Construction ☐ Addition X Upfit
EXISTING: ☐ Reconstruction X Alteration ☐ Repair ☐ Renovation
CONSTRUCTED: (date) ______ **ORIGINAL USE(S)** (Ch. 3): ______
RENOVATED: (date) ______ **CURRENT USE(S)** (Ch. 3): ______
PROPOSED USE(S) (Ch. 3): ______

BASIC BUILDING DATA
Construction Type: (check all that apply) ☐ I-A ☐ I-B ☐ II-A X II-B ☐ III-A ☐ III-B ☐ IV ☐ V-A ☐ V-B
Sprinklers: ☐ No ☐ Partial X Yes ☐ NFPA 13 ☐ NFPA 13R ☐ NFPA 13D
Standpipes: ☐ No ☐ Yes Class ☐ I ☐ II ☐ III ☐ Wet ☐ Dry
Fire District: ☐ No ☐ Yes (Primary) **Flood Hazard Area:** ☐ No ☐ Yes
Building Height: (feet) 26'-6" / sign element 36'-2"
Gross Building Area:

FLOOR	EXISTING (SQ FT)	NEW (SQ FT)	SUB-TOTAL
6th Floor			
5th Floor			
4th Floor			
3rd Floor			
2nd Floor			
Mezzanine			
1st Floor	24,334	0	24,334
Basement			
TOTAL	24,334		

ALLOWABLE AREA

Occupancy:
Assembly ☐ A-1 ☐ A-2 ☐ A-3 ☐ A-4 ☐ A-5
Business ☐
Educational ☐
Factory ☐ F-1 Moderate ☐ F-2 Low
Hazardous ☐ H-1 Detonate ☐ H-2 Deflagrate ☐ H-3 Combust ☐ H-4 Health ☐ H-5 HPM
Institutional ☐ I-1 ☐ I-2 ☐ I-3 ☐ I-4
I-3 Condition ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5
Mercantile X
Residential ☐ R-1 ☐ R-2 ☐ R-3 ☐ R-4
Storage ☐ S-1 Moderate ☐ S-2 Low ☐ High-piled
☐ Parking Garage ☐ Open ☐ Enclosed ☐ Repair Garage
Utility and Miscellaneous ☐

Accessory Occupancies:
Assembly ☐ A-1 ☐ A-2 ☐ A-3 ☐ A-4 ☐ A-5
Business X
Educational ☐
Factory ☐ F-1 Moderate ☐ F-2 Low
Hazardous ☐ H-1 Detonate ☐ H-2 Deflagrate ☐ H-3 Combust ☐ H-4 Health ☐ H-5 HPM
Institutional ☐ I-1 ☐ I-2 ☐ I-3 ☐ I-4
I-3 Condition ☐ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5
Mercantile ☐
Residential ☐ R-1 ☐ R-2 ☐ R-3 ☐ R-4
Storage ☐ S-1 Moderate ☐ S-2 Low ☐ High-piled
☐ Parking Garage ☐ Open ☐ Enclosed ☐ Repair Garage
Utility and Miscellaneous ☐

Incidental Uses (Table 508.2.5):
- ☐ Furnace room where any piece of equipment is over 400,000 Btu per hour input
- ☐ Rooms with boilers where the largest piece of equipment is over 15 psi and 10 horsepower
- ☐ Refrigerant machine room
- ☐ Hydrogen cutoff rooms, not classified as Group H
- ☐ Incinerator rooms
- ☐ Paint shops, not classified as Group H, located in occupancies other than Group F
- ☐ Laboratories and vocational shops, not classified as Group H, located in a Group E or I-2 occupancy
- ☐ Laundry rooms over 100 square feet
- ☐ Group I-3 cells equipped with padded surfaces
- ☐ Group I-2 waste and linen collection rooms
- ☐ Waste and linen collection rooms over 100 square feet
- ☐ Stationary storage battery systems having a liquid electrolyte capacity of more than 50 gallons, or a lithium-ion capacity of 1,000 pounds used for facility standby power, emergency power or uninterrupted power supplies
- ☐ Rooms containing fire pumps
- ☐ Group I-2 storage rooms over 100 square feet
- ☐ Group I-2 commercial kitchens
- ☐ Group I-2 laundries equal to or less than 100 square feet
- ☐ Group I-2 rooms or spaces that contain fuel-fired heating equipment

Special Uses: ☐ 402 ☐ 403 ☐ 404 ☐ 405 ☐ 406 ☐ 407 ☐ 408 ☐ 409 ☐ 410 ☐ 411 ☐ 412 ☐ 413 ☐ 414 ☐ 415 ☐ 416 ☐ 417 ☐ 418 ☐ 419 ☐ 420 ☐ 421 ☐ 422 ☐ 423 ☐ 424 ☐ 425 ☐ 426 ☐ 427
Special Provisions: ☐ 509.2 ☐ 509.3 ☐ 509.4 ☐ 509.5 ☐ 509.6 ☐ 509.7 ☐ 509.8 ☐ 509.9
Mixed Occupancy: ☐ No ☐ Yes Separation: ____ Hr. Exception: ______
☐ Incidental Use Separation (508.2.5)

This separation is not exempt as a Non-Separated Use (see exceptions).
☐ Non-Separated Use (508.3)
The required type of construction for the building shall be determined by applying the height and area limitations for each of the applicable occupancies to the entire building. The most restrictive type of construction, so determined, shall apply to the entire building.
☐ Separated Use (508.4) - See below for area calculations
For each story, the area of the occupancy shall be such that the sum of the ratios of the actual floor area of each use divided by the allowable floor area for each use shall not exceed 1.

$\frac{\text{Actual Area of Occupancy A}}{\text{Allowable Area of Occupancy A}} + \frac{\text{Actual Area of Occupancy B}}{\text{Allowable Area of Occupancy B}} \leq 1$

______ + ______ + ... = ______ ≤ 1.00

Story No.	Description and Use	(A) Bldg Area per Story (Actual)	(B) Table 503 Area	(C) Area for Frontage Increase[1]	(D) Area for Sprinkler Increase[2]	(E) Allowable Area or Unlimited[3]	(F) Maximum Building Area[4]

[1] Frontage area increases from Section 506.2 are computed thus:
a. Perimeter which fronts a public way or open space having 20 feet minimum width = ______ (F)
b. Total Building Perimeter = ______ (P)
c. Ratio (F/P) = ______ (F/P)
d. W = Minimum width of public way = ______ (W)
e. Percent of frontage increase $I_f = 100 [F/P - 0.25] \times W/30$ = ______ (%)
[2] The sprinkler increase per Section 506.3 is as follows:
a. Multi-story building I_s = 200 percent
b. Single story building I_s = 300 percent
[3] Unlimited area applicable under conditions of Section 507.
[4] Maximum Building Area = total number of stories in the building x E (506.4).
[5] The maximum area of open parking garages must comply with Table 406.3.5. The maximum area of air traffic control towers must comply with Table 412.1.2.

ALLOWABLE HEIGHT

	Allowable (Table 503)	Increase for Sprinklers	Shown on Plans	Code Reference
Type of Construction	Type IIB		Type IIB	
Building Height in Feet	55	Feet = H + 20' = 75	26	
Building Height in Stories	4	Stories + 1 = 5	1	

FIRE PROTECTION REQUIREMENTS

Building Element	Fire Separation Distance (feet)	Rating Req'd	Rating Provided (w/ reductions)*	Detail # and Sheet #	Design # for Rated Assembly	Design # for Rated Penetration	Design # for Rated Joints
Structural Frame, including columns, girders, trusses							
Bearing Walls		0	0				
Exterior	≥30	0	0				
North	≥30	0	0				
East	≥30	0	0				
West	≥30	0	0				
South	≥30	0	0				
Interior		0	0				
Nonbearing Walls and Partitions Exterior walls	≥30	0	0				
North	≥30	0	0				
East	≥30	0	0				
West	≥30	0	0				
South	≥30	0	0				
Interior walls and partitions		0	0				
Floor Construction Including supporting beams and joists		0	0				
Roof Construction Including supporting beams and joists		0	0				
Shaft Enclosures - Exit		n/a	[illegible]				
Shaft Enclosures - Other		n/a	n/a				
Corridor Separation			0				
Occupancy Separation			0				
Party/Fire Wall Separation		n/a	[illegible]				
Smoke Barrier Separation		n/a	n/a				
Tenant Separation		n/a	n/a				
Incidental Use Separation		n/a	n/a				

* Indicate section number permitting reduction

LIFE SAFETY SYSTEM REQUIREMENTS

Emergency Lighting: ☐ No X Yes
Exit Signs: ☐ No X Yes
Fire Alarm: ☐ No X Yes
Smoke Detection Systems: ☐ No X Yes ☐ Partial ______
Panic Hardware: ☐ No X Yes

LIFE SAFETY PLAN REQUIREMENTS

Life Safety Plan Sheet #: A1.02
- ☐ Fire and/or smoke rated wall locations (Chapter 7)
- ☐ Assumed and real property line locations

- ☐ Exterior wall opening area with respect to distance to assumed property lines (705.8)
- ☐ Existing structures within 30' of the proposed building
- ☐ Occupancy types for each area as it relates to occupant load calculation (Table 1004.1.1)
- ☐ Occupant loads for each area
- ☐ Exit access travel distances (1016)
- ☐ Common path of travel distances (1014.3 & 1028.8)
- ☐ Dead end lengths (1018.4)
- ☐ Clear exit widths for each exit door
- ☐ Maximum calculated occupant load capacity each exit door can accommodate based on egress width (1005.1)
- ☐ Actual occupant load for each exit door
- ☐ A separate schematic plan indicating where fire rated floor/ceiling and/or roof structure is provided for purposes of occupancy separation
- ☐ Location of doors with panic hardware (1008.1.10)
- ☐ Location of doors with delayed egress locks and the amount of delay (1008.1.9.7)
- ☐ Location of doors with electromagnetic egress locks (1008.1.9.8)
- ☐ Location of doors equipped with hold-open devices
- ☐ Location of emergency escape windows (1029)
- ☐ The square footage of each fire area (902)
- ☐ The square footage of each smoke compartment (407.4)
- ☐ Note any code exceptions or table notes that may have been utilized regarding the items above

ACCESSIBLE DWELLING UNITS
(SECTION 1107)

Total Units	Accessible Units Required	Accessible Units Provided	Type A Units Required	Type A Units Provided	Type B Units Required	Type B Units Provided	Total Accessible Units Provided

ACCESSIBLE PARKING
(SECTION 1106)

Lot or Parking Area	Total # of Parking Spaces Required	Total # of Parking Spaces Provided	# of Accessible Spaces Provided: Regular with 5' access aisle	Van Spaces with 132" access aisle	Van Spaces with 8' access aisle	Total Accessible Provided
TOTAL	148	193	5		1	6

STRUCTURAL DESIGN

DESIGN LOADS:

Importance Factors: Wind (I_W) ______ Snow (I_S) 1.0 Seismic (I_E) 1.0

Live Loads: Roof [illegible] psf Mezzanine n/a psf Floor 100 psf

Ground Snow Load: [illegible] psf

Wind Load: Basic Wind Speed 90 (30sec gust) mph (ASCE-7)
Exposure Category **C**
Wind Base Shears (for MWFRS) Vx = **45.3** Vy = **27.3**

SEISMIC DESIGN CATEGORY: ☐ A X B ☐ C ☐ D
Provide the following Seismic Design Parameters:
Occupancy Category (Table 1604.5) X I ☐ II ☐ III ☐ IV
Spectral Response Acceleration S_S ____ %g S_1 ____ %g
Site Classification (Table 1613.5.2) ☐ A ☐ B ☐ C ☐ D ☐ E ☐ F
Data Source: ☐ Field Test ☐ Presumptive ☐ Historical Data
Basic structural system (check one)
X Bearing Wall ☐ Dual w/Special Moment Frame
☐ Building Frame ☐ Dual w/Intermediate R/C or Special Steel
☐ Moment Frame ☐ Inverted Pendulum
Seismic base shear: V_X 0.07W V_Y ______
Analysis Procedure: ☐ Simplified X Equivalent Lateral Force ☐ Dynamic
Architectural, Mechanical, Components anchored? ☐ Yes ☐ No

LATERAL DESIGN CONTROL: Earthquake ☐ Wind ☐

SOIL BEARING CAPACITIES:
Field Test (provide copy of test report) n/a psf
Presumptive Bearing capacity [illegible] psf
Pile size, type, and capacity n/a

SPECIAL INSPECTIONS REQUIRED: ☐ Yes ☐ No

PLUMBING FIXTURE REQUIREMENTS
(TABLE 2902.1)

Use		Water Closets Male	Water Closets Female	Urinals	Lavatories Male	Lavatories Female	Showers/Tubs	Drinking Fountains Regular	Drinking Fountains Accessible
Space	Existing	2	3	1	2	2		1	1
	New								
	Required	1	1		1	1			1

SPECIAL APPROVALS

Special approval: (Local Jurisdiction, Department of Insurance, OSC, DPI, DHHS, ICC, etc., describe below)

ENERGY SUMMARY

ENERGY REQUIREMENTS:
The following data shall be considered minimum and any special attribute required to meet the energy code shall also be provided. Each Designer shall furnish the required portions of the project information for the plan data sheet. If performance method, state the annual energy cost for the standard reference design vs annual energy cost for the proposed design.

Climate Zone: ☐ 3 ☐ 4 ☐ 5

Method of Compliance:
X Prescriptive (Energy Code)
☐ Performance (Energy Code)
☐ Prescriptive (ASHRAE 90.1)
☐ Performance (ASHRAE 90.1)

THERMAL ENVELOPE

Roof/ceiling Assembly (each assembly)
Description of assembly: existing adhered membrane roof system on 3" rigid poly-Iso insul. (fm 4450 & UL 1256 conforming over existing metal roof deck
U-Value of total assembly: 0.045
R-Value of insulation: 30
Skylights in each assembly: n/a
U-Value of skylight: ______
total square footage of skylights in each assembly: ______

Exterior Walls (each assembly)
Description of assembly: existing 12" quick brick + 4" cavity filled with crush Styrofoam insulations full height
U-Value of total assembly: 0.043
R-Value of insulation: 19
Openings (windows or doors with glazing)
U-Value of assembly: 0.042
Solar heat gain coefficient: .45
projection factor: n/a
Door R-Values: 0.9

Walls below grade (each assembly)
Description of assembly: n/a
U-Value of total assembly: n/a
R-Value of insulation: n/a

Floors over unconditioned space (each assembly)
Description of assembly: n/a
U-Value of total assembly: n/a
R-Value of insulation: n/a

Floors slab on grade
Description of assembly: existing 6" concrete slab with 4 mil vapor barrier & 2" Crush stone w 1"x2" perimeter insulation.
U-Value of total assembly: interior 0.83 / Perimeter 0.19
R-Value of insulation: n/a
Horizontal/vertical requirement: n/a
slab heated: No

MECHANICAL SUMMARY

MECHANICAL SYSTEMS, SERVICE SYSTEMS AND EQUIPMENT

Thermal Zone
winter dry bulb: 18
summer dry bulb: 93

Interior design conditions
winter dry bulb: 72
summer dry bulb: 75
relative humidity: 50

Building heating load: 604 mbh (entire center)

Building cooling load: 805 mbh (entire center)

Mechanical Spacing Conditioning System Existing
Unitary
description of unit: ______
heating efficiency: ______
cooling efficiency: ______
size category of unit: ______
Boiler
Size category. If oversized, state reason.: ______
Chiller
Size category. If oversized, state reason.: ______

List equipment efficiencies: ______

ELECTRICAL SUMMARY

ELECTRICAL SYSTEM AND EQUIPMENT

Method of Compliance:
Energy Code: ☐ Prescriptive X Performance
ASHRAE 90.1: ☐ Prescriptive ☐ Performance

Lighting schedule (each fixture type) See Fixture schedule on sheet E5.00
lamp type required in fixture
number of lamps in fixture
ballast type used in the fixture
number of ballasts in fixture
total wattage per fixture
total interior wattage specified vs. allowed (whole building or space by space) 0 vs 0
total exterior wattage specified vs. allowed

Additional Prescriptive Compliance
- ☐ 506.2.1 More Efficient Mechanical Equipment
- ☐ 506.2.2 Reduced Lighting Power Density
- ☐ 506.2.3 Energy Recovery Ventilation Systems
- ☐ 506.2.4 Higher Efficiency Service Water Heating
- ☐ 506.2.5 On-Site Supply of Renewable Energy
- ☐ 506.2.6 Automatic Daylighting Control Systems

MICHAEL CRISLIP | ARCHITECT
25001 Emery Road, Suite 400
Cleveland, Ohio 44128
216.223.3200 onyxcreative.com

Design and construction documents as instruments of service are given in confidence and remain the property of Michael Crislip, Architect. The use of this design and these construction documents for purposes other than the specific project named herein is strictly prohibited without expressed written consent of Michael Crislip, Architect.

NORTHERN TOOL + EQUIPMENT.
9401 STATESVILLE ROAD
CHARLOTTE, NC 28269

Project No.: 17483
Drawn By: CGB
Date 03-08-20 Issue For Construction Only

G0.03

APPENDIX B

Job Path:H:\Master\HA STANDARDS\CAD STANDARDS\TEMPLATE\Master Template.dwt
Drawn By:C.F. Mierke

Order Plans @ WWW.LDILine.com