NO.	POLE SHAFT SPECIFICATIONS
1.	SHAFTS ARE ONE SECTION DESIGN FABRICATED FROM A WELDABLE GRADE CARBON STEEL STRUCTURAL TUBING WITH A UNIFORM WALL THICKNESS. MATERIAL SHALL CONFORM TO ASTM A-500 GRADE A WITH A MINIMUM YIELD STRENGTH OF 46,000 P.S.I.
2.	BASE PLATES ARE CONSTRUCTED OF A STRUCTURAL QUALITY HOT ROLLED CARBON STEEL PLATE (ASTM A 36 MIN) WITH A GUARANTEED MINIMUM YIELD STRENGTH OF 36,000 P.S.I.
3.	ANCHOR BOLTS (F1554 GRADE 55) ARE "L" BENT BARS HAVING A MINIMUM YIELD STRENGTH OF 55,000 P.S.I. THE BOLTS ARE FULLY GALVANIZED PER ASTM A153 SPECIFICATIONS AND FURNISHED COMPLETE WITH 2 HEX NUTS AND 2 FLAT WASHERS.
4.	POLES SHALL HAVE A POLYESTER POWDER COAT FINISH IN A STANDARD COLOR.

POLE DIMENSIONS

POLE HGT. (FT.)	TOP SHFT. SIZE (IN.)	BOTT. SHFT. SIZE (IN.)	GAUGE	WT/FT. HGT. (P.F.)
20'	4.00	4.00	7 GAUGE	2.0

BASE PLATE DIMENSIONS

BOLT CIRCLE (IN.)	SQUARE PLATE SIDE (IN.)	BOLT HOLE (IN.)	PLATE THK. (IN.)
8.00-9.00	8.00 SQ.	1.00	.75

ANCHOR BOLT DIMENSIONS

ANCHOR BOLT DIA. (IN.)	ANCHOR BOLT LENGTH (IN.)
.75	20.00

ALLOWABLE WIND LOADING (SQ. FT.)

WIDTH	80 MPH	90 MPH	100 MPH	110 MPH
EPA	9.2	7.8	6.8	4.5

WITH 1.3 GUST FACTOR

REMOVABLE CAP

DRILLED PER FIXTURE REQUIREMENTS:
D1- DRILLED FOR 1 FIXTURE
D2- DRILLED FOR 2 FIXTURES AT 90° OR 180°
D3- DRILLED FOR 3 FIXTURES
D4- DRILLED FOR 4 FIXTURES

POLE SHAFT

DRILL MOUNT OPTIONS

TENON MOUNT OPTIONS:
T2- Ø2.38 OD X 4.00 LG
T3- Ø3.00 OD X 5.00 LG
T4- Ø4.00 OD X 6.00 LG

POLE SHAFT

.25 THK. TENON MOUNT

3.00 X 5.00 HAND HOLE COVER

Ø.75

17.00

3.00

8.00 SQ.

Ø8.00-Ø9.00 BOLT CIRCLE

POLE HGT.

3.00 X 5.00 HAND HOLE W/ COVER

REMOVABLE ABS COVER

14.00

8.00 X 8.00 X .75 THK. BASE PLATE

Ø.75 X 20.00 ANCHOR BOLT

POLE DETAIL

lyte poles
P.O. Box 340
Eastpointe, MI 48021
P: (586) 771-4610 | F: (586) 771-5522
www.lytepoles.com

DRAWN:	M. KARYALA	2/13/2015
CHECKED:		
REVISION:		DATE:
APPROVED:		
QUOTE:		
REF:		SCALE: NONE

POLE DESIGNED FOR 100 MPH WIND SPEEDS WITH 1.3 GUST FACTOR AND EXPOSURE CATEGORY C. SPECIAL WIND CONDITIONS THAT CAN CREATE WIND INDUCED VIBRATIONS CAUSING A FATIGUE FAILURE CAN NOT BE MADE AND YET BOTH POLES FOR PRESENTING MOMENTS AND ARE THE RESPONSIBILITY OF A LOCAL SITE ENGINEER.

TITLE:

CATALOG:

DWG NO: 101-4007-25 | SIZE: C | SHEET 1 OF 1

180° 270° 90° 0° HANDHOLE



D-Series Size 2
LED Area Luminaire

DLC DLC PREMIUM DLC TLS lighting facts

d-series

Catalog Number
Notes
Type

Specifications

EPA: 1.1 ft²
Length: 40"
Width: 15"
Height 1: 7-1/4"
Height 2: (max): 9.5"
Weight: 36lbs



Introduction

The modern styling of the D-Series is striking yet unobtrusive - making a bold, progressive statement even as it blends seamlessly with its environment.

The D-Series distills the benefits of the latest in LED technology into a high performance, high efficacy, long life luminaire. The outstanding photometric performance results in sites with excellent uniformity, greater pole spacing and lower power density. The Size 2 is ideal for replacing 400-1000W metal halide in area lighting applications with energy savings of up to 80% and expected service life of over 100,000 hours.

Ordering Information

EXAMPLE: DSX2 LED P7 40K T3M MVOLT SPA NLTAIR2 PIRHN DDBXD

DSX2 LED									
DSX2 LED	Forward optics: P1 P2 P3 P4 P5 P6 Rotated optics: P10 P11 P12	40K 4000K 50K 5000K	T1S Type I Short T2S Type II Short T2M Type II Medium T3S Type III Short T3M Type III Medium T4M Type IV Medium T4W Type IV Wide	T5S Type V Short T5W Type V Wide T5VS Type V Very Short T5VW Type V Very Wide BLC Backlight control TFTM Top Facing Mounting	MVOLT 347 480 277 120 208 240	Shipped included: SPA Square pole mounting RPA Round pole mounting WBA Wall bracket SPUMBA Square pole universal mounting adapter RPUMBA Round pole universal mounting adapter Shipped separately: BS Bird spikes KMA Mast arm mounting bracket adapter (specify finish)

Shipped installed			
NLTAIR2 nLight AIR generation 2 enabled	PIRH Bi-level motion/ambient sensor, high/low, 24-36' mounting height, ambient sensor enabled at 5fc	DDBXD Dark bronze	DWHXD White
NLTAIR2 PIR nLight AIR generation 2 enabled with motion sensor	PIR1FC3V Bi-level motion/ambient sensor, 8-15' mounting height, ambient sensor enabled at 1fc	DBLBXD Black	DNAXD Natural aluminum
PER NEMA photocontrol receptacle	PER7 NEMA photocontrol receptacle, 7-pin	DBTXD Textured black	DSSTXD Textured sandstone
DMG 0-10V dimming wires pulled outside fixture (for use with an external control, ordered separately)	FAO Field adjustable output	DNATXD Textured natural aluminum	DWGXD Textured white
BAA Buy American Act compliant		DBLXD Black	DDBTXD Textured dark bronze
		DNAXD Natural aluminum	DBLBTXD Textured black
		DWHXD White	DSSXD Sandstone
		DSSTXD Textured sandstone	DWGXD Textured white

Accessories

DSX2HS 120C	Houseside shield (one required per fixture)
DSX2HS 208C 240C	Houseside shield (two required per fixture)
DSX2HS 277C 347C 480C	Houseside shield (two required per fixture)
DSHS SHO U	Shroud*
DSHS 86 U	Mast arm slip fitter adapter*
DSHS 96 U	Mast arm slip fitter adapter*
KMA8 DDBXD	Square mast arm adapter*
RPUMBA DDBXD	Round mast arm adapter*
DSX2HS 480C	Square pole universal mounting adapter*
DSX2HS 480C	Round pole universal mounting adapter*

NOTES
1 P10, P11, P12 only for 8FEA and mounted options 530, 800, only available together.
2 Shroud ships standard with universal mount, not available with KMA8.
3 Not available with P5.
4 MVOLT driver operates on any line voltage from 120-277V (50/60Hz).
5 Single fuse (SF) requires 120V, 277V or 347V. Double fuse (DF) requires 208V, 240V or 480V.
6 Universal mounting bracket intended for retrofit mounting over drilled pole only. 1.5 G vibration level rated per ANSI C136.31-2010 for 3G bridge and overpass applications.
7 Must order fixture with SBB (standard bird blocker) or SBBW (bird blocker, white) when ordering with BS (bird spikes) option. Not available with DDBXD finish.
8 Must be ordered with PIR8FC3V, PIR8, PIR1FC3V, PIR1, PIRH1FC3V, PIRH1, PIRH, PER, PER7, PER5, PIRHN or PIRTEN. Not available with BL30, BL50 or BLGC.
9 Must be ordered with MVOLT, 347, 480, 277 or 120.
10 Not available with P5, P6, P10, P11 or P12.
11 Not available with PIR8, PIR8FC3V, PIR1, PIR1FC3V, PIRH1, PIRH1FC3V, PIRH, PER, PER7, PER5, PIRHN or PIRTEN. Not available with P1, P2, P10, P11 or P12.
12 Not available with BL30, BL50 or BLGC.
13 Not available with NLTAIR2 PIR, NLTAIR2 PIRH, NLTAIR2 PIR1FC3V or NLTAIR2 PIRH1FC3V.
14 Not available with other dimming controls.
15 Not available with P5.

E65 - External Glare Shield

HANDHOLE ORIENTATION



Tenon Mounting Slipfitter [15]

3.00"	DSX2HS 280C	20.3 lbs	19.5 in²	40.6 lbf	19.0 lbf	30.0 ft-lbs	30.0 ft-lbs
	DSX2HS 480C	20.8 lbs	20.0 in²	41.6 lbf	19.4 lbs	30.0 ft-lbs	30.0 ft-lbs
2.50"	DSX2HS 280C	20.1 lbs	19.2 in²			30.0 ft-lbs	
	SPA DSX2HS 280C	20.6 lbs	19.7 in²	41.2 lbf	19.2 lbs	30.0 ft-lbs	30.0 ft-lbs
	RPA DSX2HS 280C	20.6 lbs	19.7 in²	41.2 lbf	19.2 lbs	30.0 ft-lbs	30.0 ft-lbs
2.375"	DSX2HS 280C	20.1 lbs	19.2 in²	40.2 lbf	18.8 lbs	30.0 ft-lbs	30.0 ft-lbs
	DSX2HS 480C	20.6 lbs	19.7 in²	41.2 lbf	19.2 lbs	30.0 ft-lbs	30.0 ft-lbs
4	DSX2HS 280C	20.6 lbs	19.7 in²	41.2 lbf	19.2 lbs	30.0 ft-lbs	30.0 ft-lbs
	DSX2HS 480C	21.1 lbs	20.2 in²	42.2 lbf	19.7 lbs	30.0 ft-lbs	30.0 ft-lbs

Tool-less Knuckle Slip Fitter



Mounting Option	Drilling Template	Weight	Effective Projected Area (EPA)	Max Allowable Vertical Load	Max Allowable Lateral Load	Max Allowable Moment	Max Allowable Torque
Round Tenon		Quick	Quick 4G x G	Quick 4G x G	Quick 4G x G	Quick 4G x G	Quick 4G x G
Quick Tenon Adapter		5lb	2FEA/1RFA	3FEA/1RFA	3FEA/1RFA	3FEA/1RFA	3FEA/1RFA

Size	A	B	C	D	E	F
2FEA	20"	2x7.5"	4.75"	3x5"	3x5"	4"	1.25"
3FEA	30"	2x7.5"	4.75"	3x5"	3x5"	4"	1.25"
4FEA	40"	2x7.5"	4.75"	3x5"	3x5"	4"	1.25"
RFA Only	10"	2.188"	2"	3"	3"	4.5"	2"

Lumen Ambient Temperature (LAT) Multipliers

Use these factors to determine relative lumen output for average ambient temperatures from 0°C to 50°C (32°-122°F).

°C	°F	Multiplier
0°C	32°F	1.05
5°C	41°F	1.04
10°C	50°F	1.03
15°C	59°F	1.02
20°C	68°F	1.01
25°C	77°F	1.00
30°C	86°F	0.99
35°C	95°F	0.98
40°C	104°F	0.97
45°C	113°F	0.96
50°C	122°F	0.95

Projected LED Lumen Maintenance

Data references the extrapolated performance projections for the luminaire when operated in a 25°C ambient, based on 10,000 hours of LED testing, per IESNA LM-80-08 and projected per IESNA TM-21-11.
To calculate L70 (hours) for other ambient temperatures, please contact factory.

Ambient	0	10,000	25,000	50,000
25°C	>1000	>1000	>1000	>1000
40°C	>1000	>1000	>1000	>1000

Electrical Load

				120	208	240	277	347	480
Forward Optics (See Notes 6)	P1	30	530	0.29	0.16	0.14	0.13	0.10	0.07
	P2	30	700	0.39	0.22	0.19	0.17	0.14	0.10
	P3	40	850	0.47	0.27	0.23	0.21	0.16	0.12
	P4	40	1050	0.58	0.33	0.29	0.26	0.20	0.15
	P5	40	1200	0.67	0.38	0.34	0.30	0.23	0.17
	P6	50	1450	0.81	0.46	0.40	0.36	0.28	0.21
Rotated Optics (See Notes 6)	P10	30	530	0.29	0.16	0.14	0.13	0.10	0.07
	P11	30	700	0.39	0.22	0.19	0.17	0.14	0.10
	P12	30	850	0.47	0.27	0.23	0.21	0.16	0.12
	P13	30	1050	0.58	0.33	0.29	0.26	0.20	0.15
	P14	30	1200	0.67	0.38	0.34	0.30	0.23	0.17
	P15	30	1450	0.81	0.46	0.40	0.36	0.28	0.21

Option	Standard Stable	0-10V Linear Fadded (Applicable)	Fluorescent Operation	Shield Band	Handle 4G Base	Factory default Value
Filter PIR8	3W (10Hz) Output	3W (10Hz) Output	Standard w/ BFT	5 min	3 sec	5 min
PIR8FC3V or PIR8H1FC3V	3W (10Hz) Output	Soft Fade to Output	Standard w/ BFT	5 min	3 sec	5 min

Price and lead times available upon request for dusk to dawn control.

Nomenclature	Description	Functionality	Primary control devices	Notes
PER	Photocontrol receptacle only (photocontrol not included). Includes shorting cap. Must be ordered with DMG option.	Allows the luminaire to be controlled by an external photocontrol (not included).	Photocontrol (not included)	Cannot be used with other control options. Not available with DS, DT, PIR, PIRH, PIR1FC3V, PIRH1FC3V, PIR8, PIR8FC3V, PIR8H1FC3V, PIRTEN, DMG, DCR, FAO, BL30, BL50, BLGC, HS, SF, DF, CR, BAA.
DS	Dual switched. Two independent switching circuits. Includes two integral toggle switches. Each switch controls one-half of the light engines.	Two-level control. Each switch controls a different light level.	Toggle switches	Requires two separately switched circuits. Consider daylighting if possible for increased energy savings.
PIR or PIRH	Bi-level, high/low, motion sensor for 8'-15' mounting height. Ambient sensor enables sensor at 5fc (PIR) or 1fc (PIRH). Intended for use in open areas. For use in mounting heights over 15', see PIR1FC3V.	Turns luminaire to high level when motion is detected within sensor's field of view. Remains at high level for 5 minutes after last motion is detected, then switches to low level.	Integral passive infrared occupancy sensor	Sensor detects motion in a 360° pattern when mounted at 15' AFG. Reduced mounting height or lens may be required for applications with mounting heights less than 15'.
PIR1FC3V or PIRH1FC3V	Bi-level, high/low, motion sensor for 8'-15' mounting height. Ambient sensor enables sensor at 1fc. Intended for use in open areas. For use in mounting heights over 15', see PIR or PIRH.	Turns luminaire to high level when motion is detected within sensor's field of view. Remains at high level for 5 minutes after last motion is detected, then switches to low level.	Integral passive infrared occupancy sensor	Sensor detects motion in a 360° pattern when mounted at 15' AFG. Reduced mounting height or lens may be required for applications with mounting heights less than 15'.
BLGC	Backlight control. Reduces backlight for improved distribution.	Reduces backlight for improved distribution.	Not applicable	Not available with P5, P6, P12, P13, P14, P15, P16, P17, P18, P19, P20, P21, P22, P23, P24, P25, P26, P27, P28, P29, P30, P31, P32, P33, P34, P35, P36, P37, P38, P39, P40, P41, P42, P43, P44, P45, P46, P47, P48, P49, P50, P51,