PANEL NO.: MDSB
USAGE: MAIN DISTRIBUTION SWITCHBOARD
LOCATION: EXISTING
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 2000A
MAIN CB AMPS: 2000A
AIC RATING: EXISTING

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: PAD
PANEL TYPE: EXISTING
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: ATS-1

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					960.4	PANEL A		3	1200	A	150	3			PANEL LS	27.5					
					948.3					B						16.7					
					941.8					C						19.8					
					381.2	PANEL B		3	600	A		4.2	3		SPACE	0.0					
					369.7					B						0.0					
					369.3					C						0.0					
					0.0	SPACE		3		A			3		SPACE	0.0					
					0.0					B						0.0					
					0.0					C						0.0					
					0.0	SPACE		3		A			3		SPACE	0.0					
					0.0					B						0.0					
					0.0					C						0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	77.921 code		43.96
EQUIPMENT	124.255	100%	124.255
LIGHTS (EXT.)	17.388	100%	17.388
LIGHTS (EXT.)	0	100%	0
HVAC	271.628	100%	271.628
KITCHEN	26.8041	51%	18.7216
TOTAL KVA	524 KVA		480 KVA
TOTAL AMPS	1454 AMPS		1331 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE
6 . IG - INDICATES CIRCUIT SHALL INCLUDE ADDITIONAL ISOLATED GROUND CONDUCTOR

PANEL NO.: LS
USAGE: LIGHTING AND APPLIANCE
LOCATION: EXISTING
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 225A
MAIN CB AMPS: MLO
AIC RATING: EXISTING

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: EXISTING
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: MDSB

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					4.2	EXISTING LIGHTING		1	20	1	A	2	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	3	B	4	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	5	C	6	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	7	A	8	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	9	B	10	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	11	C	12	20	1	EXISTING LIGHTING	4.2					
					4.2	EXISTING LIGHTING		1	20	13	A	14	20	1	EXISTING LIGHTING	4.2					
					0.0	SPACE		1		15	B	16		1	SPACE	0.0					
					0.0	SPACE		1		17	C	18		1	SPACE	0.0					
					0.0	SPACE		1		19	A	20		1	SPACE	0.0					
					0.0	SPACE		1		21	B	22		1	SPACE	0.0					
					0.0	SPACE		1		23	C	24		1	SPACE	0.0					
					0.0	SPACE		1		25	A	26		1	SPACE	0.0					
					0.0	SPACE		1		27	B	28		1	SPACE	0.0					
					0.0	SPACE		1		29	C	30		1	SPACE	0.0					
					0.0	SPACE		1		31	A	32		1	SPACE	0.0					
					0.0	SPACE		1		33	B	34		1	SPACE	0.0					
					0.0	SPACE		1		35	C	36		1	SPACE	0.0					
					0.0	SPACE		1		37	A	38		1	SPACE	0.0					
					0.0	SPACE		1		39	B	40		1	SPACE	0.0					
					0.0	SPACE		1		41	C	42		1	SPACE	0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	0	code	0
EQUIPMENT	0	100%	0
LIGHTS (EXT.)	2.882	100%	2.66
LIGHTS (EXT.)	0	100%	0
HVAC	0	100%	0
KITCHEN	0	65%	0
TOTAL KVA	8 KVA		6 KVA
TOTAL AMPS	23 AMPS		21 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE
6 . IG - INDICATES CIRCUIT SHALL INCLUDE ADDITIONAL ISOLATED GROUND CONDUCTOR

PANEL NO.: A
USAGE: DISTRIBUTION
LOCATION: EXISTING
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 1200A
MAIN CB AMPS: 1200A
AIC RATING: EXISTING

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: EXISTING
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: MDSB

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					80.0	EXISTING SERVICE #1		3	600	1	A	2	20	1	EXISTING FDD-1	22.0					
					66.0					3	B	4				22.0					
					67.5					5	C	6	45	2	EXISTING AUX HEAT FDD-1	24.0					
					53.3	EXISTING SERVICE #2		3	600	7	A	8				24.0					
					45.1					9	B	10	35	2	EXISTING CONDENSING UNIT FDD-3	5.8					
					51.8					11	C	12				6.0					
					16.7	EXISTING PANEL G		3	225	13	A	14	20	2	EXISTING SPRINKLER MAIN HOT WOR	7.2					
					16.7					15	B	16				7.2					
					18.0					17	C	18	20	1	EXISTING SPACE	0.0					
					18.7	EXISTING PANEL E		3	225	19	A	20	225	3	EXISTING PANEL S	13.7					
					10.4					21	B	22				22.9					
					17.7					23	C	24				20.3					
					16.7	EXISTING PANEL F		3	225	25	A	26	600	3	PANEL K	17.9					
					16.7					27	B	28				16.4					
					0.0					29	C	30				18.9					
					19.5	EXISTING PANEL D		3	225	31	A	32	225	3	PANEL J	16.1					
					16.2					33	B	34				10.5					
					10.4					35	C	36				18.8					
					6.9	EXISTING POOL PANEL		3	45	37	A	38	60G	3	PANEL L	20.2					
					8.2					39	B	40				20.4					
					11.7					41	C	42				19.9					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	62.361	code	38.16
EQUIPMENT	123.371	100%	111.171
LIGHTS (EXT.)	6.098	100%	9.258
LIGHTS (EXT.)	0	100%	0
HVAC	151.688	100%	135.688
KITCHEN	29.4041	65%	16.7216
TOTAL KVA	377 KVA		345 KVA
TOTAL AMPS	1047 AMPS		967 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE
6 . IG - INDICATES CIRCUIT SHALL INCLUDE ADDITIONAL ISOLATED GROUND CONDUCTOR

PANEL NO.: B
USAGE: DISTRIBUTION
LOCATION: EXISTING
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 600A
MAIN CB AMPS: 600A
AIC RATING: EXISTING

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: EXISTING
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: MDSB

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					11.5	RTU-1		3	45	1	A	2	20	1	SCAC	11.5					
					28.2					3	B	4				11.0					
					28.0					5	C	6	35	2	SPARE	0.0					
					25.5	RTU-2		3	60	7	A	8				0.0					
					29.5					9	B	10	225	3	PANEL C	124.9					
					25.5					11	C	12				124.9					
					18.8	RTU-3		3	30	13	A	14				124.9					
					18.4					15	B	16	225	3	PANEL G	41.6					
					18.8					17	C	18				41.8					
					10.9	RTU-4		3	30	19	A	20				41.8					
					10.4					21	B	22	15	2	AC-3	4.7					
					18.8					23	C	24				4.7					
					28.9	RTU-5		3	45	25	A	26	20	3	SEWAGE EJECTOR	7.8					
					28.0					27	B	28				7.8					
					28.8					29	C	30				7.5					
					32.4	AC-1		3	60	31	A	32	20	1	POOL SUMP	3.2					
					32.4					33	B	34	20	1	EF-1,3,5	10.0					
					13.8	AC-2		2	20	35	C	36	225	3	PANEL M	32.8					
					13.5					37	A	38				99.4					
					11.0	FURN-1		1	20	39	B	40				37.1					
					8.2	FURN-2		1	15	41	C	42	20	1	RECEPTACLES	0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	15.66	code	11.76
EQUIPMENT	3.168	100%	3.08
LIGHTS (EXT.)	0.61	100%	0.61
LIGHTS (EXT.)	0	100%	0
HVAC	119.94	100%	119.94
KITCHEN	0	65%	0
TOTAL KVA	132 KVA		106 KVA
TOTAL AMPS	186 AMPS		178 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE
6 . IG - INDICATES CIRCUIT SHALL INCLUDE ADDITIONAL ISOLATED GROUND CONDUCTOR

PANEL NO.: J
USAGE: LIGHTING AND APPLIANCE
LOCATION: IT ROOM
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 225A
MAIN CB AMPS: 225A
AIC RATING: 27,065 MINIMUM

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: NEMA 1
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: A

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					11.7	PWR: CKT R		1	20	1	A	2	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	3	B	4	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	5	C	6	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	7	A	8	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	9	B	10	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	11	C	12	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	13	A	14	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	15	B	16	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	17	C	18	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	19	A	20	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	21	B	22	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	23	C	24	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	25	A	26	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	27	B	28	20	1	PWR: CKT R	11.7					
					11.7	PWR: CKT R		1	20	29	C	30	20	1	PWR: CKT R	11.7					
					4.7	RECEPTACLES		1	20	31	A	32	20	1	RECEPTACLES	10.0					
					8.3	RECEPTACLES		1	20	33	B	34	20	1	RECEPTACLES	8.3					
					11.7	RECEPTACLES		1	20	35	C	36	20	1	RECEPTACLES	8.3					
					10.0	RECEPTACLES		1	20	37	A	38	20	1	RECEPTACLES	3.3					
					8.3	RECEPTACLES		1	20	39	B	40	20	1	RECEPTACLES	11.7					
					3.3	RECEPTACLES		1	20	41	C	42	20	1	RECEPTACLES	10.0					
					11.7	RECEPTACLES		1	20	43	A	44	20	1	RECEPTACLES	3.3					
					10.0	FIREPLACE		2	40	45	B	46	20	1	SPARE	0.0					
					20.0					47	C	48				0.0					
					13.3	RECEPTACLES		1	20	49	A	50	20	1	RECEPTACLES	0.0					
					9.6	PWR: CKT L		1	20	51	B	52	20	1	PWR: CKT L	9.6					
					9.6	PWR: CKT L		1	20	53	C	54	20	1	PWR: CKT L	9.6					
					10.2	LITG: KITCHEN		1	20	55	A	56	20	1	LITG: CORRIDOR/STAIR	8.4					
					4.2	PWR: P-1 AND P-2		1	20	57	B	58	20	1	LITG: CORRIDOR/STAIR	0.0					
					0.7	CIRC PUMPS		1	20	59	C	60	20	1	SPARE	0.0					
					3.4	ATTIC VENTILATOR		1	20	61	A	62	20	1	ATTIC VENTILATOR	3.4					
					10.2	ATTIC VENTILATOR		1	20	63	B	64	20	1	ATTIC VENTILATOR	3.4					
					0.0	SPARE		1	20	65	C	66	20	1	SPARE	0.0					
					0.0	SPARE		1	20	67	A	68				0.0					
					0.0	SPARE		1	20	69	B	70				0.0					
					0.0	SPARE		1	20	71	C	72				0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	90.36	code	51.28
EQUIPMENT	3.06	100%	1.06
LIGHTS (EXT.)	9.288	100%	9.288
LIGHTS (EXT.)	0	100%	0
HVAC	4.883	100%	4.883
TOTAL KVA	76 KVA		53 KVA
TOTAL AMPS	211 AMPS		148 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE

PANEL NO.: L
USAGE: LIGHTING AND APPLIANCE
LOCATION: IT ROOM
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 600A
MAIN CB AMPS: MLO
AIC RATING: 27,065 MIN

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: NEMA 1
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: A

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					8.5			1	20	1	A	2	20	1	ADD-2	8.5					
					14.0			1	20	3	B	4	20	1	ADD-3b	14.0					
					9.0			1	20	5	C	6	20	1	ADD-6	9.0					
					9.0			1	20	7	A	8	25	1	ERV-2	17.0					
					17.0	ERV-1		1	25	9	B	10	25	1	ERV-4	17.0					
					15.0	ERV-3		1	25	11	C	12				0.0					
					0.0	SPACE		1		13	A	14		1	SPACE	0.0					
					0.0	SPACE		1		15	B	16		1	SPACE	0.0					
					14.0	HP-1		2	50	17	C	18	25	2	HP-2	14.0					
					14.0					19	A	20				14.0					
					21.0	HP-3a		2	50	21	B	22	20	2	HP-3b	21.0					
					21.0					23	C	24				21.0					
					23.0	INF-5		2	35	25	A	26	25	2	INF-6	17.0					
					23.0					27	B	28				17.0					
					18.0	INF-7		2	30	29	C	30	15	2	OU/DAMG-1	11.0					
					18.0					31	A	32				11.0					
					16.0	TW-1		2	20	33	B	34	20	2	TW-1	16.0					
					16.0					35	C	36				16.0					
					16.0	TW-1		2	20	37	A	38	20	2	TW-1	16.0					
					16.0					39	B	40				16.0					
					16.0	TW-1		2	20	41	C	42	20	2	TW-1	16.0					
					16.0					43	A	44				16.0					
					16.0	TW-1		2	20	45	B	46	20	2	TW-1	16.0					
					16.0					47	C	48				16.0					
					16.0	TW-1		2	20	49	A	50	20	2	TW-1	16.0					
					16.0					51	B	52				16.0					
					16.0	TW-1		2	20	53	C	54	20	2	TW-1	16.0					
					16.0					55	A	56				16.0					
					16.0	TW-1		2	20	57	B	58	20	2	TW-1	16.0					
					16.0					59	C	60				16.0					
					16.0	TW-1		2	20	61	A	62	20	2	TW-1	16.0					
					16.0					63	B	64				16.0					
					16.0	TW-1		2	20	65	C	66	20	2	TW-1	16.0					
					16.0					67	A	68				16.0					
					16.0	TW-1		2	20	69	B	70	20	2	TW-1	16.0					
					16.0					71	C	72				16.0					
					16.0	TW-1		2	20	73	A	74	20	2	TW-1	16.0					
					16.0					75	B	76				16.0					
					16.0	TW-1		2	20	77	C	78	20	2	TW-1	16.0					
					16.0					79	A	80				16.0					
					16.0	TW-1		2	20	81	B	82		2	SPACE	0.0					
					16.0					83	C	84				0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	0	code	0
EQUIPMENT	0	100%	0
LIGHTS (EXT.)	0	100%	0
LIGHTS (EXT.)	0	100%	0
HVAC	137.02	100%	137.02
TOTAL KVA	137 KVA		137 KVA
TOTAL AMPS	380 AMPS		380 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON" DEVICE
4 . GFI - INDICATES C.B. IS GFI TYPE (30 mA FOR EQUIPMENT, 5 mA FOR PERSONNEL)
5 . ST- INDICATES C.B. EQUIPPED WITH SHUNT TRIP DEVICE

PANEL NO.: M
USAGE: LIGHTING AND APPLIANCE
LOCATION: IT ROOM
PHASES: 3
L-L VOLTS 208V
L-G VOLTS 120V
BUS AMPS: 225A
MAIN CB AMPS: 225A
AIC RATING: 18,525 MINIMUM

PROJECT: PRUITT SAVANNAH
CLIENT: AKAS
MOUNTING: SURFACE
PANEL TYPE: NEMA 1
ENGINEER: DPF
DSA PROJECT NO.: 19031
FED FROM: B

CIRCUIT SETS	WIRE	NEUT.	GND.	COND.	LOAD AMPS	DESCRIPTION	NOTES	BREAKER POLE	AMP.	CKT. #	CKT. #	BREAKER AMP.	POLE	NOTES	DESCRIPTION	LOAD AMPS	CIRCUIT SETS	WIRE	NEUT.	GND.	COND.
					13.3	PWR: CKT C		1	20	1	A	2	20	1	PWR: CKT C	13.3					
					13.3	PWR: CKT C		1	20	3	B	4	20	1	PWR: CKT C	13.3					
					13.3	PWR: CKT C		1	20	5	C	6	20	1	PWR: CKT C	13.3					
					10.3	PWR: CKT C		1	20	7	A	8	20	1	RECEPTACLES	1.7					
					1.7	RECEPTACLES		1	20	9	B	10	20	1	RECEPTACLES	6.7					
					3.4	LIGHTING		1	20	11	C	12		1	SPACE	0.0					
					0.0	SPACE		1		13	A	14		1	SPACE	0.0					
					0.0	SPACE		1		15	B	16		1	SPACE	0.0					
					0.0	SPACE		1		17	C	18		1	SPACE	0.0					
					0.0	SPACE		1		19	A	20		1	SPACE	0.0					
					0.0	SPACE		1		21	B	22		1	SPACE	0.0					
					0.0	SPACE		1		23	C	24		1	SPACE	0.0					
					0.0	SPACE		1		25	A	26		1	SPACE	0.0					
					0.0	SPACE		1		27	B	28		1	SPACE	0.0					
					0.0	SPACE		1		29	C	30		1	SPACE	0.0					
					0.0	SPACE		1		31	A	32		1	SPACE	0.0					
					0.0	SPACE		1		33	B	34		1	SPACE	0.0					
					0.0	SPACE		1		35	C	36		1	SPACE	0.0					
					0.0	SPACE		1		37	A	38		1	SPACE	0.0					
					0.0	SPACE		1		39	B	40		1	SPACE	0.0					
					0.0	SPACE		1		41	C	42		1	SPACE	0.0					

LOAD SUMMARY	CON. KVA	%	DEM. KVA
RECEPTACLES	14.68	code	12.24
EQUIPMENT	0	100%	0
LIGHTS (EXT.)	0.41	100%	0.41
LIGHTS (EXT.)	0	100%	0
HVAC	0	100%	0
TOTAL KVA	15 KVA		13 KVA
TOTAL AMPS	41 AMPS		35 AMPS

PANEL NOTES:
1 . PROVIDE GROUND BUS
2 . PROVIDE FULL SIZE NEUTRAL BUS UNLESS NOTED OTHERWISE
3 . LO - INDICATES C.B. EQUIPPED WITH "LOCK-ON