PANEL DP

MAIN TYPE: **MAIN BREAKER** | VOLTAGE (L-L): **208** | PHASE: **3**
AMPERE RATING: **800** | VOLTAGE (L-N): **120** | WIRE: **4**
LUG OPTIONS: | BUS RTG (AMPS): **800** | MIN. KAIC: **30**
REMARKS: **NEW PANEL** | MOUNTING: **FLUSH**

CCT BRKR NO.	AMPS	P	LOAD DESCRIPTION	COM.	WIRE SIZE	LOAD KVA	PHASE A	PHASE B	PHASE C	LOAD KVA	WIRE SIZE	COM	LOAD DESCRIPTION	CCT BRKR P	AMPS	NO.
						2.0	2.0						SPARE	1	20	2
3	25	3	CONVECTION OVEN (B1G)		10	2.0		6.7		6.7						
						2.0			6.7	6.7	4		RTU-4	3	70	6
						2.0	6.7			6.7			(NEW UNIT)			
9	25	3	CONVECTION OVEN (B1G)		10	2.0		2.6		0.6						
						2.0			2.6	0.6	12		WALK IN COOLER	3	20	12
13	30	2	INSTANT WATER HEATER		10	2.1	2.7			0.6						
						2.1		2.8		0.7						
17	20	1	SPARE						0.7	0.7	10		WALK IN FREEZER	3	30	16
21	225	3	PANEL A	A	4/0	12.5	13.2			0.7						
						13.9		18.7		4.8						
						12.5			17.3	4.8	6		RTU-2	3	50	24
						9.5	14.3			4.8			(EXISTING UNIT)			
27	225	3	PANEL B	A	4/0	8.5		15.2		6.7						
						8.6			15.3	6.7	8		RTU-1	3	50	30
						32.4	39.1			6.7			(EXISTING UNIT)			
33	225	3	PANEL C	A	4/0	26.8		33.6		4.8						
						27.0			31.8	4.8	4		RTU-3	3	60	36
						0.2	5.0			4.8			(EXISTING UNIT)			
39	20	3	COOLER EVAPORATOR		12	0.2		5.0		4.8	4		CHUB WARMER (D81)	2	60	40
						0.2			5.0	4.8						
						85.0	86.6	61.4								

NEC ARTICLE 220 LOAD CATEGORY:	CONN KVA	DEMD FACT	DEMD KVA	DEMD KVA	DEMD FACT	CONN KVA	NEC ARTICLE 220 LOAD CATEGORY:
TOTAL INTERIOR LIGHTS	3.4	1.25	4.3				
I ENERGY CODE REQD.				2.4	1.00	2.4	MISC. HVAC S
N NONENER. CODE REQD.				0.0	1.00	0.0	MOTORS M
E EXTERIOR LIGHTS	12.1	1.25	15.1	0.0	0.25	0.0	LARGEST MOTOR LM
R RECEPTACLES (FIRST 10)	10.0	1.00	10.0	10.0	1.00	10.0	WATER HEATERS W
(REMAINDER)	10.4	0.50	5.2	0.0	1.00	0.0	ELEVATORS L
P HVAC PACKAGED UNITS	69.5	1.00	69.5	119.1	1.00	119.1	KITCHEN EQUIPMENT K
H HEAT PUMPS	0.0	1.00	0.0			6	NO. OF UNITS OF EQUIP.
A AIR HANDLING UNITS	0.0	1.00	0.0	0.0	1.25	0.0	COMPUTER LOADS O
X CHILLER / COOLING TOWER	0.0	1.00	0.0	0.0	1.00	0.0	SHOP EQUIPMENT Q
T ELECTRIC HEAT	0.0	1.00	0.0	9.1	1.00	9.1	MISC. LOADS C
V VAV BOXES / FAN BOXES	0.0	1.00	0.0	0.0	1.00	0.0	SYSTEM FURNITURE Z

NOTES: A PROVIDE BREAKER WITH LOCK-ON DEVICE.

CONNECTED KVA: **253.0**
CONNECTED AMPS: **703**
DEMAND AMPS: **579.6**

PANEL A

MAIN TYPE: **MAIN BREAKER** | VOLTAGE (L-L): **208** | PHASE: **3**
AMPERE RATING: **225** | VOLTAGE (L-N): **120** | WIRE: **4**
LUG OPTIONS: | BUS RTG (AMPS): **225** | MIN. KAIC: **30**
REMARKS: | MOUNTING: **FLUSH**

CCT BRKR NO.	AMPS	P	LOAD DESCRIPTION	COM.	WIRE SIZE	LOAD KVA	PHASE A	PHASE B	PHASE C	LOAD KVA	WIRE SIZE	COM	LOAD DESCRIPTION	CCT BRKR P	AMPS	NO.
1	20	1	FAN HEF-1		12	1.7	2.1			0.4	12		FAN EF-1	1	20	2
3	20	1	FAN HEF-2		12	0.75		1.1		0.3	12		HOOD CONTROLS	1	20	4
5	20	1	MONITOR (A31)		12	0.6			1.9	1.3	12		RECEPTACLES	1	20	6
7	20	1	CARBONATORS (K42)		12	0.9	1.0			0.1	12		OFFICE CABINET FAN	1	20	8
9	20	1	TOASTER (C31)		12	1.8		1.8		0.1	12		SERVICE DOORBELL	1	20	10
11	20	1	REFRIGERATOR (C18)		12	0.9			1.3	0.6	12		IRRIGATION CONTROLS	1	20	12
13	20	1	SPARE				0.6			0.6	12	A	ANSUL SYSTEM	1	20	14
15	20	1	FREEZER (A54)		12	1.1		2.5		1.4	12		REFRIGERATOR (B80)	1	20	16
						0.2			1.3	1.1	12		RECEPTACLES - DINING	1	20	18
19	20	3	FREEZER EVAPORATOR		12	0.2	1.3			1.1	12		RECEPTACLES - DINING	1	20	20
						0.2		0.9		0.7	12	A	SECURITY CAMERAS	1	20	22
23	25	1	HOLDING CABINET (D50)		10	2.1			2.3	0.2	12		WATER HEATER CONTROLS	1	20	24
25	20	2	PACKING STATION (D29)		12	0.6	2.0			1.4	12		SANDWICH HOLDING UNIT (C17)	1	20	26
						0.6		1.1		0.5	12		RECEPTACLES	1	20	28
29	20	1	SPARE						1.9	1.9	12		HEAT TRACE	1	20	30
31	30	2	INSTANT WATER HEATER		10	2.1	3.8			1.7	10		SITE LIGHTS	2	30	32
						2.1		3.8		1.7						
35	20	1	FAN HEF-3		12	0.5			2.2	1.7	10		SITE LIGHTS	2	30	36
37	20	1	SPARE				1.7			1.7						
39	20	2	MICROWAVE (D20)		12	0.9		2.8		1.7	10		SITE LIGHTS	2	30	40
						0.9			2.8	1.7						
							12.5	13.9	12.5							

NEC ARTICLE 220 LOAD CATEGORY:	CONN KVA	DEMD FACT	DEMD KVA	DEMD KVA	DEMD FACT	CONN KVA	NEC ARTICLE 220 LOAD CATEGORY:
TOTAL INTERIOR LIGHTS	0.0	1.25	0.0				
I ENERGY CODE REQD.				2.4	1.00	2.4	MISC. HVAC S
N NONENER. CODE REQD.				0.0	1.00	0.0	MOTORS M
E EXTERIOR LIGHTS	10.2	1.25	12.8	0.0	0.25	0.0	LARGEST MOTOR LM
R RECEPTACLES (FIRST 10)	6.1	1.00	6.1	4.4	1.00	4.4	WATER HEATERS W
(REMAINDER)	0.0	0.50	0.0	0.0	1.00	0.0	ELEVATORS L
P HVAC PACKAGED UNITS	0.0	1.00	0.0	12.9	1.00	12.9	KITCHEN EQUIPMENT K
H HEAT PUMPS	0.0	1.00	0.0			11	NO. OF UNITS OF EQUIP.
A AIR HANDLING UNITS	0.0	1.00	0.0	0.0	1.25	0.0	COMPUTER LOADS O
X CHILLER / COOLING TOWER	0.0	1.00	0.0	0.0	1.00	0.0	SHOP EQUIPMENT Q
T ELECTRIC HEAT	0.0	1.00	0.0	1.6	1.00	1.6	MISC. LOADS C
V VAV BOXES / FAN BOXES	0.0	1.00	0.0	0.0	1.00	0.0	SYSTEM FURNITURE Z

NOTES: A PROVIDE BREAKER WITH LOCK-ON DEVICE.

CONNECTED KVA: **38.8**
CONNECTED AMPS: **108**
DEMAND AMPS: **98.9**

KITCHEN EQUIPMENT CONNECTION SCHEDULE

CONNECTION DESIGNATION	LOAD DESCRIPTION	VOLTS/PH	LOAD INFORMATION HP	LOAD	MCA	MOCP	CONNECTION TYPE TYPE	NEMA RECEPT. TYPE	CIRCUIT ID	CONNECTION NOTES	CONNECTION DESIGNATION
A10-U3	FRYER BATTERY (GAS) (X2)	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A10-U3
A24L2	FRYER BATTERY (GAS)	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A24L2
A31	MARINATOR	120/1	-	0.9 KVA	5		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A31
A47.3	ICE BATTERY(SPTR DC)	120/1	-	0.3 KVA	2.5		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A47.3
A54	FREEZER	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A54
A81	GREASE COLLECTION SYS	120/1	-	1.9 KVA	16		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	A81
B10	OVEN	208/3	-	5.6 KVA	24		CORD & PLUG	-	SEE PLANS	1,2,3	B10
B60	REFRIGERATOR	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	B60
B85	BISCUIT HOLDING UNIT	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	
C17	SANDWICH HOLDING UNIT	120/1	-	1.4 KVA	12		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	C17
C18	REFRIGERATOR	120/1	-	0.8 KVA	4.8		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	C18
C21	TOASTER	120/1	-	1.8 KVA	15		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	C21
D20	MICROWAVE (X2)	208/1	-	3.6 KVA	14.3		CORD & PLUG	NEMA 6-20	SEE PLANS	1,2,3	D20
D29	PACKING STATION	208/1	-	1.2 KVA	6		DIRECT CONNECTION	-	SEE PLANS	1,2,3	D29
D70	DISPENSER (X2)	208/1	-	4.1 KVA	19.8		CORD & PLUG	NEMA 6-20	SEE PLANS	1,2,3	D70
D81	CHUB WARMER	208/1	-	3.6 KVA	17.6		DIRECT CONNECTION	-	SEE PLANS	1,2,3	D81
D90	HOLDING CABINET	120/1	-	2.1 KVA	9.1		DIRECT CONNECTION	-	SEE PLANS	1,2,3	D90
D92	SIDE ITEM HOLDING UNIT	208/3	-	5.0 KVA	13.87		CORD & PLUG	-	SEE PLANS	1,2,3	D92
D93.1	CHICKEN HOLDING UNIT	208/3	-	12.7 KVA	34.75		CORD & PLUG	-	SEE PLANS	1,2,3	D93.1
D94	DEDICATED HOLD UNIT	208/3	-	4.8 KVA	23.7		CORD & PLUG	-	SEE PLANS	1,2,3	D94
E10.1	WALK-IN COOLER	208/3	-	-	-		DIRECT CONNECTION	-	SEE PLANS	1,2,3	E10.1
E10.2	WALK-IN FREEZER	208/3	-	-	-		DIRECT CONNECTION	-	SEE PLANS	1,2,3	E10.2
F15.1	HEATED HOLDING UNIT	208/1	-	3.6 KVA	18.2		DIRECT CONNECTION	-	SEE PLANS	1,2,3	F15.1
H10.3PD	PRODUCTION COUNTER	208/1	-	2.9 KVA	14		DIRECT CONNECTION	-	SEE PLANS	1,2,3	H10.3PD
H83	WINDOW/WIDE	120/1	-	1.8 KVA	15		DIRECT CONNECTION	-	SEE PLANS	1,2,3	H83
J40	REFRIGERATOR	120/1	-	0.6 KVA	4.8		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	J40
K10	ICE CUBER	208/1	-	2.8 KVA	11.9		DIRECT CONNECTION	-	SEE PLANS	1,2,3	K10
K11	ICE CUBER	208/1	-	3.6 KVA	17.1		DIRECT CONNECTION	-	SEE PLANS	1,2,3	K11
K31	SODA DISPENSER	120/1	-	0.2 KVA	1.5		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	K31
K32	SODA DISPENSER	120/1	-	0.5 KVA	4		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	K32
K42L	BAG-IN-BOX RACK CARBON	120/1	-	0.9 KVA	7.2		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	K42L
K71	TEA/COFFEE BREWER	120/1	-	1.7 KVA	14		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	K71
K32F	SODA DISPENSER FREESTYLE (OPTION)	120/1	-	1.9 KVA	16		CORD & PLUG	NEMA 5-20	SEE PLANS	1,2,3	K32F
M10	WALL CABINET	120/1	-	0.9 KVA	4		DIRECT CONNECTION	-	SEE PLANS	1,2,3	M10
M11	WORK TABLE	120/1	-	0.9 KVA	4		DIRECT CONNECTION	-	SEE PLANS	1,2,3	M11
M30	SAFE	120/1	-	0.6 KVA	5		DIRECT CONNECTION	-	SEE PLANS	1,2,3	M30
M61	EMPLOYEE TRAINING DESK	120/1	-	0.6 KVA	5		DIRECT CONNECTION	-	SEE PLANS	1,2,3	M61
N92	RINNAI TANKLESS WATER HTR	120/1	-	0.5 KVA	4		DIRECT CONNECTION	-	SEE PLANS	1,2,3	N92
N93	HAND DRYER	120/1	-	1.5 KVA	12.5		DIRECT CONNECTION	-	SEE PLANS	1,2,3	N93
P20	CASH REGISTER	120/1	-	0.2 KVA	2		CORD & PLUG	-	SEE PLANS	ISOLATED CIRCUIT	P20
P30	PRINTER	120/1	-	0.2 KVA	2		CORD & PLUG	-	SEE PLANS	ISOLATED CIRCUIT	P30
Q11	DIGITAL MENU BOARD	120/1	-	0.7 KVA	6		DIRECT CONNECTION	-	SEE PLANS		Q11
Q12	DIGITAL PRE-SELL MENU BD	120/1	-	1.3 KVA	11		DIRECT CONNECTION	-	SEE PLANS		Q12
Q21	DRIVE THRU CANOPY	120/1	-	0.9 KVA	7.5		DIRECT CONNECTION	-	SEE PLANS		Q21
Q24	DRIVE-THRU CONTROL BD	120/1	-	1.6 KVA	13		DIRECT CONNECTION	-	SEE PLANS	ISOLATED CIRCUIT	Q24
Q28	DRIVE-THRU MENU BOARD	120/1	-	0.7 KVA	6		DIRECT CONNECTION	-	SEE PLANS		Q28
Q27	ORDER KIOSK	120/1	-	0.2 KVA	2		DIRECT CONNECTION	-	SEE PLANS		Q27

NOTES:
1. ALL KITCHEN CIRCUITS SHALL BE GROUND FAULT PROTECTED.
2. COORDINATE EXACT RECEPTACLE TYPE WITH EQUIPMENT MANUFACTURER / KITCHEN EQUIPMENT PLANS.
3. FOR EQUIPMENT UNDER THE EXHAUST HOOD, EQUIPMENT SHALL BE SHUNT-TRIPPED WITH HOOD ANSUL SYSTEM.

PANEL C

MAIN TYPE: **MAIN BREAKER** | VOLTAGE (L-L): **208** | PHASE: **3**
AMPERE RATING: **225** | VOLTAGE (L-N): **120** | WIRE: **4**
LUG OPTIONS: | BUS RTG (AMPS): **225** | MIN. KAIC: **30**
REMARKS: **EXISTING PANEL TO REMAIN** | MOUNTING: **FLUSH**

CCT BRKR NO.	AMPS	P	LOAD DESCRIPTION (H10.3PD) LOAD CENTER	COM.	WIRE SIZE	LOAD KVA	PHASE A	PHASE B	PHASE C	LOAD KVA	WIRE SIZE	COM	LOAD DESCRIPTION	CCT BRKR P	AMPS	NO.
1	125	2			1	9.8	10.0			1.1						
						8.9		10.0		1.1	12		SIDE ITEM HOLD UNIT (D92)	1	20	4
5	20	1	FRYER (A10.U3)		12	1.4			2.5	1.1						
7	20	1	FRYER (A10.U3)		12	1.4	2.5			1.1						
9	25	2	HOLDING UNIT (F15.1)		10	2.0		3.1		1.1	12		SIDE ITEM HOLD UNIT (D92)	3	20	10
						2.0			3.1	1.1						
13	20	1	ICE/BATTER/SIFTER (A47.3		12	1.4	1.7			0.3	12		BISCUIT HOLDING (B85)	1	20	14
15	20	1	FRYER (A24U2)		12	1.4		2.6		1.2	12		HEAT TRACE	1	20	16
17	20	1	EXIST. WATER HEATER		12	1.5			3.4	1.9	12		GREASE COLLECTION SYS.	1	20	18
19	20	1	EXIST. WATER HEATER		12	1.5	1.5						SPARE	1	20	20
21	20	2	MICROWAVE (D20)		12	0.9		2.1		1.2	12		ICE MACHINE (K10)	2	20	22
						0.9			2.1	1.2						
25	20	1	HAND DRYER (D83)		12	1.5	2.7			1.2	12		ICE MACHINE (K11)	2	20	26
27	20	1	SPARE					1.2		1.2						
						2.8										
31	30	3	DEDICATED HOLD UNIT (D94)		10	2.8	5.1			2.3	10		HOT WATER DISP (D70)	2	30	30
						2.8			5.1	2.3						32
						2.8		9.4		6.6						
35	30	2	HOT WATER DISP. (D70)		10	2.3			8.6	6.6	4		CHICKEN HOLD UNIT (D93.1)	3	70	36
						2.3	8.9			6.6						
39	20	2	HEAT LAMPS		12	0.4		0.4					SPACE ONLY			40
						0.4			1.9	1.5	12		HAND DRYER (D83)	1	20	42
						32.4	28.8	27.0								

NEC ARTICLE 220 LOAD CATEGORY:	CONN KVA	DEMD FACT	DEMD KVA	DEMD KVA	DEMD FACT	CONN KVA	NEC ARTICLE 220 LOAD CATEGORY:
TOTAL INTERIOR LIGHTS	0.0	1.25	0.0				
I ENERGY CODE REQD.				0.0	1.00	0.0	MISC. HVAC S
N NONENER. CODE REQD.				0.0	1.00	0.0	MOTORS M
E EXTERIOR LIGHTS	0.0	1.25	0.0	0.0	0.25	0.0	LARGEST MOTOR LM
R RECEPTACLES (FIRST 10)	0.0	1.00	0.0	7.6	1.00	7.6	WATER HEATERS W
(REMAINDER)	0.0	0.50	0.0	0.0	1.00	0.0	ELEVATORS L
P HVAC PACKAGED UNITS	0.0	1.00	0.0	76.4	1.00	76.4	KITCHEN EQUIPMENT K
H HEAT PUMPS	0.0	1.00	0.0			12	NO. OF UNITS OF EQUIP.
A AIR HANDLING UNITS	0.0	1.00	0.0	0.0	1.25	0.0	COMPUTER LOADS O
X CHILLER / COOLING TOWER	0.0	1.00	0.0	0.0	1.00	0.0	SHOP EQUIPMENT Q
T ELECTRIC HEAT	0.0	1.00	0.0	4.2	1.00	4.2	MISC. LOADS C
V VAV BOXES / FAN BOXES	0.0	1.00	0.0	0.0	1.00	0.0	SYSTEM FURNITURE Z

NOTES: A PROVIDE HACR BREAKER.

CONNECTED KVA: **88.2**
CONNECTED AMPS: **245**
DEMAND AMPS: **[illegible]**

PANEL B

MAIN TYPE: **MAIN BREAKER** | VOLTAGE (L-L): **208** | PHASE: **3**
AMPERE RATING: **225** | VOLTAGE (L-N): **120** | WIRE: **4**
LUG OPTIONS: | BUS RTG (AMPS): **225** | MIN. KAIC: **30**
REMARKS: | MOUNTING: **FLUSH**

CCT BRKR NO.	AMPS	P	LOAD DESCRIPTION	COM.	WIRE SIZE	LOAD KVA	PHASE A	PHASE B	PHASE C	LOAD KVA	WIRE SIZE	COM	LOAD DESCRIPTION	CCT BRKR P	AMPS	NO.
1	20	1	ROOF RECEPTACLES		12	0.6	0.6						SPARE	1	20	2
3	20	1	MENU BOARD (Q11)		12	1.3		1.8		0.5	12		KITCHEN AND BAR LIGHTS	1	20	4
5	20	1	KITCHEN AND SALES LIGHTS		12	1.0			1.7	0.7	12		EMT TERMINAL BOARD	1	20	6
7	20	1	KITCHEN LIGHTS - NL		12	0.4	0.8			0.4	12		RECEPTACLES OFFICE	1	20	8
9	20	1	DINING LIGHTS		12	1.1		1.8		0.7	12		[illegible]	1	20	10
11	20	1	TEA BREWER (K71)		12	1.7			2.1	0.4	12		DRIVE THRU EQUIPMENT	1	20	12
13	20	1	SODA DISPENSER (K31)		12	1.5	3.3			1.8			DRIVE THRU WINDOW	1	20	14
15	20	1	FRONT SIGN		12	0.1		0.1					SPARE	1	20	16
17	20	1	VIDEO MONITORS		12	0.7			3.0	2.3	10		DRIVE THRU BOARD	2	25	18
19	20	2	PYLON SIGN		12	1.2	1.2						SPARE	1	20	20
						1.2		2.4		1.2	12		DRIVE THRU AUDIO	1	20	22
23	20	1	SPARE						0.6	0.6	12		STOREFRONT RECEPTACLES	1	20	24
25	20	1	SECURITY SYSTEM	A	12	0.5	1.0			0.5	12		STOREFRONT RECEPTACLES	1	20	26
27	20	1	POS SYTEM (FRONT CNTR)		12	1.1		1.9		0.8	12		EXT. SOFFIT LIGHTS	1	20	28
29	20	1	DRIVE-THRU P.O.S.		12	0.2			0.2				SPARE	1	20	30
31	20	2	SAFE (L39)	A	12	0.5	1.3			0.8	12		EXT. SOFFIT LIGHTS	1	20	32
33	20	1	SODA DISPENSER (K32)		12	0.5		0.5					SPARE	1	20	34
35	20	1	ORDER KIOSKS		12	1.2	1.2						SPARE	1	20	36
37	20	1	DRIVE-THRU CANOPY (Q21)		12	0.9		1.1		0.2			SPARE	1	20	38
39	20	1	SPARE				0.9						SPARE	1	20	40
41	20	2	SPARE					0.0		0.0			SPARE	1	20	42
							9.2	8.6								

NEC ARTICLE 220 LOAD CATEGORY:	CONN KVA	DEMD FACT	DEMD KVA	DEMD KVA	DEMD FACT	CONN KVA	NEC ARTICLE 220 LOAD CATEGORY:
TOTAL INTERIOR LIGHTS	3.4	1.25	4.3				
I ENERGY CODE REQD.				0.0	1.00	0.0	MISC. HVAC S
N NONENER. CODE REQD.				0.0	1.00	0.0	MOTORS M
E EXTERIOR LIGHTS	1.9	1.25	2.4	0.0	0.25	0.0	LARGEST MOTOR LM
R RECEPTACLES (FIRST 10)	10.0	1.00	10.0	0.0	1.00	0.0	WATER HEATERS W
(REMAINDER)	4.3	0.50	2.2	0.0	1.00	0.0	ELEVATORS L
P HVAC PACKAGED UNITS	0.0	1.00	0.0	3.7	1.00	3.7	KITCHEN EQUIPMENT K
H HEAT PUMPS	0.0	1.00	0.0			3	NO. OF UNITS OF EQUIP.
A AIR HANDLING UNITS	0.0	1.00	0.0	0.0	1.25	0.0	COMPUTER LOADS O
X CHILLER / COOLING TOWER	0.0	1.00	0.0	0.0	1.00	0.0	SHOP EQUIPMENT Q
T ELECTRIC HEAT	0.0	1.00	0.0	3.3	1.00	3.3	MISC. LOADS C
V VAV BOXES / FAN BOXES	0.0	1.00	0.0	0.0	1.00	0.0	SYSTEM FURNITURE Z

NOTES: A PROVIDE BREAKER WITH LOCK-ON DEVICE.

CONNECTED KVA: **26.5**
CONNECTED AMPS: **73.9**
DEMAND AMPS: **70.6**



ELECTRICAL EQUIPMENT CONNECTION SCHEDULE

CONNECTION DESIGNATION	LOAD DESCRIPTION	VOLTS/PH	LOAD INFORMATION HP	LOAD	MCA	MOCP	DISCONNECT INFORMATION FURN. BY	INSTALLED BY	TYPE	SWITCH RATING	POLE	FUSE OR TRIP RATING	NEMA ENCL. TYPE	CIRCUIT ID	CONNECTION NOTES	CONNECTION DESIGNATION
HEF-1	FAN HEF-1	120/1	0.75	1.7 KVA	13.6	-	EQ. MFGR.	EQ. MFGR.	-	-	-	-	-	A-1	-	HEF-1
HEF-2	FAN HEF-2	120/1	0.75	1.7 KVA	13.6	-	EQ. MFGR.	EQ. MFGR.	-	-	-	-	-	A-3	-	HEF-2
HEF-3	FAN HEF-3	120/1	0.5	1.2 KVA	9.8	-	EQ. MFGR.	EQ. MFGR.	-	-	-	-	-	A-3	-	HEF-3
EF-1	FAN EF-1	120/1	-	0.2 KVA	2	-	EQ. MFGR.	EQ. M