This document together with the concepts and designs presented herein, as an instrument of service, is intended only for the specific purpose and client for which it was prepared. Reuse of and improper reliance on this document without written authorization and adaptation by Kimley-Horn and Associates, Inc. shall be without liability to Kimley-Horn and Associates, Inc.

McGraw-Edson

Catalog #	Type
Project	
Comments	Date
Prepared by	

DESCRIPTION

The Galleon™ Wall LED luminaire's appearance is complementary with the Galleon area and site luminaire bringing a modern architectural style to lighting applications. Flexible mounting options accommodate wall surfaces in both an upward and downward configuration. The Galleon family of LED products deliver exceptional performance with patented, high-efficiency AccuLED Optics™, providing uniform and energy conscious lighting for parking lots, building and security lighting applications.

SPECIFICATION FEATURES

Construction
Driver enclosure thermally isolated from optics for optimal thermal performance. Heavy wall aluminum housing die-cast with integral external heat sinks to provide superior structural rigidity and an IP66 rated housing. Overall construction passes a 1.5G vibration test to ensure mechanical integrity. UPLIGHTING: Specify with the UPL option for inverted mount uplight housing with additional protections to maintain IP rating.

Optics
Choice of thirteen patented, high-efficiency AccuLED Optics. The optics are precisely designed to shape the distribution maximizing efficiency and application spacing. AccuLED Optics create consistent distributions with the scalability to meet customized application requirements. Offered standard in 4000K (+/- 275K) CCT and minimum 70 CRI. Optional 3000K, 5000K and 6000K CCT. Greater than 90% lumen maintenance expected at 60,000 hours. Available in standard 1A drive current and optional 1200mA, 700mA, and 600mA drive currents.

Electrical
LED drivers are mounted for ease of maintenance. 120-277V 50/60Hz, 347V or 480V 60Hz operation. 480V is compatible for use with 480Y Wye systems only. Drivers are provided standard with 0-10V dimming. An optional Cooper Lighting Solutions proprietary surge protection module is available and designed to withstand 10kV of transient line surge. The Galleon Wall LED luminaire is suitable for operation in -40°C to 40°C ambient environments. For applications with ambient temperatures exceeding 40°C, specify the HA (High Ambient) option. Emergency egress options for -20°C ambient environments and occupancy sensor available.

Mounting
Gasketed and fine plated rigid steel mounting attachment fits directly to 4" j-box or wall with the Galleon Wall "Hook-N-Lock" mechanism for quick installation. Secured with two captive corrosion resistant black oxide coated allen head set screws which are concealed but accessible from bottom of fixture.

Finish
Housing finished in super durable TGIC polyester powder coat paint, 2.5 mil nominal thickness for superior protection against fade and wear. Standard colors include black, bronze, grey, white, dark platinum and graphite metallic. RAL and custom color matches available. Consult the McGraw-Edison Architectural Colors brochure for the complete selection.

Warranty
Five-year warranty.



GWC GALLEON WALL

1-2 Light Squares
Solid State LED

WALL MOUNT LUMINAIRE

WaveLinx

DIMENSIONS



HOOK-N-LOCK MOUNTING



BATTERY BACKUP AND THRU-BRANCH BACK BOX



DLC DLC

CERTIFICATION DATA
UL/cUL Listed
LM79 - IP66 Compliant
IP66 Housing
ISO 9001
DesignLights Consortium® Qualified*

ENERGY DATA
Electronic LED Driver
>0.9 Power Factor
<20% Total Harmonic Distortion
120-277V 50/60Hz
347V, 480V 60Hz
-40°C Min. Temperature
40°C Max. Temperature
50°C Max. Temperature (HA Option)

SHIPPING DATA
Approximate Net Weight:
29 lbs. (12.2 kgs.)

ISTI

TDS140176N
March 10, 2020 9:37 AM

*www.designlights.org

POWER AND LUMENS

Number of Light Squares		1				2			
Drive Current		500mA	700mA	1.0A	1.2A	500mA	700mA	1.0A	1.2A
Nominal Power (Watts)		54	64	88	97	88	86	113	129
Input Current @ 120V (A)		0.50	0.59	0.81	0.88	0.66	0.77	1.02	1.16
Input Current @ 208V (A)		0.27	0.32	0.49	0.50	0.34	0.44	0.59	0.63
Input Current @ 240V (A)		0.23	0.28	0.36	0.46	0.30	0.38	0.46	0.55
Input Current @ 277V (A)		0.24	0.27	0.33	0.35	0.26	0.35	0.40	0.46
Input Current @ 347V (mA)		0.21	0.25	0.27	0.35	0.19	0.24	0.32	0.38
Input Current @ 480V (mA)		0.58	0.21	0.14	0.15	0.15	0.19	0.24	0.30
Optics									
T2	4000K/5000K Lumens	4,204	5,156	6,781	7,800	8,215	10,075	12,470	13,685
	3000K Lumens	3,975	4,874	6,033	6,814	7,767	9,525	11,790	12,304
	BUG Rating	B1-U0-G1	B1-U0-G1	B2-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G2
T3	4000K/5000K Lumens	4,283	5,256	6,505	7,139	8,376	10,266	12,710	13,948
	3000K Lumens	4,051	4,969	6,150	6,748	7,918	9,710	12,017	13,192
	BUG Rating	B1-U0-G1	B1-U0-G1	B1-U0-G2	B1-U0-G2	B1-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G2
T4FT	4000K/5000K Lumens	4,311	5,286	6,542	7,177	8,422	10,328	12,784	14,024
	3000K Lumens	4,075	4,998	6,185	6,786	7,963	9,766	12,084	13,265
	BUG Rating	B1-U0-G1	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G3
T6W	4000K/5000K Lumens	4,256	5,217	6,458	7,084	8,303	10,185	12,608	13,833
	3000K Lumens	4,023	4,933	6,105	6,698	7,850	9,628	11,921	13,080
	BUG Rating	B1-U0-G1	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G3
GL2	4000K/5000K Lumens	4,186	5,147	6,370	6,988	8,202	10,059	12,448	13,656
	3000K Lumens	3,967	4,866	6,022	6,607	7,775	9,539	11,771	12,911
	BUG Rating	B1-U0-G1	B1-U0-G1	B1-U0-G2	B1-U0-G2	B1-U0-G2	B2-U0-G2	B2-U0-G2	B2-U0-G3
BLS	4000K/5000K Lumens	4,284	5,256	6,504	7,134	8,374	10,266	12,709	13,941
	3000K Lumens	5,649	4,930	6,842	6,698	7,920	9,714	11,958	12,929
	BUG Rating	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G3	B1-U0-G3	B1-U0-G3
SL4	4000K/5000K Lumens	4,071	4,992	6,179	6,778	7,904	9,696	12,006	13,246
	3000K Lumens	3,860	4,739	5,862	6,430	7,500	9,200	11,386	12,563
	BUG Rating	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G3	B1-U0-G3	B1-U0-G3
SNG	4000K/5000K Lumens	4,429	5,420	6,709	7,359	8,607	10,561	13,106	14,380
	3000K Lumens	4,179	5,124	6,342	6,957	8,166	10,013	12,393	13,585
	BUG Rating	B2-U0-G1	B2-U0-G1	B2-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G2	B3-U0-G2
SM6	4000K/5000K Lumens	4,601	5,620	6,931	7,604	8,755	10,736	13,302	14,644
	3000K Lumens	4,354	5,316	6,459	7,085	8,116	10,166	12,620	13,945
	BUG Rating	B3-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G2	B3-U0-G2	B4-U0-G2	B4-U0-G2
SWG	4000K/5000K Lumens	4,313	5,634	6,949	7,614	8,619	10,615	13,280	14,568
	3000K Lumens	4,258	5,292	6,475	7,104	8,338	10,234	12,685	13,982
	BUG Rating	B3-U0-G1	B3-U0-G1	B3-U0-G2	B3-U0-G2	B3-U0-G2	B4-U0-G2	B4-U0-G2	B4-U0-G2
SLA/SLR	4000K/5000K Lumens	3,286	4,816	5,756	6,370	7,356	9,029	11,167	12,281
	3000K Lumens	3,060	4,267	5,404	5,927	6,997	8,581	10,588	11,663
	BUG Rating	B1-U0-G1	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G2	B1-U0-G3	B2-U0-G3
RW	4000K/5000K Lumens	4,579	5,370	6,647	7,253	8,268	10,494	12,985	14,250
	3000K Lumens	4,341	5,091	6,298	6,895	8,060	9,922	12,291	13,473
	BUG Rating	B2-U0-G1	B2-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G1	B3-U0-G2	B3-U0-G2

* Nominal lumens data for 70 CRI. BUG rating for 4000K/5000K. Refer to IES files for 3000K BUG ratings.

OPTICAL DISTRIBUTIONS

Asymmetric Area Distributions

T2 (Type II)

GL2 (Type II with Uplit Control)

T3 (Type III)

GL3 (Type III with Uplit Control)

T4FT (Type IV Forward Throw)

T4W (Type IV Wide)

BLS (Type IV with Uplit Control)

Symmetric Distributions

SNG (Type V Square Narrow)

SM6 (Type V Square Medium)

SWG (Type V Square Wide)

Specialized Distributions

RW (Rectangular Wide Type I)

SLA (Uplight Light Concentrator Left)

SLR (90° Uplit Light Concentrator Right)

LUMEN MAINTENANCE

Drive Current	Ambient Temperature	TM-21 Lumen Maintenance (60,000 Hours)	Projected L70 (Hours)
Up to 1A	Up to 25°C	> 78%	> 416,000
1.2A	Up to 40°C	> 90%	> 200,000



LUMEN MULTIPLIER

Ambient Temperature	Lumen Multiplier
0°C	1.02
10°C	1.01
25°C	1.00
40°C	0.98
50°C	0.97

CONTROL OPTIONS

0-10V
This fixture is offered standard with 0-10V dimming driver(s). This DIM option provides 0-10V dimming wire leads for use with a lighting control panel or other control method.

Photocontrol (R, R and PER7)
Optional button-type photocontrol (R) and photocontrol receptacles (R and PER7) provide a flexible solution to enable "dusk-to-dawn" lighting by sensing light levels. Advanced control systems compatible with NEMA 7-pin standards can be utilized with the PER7 receptacle.

After Hours Dim (AHD)
This feature allows photocontrol-enabled luminaires to achieve additional energy savings by dimming during scheduled portions of the night. The dimming profile will automatically take effect after a "dusk-to-dawn" period has been calculated from the photocontrol input. Specify the desired dimming profile for a simple, factory-shipped dimming solution requiring no external control wiring. Reference the After Hours Dim supplemental guide for additional information.

Dimming Occupancy Sensor (MS/DIM-LXX and MS-LXX)
These sensors are factory installed in the luminaire housing. When the MS/DIM-LXX sensor option is selected, the occupancy sensor is connected to a dimming driver and the entire luminaire dims when there is no activity detected. When activity is detected, the luminaire returns to full light output. The MS/DIM sensor is factory preset to dim down to approximately 50 percent power with a time delay of five minutes. The MS-LXX sensor is factory preset to turn the luminaire off after five minutes of no activity. The MS/X-LXX is also preset for five minutes and only controls the specified number of light engines to maintain steady output from the remaining light engines.

These occupancy sensors include an integral photocell that can be activated with the FSIR-100 accessory for "dusk-to-dawn" control or daylight harvesting - the factory preset is OFF. The FSIR-100 is a wireless tool utilized for changing the dimming level, time delay, sensitivity and other parameters. A variety of sensor lens are available to optimize the coverage pattern for mounting heights from 8'-40'.

For mounting heights up to 8' (LCCE)


For mounting heights up to 20' (LCCE)


For mounting heights up to 40' (LCCE)


For mounting heights up to 40' (LCCE)

LumaWatt Pro Wireless Control and Monitoring System (LWR-LW and LWR-LN)
The Eaton's LumaWatt Pro powered by Enlighted is a connected lighting solution that combines the selection of energy efficient LED luminaires with a powerful integrated wireless sensor system. The sensor control and lighting system is compliant with the latest energy codes and collects valuable data about building performance and use. Software applications then translate data into insights on the high energy dashboards and specialized apps that make it simple and help optimize the use of building resources, people and lighting.

For mounting heights from 9' to 16' (LWR-LW)


For mounting heights 16' to 40' (LWR-LN)

WaveLinx Wireless Outdoor Lighting Control Module (WOLC-9P-10A)
The 7-pin wireless outdoor lighting control module enables WaveLinx to control outdoor area, site and flood lighting. WaveLinx controls outdoor lighting using schedules to provide ON, OFF and dimming controls based on astronomic or time schedules based on a 7 day week.

ORDERING INFORMATION

Sample Number: GWC-NF-02-LED-E1-T3-GM

Product Family *	Light Engine	Number of Light Squares	Lamp Type	Voltage	Distribution	Color	Mounting Options
GWC=Galleon Wall	AF=1A Drive Current	01=1 02=2	LED=Solid State Light Emitting Diodes	61=120-277V 347=347V * 480=480V * 2	T2=Type II T3=Type III T4FT=Type IV Forward Throw T4W=Type IV Wide SL2=Type II w/Uplit Control SL3=Type III w/Uplit Control SL4=Type IV w/Uplit Control SLA=Asymmetric Uplight Concentrator Left SLR=90° Uplit Light Concentrator Right RW=Rectangular Wide Type I SNG=Type V Square Narrow SMG=Type V Square Medium SWG=Type V Square Wide	AP=Architectural Bronze DP=Dark Platinum GM=Graphite Metallic MP=Medium Platinum WH=White CC=Custom Color	XH18=Arm, Knuckle, Mounting Plate

Options (Add as Suffix)

7022=7.0 CRI / 2700K *	Accessories (Ordered Separately)
7030=70 CRI / 3000K *	CA 8161EB=Premium Electrical Cap **
7040=70 CRI / 4000K *	CA 8161HS=Premium Electrical Cap for Top Hub 208V **
7050=70 CRI / 5000K *	CA 8161PE=Premium Electrical Cap **
7060=70 CRI / 6000K *	CA 8161ZT=Premium Electrical Cap **
8030=80 CRI / 3000K *	MA 8=Replacement Module Replacement
8040=80 CRI / 4000K *	NAA=Non-Standard Branch Base Color (Must Specify Color)
FA=Single Fused (120, 277 or 347V. Must Specify Voltage)	PSIR=Programmable Configuration Tool for Occupancy Sensor **
FB=Double Fused (208, 240 or 480V. Must Specify Voltage)	RA=Reflector Assembly Loaded in Side Shield **
HA=-40°C High Ambient **	SCE-7P-16A=Wavelinx Outdoor Control Module (7-pin) **
UPL=Uplight Housing **	SWPDEX=Wavelinx Wireless Sensor, 7' - 15' Mounting Height **
BBB=Battery Pack with Back Box **	SWPDSX=Wavelinx Wireless Sensor, 15' - 40' Mounting Height **
BWB=Cold Weather Battery Pack with Back Box **	
EM=Emergency Battery Pack Only (-20°C, 3 Hour Minimum) **	
ETL=ETL Retrofit Housing Fixture Recognition **	
NDS=NEMA 7 Pin Receptacle, Shorting Cap **	
PER=Single Twist-Lock Photocontrol Receptacle **	
PER7=Single NEMA 7 Pin Photocontrol Receptacle **	
AHD=After Hours Dim, 7 Hours **	
AHD6=After Hours Dim, 6 Hours **	
HS=Extended Shield (Specify Color) **	
SCE-LP=Premium 2nd Generation Wireless Control **	
SES=Shorting Cap for Motion Sensor Dimming Operation **	
LWR-LW=Lumawatt Wireless Sensor, Wide Lens field 8 - 16' Mounting Height **	
LWR-LN=Lumawatt Wireless Sensor, Narrow Lens for 16' - 40' Mounting Height **	
L90=Optics Rotated 90° Left	
R90=Optics Rotated 180° Right	
RT=Factory Installed Mesh Top	
LCR=Light Square Trim Plate Painted to Match Housing **	
HSS=Factory Installed House Side Shield **	
CE=CE Marking and Board Terminal Block **	
ZW=Wiring Harness 4-PIN Twistlock Receptacle **	
ZW-SWPDEX=Wavelinx Wireless Sensor, 7' - 15' Mounting Height **	
ZW-SWPDSX=Wavelinx Wireless Sensor, 15' - 40' Mounting Height **	

NOTES:
1. DesignLights Consortium® Qualified. Refer to www.designlights.org Qualified Products List under Family Models for details.
2. Standard 4000K CCT and minimum 70 CRI.
3. Two light squares with BRW or UWH options, limited to 347V, 120-277V only. Not available in combination with sensor options at 1200mA.
4. Requires the use of a step down transformer. Not available in combination with sensor options at 1200mA.
5. Not available with 480V. Not available with SCE, SCE-LP, nor any wireless/networked systems. Not available on models with fusing. Not available with Single Fuse (SF), Double Fuse (DF), Dual Fusing (DFDU) or Three Phase Fusing (TF).