



- Notes:**
- 1)- Face of Sonny's-PS 4" from curb edge.
 - 2)- Face of Gate 18" from curb edge.
 - 3)- RFID should be 12" from curb edge.
 - 4)- Curb should be 6" in height.
 - 5)- Curb should have bollards (ø4"X36" A.F.F.) at both ends to protect hardware.
 - 6)- Sonny's-PS and gate should be no less than 9' and should not exceed 10'.
 - 7)- Lanes between curbs should be no less than 9' (recommended) and should not exceed 12'.
 - 8)- Loops provided by CarWash Controls Installation by G.C.

NOT FOR CONSTRUCTION UNTIL APPROVED BELOW.

APPROVED BY: _____ DATE _____

DISCLAIMER
 ALTHOUGH BUILDING CODES HAVE BEEN CONSIDERED IN DEVELOPING THIS DRAWING, VERIFICATION OF SITE SPECIFIC CONDITIONS AND COMPLIANCE WITH FEDERAL, STATE AND LOCAL BUILDING CODES IS THE EXCLUSIVE RESPONSIBILITY OF THE CUSTOMER AND/OR ARCHITECT AND ENGINEER. THESE DRAWINGS REFLECT REQUIREMENTS FOR SONNY'S FURNISHED EQUIPMENT ONLY UNLESS OTHERWISE NOTED. PLEASE REFER TO OTHER MANUFACTURERS, IF ANY, FOR THEIR EQUIPMENT REQUIREMENTS.

CONFIDENTIAL WARNING:
 THIS SHEET CONTAINS AND CONSTITUTES CONFIDENTIAL INFORMATION, IMAGES AND TRADE SECRETS OF SONNY'S ENTERPRISES INC. ANY UNAUTHORIZED USE OR DISCLOSURE OF ANY OR PORTION THEREOF, IS STRICTLY PROHIBITED. THIS WORK IS THE EXCLUSIVE PROPERTY OF SONNY'S ENTERPRISES INC. ALL RIGHTS RESERVED.

19581-D9-CALIBER LAKE WALES

SCALE: N.T.S. LOCATION: -FL-

Sheet	Rev.
11.1	--

http://www.SonnysDirect.com

© 2020 SONNY'S ENTERPRISES, INC. 5605 Hiatus Road, Tamarac, FL 33321 USA. TEL. 800-327-8723

POS CONFIGURATION; GC SCHEMATIC

DATE: 09.25.19
 REVISION DATE: 03.06.20
 CREATED BY: LV
 REVISED BY: FAO
 CHECKED BY: Luis V.