



EROSION CONTROL LEGEND

TEMPORARY SILT FENCE TEMPORARY DOUBLE SILT FENCE SAW CUT LINE -9-0-9-9-0-0-

EROSION AND SEDIMENT CONTROL NOTES

- (14) DAYS AFTER WORK HAS CEASED, EXCEPT AS STATED BELOW:

ALL PERIMETER DIKES, SWALES, DITCHES, PERIMETER SLOPES AND ALL SLOPES STEEPER THAN 3 HORIZONTAL T ALL PERINE ER DIRCS, SWALES, UTTCHES, PERINE IES SLOPES AND AS SUPEZ SEPEZER I HAM 3 HOULKUIN VERTICAL (31-3) BALL BE PROVIDED TEMPORARY OR PERMANENT STABILIZATION WITH RORUND COVER SOON AS PRACTICABLE BUT IN ANY EVENT WITHIN 7 CALENDAR DAYS FROM THE LAST LAND-DISTURBING CATTUTY, ALL DIFFER DETSINBERO AREAS SHALL BE PROVIDED TEMPORARY OR REPRINANENT STABLES WITH GROUND COVER AS SOON AS PRACTICABLE BUT IN ANY EVENT WITHIN 24 CALENDAR DAYS FROM TH

- ALL CUT AND FILL SLOPES AND CHANNEL SIDE SLOPES WHICH ARE NOT TO BE PAVED SHALL BE SEEDED UNTR. A GOOD STAND OF GRASS IS OBTAINED IN ACCORDANCE WITH THE SEEDING SCHEDULE ON SHEET CS.S. ALL SEEDING WILL BE MILLCHED.

- ALL EROSION CONTROL DEVICES SHALL BE PROPERLY MAINTAINED DURING ALL PHASES OF CONSTRUCTION LIVTH THE COMPLETION OF ALL CONSTRUCTION ACTIVITIES AND ALL DISTURBED AREAS HAVE BEEN STABLIZED. ADDITIONAL CONTROL DEVICES MAY BE REQUIRED DURING CONSTRUCTION IN ORDER TO CONTROL ERISION AND/DIO OFFSTE SEDIMENTATION. ALL TEMPORARY CONTROL DEVICES SHALL BE REMOVED ONCE CONSTRUCTION COMPLETE AND THE STIES STABLIZED.
- THE CONTRACTOR MUST TAKE NECESSARY ACTION TO MINIMIZE THE TRACKING OF MUD ONTO PAVED ROADWAY FROM CONSTRUCTION BARES AND THE GENERATION OF DUST. THE CONTRACTOR SHALL DAILY REMOVE MUD/SOIL ROAD MANWENT, AS MAY BE REQUIRED.

- 12. SLOPES SHALL BE GRADED NO STEEPER THAN 2:1. FILL SLOPES GREATER THAN 10' REQUIRE ADEQUATE TERRACING
- GRADING MORE THAN ONE ACRE WITHOUT AN APPROVED EROSION CONTROL CITY/COUNTY EROSION CONTROL ORDINANCE AND IS SUBJECT TO A FINE.
- 17. A PREWORK MEETING SHALL BE SCHEDULED WITH THE CITY INSPECTOR PRIOR TO CONSTRUCTION

CONTACT NORTH CARDLINA ONE CALL SERVICE @ 811 OR 800-632-4949 AND CITY CONCORD, A
MINIMUM OF 72 HOURS BEFORE DIGGING.

SITE

- NO BMPS SHALL BE PLACED ON ADJACENT PROPERTY WITHOUT THE WRITTEN CONSENT OF THE PROPERTY OWNER AND THE CITY OF CHARLOTTE.
- THE NCDENR EROSION CONTROL MANUAL AND CITY OF CONCORD STANDARDS SHALL BE USED AS A GUIDELINE FOR IMPLEMENTATION AND MAINTENANCE OF BMPS, THE FOLLOWING BMPS
- SURFACE ROUGHENING
 STABILIZED CONSTRUCTION ENTRANCE
- SILT FENCE HARDWARE FABRIC AND STONE INLET PROTECTION

DO NOT DISPOSE OF CONCRETE TRUCK WASHOUT WASTE BY DUMPING INTO A SANITARY SEWER, STORM DRAIN OR ONTO SOIL OR PAVEMENT THAT CARRIES STORM WATER RUNOFF

- ALL CHEMICAL SPILLS, OR. SPILLS, OR FISH KILLS MUST BE REPORTED TO NCDENR CALL THE 24-HOUR EMERGENCY RESPONSE LINE AT 1-800-858-9568.
- FINAL GRADES FOR GRASSED AND LANDSCAPED AREAS SHALL REQUIRE A MINIMUM OF 4-6" OF CLEAN TOP SOIL, FREE OF DEBRIS AND CONTAMINANTS, AND PREFERABLY OF NATIVE ORIGIN,
- SIGHT TRIANGLES SHOWN ARE THE MINIMUM REQUIRED.

- SUBSURFACE DRAINAGE FACILITIES MAY BE REQUIRED IN THE STREET RIGHT-OF-WAY IF DEEMED NECESSARY BY THE



POPEYE' CONCORD F

MODIFICATION LOG

JOB NUMBER:	C200030
CHECKED BY:	CM.
DRAWN BY:	CDA
DATE:	8-19-2020

AMERICAN COMPANY COMPA

EIBW # C-3884

DEMOLITION AND EROSION AND **SEDIMENT** CONTROL PLAN PH1

C4.1