

1 E400 DETAIL – TYPICAL LAY-IN FIXTURE INSTALLATION

Not To Scale



2 E400 DETAIL – TYPICAL DUPLEX RECEPTACLE INSTALLATION

NOT TO SCALE



3 E400 DETAIL – OCCUPANCY SENSOR CONTROL

NOT TO SCALE



4 E400 TYPICAL LOCATION OF SWITCHES/ ALARMS/THERMOSTATS/OUTLETS

NO SCALE

NOTES:

1. SEE ELECTRICAL DRAWINGS FOR SPECIAL CONDITIONS (IE. RECEPTACLES ABOVE COUNTERS, ETC.)
2. ALL THERMOSTATS, SWITCHES, STROBES, HORNS AND OTHER DEVICES SHALL BE INSTALLED IN A NEAT AND ORDERLY FASHION, WITH EACH ITEM BEING PLUMB AND SQUARE.
3. FOR STROBES, HORNS, ETC. NOT ADJACENT TO DOORS, ALIGN VERTICALLY AS DIRECTED BY ARCHITECT.
4. DIMENSIONS SHOWN ARE TO FACE PLATES UNLESS NOTED OTHERWISE.



5 E400 DETAIL – GROUND BAR

NOT TO SCALE

PANELBOARD:	EX. PANEL P					GROUND BUS				SC RATING:	22 KAMPS RMS SYMM.		
SERVICE:	208Y/120V 3PH 4W									MOUNTING:	SURFACE		
MAINS:	225 AMP MLO					TYPE: BRANCH				ENCLOSURE:	NEMA 1		
LOAD DESCRIPTION	WIRE	BKR	CKT	MOUT	CONNECTED LOAD (KVA) A	B	C	CKT	BKR	WIRE	LOAD DESCRIPTION
EX. PUMP 1.5HP	EX	20/3	1A		0.8			2A	20/1	EX	EXISTING CIRCUIT
	EX	/	3B		1.0	0.8		4B	20/1	EX	EXISTING CIRCUIT
	EX	/	5C			1.0	0.8	6C	20/1		SPARE
EX. CKT.	EX	20/1	7A		1.0		0.0	8A	110/3	2	PANEL HP
EX. CKT.	EX	20/1	9B		0.0	1.0		10B	/	2	VIA KFMR THP
EX. CKT.	EX	20/1	11C		0.0		1.0	12C	/	2	
EX. REC. CKT.	EX	20/1	13A		0.9	7.0		14A	20/1	EX	EXISTING CIRCUIT
EX. REC. CKT.	EX	20/1	15B		0.0	0.9		16B	30/2	EX	EX. WATER HEATER
EX. REC. CKT.	EX	20/1	17C			2.3	0.9	18C	/	EX	
EX. REC. CKT.	EX	20/1	19A		0.9		2.3	20A	20/3	EX	EX AHU 1.5HP
EX. REC. CKT.	EX	20/1	21B		0.0	0.9		22B	/	EX	
EX. REC. CKT.	EX	20/1	23C			0.8	0.9	24C	/	EX	
EX. REC. CKT.	EX	20/1	25A		0.8		0.8	26A	20/3	EX	EX AHU 3HP
EX. REC. CKT.	EX	20/1	27B		1.3	0.9		28B	/	EX	
EX. LTG. CKT.	EX	20/1	29C			1.3	1.0	30C	/	EX	
EX. LTG. CKT.	EX	20/1	31A		1.0		1.3	32A	20/3	EX	EX AHU 3HP
EX. LTG. CKT.	EX	20/1	33B		1.3	1.0		34B	/	EX	
EX. LTG. CKT.	EX	20/1	35C			1.3	1.0	36C	/	EX	
EX. LTG. CKT.	EX	20/1	37A		1.0		1.3	38A	40/3	EX	EX. AHU 5HP
EX. LTG. CKT.	EX	20/1	39B		2.0	1.0		40B	/	EX	
EX. CONTROLS CKT.	EX	20/1	41C			2.0	0.5	42C	/	EX	
					0.0	19.8	22.3				

NOTES:		
	LIGHTS	8.0 KVA
	RECEPTS	7.2 KVA
	MOTORS	39.4 KVA
	HEAT	4.3 KVA
	KITCHEN	0.0 KVA
	EMPTR	0.0 KVA
	OTHER	5.3 KVA
	TOTAL	62.8 KVA

PANELBOARD:	HP					GROUND BUS				SC RATING:	14 KAMPS RMS SYMM.		
SERVICE:	480Y/277V, 3PH, 4W									MOUNTING:	SURFACE		
MAINS:	45 AMP MCB					TYPE: BRANCH				ENCLOSURE:	NEMA 1		
LOAD DESCRIPTION	WIRE	BKR	CKT	MOUT	CONNECTED LOAD (KVA) A	B	C	CKT	BKR	WIRE	LOAD DESCRIPTION
DATAIRE INDOOR	8	40/3	1A		6.4			2A	15/3	12	DATAIRE OUTDOOR
UNIT	8	/	3B		0.6	6.4		4B	/	12	UNIT
	8	/	5C			0.8	6.4	6C	/	12	
SPACE ONLY		/	7A		0.0		0.5	8A	/		SPACE ONLY
		/	9B		0.0	0.0		10B	/		
		/	11C			0.0	0.0	12C	/		
		/							/		
		/							/		
		/					