

Order Plans @ WWW.LDILLING.COM

PLUMBING FIXTURE SCHEDULE

MARK	DESCRIPTION	FIXTURE		TRIM		FLUSH / FLOW (GPM)	FIXTURE COMMENTS
		MANUFACTURER	MODEL	MANUFACTURER	MODEL		
WC-1	WATER CLOSET	AMERICAN STANDARD	3451.001	SLOAN	111-1.28	1.28 GPF	FLOOR MOUNTED, 15" HIGH, ELONGATED, 1-1/2" TOP SPUD, VITREOUS CHINA, MANUAL FLUSH VALVE, 1.28 GPF. CENTOCO NO. 1500STSCSS OPEN FRONT SEAT LESS COVER, STAINLESS STEEL CHECK HINGE.
WC-2	WATER CLOSET ADA	AMERICAN STANDARD	3461.001	SLOAN	111-1.28	1.28 GPF	FLOOR MOUNTED, 16-1/2" HIGH, ELONGATED, 1-1/2" TOP SPUD, VITREOUS CHINA, MANUAL FLUSH VALVE, 1.28 GPF. CENTOCO NO. 1500STSCSS OPEN FRONT SEAT LESS COVER, STAINLESS STEEL CHECK HINGE.
UR-1	URINAL (ACCESSIBLE)	AMERICAN STANDARD	6590.001	SLOAN	186-0.5	0.5 GPF	WALL HUNG VITREOUS CHINA, WASHOUT FLUSH ACTION WITH INTEGRAL FLUSHING RIM, INTEGRAL TRAP, AND 2" FEMALE FLANGED OUTLET CONNECTION. MANUAL FLUSH VALVE. 0.5 GPF. REFER TO ARCHITECTS PLANS FOR ADA LOCATIONS AND MOUNTING HEIGHTS.
L-1	RECTANGULAR LAVATORY	AMERICAN STANDARD	0614.000	CHICAGO FAUCETS	3500-E2805AB CP	0.5 GPM	UNDERMOUNT, VITREOUS CHINA, UNGLAZED RIM, CHROME FAUCET, PRESSURE COMPENSATING NON-AERATING LAMINAR SPRAY, 0.25 GAL/CYCLE MAX., METERING PUSH HANDLE, ACTUATOR ASSEMBLY, METERING CARTRIDGE, PROVIDE ASSE 1070 MIXING VALVE SET TO 110° F. WATTS LFUSG-B MIXING VALVE SHALL BE HARD PIPED TO STOPS. FLEXIBLE CONNECTIONS MAY BE USED FROM MIXING VALVE TO FAUCET. PROVIDE CHROME STOPS, SUPPLIES, TRAP, ETC., TO MAKE A COMPLETE INSTALLATION.
L-2	LAVATORY (ACCESSIBLE)	AMERICAN STANDARD	0356.421	CHICAGO FAUCETS	3500-E2805AB CP	0.5 GPM	WALL HUNG VITREOUS CHINA, SINGLE HOLE LAVATORY FOR CONCEALED ARM SUPPORT CHROME FAUCET, PRESSURE COMPENSATING NON-AERATING LAMINAR SPRAY, 0.25 GAL/CYCLE MAX., METERING PUSH HANDLE, ACTUATOR ASSEMBLY, METERING CARTRIDGE, CONCEALED ARM HANGER TO BE WATTS WCA-411. PROVIDE ASSE 1070 MIXING VALVE SET TO 110° F. WATTS LFUSG-B MIXING VALVE SHALL BE HARD PIPED TO STOPS. FLEXIBLE CONNECTIONS MAY BE USED FROM MIXING VALVE TO FAUCET. PROVIDE PRE-CUT TRUBRO LAV SHIELD TO COVER SINK, TRAP AND MIXING VALVE. PROVIDE CHROME STOPS, SUPPLIES, TRAP, ETC., TO MAKE A COMPLETE INSTALLATION.
SH-1	SHOWER (ACCESSIBLE)	SYMMONS	C-96-500-B30-V-X	MUSTEE	3739M	2 GPM	PRESSURE-BALANCED MIXING VALVE WITH SINGLE LEVER HANDLE, INTEGRAL SERVICE STOPS, ADJUSTABLE STOP SCREW TO LIMIT HANDLE TURN, 1/2" LEVER VALVE, SHOWER HEAD, WALL/HAND SHOWER WITH FLEXIBLE METAL HOSE, IN-LINE VACUUM BREAKER, 30" SLIDE BAR. PROVIDE WITH PULL DOWN SHOWER SEAT, STAINLESS STEEL TRAP BARS. PROVIDE TRAP, ETC., TO MAKE A COMPLETE INSTALLATION. PROVIDE FIBERGLASS, SURFACE TO BE SLIP-RESISTANT. SIZE: 37" X 39". SHOULDER WILL BE NOT LESS THAN 3" HIGH OR LESS THAN 1 1/2" WIDE. 1" HIGH TILING FLANGE, 1/2" HIGH THRESHOLD, 2" MOLDED-IN DRAIN AND DRAIN SEAL, REMOVABLE STRAINER. COLOR WHITE.
S-1	UNDERMOUNT SINK	ELKAY	DCFU31189	ELKAY	LKD2439BHC	1.5 GPM	DAYTON STAINLESS STEEL 23-1/2" x 18-1/4" x 9" DEEP. PROVIDE WITH LK35 STRAINER BASKET. CHROME FAUCET, 8" CENTERSET CONCEALED DECK MOUNT FAUCET WITH ARC SPOUT AND 4" LEVER HANDLE. CHROME PLATED BRASS WITH A QUARTER TURN CERAMIC DISC VALVE. PROVIDE STOPS, SUPPLIES, OFF SET DRAIN, TRAP, ETC., TO MAKE A COMPLETE INSTALLATION.
S-2	UNDERMOUNT SINK	ELKAY	DCFU2115	ELKAY	LKD2439BHC	1.5 GPM	DAYTON STAINLESS STEEL 23-1/2" x 18-1/4" x 8" DEEP. PROVIDE WITH LK35 STRAINER BASKET. CHROME FAUCET, 8" CENTERSET CONCEALED DECK MOUNT FAUCET WITH ARC SPOUT AND 4" LEVER HANDLE. CHROME PLATED BRASS WITH A QUARTER TURN CERAMIC DISC VALVE. PROVIDE STOPS, SUPPLIES, OFF SET DRAIN, TRAP, ETC., TO MAKE A COMPLETE INSTALLATION.
MS-1	MOP SINK	FIAT	TSBC1610	FIAT	830-AA	2.5 GPM	FLOOR MOUNTED PRECAST TERRAZO WITH STAINLESS STEEL CAP, 24"x24"x12". DRAIN BODY SHALL BE STAINLESS STEEL CAST INTEGRAL, AND SHALL PROVIDE FOR A CAULKED LEAD CONNECTION AND NOT LESS THAN 1" DEEP TO A 3" PIPE. PROVIDE WITH HOSE AND HOSE HOOK AND MOP BRACKET, 1/2" CW, 1/2" HW, 3" SAN.
EWC-1	ELECTRIC WATER COOLER (TWO-LEVEL)	ELKAY	LZSTL8W5	N/A		8.0 GPH	WALL MOUNTED, PUSH BARS ON THE FRONT AND BOTH SIDES, STAINLESS STEEL BASINS, 120V. MOUNT PER MANUFACTURE TO MEET ADA CODE REQUIREMENTS. PROVIDE FLOOR CARRIER STOP, SUPPLY TRAP, ETC., TO MAKE COMPLETE INSTALLATION.
ICE-1	ICE MAKER SUPPLY BOX	GUY GREY	MIB1HA	N/A	N/A		4"x5" RECESSED SUPPLY BOX WITH WALL FLANGE MANUFACTURED FROM 18 GAUGE STEEL WITH WHITE POWDER COAT FINISH. FURNISH WITH 1/2"x1/4" COMPRESSION ANGLE VALVE AND CODE APPROVED BACKWATER VALVE.
FD-1	FLOOR DRAIN	ZURN	Z415B-P				EPOXY COATED CAST IRON BODY WITH ANCHOR FLANGE, WEEPHOLES, ADJUSTABLE LIGHT DUTY POLISHED NICKEL BRONZE ROUND STRAINER, NO-HUB OUTLET AND TRAP PRIMER CONNECTION.
FD-2	FLOOR DRAIN	ZURN	Z415B				EPOXY COATED CAST IRON BODY WITH ANCHOR FLANGE, WEEPHOLES, ADJUSTABLE LIGHT DUTY POLISHED NICKEL BRONZE ROUND STRAINER, NO-HUB OUTLET PROVIDE WITH TRAP GUARD DEVICE - PROSET TG-33-P, 3" INSERT FITS INSIDE 3" PVC PIPE.
FD-3	RECESSED FLOOR DRAIN	ZURN	Z115I				RECESSED FLOOR DRAIN EPOXY COATED CAST IRON BODY WITH ANCHOR FLANGE, WEEPHOLES, ADJUSTABLE LIGHT DUTY POLISHED NICKEL BRONZE ROUND STRAINER, NO-HUB OUTLET. 12 x 12 ACID RESISTANCE ENAMEL FLOOR SINK WITH 3" OUTLET CONNECTION.
FS-1	FLOOR SINK	ZURN	Z-1901				TEE KEY, BRASS CONSTRUCTION, POLISHED CHROME PLATE WITH MODEL 34 HF VACUUM BREAKER.
HB-1	HOSE BIB	WOODFORD	24P-3/4				WALL MOUNTED IN BRASS BOX WITH LOCKING COVER, REMOVABLE TEE KEY, BRASS CONSTRUCTION, CHROME PLATED WITH MODEL 34HA-CH VACUUM BREAKER.
HB-2	HOSE BIB	WOODFORD	B65				11"x9" RECESSED SUPPLY BOX WITH WALL FLANGE MANUFACTURED FROM 18 GAUGE STEEL WITH WHITE POWDER COAT FINISH. FURNISH WITH SUPPLY VALVES AND 2" DRAIN OUTLET.
WB-1	WASHING MACHINE SUPPLY AND DRAIN BOX	GUY GREY	MWB19	N/A	N/A	N/A	EPOXY COATED CAST IRON ROOF DRAIN WITH FLASHING CLAMP WITH INTEGRAL GRAVEL STOP, PROVIDE WITH SUMP RECEIVER AND DUCTILE IRON LOW DOME AND NO HUB OUTLET.
RD-1	ROOF DRAIN	WATTS	RD-100-B-K40				EPOXY COATED CAST IRON ROOF DRAIN WITH FLASHING CLAMP WITH INTEGRAL GRAVEL STOP, PROVIDE WITH SUMP RECEIVER, DUCTILE IRON LOW DOME AND NO HUB OUTLET AND 2" EXTERNAL WATER DAM.
RD-2	ROOF DRAIN	WATTS	RD-100-B-K40-R				EPOXY COATED CAST IRON ROOF DRAIN WITH FLASHING CLAMP WITH INTEGRAL GRAVEL STOP, PROVIDE WITH SUMP RECEIVER, DUCTILE IRON LOW DOME AND NO HUB OUTLET AND 2" EXTERNAL WATER DAM.
DSN-1	DOWNSPOUT NOZZLE	WATTS	RD-940				CAST NICKEL BRONZE DOWNSPOUT NOZZLE WITH ANCHOR FLANGE, COUNTERSUNK MOUNTING HOLES, NO HUB CONNECTION.

ELECTRIC WATER HEATER SCHEDULE

MARK	KW	RECOVERY @ 60°F	STORAGE TANK (GAL)	STORAGE TEMPERATURE	TANK DIA	TANK HEIGHT	OPERATING WEIGHT	ELECTRICAL			MANUFACTURER	MODEL
								VOLTS	PHASE	HERTZ		
EWH-1	9		52	140	20-1/2"	54-7/8"	550	208	1	60	AO SMITH	DEN-52

PLUMBING PUMP SCHEDULE

MARK	LOCATION	MANUFACTURE	MODEL	GPM	RPM	HEAD (FT)	VOLTS	PHASE	DESCRIPTION
CP-1	JANITOR 129	TACO	006e3	11	1440-3720	13	120	1	ECM HIGH-EFFICIENCY HOT WATER CIRCULATING PUMP, PROVIDE WITH AQUASTAT AND 24-HOUR TIMER.


VOLT AIR
 THESE HAS BEEN ELECTRICALLY
 BY: BRYAN R. ZEMINA, P.E.
 COPIES OF THIS DOCUMENT ARE NOT
 VALID UNLESS SIGNED AND SEALED BY
 THE ENGINEER.
 6005 Benjamin Road, Suite A
 Tampa, Florida 33634
 Tel: 888.881.8713
 www.voltaair.com
 Project # 11-1804
 COA # 27158
 Engineer of Record:
 BRYAN R. ZEMINA, P.E. #7898

FLEISCHMAN
 ARCHITECTS
 3515 HUNTERS VILLAGE RD.
 SUITE 100
 TAMPA, FL 33647
 PHONE: (727) 725-1000
 FAX: (727) 725-1000
 www.fleischmanarch.com

**HILLSBOROUGH COUNTY
 NEW TAMPA PERFORMING ARTS
 CENTER**
 8550 HUNTERS VILLAGE RD.
 TAMPA FL, 33647

THIS DESIGN AND DRAWING IS THE SOLE
 PROPERTY OF FLEISCHMANGARCIA. NO
 PART OF THIS WORK MAY BE
 REPRODUCED WITHOUT PRIOR WRITTEN
 PERMISSION FROM FLEISCHMANGARCIA.

CERTIFY TO THE BEST OF MY
 KNOWLEDGE THAT THESE DRAWINGS
 COMPLY WITH ALL RELEVANT BUILDING
 CODES



PERMIT SET
 05/06/2020
 FGA PROJECT NUMBER
 19048

ISSUE DATE
 04-15-2020

NO	DATE	NOTES

SHEET NAME
 SCHEDULES -
 PLUMBING

SHEET NUMBER
P0.1