RTC.

Firestone Complete auto Care

THIS DRAWING IS THE PROPERTY IS NOT TO BE USED BY THE ACCEPTANCE OF THIS DRAWING DAYS IN STATE DAYS

STORE

NEW FCAC STORE
2020 I
283 DAWSONVILLE HIGHWAY SW
GAINESVILLE, GA 30501

ISSUE BLOCK 07/20/20 REV #1 2 10/02/20 REV #2 10/16/20 REV #4 11/13/20 IFC

PROPERTY NO. DIGIT NO.: 908074 DIGIT NO.:

AOR PROJECT NUMBER: 1955B55 TO PERMIT: DATE: 04/08/20 TO BID: DATE: #####

SHEET TITLE:

XSP Series Mount Laminaire featuring Cree TrueWhite" Technology PRI DESIMENTAL PER NA PROSOCIO

Name of professional times between a safety metric.

Assumpticed in the U.S.A. of E.U.S. and imported parts. ERI Minimum St. CE. (2009), 4020 S. S. SKRK), *C. CE (BIRKS).

Eighted Warranty". If years on unattack this years on Construct Scales and Bright

284, 200 × -101.05 460 H -101.05 460 K 460 H -101.05 460 K 500 H -101.05 500 K 500 K

CREE & (U) us (II) (II)

CREE ⊕ LIGHTING

XSPW** LED Wall Mount Luminaire

Product Specifications

unanteres e con mercen pulmentanten ante tribet gang 1- Sates, une must ring angle geng 1- Bases Lumingko mosting bas disastraping peng 1- Bases Lumingko pas arsa ba disastraping ar a wait zera curtapa sosad

XSP Series

Product Description

Name to be for a count deliver a City out a Assemblies in the U.S.A. of U.S. and imported pure.

CEN Minimum 77 ERI PROBE & SERVE & STERRE MICH. (BORDE) Limited Warrantp's following confidential state

Leinger Suckage 2015 10/16/6/ - 76 (79) 40% (C) 10% (- 76 (79) 60% (- 76 (79) 90% (- 100) 100 (10)

CREE ♠ LIGHTING

5,446 4,279 8,676 8,676

XSPW** LED Wall Mount Luminaire

6000K #16 Things** India Descript \$15 Hangs** Still Secures
For TH-16-31 Lengths* For This Pink Secures (RIPS Surenys** Install Showness - IRSS Solvense** Fee: Tel-15-11 - Leonaro* - Peer Tel-15-11 81 55 60 81 52 60 31 93 54 88 63 62 8: :06: 9: :05: 9: :05:67 9: :05:67 61 U161 61 U161 61 U161

OSQ Series

Performance Summary

DET. 1000%, ABOOK, 5000M, 5700K

tikitops, Drag Truelifeite® Yestmology an Séidir Lom NamoOptie® Precision Delivery Grid™ spris

Assembled in the U.S.A. of U.S. and imperced purch Initial Delivered Lumens: Up to 29,400.

Weigne: 060-CA 32.4 lbs. [13:75g]; 050-B-AA 78.0 lbs. [14:55g]; 060-t-199-as-lbs. £800-g]; 050-TM, 36-I lbs. [18:45g].

US: specializations (950) 234-8809 Canada: translation conspictors, (890) 473-1204

CREE ♦ LIGHTING

New Control (1987) and the second of the sec

CREE & LIGHTING

05QPH LED Area/Flood Luminaire Issuuring Cree TrueWhite® Technology

| inpus Penins Obsequator | Satacharde | | selex bd ceg | | 980K 50 CS4 | | 3750H 676 688 | |
|----------------------------|--------------------------------|------------------------------|--------------------------------|-------------------------------|-----------------------------|--------------------------------|---------------------------------|--------------------------|
| | instal Epiterned Company | BIAN Europe" Per TM-15-11 | initial Get vened Lumens | BUG Ratings* For ISA-15-11 | jatus Delimens Lumans | BUS Statings* For 156-15-11 | in-Fac Deficieras Lumbras | HLO Reing Day 3No 151 |
| 1 | | es us-sp | 15,600 | 92 id: 62 | 50,088 | 5213463 | 17,159 | to use: |
| Ç. | 21 46% | 80 UEQ) | \$2.797 | 891005 | 17,165 | 80 0440 | 4230 | \$9 Ve og |

CREE ♦ LIGHTING

CSO** LED Area/Flood Luminaire featuring Cree TrueWhite** Technology - Large

Luminaire EPA

4º Square \$ Square ... E Resid

Luminaire EPA

47.64 N Ge et fac

CREE & LIGHTING

CREE ⊕ LIGHTING

CREE ♣ LIGHTING

USG STEP (RESERVED AND STANDARD BOOK 22-12:36

PHOTOMETRIC

PSL₂

CUTSHEETS