


- STANDING SEAM ALUMINUM ROOFING OVER SELF-ADHERING UNDERLAYMENT ON 5/8" PLYWOOD SHEATHING
- R-19 BATT ROOF INSULATION
- PRE-ENGINEERED WOOD TRUSS
- 1/2" EXTERIOR GRADE PLYWOOD ATTIC CLOSURE - SEAL ALL JOINTS
- ALUMINUM GUTTER
- STANDING SEAM MTL. FASCIA PANELS
- JUNCTION BOX W/ STAINLESS STEEL COVER PLATE & 3/4" CONDUIT TO DOOR OPERATOR (FOR ANTENNA CABLE)
- 21'-4" TRUSS BEARING
- COAXIAL ANTENNA FOR DOOR RADIO CONTROL SYSTEM, CENTERED ABOVE EACH DOOR. PROVIDE WOOD BLOCKING AS REQ'D FOR ATTACHMENT OF ANTENNA BASE THROUGH SOFFIT
- FLEXIBLE SELF-ADHERING FLASHING, EXTEND 18" UP BEAM, WALL TOP @ 16" O.C.
- BRICK ARCH
- GALVANIZED STEEL LINTEL ROLLED, PAINT TO MATCH BRICK
- CHAMFER CORNER AT EXPOSED BEAMS W 3/4" QUARTER ROUND MOULDING
- RUB BOTTOM OF CAST ARCHED CONCRETE BEAM SMOOTH AND PAINT
- FOUR FOLD DOOR
- BRICK BEAM
- CONCRETE SLAB POLYURETHANE SEALANT CONC SLAB
- 1/2" THICK FOAM FILLER WITH PRE-SCORED REMOVABLE TOP STRIP.
- DETAIL - 1 1/2" = 1'-0"
- BOLLARD - SEE DETAIL D14/A8.7
- VAPOR BARRIER
- CONCRETE FOUNDATION
- BOLLARD FOUNDATION BEYOND-SEE DETAIL

- STANDING SEAM ALUMINUM ROOFING OVER SELF-ADHERING UNDERLAYMENT ON 5/8" PLYWOOD SHEATHING
- R-19 BATT ROOF INSULATION
- PRE-ENGINEERED WOOD TRUSS
- 1/2" EXTERIOR GRADE PLYWOOD ATTIC CLOSURE - SEAL ALL JOINTS
- ALUMINUM GUTTER
- STANDING SEAM MTL. FASCIA PANELS
- 3'-6" TRUSS EXTENSION TYP.
- TRUSS BEARING
- PRE-FORMED SOFFIT PANELS
- PAINTED 1/8" PLASTER SKIM COAT
- 8" CMU
- FIBERED EMULSION DAMPPROOFING, KARNAC 220AF OR EQUAL AT ALL UNINSULATED WALL CAVITIES
- 5/8" GYPSUM BOARD ON 3 5/8" METAL STUDS @ 16" O.C.
- OVERHEAD COILING DOOR
- PAINTED 1/8" PLASTER SKIM COAT
- BRICK SOLDIER COURSE
- BRICK WALL TIES @ 16" O.C.
- 12" CMU
- BRICK VENEER
- AIR SPACE
- FLEXIBLE FLASHING
- CAVITY DRAINAGE MATERIAL
- WEEP HOLES @ 16" O.C.
- GROUT SOLID
- VAPOR BARRIER
- CONCRETE FOUNDATION

- STANDING SEAM ALUMINUM ROOFING OVER SELF-ADHERING UNDERLAYMENT ON 5/8" PLYWOOD SHEATHING
- R-19 BATT ROOF INSULATION
- PRE-ENGINEERED WOOD TRUSS
- 1/2" EXTERIOR GRADE PLYWOOD ATTIC CLOSURE - SEAL ALL JOINTS
- ALUMINUM GUTTER
- STANDING SEAM MTL. FASCIA PANELS
- 8'-2" TRUSS BEARING
- PRE-FORMED SOFFIT PANELS
- 8" PRECAST FLOOR SLAB W/ 2" OF CONCRETE TOPPING
- 12'-2" TOP OF SLAB
- ACOUSTICAL PANEL CEILING
- 5/8" GYPSUM BOARD ON 1 5/8" MTL STUDS @ 16" O.C.
- ALUMINUM FRAMED WINDOW
- BRICK SOLDIER COURSE
- BRICK WALL TIES @ 16" O.C.
- 8" CMU
- BRICK VENEER
- AIR SPACE
- 1" RIGID INSULATION
- FLEXIBLE FLASHING
- CAVITY DRAINAGE MATERIAL
- WEEP HOLES @ 16" O.C.
- GROUT SOLID
- VAPOR BARRIER
- CONCRETE FOUNDATION



FleischmanGarcia
ARCHITECTS

354 HYDRA PARK AVENUE, SUITE 300
TAMPA, FLORIDA 33609
PHONE (813) 721-1400
FAX (813) 721-2800
REGISTRATION NUMBER AA 0000371

**Pasco County
Fire & Rescue Station
No. 17**

New Port Richey, Florida

THIS PERSON AND DRAWING IS THE SOLE PROPERTY OF FLEISCHMAN-GARCIA ARCHITECTS. NO PART OF THIS WORK MAY BE REPRODUCED WITHOUT THE WRITTEN PERMISSION OF FLEISCHMAN-GARCIA ARCHITECTS.

CHECKED BY: J. GARCIA
DRAWN BY: J. GARCIA
DATE: 05-25-20

FGA PROJECT NUMBER 19039						
ISSUE DATE 05-25-20						
REVISIONS <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 10px; text-align: center;">▲</td> <td style="width: 80%;">DATE: -</td> </tr> <tr> <td style="width: 10px; text-align: center;">▲</td> <td style="width: 80%;">DATE: -</td> </tr> <tr> <td style="width: 10px; text-align: center;">▲</td> <td style="width: 80%;">DATE: -</td> </tr> </table>	▲	DATE: -	▲	DATE: -	▲	DATE: -
▲	DATE: -					
▲	DATE: -					
▲	DATE: -					
SHEET NUMBER A6.2						