

PLUMBING FIXTURE SCHEDULE

MARK	DESCRIPTION	MANUFACTURER	MODEL NO.	BRANCH CONNECTIONS ①		
				WASTE	C.W.	H.W.
WC1	WATER CLOSET - FLOOR MOUNTED, FLUSH VALVE, 1.6 GPF, ELONGATED VITREOUS CHINA, SIPHON JET ACTION, TOP SPUD, BOLT CAPS, ELONGATED BOWL, 17 1/4" HEIGHT. FLUSH VALVE - NON-HOLD-OPEN HANDLE, 1" I.P.S. SCREW DRIVER ANGLE STOP, VACUUM BREAKER FLUSH ACTION, TOP SPUD, SWEAT ADAPTOR, 1.6 GPF, SOLID RING PIPE SUPPORT. SEAT - FINISH WHITE, ANTI-MICROBIAL AGENT, ELONGATED BOWL, OPEN FRONT LESS COVER, SELF SUSTAINING CHECK HINGE, INTEGRAL HANDLE.	AMERICAN STANDARD KOHLER CRANE SLOAN ZURN KOHLER	3043.102 K-4368 3H701 111-YBYC ROYAL ZB000AV-WS1-YK K-4731	3"	1 1/4"	-
UR	URINAL - WALL MOUNTED, ELONGATED BOWL, INTEGRAL TRAP, TOP SPUD, FLUSH VALVE, 1.0 GALLON FLUSH, VITREOUS CHINA, SIPHON JET FLUSH ACTION, 3/4" TOP SPUD, 2" I.P.S. OUTLET CONNECTION, INSTALL WITH RIM AT 17" A.F.F. FLUSH VALVE - VACUUM BREAKER, 3/4" I.P.S. SCREWDRIVER ANGLE STOP, FLUSH CONNECTIONS, ADJUSTABLE TAILPIECE, 3/4" TOP SPUD, 1.0 GALLON FLUSH, HANDLE SHALL MEET ADA REQUIREMENTS. CARRIER - DURA-COATED CAST IRON, STEEL UPRIGHTS, ADJUSTABLE SUPPORT PLATE, HEAVY CAST IRON FEET, MOUNTING FASTENERS, BEARING JACKS.	AMERICAN STANDARD CRANE SLOAN DELANY ZURN ZURN JOSAM J.R. SMITH	6541.132 7309 ROYAL 186-1-YB Z-1221 17800 0636	2"	1"	-
EW	EMERGENCY EYEWASH - WALL MOUNTED, HAND HELD DUAL SPRAY HEADS, ANGLED SPRAY HEAD, POP-OFF PROTECTIVE SPRAY HEAD COVERS, CHROME-PLATED VALVE, EXTENDED REINFORCED HANDLE, 12 FOOT THERMOPLASTIC HOSE, 3/8" I.P.S. MALE THREAD WITH REMOVABLE 1/2" I.P.S. FEMALE REDUCING COUPLING, HOSE HOLDER MOUNTED TO WALL. INSTALL ON WALL, ABOVE SINK. SEE FL. PLAN FOR LOCATION.	HANS BRADLEY GUARDIAN	8905 S19-435EFW G5026	1/2"	-	-
CFF	COOLER FILL FAUCET - WALL MOUNTED, CHROME PLATED BRASS BODY, SINGLE CONTROL, VACUUM BREAKER, 68" FLEXIBLE S.S. HOSE, SPRAY VALVE & HOOK, 3.14 GPM, CERAMIC CARTRIDGE W/ CHECK VALVE, 4-ARM HANDLE, 1/2" NPT FEMALE INLET. INSTALL VALVE HANDLE AT 36" A.F.F. UNLESS OTHERWISE NOTED ON ARCHITECTURAL PLANS.	T&S BRASS CHICAGO	8-0805-CR	1/2"	-	-
PFF	POT/KETTLE FILL FAUCET - WALL MOUNTED, CHROME PLATED BRASS BODY, 8" CENTERS, 18" DOUBLE JOINT SWING NOZZLE W/ HEAT RESISTANT HANDLE, CERAMIC CARTRIDGE W/ CHECK VALVE, 2.2 GPM, LEVER HANDLES, 1/2" NPT FEMALE INLET. INSTALL VALVE AT 50" A.F.F. UNLESS OTHERWISE NOTED ON ARCHITECTURAL PLANS.	T&S BRASS CHICAGO	8-0597-LF20	1/2"	-	-

① BRANCH CONNECTION SIZES ARE INTENDED FOR BRANCH SIZES FROM WATER SUPPLY. REFER TO DESCRIPTION IN SCHEDULE FOR ACTUAL ROUGH IN PIPE SIZE CONNECTION TO FIXTURE.

GAS WATER HEATER SCHEDULE

MARK	MANUFACTURER	MODEL	STORAGE	GPH RECOVERY 70°F RISE	TYPE OF GAS	BTUH	INLET & OUTLET	GAS INLET	THERMAL EFFICIENCY	DIAMETER	HEIGHT
GWH	A.O. SMITH	BTH-199	100 GAL	329 GPH	NATURAL	199,000	1 1/2"	3/4"	95%	27 3/4"	75 1/2"

NOTES:
1. PROVIDE & INSTALL 3" PVC INTAKE & EXHAUST VENT.
2. PROVIDE & INSTALL THERMAL EXPANSION TANK EQUAL TO AMTROL ST-2

ELECTRIC WATER HEATER SCHEDULE

MARK	MANUFACTURER	MODEL	GALLON	V/P/HZ	WATTS	RECOVERY 70°F RISE	DIAMETER	HEIGHT	INLET / OUTLET	LOCATION
WH1	A.O. SMITH	DEL-20	20	208/1/60	4500	25	22"	23"	3/4"	DECON

NOTES:
1. PROVIDE ASME RATED T&P RELIEF VALVE. ROUTE DISCHARGE AS INDICATED ON WATER HEATER DETAIL.
2. PROVIDE EXPANSION TANK EQUAL TO AMTROL MODEL ST-5.
3. REFER TO WATER HEATER DETAIL FOR ADDITIONAL INFORMATION.

FIXTURE CONNECTION SCHEDULE

DESCRIPTION	WASTE	VENT	TRAP
DRINKING FOUNTAIN	2"	1 1/2"	1 1/4"
ELECTRIC WATER COOLER	2"	1 1/2"	1 1/4"
EMERGENCY SHOWER/EYEWASH	2"	1 1/2"	1 1/2"
EMERGENCY EYEWASH	2"	1 1/2"	1 1/2"
FLOOR DRAIN	3"-4"	-	3"-4"
FLOOR SINK	3"-4"	-	3"-4"
LAVATORY	1 1/2"	1 1/4"	-
SINK	1 1/2"	1 1/2"	-
URINAL	2"	1 1/2"	INTEGRAL
WASHING MACHINE FITTING	3"	2"	2"
WATER CLOSET	-	-	INTEGRAL

NOTE: CONNECTION SIZES SHOWN FOR MINIMUM PIPE SIZES ONLY. REFER TO FLOOR PLANS AND/OR RISER DIAGRAMS.

PLUMBING FIXTURE SCHEDULE

MARK	DESCRIPTION	MANUFACTURER	MODEL NO.	BRANCH CONNECTIONS ①		
				WASTE	C.W.	H.W.
SH1	SHOWER VALVE - PRESSURE BALANCING MIXING VALVE, ADJUSTABLE STOP SCREW, IN-LINE VACUUM BREAKER, PROVIDE REVERSE CORING FOR BACK-TO-BACK INSTALLATION WHERE NECESSARY (SEE PLAN). INSTALL VALVE AT 44" ABOVE FLOOR TO CENTERLINE. VACUUM BREAKER, POLISHED CHROME FINISH. HAND-HELD SHOWER - CHROME PLATED, TWO SPRAY PATTERNS (WIDE & CHAMPAGNE), SPEEDCLEAN ANTI-LIME SYSTEM, SWIVEL CONNECTION, 2.5 GPM FLOW RATE, 79" HEAVY DUTY METAL, CHROME PLATED HAND SHOWER HOSE, 40" CHROME PLATED HAND SHOWER BAR, SWIVEL HAND SHOWER HOLDER, ADJUSTABLE HEIGHT & ANGLE FOR HAND SHOWER, HEIGHT ADJUSTABLE CHROME SOAP DISH (MOUNT ON HAND BAR), WALL UNION FOR HAND SHOWER HOSE CONNECTION, 1/2" NPT FEMALE THREAD INLET. SHOWER DRAIN - NEO-LOG PIPE CONNECTION DRAIN, COATED CAST IRON BODY WITH NEOPRENE GASKET, 5" STRAINER, COMBINATION INVERTIBLE MEMBRANE CLAMP AND ADJUSTABLE TYPE 'B' NICKEL BRONZE STRAINER.	SYMMONS POWERS LEONARD HANSGRÖHE: SHOWER VALVE SHOWER BAR HOSE SOAP DISH OULIET ZURN JOSAM J.R. SMITH	66-2 04212000 & 0412118 06497000 28631000 28276000 28678000 27454002 ZN-415 30000-5A 2005 46 NB	2"	3/4"	3/4"
SS1	SERVICE SINK - FLOOR MOUNTED, ONE-PIECE PRE-CAST TERRAZZO, 24" X 24" X 12" SIZE, 12" HIGH ON THREE SIDES & 6" HIGH ON FRONT SIDE, SQUARE MODEL, STAINLESS STEEL RIM GUARD, GRID DRAIN. TRM - SERVICE SINK FAUCET, THREADED SPOUT, POLISHED CHROME, VACUUM BREAKER, FILL HOOK, WALL BRACE, RENEWABLE VALVES, INTEGRAL STOPS. 24" LONG X 3" WIDE, STAINLESS STEEL ATTACHED WITH THREE (3) RUBBER TOOL GRIPS. 30" LONG FLEXIBLE, HEAVY DUTY 5/8" RUBBER HOSE, CLOTH REINFORCED, WITH 3/4" BRASS COUPLING AT ONE END, 5" LONG X 3" WIDE BRACKET, 18 GA. #302 STAINLESS STEEL WITH RUBBER GRIP.	FIAT WILLIAMS FLORESTONE CHICAGO T&S BRASS ZURN FIAT T&S BRASS OR EQUAL FIAT T&S BRASS OR EQUAL	TSB-3000 897-CP B-0667-POL Z841M1 889-CC B-0635 832-AA B-5654	3"	3/4"	3/4"
IMVB	ICE MAKER VALVE BOX - 1/2" O.D. WELD COMBO CONNECTION, 1 1/4" O.D. COMPRESSION OUTLET, 11.63" X 9.50" OVERALL DIMENSION, 18 GA. STEEL BOX, REFER TO MANUFACTURER'S RECOMMENDATIONS FOR ROUGH IN REQUIREMENTS. PROVIDE FLEXIBLE TUBING FROM VALVE TO ICE MAKER. INSTALL 5'-0" A.F.F. DIRECTLY BEHIND REFRIGERATOR.	GUY GREY OR APPROVED EQUAL	BM875	-	1/2"	-
CP	CIRCULATING PUMP - BRONZE CONSTRUCTION, REPLACEABLE STAINLESS STEEL CARTRIDGE IMPELLER ASSEMBLY, VENT PLUG FOR PURGING, EJECTOR PROTECTIVE GASKETS, IMPEDANCE PROTECTED MOTOR. PROVIDE ON/OFF SWITCH FOR OVERLOAD PROTECTION. PROVIDE & INSTALL WITH AQUASTAT, REFER TO WH-1 SPECIFICATION. CAPACITY OF 5 GPM AGAINST A TOTAL HEAD OF 16 FT. 3000 RPM, 80 INPUT WATTS, .70 FULL LOAD AMPS. ELECTRICAL REG.: 115V/1/60	ARMSTRONG BELL & GOSSETT OR EQUAL	ASTRO 50B NSF-22	-	-	-
FD1	FLOOR DRAIN - COATED CAST IRON BODY WITH NEOPRENE GASKET, 5" STRAINER, COMBINATION INVERTIBLE MEMBRANE CLAMP, INTEGRAL 1/2" PRIMER CONNECTION AND ADJUSTABLE NICKEL BRONZE STRAINER WITH VANDAL-PROOF SCREWS. (REFER TO PLANS FOR PIPE SIZES)	ZURN JOSAM J.R. SMITH	415-B 2005-A	-	-	PROVIDE DEEP SEAL TRAPS WHERE TRAP PRIMERS ARE NOT INDICATED.
FD2	FLOOR DRAIN - COATED CAST IRON BODY WITH NEOPRENE GASKET, 5" STRAINER, COMBINATION INVERTIBLE MEMBRANE CLAMP, ADJUSTABLE NICKEL BRONZE STRAINER WITH RAISED FLANGE. NICKEL BRONZE STRAINER (TYPE '1') WITH RAISED FLANGE. (REFER TO PLANS FOR PIPE SIZE)	ZURN JOSAM J.R. SMITH	ZN-415-1 30000-E1 2005-F37	-	-	PROVIDE DEEP SEAL TRAPS WHERE TRAP PRIMERS ARE NOT INDICATED.
IP	TRAP PRIMER - CONNECT TO NEAREST LAVATORY. REFER TO DETAIL #3 ON P5.2	-	-	-	-	REFER TO DETAIL
ETP	ELECTRONIC TRAP PRIMER - FACTORY PROGRAMMED ASSEMBLED, SURFACE MOUNTED HOUSING COVER, LEAK FREE COMPONENTS. REFER TO DETAIL FOR ADDITIONAL INFORMATION & SPECIFICATIONS. OVERALL SIZE: 14.5" X 12" X 3.5".	ZURN P.P.P. J.R. SMITH	Z1020XL-CW	-	1/2"	-
HD1	HUB DRAIN - 7" PANEL, CAST IRON BODY, PLASTIC BALL FLOAT, BRONZE BACK WATER VALVE BUSHING, REPLACEABLE NEOPRENE SEAT, SEE FLOOR PLAN FOR SIZE. INSTALL RIM MAXIMUM 3 INCHES ABOVE FINISHED FLOOR.	ZURN OR EQUAL	Z-325	-	-	REFER TO PLANS FOR SIZES.
CO	CLEANOUT - DURA-COATED CAST IRON FERRULE WITH THREADED BRASS CLEANOUT PLUG, INSTALL CLEARANCE IN 12" X 12" CONCRETE FLUSH WITH GRADE. REFER TO PLANS FOR SIZES.	ZURN JOSAM J.R. SMITH	Z-1440-BP 58500-22 4031-PB	-	-	-
HB1	FLOOR CLEANOUT - ADJUSTABLE FLOOR CLEANOUT, COATED CAST IRON BODY, GAS AND WATERTIGHT ABS TAPERED THREAD PLUG, ROUND SCORRIATED SECURED HEAVY DUTY TOP, ADJUSTABLE TO FINISHED FLOOR. REFER TO PLANS FOR SIZES.	ZURN JOSAM J.R. SMITH	ZN-1440-VP 56000 4231-U	-	-	-
WMB	HOSE BIB - VACUUM BREAKER, BACK FLOW PROTECTED, WALL FAUCET, 3/4" INLET, POLISHED CHROME PLATED, VACUUM BREAKER, LOOSE KEY HANDLE, WALL FLANGE. WASHING MACHINE FITTING - TOP SUPPLIES, 1/2" INLETS, THREADED OUTLETS, QUARTER TURN BRASS BALL VALVES, 2" THREADED DRAIN OUTLET CENTERED, FIRE RATED RECESSED BOX, (2) INTEGRAL WATER HAMMER ARRESTORS. REFER TO SPECIFICATIONS FOR PIPING REQUIREMENTS I.E. COPPER OR CPVC CONNECTIONS. PROVIDE & INSTALL NYLON LINT TRAP POLYPROPYLENE MESH SCREEN & SECURE TO DRAIN OUTLET OF WASHING MACHINE.	CHICAGO T & S BRASS KOHLER GUY GREY OATEY OR EQUAL	387-CP & E27 8737-POL HY2850-F34-PC-LK-UB FR-12 SERIES	-	3/4"	-
WHA	WATER HAMMER ARRESTOR - WROUGHT COPPER SHELL, HYDRO-PNEUMATIC AIR CUSHION, TRIPLE O-RING SEALED PISTON, WROUGHT COPPER ADAPTER AND MALE THREADED CONNECTION. SIZED PER STANDARD P.D.I. - WH201. TYPE A = 'P.D.I.' SIZE A = 1-11 FIX. UNITS, 1/2" CONN. TYPE B = 'P.D.I.' SIZE B = 12-32 FIX. UNITS, 3/4" CONN. TYPE C = 'P.D.I.' SIZE C = 33-60 FIX. UNITS, 1" CONN. TYPE D = 'P.D.I.' SIZE D = 61-113 FIX. UNITS, 1" CONN.	JOSAM SOUX CHIEF ZURN-WILKINS	75000-S SERIES "HYDRA-RESTER" 1250 SERIES	-	-	-

① BRANCH CONNECTION SIZES ARE INTENDED FOR BRANCH SIZES FROM WATER SUPPLY. REFER TO DESCRIPTION IN SCHEDULE FOR ACTUAL ROUGH IN PIPE SIZE CONNECTION TO FIXTURE.

PLUMBING FIXTURE SCHEDULE

MARK	DESCRIPTION	MANUFACTURER	MODEL NO.	BRANCH CONNECTIONS ①			
				WASTE	C.W.	H.W.	
EWCB	ELECTRIC WATER COOLER - DUAL UNIT, SELF-CONTAINED WALL HUNG, REFRIGERANT COOLER & BOTTLE FILLING STATION, HOODED STREAM PROJECTOR, STAINLESS STEEL BASIN, "LIGHT TOUCH" PUSH BAR, BUILT-IN FLOW REGULATOR, FULLY PROTECTED BUBBLER. BOTTLE FILLING STATION - MOUNTED ON HIGH WATER COOLER, SENSOR ACTIVATED, 30 SECOND SHUT-OFF TIMER, GREEN TICKER: COUNTS QUANTITY 16 OZ. BOTTLES FILLED. SUPPLIES - STRAIGHT STOP FITTING WITH LOOSE KEY, POLISHED CHROME PLATED SOLID BRASS CONSTRUCTION, METAL TEE HANDLE, 1/2" NPT INLET & OUTLET, MOUNTING HARDWARE. TRAP - 1 1/4" X 1 1/4" CHROME PLATED, CAST BRASS, ONE PIECE P-TRAP CLEANOUT PLUG, NIPPLE AND CAST BRASS FLANGE, POLISHED CHROME THREADED BOTH ENDS. CARRIER - TOP & BOTTOM PLATES, DURA-COATED RECTANGULAR STEEL UPRIGHTS WITH WELDED FEET, ADJUSTABLE SUPPORT PLATES, MOUNTING FASTENERS. MOUNTING HEIGHT - COOLER SHALL BE INSTALLED WITH THE SPOUT A MAXIMUM OF 34" A.F.F. AND PROVIDE A MIN. OF 27" BETWEEN BOTTOM OF APRON AND FLOOR.	ELKAY HAVIS OASIS CHICAGO MCGUIRE BRASSCRAFT MCGUIRE ZURN ZURN JOSAM J.R. SMITH	LZSLBWSSP 45-LKCP ST15SLKSB SCR39 C 899-117 173-925-B 834	1 1/2"	1/2"	-	
S1	SINK - FLOOR MOUNTED, 16 GA. TYPE 304 STAINLESS STEEL SCULLERY SINK, 27" X 29.75" OVERALL SIZE, 16" X 24" CENTERED BOWL, 8" HIGH FULL LENGTH BACKWASH, S.S. FLAT STRAINER, 1/4" S.S. TAILPIECE, LONG 4" S.S. TUBULAR LEGS, ADJUSTABLE FEET, CENTERED DRAIN HOLE REQUIRED FOR SINGLE HOLE MOUNT. TRIM - SINK FAUCET, 8.2" HIGH GOOSENECK, CHROME PLATED, 1/2" IPS INLET WITH MALE THREAD BY 1/2" BRASS ELBOW, 1/2" HANDLE, W/ LOCKNUT, 1/2" BRASS STRATOR, VANDAL-RESISTANT MOUNTED ON BACK SPLASH PROVIDE & INSTALL THERMOSTATIC MIXING VALVE UNDER SINK. TRAP PEDAL VALVE - FLOOR MOUNT, ROUGH CHROME FINISH, TWO FOOT PEDALS, 1/2" IPS FEMALE INLETS & OUTLETS, STRAINER SHALL PROVIDE ALL PIPING FROM FOOT PLATE VALVE UP TO GOOSENECK FAUCET, FASTER PEDALS TO FLOOR. SUPPLIES - SAME AS S-1. TRAP - SAME AS S-1.	ELKAY JUST OR EQUAL ELKAY JUST OR EQUAL ELKAY JUST OR EQUAL	LK395A LK398A	1 1/2"	1/2"	1/2"	
S2	SINK - COUNTER MOUNTED, DOUBLE COMPARTMENT, STAINLESS STEEL, 18 GAUGE TYPE 304 (18-8) NICKEL BEARING, 33" X 22" OVERALL SIZE, 12 1/8" BOWL DEPTH, FIVE (5) FAUCET HOLES, STAINLESS STEEL STRAINER BASKET, 1 1/2" O.D., STAINLESS STEEL TAILPIECE, 4" LONG. INSTALL SPRAY UNIT ON RIGHT SIDE OF FAUCET. INSTALL C.W. DISPENSER OF LEFT SIDE OF FAUCET. REFER TO COLD WATER DISPENSER DETAIL FOR DISPENSER & FILTER SPECIFICATION	ELKAY	DLR32212-5	-	-	-	
S3	SINK - DECK MOUNTED, POLISHED CHROME PLATED, ADD-ON FAUCET, 4" WRIST HANDLES, 8" WING NOZZLE W/ STREAM REGULATOR, 8" RESER. 24" FLEXIBLE HOSE W/ 1/2" RESISTANT HANDLE, .85 GPM SPRAY VALVE, 1/2" NPT INLET, IN LIEU OF WALL BRACKET FURNISH & INSTALL BI-POD SUPPORT BRACKET. SUPPLIES - SAME AS S-1. TRAP - SAME AS S-1.	T&S BRASS	MPY-BDWN-08-OR & B-0119	1 1/2"	1/2"	1/2"	
L1	LAVATORY - WALL MOUNTED 20 1/2" X 18 1/4" SIZE, VITREOUS CHINA, SINGLE CENTER FAUCET HOLE, SELF-DRAINING DECK, FAUCET LEDGE, FRONT OVERFLOW, CONCEALED ARM SUPPORT, INSTALL WITH 28" CLEAR FROM FLOOR TO UNDERSIDE OF LAVATORY. TRIM - FAUCET, SINGLE CONTROL HANDLE, CHROME PLATED FINISH, SOLID BRASS BODY, LESS POP-UP, 3/8" O.D. COPPER INLET TUBES, 1.5 GPM, INTEGRAL PERFORATED GRID DRAIN, 1 1/4" TAILPIECE. SUPPLIES - ANGLE STOP FITTING WITH SUPPLY TUBE, 1/2" NPT FLEXIBLE FEMALE INLET, LOOSE KEY, ESCUTCHEONS, 3/8" O.D. X 12" FLEX SUPPLY RISER. TRAP - CHROME PLATED CAST BRASS WITH CLEANOUT, 17 GAUGE SEAMLESS TUBULAR WALL BEAND, CAST BRASS SLIP NUTS, RUBBER WASHER, STEEL WALL FLANGE WITH SET SCREW, 1 1/4" O.D., OFFSET GRID DRAIN. CARRIER - DURA-COATED CAST IRON, STEEL UPRIGHTS, CONCEALED ARMS AND SLEEVES, HEAVY CAST IRON FEET, ADJUSTABLE HEADERS, ALIGNMENT TRUSS, MOUNTING FASTENERS, LESS ESCUTCHEONS. P-TRAP AND ANGLE VALVE ASSEMBLIES SHALL BE INSULATED WITH MOLDED SEAMLESS AMBROBOL CLAMP MATERIAL, MINIMUM 3/16" THICKNESS, COLOR WHITE.	AMERICAN STANDARD KOHLER CRANE HANSGRÖHE (NO SUBSTITUTES) CHICAGO MCGUIRE BRASSCRAFT MCGUIRE ZURN ZURN JOSAM J.R. SMITH MCGUIRE TRUEBRO OR EQUAL	0356.421 31711001 1017-CP H2165KC ORC1920A C 8872 28700 ZR-1231 17100 0700 PW 2000 WC	-	1 1/4"	1/2"	1/2"
L2	LAVATORY - UNDER COUNTER MOUNTED, VITREOUS CHINA, ROUND BOWL, SIZE (NOMINAL 17"x14"), 7.5" DEPTH (ADA COMPLIANT), OVERFLOW, CLAMP ASSEMBLY. TRIM - SAME AS L-1. SUPPLIES - SAME AS L-1. TRAP - SAME AS L-1.	KOHLER	K-2210	1 1/4"	1/2"	1/2"	
AD1	AREA DRAIN - 8" PROM-DECK DRAIN, COATED CAST IRON BODY, SQUARE PROMENADE FRAME, HEEL PROOF GRAITE WITH COMBINATION MEMBRANE FLASHING CLAMP GRAVEL GUARD, VANDAL PROOF SECURED TOP, POLISHED BRASS GRAITE, SECONDARY STRAINER, SEDIMENT BUCKET.	ZURN JOSAM J.R. SMITH	ZB-158-VP-S-Y 23730-30-SI 1470-U-PB	-	-	REFER TO PLANS FOR SIZES	

① BRANCH CONNECTION SIZES ARE INTENDED FOR BRANCH SIZES FROM WATER SUPPLY. REFER TO DESCRIPTION IN SCHEDULE FOR ACTUAL ROUGH IN PIPE SIZE CONNECTION TO FIXTURE.

ENGINEERING MATRIX, INC.
CONSULTING ENGINEERS
2880 SCHERER DRIVE, SUITE 640
ST. PETERSBURG, FLORIDA, 33716
(941) 392-4668 FAX (941) 392-4666
EMAIL: enr@matrixinc.com
CERT. OF AUTHORIZATION NO. 4898
© 2019 Engineering Matrix, Inc. DRAWN BY: SCD CHECKED BY: JSW

Fleischman Garcia
REGISTERED PROFESSIONAL ENGINEER
3510 LYNN PARK AVENUE, SUITE 100
TALLAHASSEE, FLORIDA 32310
PHONE (904) 727-8800
FAX (904) 727-8800
REGISTRATION NUMBER: AA 000223

Pasco County Fire & Rescue Station No. 17
New Port Richey, Florida

THIS DESIGN AND DRAWING IS THE PROPERTY OF PASCO COUNTY. IT IS TO BE REPRODUCED WITH THE ORIGINAL DRAWING ONLY. IT IS NOT TO BE REPRODUCED OR COPIED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF PASCO COUNTY.

FGA PROJECT NUMBER
19039

ISSUE DATE
05-25-20

REVISIONS
DATE: _____
DATE: _____
DATE: _____

SHEET NUMBER
P5.1

Johnna Wickham_20191015-0800 FGA CPA Fire Station 17/Plumbing/150800_P5_1_FIXTURE_SCHEDULE.dwg 05/27/20