SEE PANEL SCHEDULE '3H' SHEET E-2.1

## TROUGH SCHEDULE - 'SCWT'

VOLTAGE: 480/277 | PHASE 3 | WIRE: 4
MTG: SURFACE | AIC: 22,000 | NOTES:

| CKT # | CIRCUIT BREAKER SIZE | SIZE | POLE | WIRE SIZE | COND SIZE | DESCRIPTION | LTG | REC | MTR | A/C | HTG | KIT | MISC | PHASE A B C |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 800 | | 3 | SEE | RISER | PANEL '1H' | 7.8 | 0.0 | 2.4 | 0.0 | 95.5 | 0.0 | 140.0 | |
| | - | - | - | | | - | 4.8 | 0.0 | 2.4 | 0.0 | 95.5 | 0.0 | 140.0 | |
| | - | - | - | | | - | 3.3 | 0.0 | 2.4 | 0.0 | 95.5 | 0.0 | 140.0 | |
| 2 | 200 | | 3 | SEE | RISER | DISCONNECT '1T' | 1.5 | 8.5 | 0.0 | 0.0 | 0.0 | 0.0 | 10.5 | |
| | - | - | - | | | - | 2.4 | 6.7 | 0.2 | 0.0 | 1.5 | 0.0 | 5.7 | |
| | - | - | - | | | - | 4.6 | 6.0 | 0.3 | 0.0 | 1.5 | 0.0 | 10.2 | |
| | | | | | | | 23.6 | 21.2 | 7.8 | 0.0 | 289.4 | 0.0 | 446.3 | |

CONNECTED LOAD (KVA): 788.3
DEMAND LOAD (KVA): 788.6
PHASE A 958.3 265.4
PHASE B 935.6 259.2
PHASE C 952.0 263.7
AMPS KVA
CONNECTED LOAD (AMPS): 948.2
DEMAND LOAD (AMPS): 948.6

NOTES:
14X14XL SCREW COVER WIRING TROUGH WITH NSI POLARIS LUGS

## SCWT' DEMAND CALCS

| | | | | | |
|---|---|---|---|---|---|
| LIGHTING | 23.62 | KVA X | 125 % | = | 29.5 KVA |
| RECEPTAC TOTAL | 21.16 | KVA | | | |
| 1ST | 10.00 | KVA X | 100 % | = | 10.0 KVA |
| REMAIN | 11.16 | KVA X | 50 % | = | 5.6 KVA |
| MOTORS | 7.79 | KVA X | 100 % | = | 7.8 KVA |
| A/C | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| HEATING | 289.44 | KVA X | 100 % | = | 289.4 KVA |
| LOCKED-OUT LOAD | ____ | KVA X | 100 % | = | 0.0 KVA |
| KITCHEN | 0.00 | KVA X | 65 % | = | 0.0 KVA |
| MISCELLANEOUS | 446.32 | KVA X | 100 % | = | 446.3 KVA |
| TOTAL | = | 948.6 amps | | = | 788.6 KVA |

## VOLTAGE DROP SCHEDULE

120 VOLT BRANCH CIRCUITS UP TO 8 AMPS

| RUN DISTANCE IN FEET | | | WIRE SIZE AWG |
|---|---|---|---|
| 1' | - | 120' | #12 |
| 121' | - | 190' | #10 |
| 191' | - | 300' | #8 |
| 301' | - | 470' | #6 |

120 VOLT BRANCH CIRCUITS 9 AMPS TO 14 AMPS

| RUN DISTANCE IN FEET | | | WIRE SIZE AWG |
|---|---|---|---|
| 1' | - | 65' | #12 |
| 66' | - | 110' | #10 |
| 111' | - | 170' | #8 |
| 171' | - | 270' | #6 |

277 VOLT BRANCH CIRCUITS UP TO 14 AMPS

| RUN DISTANCE IN FEET | | | WIRE SIZE AWG |
|---|---|---|---|
| 1' | - | 160' | #12 |
| 161' | - | 250' | #10 |
| 251' | - | 390' | #8 |
| 391' | - | 620' | #6 |

WIRE SIZES INDICATED IN PANEL SCHEDULES ARE MINIMUM WIRE SIZES. CONTRACTOR SHALL UPSIZE WIRES BASED ON LOAD AND LENGTH OF RUN AS INDICATED IN SCHEDULE ABOVE.

## SE RATED PANELBOARD SCHEDULE - '1H' GFI

MAIN: 1000A MCB W/FEED THRU LUG | VOLTAGE: 480/277 | PHASE: 3 | WIRE: 4 | MOUNTING: SURFACE | AIC: 22,000 | NOTES: 100% RATED MAIN BREAKER

| CKT # | BKR TRIP | POLE | WIRE SIZE | COND SIZE | DESCRIPTION | LTG | REC | MTR | A/C | HTG | KIT | MISC | PHASE ABC | LTG | REC | MTR | A/C | HTG | KIT | MISC | DESCRIPTION | COND SIZE | WIRE SIZE | POLE | BKR TRIP | CKT # |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 2 |
| 3 | 40 | 3 | 6 | 3/4" | EUH-1 | | | | | 8.3 | | | | | | | | 8.3 | | | EUH-4 | 3/4" | 6 | 3 | 40 | 4 |
| 5 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 6 |
| 7 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 8 |
| 9 | 40 | 3 | 6 | 3/4" | EUH-2 | | | | | 8.3 | | | | | | | | 8.3 | | | EUH-5 | 3/4" | 6 | 3 | 40 | 10 |
| 11 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 12 |
| 13 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 14 |
| 15 | 40 | 3 | 6 | 3/4" | EUH-3 | | | | | 8.3 | | | | | | | | 8.3 | | | EUH-6 | 3/4" | 6 | 3 | 40 | 16 |
| 17 | | | | | | | | | | 8.3 | | | | | | | | 8.3 | | | | | | | | 18 |
| 19 | | | | | | | | 0.8 | | | | | | | | 0.8 | | | | | | | | | | 20 |
| 21 | 15 | 3 | 12 | 1/2" | CF-1 | | | 0.8 | | | | | | | | 0.8 | | | | | CF-2 | 1/2" | 12 | 3 | 15 | 22 |
| 23 | | | | | | | | 0.8 | | | | | | | | 0.8 | | | | | | | | | | 24 |
| 25 | | | | | | | | 0.8 | | | | | | | | | | 8.3 | | | | | | | | 26 |
| 27 | 15 | 3 | 12 | 1/2" | EF-4 | | | 0.8 | | | | | | | | | | 8.3 | | | AH-3 | 3/4" | 8 | 3 | 40 | 28 |
| 29 | | | | | | | | 0.8 | | | | | | | | | | 8.3 | | | | | | | | 30 |
| 31 | | | | | | | | | | 5.0 | | | | | | | | 8.3 | | | | | | | | 32 |
| 33 | 25 | 3 | 10 | 3/4" | AH-1 | | | | | 5.0 | | | | | | | | 8.3 | | | AH-4 | 3/4" | 8 | 3 | 40 | 34 |
| 35 | | | | | | | | | | 5.0 | | | | | | | | 8.3 | | | | | | | | 36 |
| 37 | | | | | | | | | | 5.0 | | | | | | | | 5.0 | | | | | | | | 38 |
| 39 | 25 | 3 | 10 | 3/4" | AH-2 | | | | | 5.0 | | | | | | | | 5.0 | | | AH-5 | 3/4" | 10 | 3 | 25 | 40 |
| 41 | | | | | | | | | | 5.0 | | | | | | | | 5.0 | | | | | | | | 42 |
| | | | | | SECTION 2 | | | | | | | | | | | | | | | | SECTION 2 | | | | | |
| 43 | | | | | | | | | | | | 1.1 | | 3.7 | | | | | | | LIGHTS | 1/2" | 12 | 1 | 20 | 44 |
| 45 | 20 | 3 | 12 | 1/2" | EUH-7 | | | | | | | 1.1 | | 3.3 | | | | | | | LIGHTS SHOP | 1/2" | 12 | 1 | 20 | 46 |
| 47 | | | | | | | | | | | | 1.1 | | 2.2 | | | | | | | LIGHTS SHOP | 1/2" | 12 | 1 | 20 | 48 |
| 49 | | | | | | | | | | 1.7 | | | | 3.3 | | | | | | | LIGHTS SHOP | 1/2" | 12 | 1 | 20 | 50 |
| 51 | 15 | 3 | 12 | 1/2" | HP-1 | | | | | 1.7 | | | | | | | | 4.0 | | | | | | | | 52 |
| 53 | | | | | | | | | | 1.7 | | | | | | | | 4.0 | | | DWH-1 | 1/2" | 12 | 3 | 20 | 54 |
| 55 | | | | | | | | | | 1.7 | | | | | | | | 4.0 | | | | | | | | 56 |
| 57 | 15 | 3 | 12 | 1/2" | HP-2 | | | | | 1.7 | | | | 1.5 | | | | | | | LT SITE (WEST/SOUTH) | 3/4" | 10 | 1 | 20 | 58 |
| 59 | | | | | | | | | | 1.7 | | | | 1.1 | | | | | | | LT SITE (NORTH/EAST) | 3/4" | 10 | 1 | 20 | 60 |
| 61 | | | | | | | | | | 2.5 | | | | | | | | | | | SPACE ONLY | | | | | 62 |
| 63 | 15 | 3 | 12 | 1/2" | HP-3 | | | | | 2.5 | | | | | | | | | | | SPACE ONLY | | | | | 64 |
| 65 | | | | | | | | | | 2.5 | | | | | | | | | | | SPACE ONLY | | | | | 66 |
| 67 | | | | | | | | | | 2.5 | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 20.0 | | | | | | 68 |
| 69 | 15 | 3 | 12 | 1/2" | HP-4 | | | | | 2.5 | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 20.0 | PANEL'3H' | 2" | 3/0 | 3 | 200 | 70 |
| 71 | | | | | | | | | | 2.5 | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 20.0 | | | | | | 72 |
| 73 | | | | | | | | | | 1.7 | | | | | | | | | | 22.1 | | | | | | 74 |
| 75 | 15 | 3 | 12 | 1/2" | HP-5 | | | | | 1.7 | | | | | | | | | | 22.1 | CNC MACHINE (4) | 1 1/4" | 3 | 3 | 100 | 76 |
| 77 | | | | | | | | | | 1.7 | | | | | | | | | | 22.1 | | | | | | 78 |
| 79 | | | | | SPACE ONLY | | | | | | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 96.8 | SUB FEED BREAKER | | | | | 80 |
| 81 | | | | | SPACE ONLY | | | | | | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 96.8 | PANEL '2H' | SEE | RISER | 3 | 400 | 82 |
| 83 | | | | | SPACE ONLY | | | | | | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 96.8 | | | | | | 84 |
| LIGHTING (KVA): | | | | | 15.1 | 0.0 | 0.0 | 4.8 | 0.0 | 134.7 | 0.0 | 3.3 | | 15.1 | 0.0 | 2.4 | 0.0 | 151.7 | 0.0 | 416.7 | CONNECTED LOAD (KVA): | | | | | 728.9 |

RECEPTACLES (KVA): 0.0 — DEMAND LOAD (KVA): 732.7
MOTORS (KVA): 7.3 — PHASE A 245 884.4
A/C (KVA): 0.0 — PHASE B 243 878.3 — CONNECTED LOAD (AMPS): 876.7
HEATING (KVA): 286.4 — PHASE C 241 870.8 — DEMAND LOAD (AMPS): 881.3
KITCHEN (KVA): 0.0 — KVA AMPS
MISCELLANEOUS (KVA): 420.0
NOTES: BASIS OF DESIGN BASED ON SQUARE D EQUIPMENT.

## PNL '1H' DEMAND CALCS

| | | | | | |
|---|---|---|---|---|---|
| LIGHTING | 15.13 | KVA X | 125 % | = | 18.9 KVA |
| RECEPTAC TOTAL | 0.00 | KVA | | | |
| 1ST | 10.00 | KVA X | 100 % | = | 0.0 KVA |
| REMAIN | 0.00 | KVA X | 50 % | = | 0.0 KVA |
| MOTORS | 7.29 | KVA X | 100 % | = | 7.3 KVA |
| A/C | 0.00 | KVA X | 100 % | = | [illegible] KVA |
| HEATING | 286.44 | KVA X | 100 % | = | 286.4 KVA |
| LOCKED-OUT LOAD | ____ | KVA X | 100 % | = | 0.0 KVA |
| KITCHEN | 0.00 | KVA X | 65 % | = | 0.0 KVA |
| MISCELLANEOUS | 420.00 | KVA X | 100 % | = | 420.0 KVA |
| TOTAL | = | 881.3 amps | | = | 732.7 KVA |

## PANELBOARD SCHEDULE - '2H'

MAIN: 400A MLO W/FEED THRU LUGS | VOLTAGE: 480/277 | PHASE: 3 | WIRE: 4 | MOUNTING: SURFACE | AIC: 14,000 | NOTES:

| CKT # | BKR TRIP | POLE | WIRE SIZE | COND SIZE | DESCRIPTION | LTG | REC | MTR | A/C | HTG | KIT | MISC | PHASE ABC | LTG | REC | MTR | A/C | HTG | KIT | MISC | DESCRIPTION | COND SIZE | WIRE SIZE | POLE | BKR TRIP | CKT # |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 2 |
| 3 | 20 | 3 | 12 | 1/2" | WELDER (2) | | | | | | | 3.4 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 4 |
| 5 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 6 |
| 7 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 8 |
| 9 | 20 | 3 | 12 | 1/2" | WELDER (2) | | | | | | | 3.4 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 10 |
| 11 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 12 |
| 13 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 14 |
| 15 | 25 | 3 | 10 | 3/4" | WELD STATION (1) | | | | | | | 5.3 | | | | | | | | 5.3 | WELD STATION (1) | 3/4" | 10 | 3 | 25 | 16 |
| 17 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 18 |
| 19 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 20 |
| 21 | 20 | 3 | 12 | 1/2" | WELDER (2) | | | | | | | 3.4 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 22 |
| 23 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 24 |
| 25 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 26 |
| 27 | 20 | 3 | 12 | 1/2" | WELDER (2) | | | | | | | 3.4 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 28 |
| 29 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 30 |
| 31 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 32 |
| 33 | 25 | 3 | 10 | 3/4" | WELD STATION (1) | | | | | | | 5.3 | | | | | | | | 5.3 | WELD STATION (1) | 3/4" | 10 | 3 | 25 | 34 |
| 35 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 36 |
| 37 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 38 |
| 39 | 25 | 3 | 10 | 3/4" | WELD STATION (1) | | | | | | | 5.3 | | | | | | | | 5.3 | WELD STATION (1) | 3/4" | 10 | 3 | 25 | 40 |
| 41 | | | | | | | | | | | | 5.3 | | | | | | | | 5.3 | | | | | | 42 |
| | | | | | SECTION 2 | | | | | | | | | | | | | | | | SECTION 2 | | | | | |
| 43 | | | | | | | | | | | | 3.4 | | | | | | | | | | | | | | 44 |
| 45 | 20 | 3 | 12 | 1/2" | WELDER [illegible] | | | | | | | [illegible] | | | | | | | | | SPARE | | | 3 | 20 | 46 |
| 47 | | | | | | | | | | | | 3.4 | | | | | | | | | | | | | | 48 |
| 49 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 50 |
| 51 | 20 | 3 | 12 | 1/2" | WELDER (2) | | | | | | | 3.4 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 52 |
| 53 | | | | | | | | | | | | 3.4 | | | | | | | | 3.4 | | | | | | 54 |
| 55 | | | | | | | | | | | | 3.6 | | | | | | | | 3.4 | | | | | | 56 |
| 57 | 20 | 3 | 12 | 1/2" | ROBOT (6) | | | | | | | 3.6 | | | | | | | | 3.4 | WELDER (2) | 1/2" | 12 | 3 | 20 | 58 |
| 59 | | | | | | | | | | | | 3.6 | | | | | | | | 3.4 | | | | | | 60 |
| 61 | | | | | | | | | | | | 3.6 | | | | | | | | | SPACE | | | | | 62 |
| 63 | 20 | [illegible] | [illegible] | [illegible] | ROBOT (6) | | | | | | | 3.6 | | | | | | | | | SPACE | | | | | 64 |
| 65 | | | | | | | | | | | | 3.6 | | | | | | | | | SPACE | | | | | 66 |
| 67 | | | | | | | | | | | | 4.0 | | | | | | | | | SPACE | | | | | 68 |
| 69 | 30 | [illegible] | 10 | [illegible] | CONVEYOR (8) | | | | | | | 4.0 | | | | | | | | | SPACE | | | | | 70 |
| 71 | | | | | | | | | | | | 4.0 | | | | | | | | | SPACE | | | | | 72 |
| 73 | | | | | | | | | | | | | | | | | | | | | SPACE | | | | | 74 |
| 75 | 30 | 3 | | | SPARE | | | | | | | | | | | | | | | | SPACE | | | | | 76 |
| 77 | | | | | | | | | | | | | | | | | | | | | SPACE | | | | | 78 |
| 79 | | | | | | | | | | | | 13.3 | | | | | | | | | SPACE | | | | | 80 |
| 81 | 60 | 3 | 6 | 1" | VACUUM PUMP (5) | | | | | | | 13.3 | | | | | | | | | SPACE | | | | | 82 |
| 83 | | | | | | | | | | | | 13.3 | | | | | | | | | SPACE | | | | | 84 |
| LIGHTING (KVA): | | | | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 181.9 | | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 0.0 | 108.5 | CONNECTED LOAD (KVA): | | | | | 290.4 |

RECEPTACLES (KVA): 0.0 — DEMAND LOAD (KVA): 290.4
MOTORS (KVA): 0.0 — PHASE A 97 349.5
A/C (KVA): 0.0 — PHASE B 97 349.5 — CONNECTED LOAD (AMPS): 349.3
HEATING (KVA): 0.0 — PHASE C 97 349.5 — DEMAND LOAD (AMPS): 349.3
KITCHEN (KVA): 0.0 — KVA AMPS
MISCELLANEOUS (KVA): 290.4
NOTES: BASIS OF DESIGN BASED ON SQUARE D EQUIPMENT.

## PNL '2H' DEMAND CALCS

| | | | | | |
|---|---|---|---|---|---|
| LIGHTING | 0.00 | KVA X | 125 % | = | 0.0 KVA |
| RECEPTAC TOTAL | 0.00 | KVA | | | |
| 1ST | 10.00 | KVA X | 100 % | = | 0.0 KVA |
| REMAIN | 0.00 | KVA X | 50 % | = | 0.0 KVA |
| MOTORS | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| A/C | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| HEATING | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| LOCKED-OUT LOAD | ____ | KVA X | 100 % | = | 0.0 KVA |
| KITCHEN | 0.00 | KVA X | 65 % | = | 0.0 KVA |
| MISCELLANEOUS | 290.45 | KVA X | 100 % | = | 290.4 KVA |
| TOTAL | = | 349.3 amps | | = | 290.4 KVA |

## PANELBOARD SCHEDULE - '1L'

MAIN: 400A MCB W/ FEED THRU LUG | VOLTAGE: 208/120 | PHASE: 3 | WIRE: 4 | MOUNTING: SURFACE | AIC: 10,000 | NOTES:

| CKT # | BKR TRIP | POLE | WIRE SIZE | COND SIZE | DESCRIPTION | LTG | REC | MTR | A/C | HTG | KIT | MISC | PHASE ABC | LTG | REC | MTR | A/C | HTG | KIT | MISC | DESCRIPTION | COND SIZE | WIRE SIZE | POLE | BKR TRIP | CKT # |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | 12 | 1/2" | EWC * | | | | | | | 0.3 | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 2 |
| 3 | 20 | 1 | 12 | 1/2" | RECEPTS GEN. | | 0.7 | | | | | | | | 0.5 | | | | | | RECEPTS-CORD | [illegible] | 12 | [illegible] | [illegible] | 4 |
| 5 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 1.1 | | | | | | | | | | | | | 0.3 | EWC * | 1/2" | [illegible] | 1 | 20 | 6 |
| 7 | 20 | 1 | 12 | 1/2" | RECEPTS | | 1.1 | | | | | | | | | | | | | 0.3 | EWC * | 1/2" | [illegible] | 1 | 20 | 8 |
| 9 | 20 | 1 | 12 | 1/2" | VENDING * | | | | | | | 1.2 | | | | | | | | | SPARE | | | 1 | 20 | 10 |
| 11 | 20 | 1 | 12 | 1/2" | VENDING * | | | | | | | 1.2 | | | | | | | | 1.0 | PARTITION | [illegible] | 12 | [illegible] | 20 | 12 |
| 13 | 20 | 1 | 12 | 1/2" | VENDING * | | | | | | | 1.2 | | | | | | | | [illegible] | FIRE ALARM * | [illegible] | 12 | 1 | 20 | 14 |
| 15 | 20 | 1 | 12 | 1/2" | SMALL APP. REC * | | | | | | | 1.5 | | | | | | | | | PHONE BOARD * | [illegible] | 12 | 1 | 20 | 16 |
| 17 | 20 | 1 | 12 | 1/2" | SMALL APP. REC * | | | | | | | 1.5 | | 1.2 | | | | | | | SIGN CONNECTION | 1/2" | 12 | 1 | 20 | 18 |
| 19 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 1.1 | | | | | | | 0.3 | | | | | | | [illegible] | 1/2" | 12 | 1 | 20 | 20 |
| 21 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.9 | | | | | | | 1.2 | | | | | | | MONUMENT SIGN | 1/2" | 12 | 1 | 20 | 22 |
| 23 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 1.1 | | | | | | | 1.2 | | | | | | | SIGN CONNECTION | 1/2" | 12 | 1 | 20 | 24 |
| 25 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 1.1 | | | | | | | 1.2 | | | | | | | SIGN CONNECTION | 1/2" | 12 | 1 | 20 | 26 |
| 27 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | 0.8 | | | | | | | LIGHTS EXTERIOR | 1/2" | 12 | 1 | 20 | 28 |
| 29 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | | | | | | | LIGHTS EXTERIOR | 1/2" | 12 | 1 | 20 | 30 |
| 31 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | | | | | | 0.3 | LIGHTING CLTS | 1/2" | 12 | 1 | 20 | 32 |
| 33 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.2 | | | | | | | | | | | 1.5 | | | RPZ HEATER | 3/4" | 6 | 1 | 20 | 34 |
| 35 | 20 | 1 | 12 | 1/2" | RECEPTS. | | [illegible] | | | | | | | | | | | 1.5 | | | RPZ HEATER | 3/4" | 6 | 1 | 20 | 36 |
| 37 | 20 | 1 | | | SPARE | | | | | | | | | [illegible] | 2.2 | 0.0 | 0.0 | 0.0 | 0.0 | 7.4 | SUB FEED BREAKER | | | | | 38 |
| 39 | 20 | 1 | 12 | 1/2" | LIGHTS 2ND | 0.5 | [illegible] | | | | | | | [illegible] | 2.2 | 0.0 | 0.0 | 0.0 | 0.0 | 2.0 | PANEL '2L' | 2 1/2" | 4/0 | 3 | 225 | 40 |
| 41 | 20 | 1 | 12 | 1/2" | LIGHTS 1ST | 1.2 | 0.3 | | | | | | | 0.0 | 1.6 | 0.0 | 0.0 | 0.0 | 0.0 | 6.2 | | | | | | 42 |
| | | | | | SECTION 2 | | | | | | | | | | | | | | | | SECTION 2 | | | | | |
| 43 | 20 | 1 | 12 | 1/2" | RECEPTS. | | [illegible] | | | | | | | | 0.5 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 44 |
| 45 | 20 | 1 | 12 | 1/2" | RECEPTS. | | [illegible] | | | | | | | | 0.5 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 46 |
| 47 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.5 | | | | | | | | 0.5 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 48 |
| 49 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.5 | | | | | | | | 0.5 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 50 |
| 51 | 20 | 1 | | | SPARE | | | | | | | | | | 0.7 | | | | | | RECEPTS | 1/2" | 12 | 1 | 20 | 52 |
| 53 | 20 | 1 | | | SPARE | | | | | | | | | | | | | | | | SPACE | | | | | 54 |
| 55 | 20 | 1 | | | SPARE | | | | | | | | | | | | | | | | SPACE | | | | | 56 |
| 57 | 20 | 1 | | | SPARE | | | | | | | | | | | | | | | | SPACE | | | | | 58 |
| 59 | 20 | 1 | | | SPARE | | | | | | | | | | | | | | | | SPACE | | | | | 60 |
| 61 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 62 |
| 63 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 64 |
| 65 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 66 |
| 67 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 68 |
| 69 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 70 |
| 71 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 72 |
| 73 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 74 |
| 75 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 76 |
| 77 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 78 |
| 79 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 80 |
| 81 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 82 |
| 83 | | | | | SPACE | | | | | | | | | | | | | | | | SPACE | | | | | 84 |
| LIGHTING (KVA): | | | | | 8.5 | 1.7 | 11.3 | 0.5 | 0.0 | 0.0 | 0.0 | 6.9 | | 6.8 | 9.9 | 0.0 | 0.0 | 3.0 | 0.0 | 19.4 | CONNECTED LOAD (KVA): | | | | | 59.4 |

RECEPTACLES (KVA): 21.2 — DEMAND LOAD (KVA): 56.0
MOTORS (KVA): 0.5 — PHASE A 20 170.6
A/C (KVA): 0.0 — PHASE B 16 137.1 — CONNECTED LOAD (AMPS): 164.9
HEATING (KVA): 3.0 — PHASE C 22 187.4 — DEMAND LOAD (AMPS): 155.3
KITCHEN (KVA): 0.0 — KVA AMPS
MISCELLANEOUS (KVA): 26.3
NOTES: 1. BASIS OF DESIGN BASED ON SQUARE D EQUIPMENT. 2. * - INDICATES GFCI RATED BREAKER. 3. ** - INDICATES BREAKER WITH LOCK OFF DEVICE.

## PNL '1L' DEMAND CALCS

| | | | | | |
|---|---|---|---|---|---|
| LIGHTING | 8.49 | KVA X | 125 % | = | 10.6 KVA |
| RECEPTAC TOTAL | 21.16 | KVA | | | |
| 1ST | 10.00 | KVA X | 100 % | = | 10.0 KVA |
| REMAIN | 11.16 | KVA X | 50 % | = | 5.6 KVA |
| MOTORS | 0.50 | KVA X | 100 % | = | 0.5 KVA |
| A/C | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| HEATING | 3.00 | KVA X | 100 % | = | 3.0 KVA |
| LOCKED-OUT LOAD | ____ | KVA X | 100 % | = | 0.0 KVA |
| KITCHEN | 0.00 | KVA X | 65 % | = | 0.0 KVA |
| MISCELLANEOUS | 26.27 | KVA X | 100 % | = | 26.3 KVA |
| TOTAL | = | 155.3 amps | | = | 56.0 KVA |

## PANELBOARD SCHEDULE - '2L'

MAIN: 225A MLO W/FEED THRU LUGS | VOLTAGE: 208/120 | PHASE: 3 | WIRE: 4 | MOUNTING: SURFACE | AIC: 10,000 | NOTES:

| CKT # | BKR TRIP | POLE | WIRE SIZE | COND SIZE | DESCRIPTION | LTG | REC | MTR | A/C | HTG | KIT | MISC | PHASE ABC | LTG | REC | MTR | A/C | HTG | KIT | MISC | DESCRIPTION | COND SIZE | WIRE SIZE | POLE | BKR TRIP | CKT # |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 2 |
| 3 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 4 |
| 5 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 6 |
| 7 | 20 | 1 | 12 | 1/2" | RECEPTS. | | 0.4 | | | | | | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 8 |
| 9 | 20 | 1 | 12 | 1/2" | I/S EVAL BOOTH | | | | | | | 0.4 | | | 0.5 | | | | | | RECEPTS-CORD | 1/2" | 12 | 1 | 20 | 10 |
| 11 | 20 | 1 | 12 | 1/2" | I/S TRAINING REC | | 0.4 | | | | | | | | 0.4 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 12 |
| 13 | 20 | 1 | 12 | 1/2" | PLC (7) | | | | | | | 1.2 | | | 0.4 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 14 |
| 15 | 20 | 1 | 12 | 1/2" | ROBOT AREA REC. | | 0.2 | | | | | | | | 0.4 | | | | | | RECEPTS. | 1/2" | 12 | 1 | 20 | 16 |
| 17 | 30 | 2 | 10 | 3/4" | RADIAL ARM SAW (10) | | | | | | | 1.5 | | | | | | | | 1.6 | WELDING REC | 1/2" | 12 | 1 | 20 | 18 |
| 19 | | | | | | | | | | | | 1.5 | | | | | | | | 1.6 | WELDING REC | 1/2" | 12 | 1 | 20 | 20 |
| 21 | 20 | 1 | 12 | 1/2" | RADIAL AREA REC. | | 0.2 | | | | | | | | | | | | | 1.6 | WELDING REC | 1/2" | 12 | 1 | 20 | 22 |
| 23 | | | | | SPACE ONLY | | | | | | | | | | | | | | | 1.6 | WELDING REC | 1/2" | 12 | 1 | 20 | 24 |
| 25 | | | | | SPACE ONLY | | | | | | | | | | | | | | | 1.6 | WELDING REC | 1/2" | 12 | 1 | 20 | 26 |
| 27 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPARE | | | 1 | 20 | 28 |
| 29 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 30 |
| 31 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 32 |
| 33 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 34 |
| 35 | 20 | 2 | 12 | 1/2" | TABLE SAW (7) | | | | | | | 1.5 | | | | | | | | | SPACE ONLY | | | | | 36 |
| 37 | | | | | | | | | | | | 1.5 | | | | | | | | | SPACE ONLY | | | | | 38 |
| 39 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 40 |
| 41 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 42 |
| | | | | | SECTION 2 | | | | | | | | | | | | | | | | SECTION 2 | | | | | |
| 43 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 44 |
| 45 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 46 |
| 47 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 48 |
| 49 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 50 |
| 51 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 52 |
| 53 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 54 |
| 55 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 56 |
| 57 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 58 |
| 59 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 60 |
| 61 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 62 |
| 63 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 64 |
| 65 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 66 |
| 67 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 68 |
| 69 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 70 |
| 71 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 72 |
| 73 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 74 |
| 75 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 76 |
| 77 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 78 |
| 79 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 80 |
| 81 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 82 |
| 83 | | | | | SPACE ONLY | | | | | | | | | | | | | | | | SPACE ONLY | | | | | 84 |
| LIGHTING (KVA): | | | | | 0.0 | 0.0 | 2.2 | 0.0 | 0.0 | 0.0 | 0.0 | 7.5 | | 0.0 | 3.8 | 0.0 | 0.0 | 0.0 | 0.0 | 8.0 | CONNECTED LOAD (KVA): | | | | | 21.4 |

RECEPTACLES (KVA): 5.9 — DEMAND LOAD (KVA): 21.4
MOTORS (KVA): 0.0 — PHASE A 10 78.3
A/C (KVA): 0.0 — PHASE B 4 34.3 — CONNECTED LOAD (AMPS): 59.4
HEATING (KVA): 0.0 — PHASE C 8 64.8 — DEMAND LOAD (AMPS): 59.4
KITCHEN (KVA): 0.0 — KVA AMPS
MISCELLANEOUS (KVA): 15.5
NOTES: 1. BASIS OF DESIGN BASED ON SQUARE D EQUIPMENT.

## PNL '2L' DEMAND CALCS

| | | | | | |
|---|---|---|---|---|---|
| LIGHTING | 0.00 | KVA X | 125 % | = | 0.0 KVA |
| RECEPTAC TOTAL | 5.94 | KVA | | | |
| 1ST | 10.00 | KVA X | 100 % | = | 5.9 KVA |
| REMAIN | 0.00 | KVA X | 50 % | = | 0.0 KVA |
| MOTORS | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| A/C | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| HEATING | 0.00 | KVA X | 100 % | = | 0.0 KVA |
| LOCKED-OUT LOAD | ____ | KVA X | 100 % | = | 0.0 KVA |
| KITCHEN | 0.00 | KVA X | 65 % | = | 0.0 KVA |
| MISCELLANEOUS | 15.47 | KVA X | 100 % | = | 15.5 KVA |
| TOTAL | = | 59.4 amps | | = | 21.4 KVA |

Order Plans @ WWW.LDILine.com

ROBERT JOHNSON
architects
1808 West Morehead St.
Charlotte, NC 28208
T 704 / 342.1058
F 704 / 342.3043

STAMPS
9/30/2020

CONSULTANT

WAVE ENGINEERING
1300 S. MINT ST. SUITE 110
CHARLOTTE NC, 28203
980.259.7728
INFO@WAVE-ENGINEERING.COM
NC CORP. LICENSE #P-1621
WAVE PROJECT #20139

MIDSOUTH CARPENTER'S TRAINING TRUST
La Vergne, TN

PROJECT NUMBER 1982

ISSUE DATE
FOR PERMIT 09.30.20

DRAWING DATA
DRAWN BY: GKG
CHECKED BY: MJS

SHEET TITLE
PANEL SCHEDULES

This drawing is the property of ROBERT JOHNSON ARCHITECTS, Inc. and is not to be reproduced or copied in whole or in part. It is only to be used for the project and site specifically identified herein and is not to be used on any other project. It is to be returned upon request.

SHEET NUMBER
E-4.1