


FLOOR PLAN 1/4"=1'-0" **A**

| WALL LEGEND | | E | |
|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | TYPICAL EXTERIOR WALL: 2x6 WD STUDS AT 16" O.C. W/ SHEATHING AS SCHEDULED (SEE STRUCT. DWGS.) AND R-19 KRAFT-FACED FIBERGLASS BATT INSULATION U.O.N. BLUESKIN VP WATER RESISTIVE AIR BARRIER MEMBRANE OVER SHEATHING. | | INTERIOR SOUND-RATED WALL: TYPICAL INTERIOR WALL W/ 3-1/2" UNFACED FIBERGLASS BATT INSULATION. ◆ 2X4 WOOD STUDS ◆ 2X6 WOOD STUDS |
| | TYPICAL INTERIOR WALL: WD STUDS AT 16" O.C. AS INDICATED. ◆ 2X4 WOOD STUDS ◆ 2X6 WOOD STUDS | | HOOD WALL: INTERIOR NON-COMBUSTIBLE WALL WITH 20 GA. S.S. PANEL BEHIND HOOD. EXTEND MIN. 18" BEYOND END OF HOOD. M. STUD FRAMING. REFER TO DETAIL 2/M3.0 FOR EXTENT OF S.S. PANEL. ◆ 6" METAL STUDS |
| | WALL SUBSTRATES: - DINING ROOM: 1/2" GYPSUM WALLBOARD FROM FLOOR SLAB TO 6" ABOVE CEILING HEIGHT U.O.N. SEE 6 & 8 / A6.3 (NOTE: THE CEMENT BOARD SPECIFICATION IS DESIGNED TO ALLOW THE G.C. FLEXIBILITY.) - KITCHEN WALLS AND DINING ROOM CLOSET: 1/2" CEMENT WALLBOARD FROM T.O. SLAB TO 12" AFF. AT 12" AFF. USE 1/2" CDX PLYWOOD W/FRP SURFACE FINISH TO 6" ABOVE CEILING HEIGHT U.O.N. IF DOUBLE SIDED SHEAR WALL PLYWOOD SPECIFIED THE PLYWOOD SHALL BE CONTINUOUS FROM SILL PLATE TO TOP PLATE. SEE 4 & 11 / A6.3. - RESTROOM WALLS: 5/8" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F. WITH 5/8" H-IMPACT BRAND XP WALLBOARD, TYPE X CORE FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N.. NO SUBSTITUTIONS ALLOWED. FINISH AS SCHEDULED. - ALL OTHER FRAME WALL CONDITIONS: 1/2" CEMENT WALLBOARD FROM T.O. SLAB OR T.O. CONCRETE CURB TO 48" A.F.F. WITH 1/2" GYPSUM WALLBOARD FROM T.O. CEMENT BOARD TO 6" ABOVE CEILING HEIGHT U.O.N. FINISH AS SCHEDULED. | | DASHED LINE INDICATES INTERIOR SUBSTRATE LOCATION |
| | LOW WALL: 2X4 WOOD STUDS AT 16" O.C. AS SCHEDULED (SEE DETAIL 3/A6.7) ◆ 2X4 WOOD STUDS ◆ 2X6 WOOD STUDS | | |

| FLOOR PLAN NOTES | | D | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| DIMENSIONS: A. ALL DIMENSIONS ARE TO FACE OF STUD ALONG EXTERIOR AND TO FACE OF FINISH ON INTERIOR. U.O.N. REFER TO FOUNDATION PLAN FOR FACE OF CONC. DIMENSIONS. B. DIMENSIONS NOTED AS "CLEAR" OR "HOLD" ARE MIN. REQ'D. NET CLEARANCE FROM FACE OF WALL / WAJNSCOT FINISH. VERIFY FINAL EQUIPMENT SIZES W/ VENDOR PRIOR TO INT. WALL FRAMING. | | WINDOWS / DOORS: A. SEE SHT. A7.1 FOR WINDOW TYPES AND DOOR SCHEDULE. B. ALL DOOR AND WINDOW OPENING DIMENSIONS ARE TO ROUGH OPENING. | |
| FINISH SUBSTRATES: A. PROVIDE 1/2" THICK CEMENTITIOUS BD. FROM FLOOR SLAB TO 12" A.F.F. MIN. IN LIEU OF GYP. BD. AT ALL WALLS EXCEPT SHEARWALL SURFACES. U.O.N. B. ALL JOINTS, GAPS OR SPACES LEADING TO ALL HOLLOW OR INACCESSIBLE SPACES SHALL BE SEALED WITH NSF INTERNATIONAL APPROVED SEALANTS. C. ALL BACK OF HOUSE AND OFFICE WALLS SHALL HAVE 1/2" CDX PLYWOOD SUBSTRATE. U.O.N. | | DECOR: A. SEE A2.0 FOR SEATING PLAN AND DETAILS. B. SEE A7.0 FOR FLOOR FINISHES. C. SEE A8.0 - A8.3 FOR WALL FINISHES. D. SEE A7.1 FOR CEILING FINISHES. | |
| GENERAL: A. PROVIDE THREE FIRE EXTINGUISHERS - (2) 10 lb. BC and (1) 10 lb. ABC - TO COMPLY WITH LOCAL FIRE CODE. LOCATE PER DIRECTION OF FIRE MARSHALL OR LOCAL AUTHORIZING AGENT. B. DRAWINGS ARE BASED UPON WOOD FRAMING. UTILIZATION OF METAL STUDS ON NON-BEARING INTERIOR PARTITIONS, BULKHEADS AND SOFFITS IS ACCEPTABLE. C. ALL ATTACHMENTS MADE THROUGH E.I.F.S. SHALL BE BUSHED TO PREVENT DAMAGE TO THE FINISH. PER 9/A6.2. D. ALL PENETRATIONS THROUGH E.I.F.S. SHALL BE SEALED USING MFRS APPROVED METHOD. | | | |

| KEY NOTES | | B | |
|-----------|------------------------------------------------------------------------------------------------------------------------------|----|-------------------------------------------------------------------------------------------|
| 2 | NO FRP BEHIND W-059 WALK-IN COOLER/FREEZER | 34 | TILE TO METAL THRESHOLD ADA COMPLIANT. |
| 3 | PIPE BOLLARD SEE DETAIL 6/CT1.0 | 35 | INDICATES HOT WATER HEATER LOCATION. REFER TO PLUMBING DRAWING FOR ADDITIONAL INFORMATION |
| 4 | HOOD WALL. SEE WALL LEGEND | | |
| 6 | KEEP CLEAR FOR UTILITIES AND SYRUP LINES | | |
| 10 | SS CORNER GUARDWALL CAP (TM-2). TYP. ALL CORNERS IN BACK OF HOUSE FROM REAR WALL TO THE KITCHEN SIDE OF THE SERVICE COUNTER. | | |
| 13 | SYRUP LINE CHASE (ABOVE) | | |
| 14 | 14"x14" HORIZONTAL OPENING FOR SYRUP TUBES. COORDINATE WALL PENETRATION WITH COUNTER INSTALLER SEAL CHASE TO COUNTER | | |
| 15 | ROOF LADDER | | |
| 16 | ADD SECOND 2X4 WALL ON KITCHEN SIDE | | |
| 24 | CASED OPENING. REFER TO DETAIL 5/A6.4 (IF NO DOOR SPECIFIED) | | |
| 25 | FUR OUT WALL AS INDICATED WITH 2X4 WOOD STUDS AT 16" O.C. | | |
| 28 | LOW WALL BY G.C. COORDINATE WITH STRUCTURAL DRAWINGS. | | |
| 30 | STAINLESS STEEL SPLASH GUARD SEE DETAIL 9/A6.3 | | |
| 31 | CORNER GUARD TILE SCHLUTER | | |
| 32 | REMOVABLE ASTRAGAL FROM INSIDE ONLY | | |
| 33 | MOPSINK. REFER TO SHEET A2.0 & A2.1 | | |



| | |
|-----------------|-----------------|
| CONTRACT DATE: | 11/17/20 |
| BUILDING TYPE: | ENDEAVOR MED 40 |
| PLAN VERSION: | SEPT 2020 |
| BRAND DESIGNER: | 200109 |
| SITE NUMBER: | 297222 |
| STORE NUMBER: | 003717 |
| ARCVISION: | 200188 |

TACO BELL
 8151 HWY 278 NW
 COWINGTON, GA 30014



FLOOR PLAN
A1.0