



**FLOOR FINISH PLAN** 1/4"=1'-0" **A**

A. FINISH MATERIAL. REFER TO SHT A7.2 FOR FINISHES

B. JOINTS (U.O.)  
 QUARRY FLOOR TILE : 1/4"  
 CERAMIC FLOOR TILE : 3/16"  
 WALL TILE : 1/8"  
 BASE, TRIM AND ACCESSORIES : MATCH ADJOINING TILE UNITS

TILE INSTALLATIONS REQUIRE MANUFACTURERS STANDARD MOLDED CORNERS AT BOTH INSIDE AND OUTSIDE CORNERS.

D. ALL BASE TILE SHALL BE SANITARY COVE STYLE WITH 3/8" MIN RADIUS UNLESS NOTED OTHERWISE.

E. SEE SCOPE OF WORK SHEETS FOR RESPONSIBILITIES.

F. PROVIDE CLEAR SILICONE CAULK WHERE FRP STOPS AT TOP OF COVE BASE.

G. TILE CHIPPING AROUND CORE DRILL HOLES FOR SEATING FIXTURE WILL NOT BE ACCEPTED.

- 1 NEW ADA COMPLIANT THRESHOLD
- 2 6" COVE TILE BASE. SEE DETAILS 8/A6.3 (INTERIOR) AND 16/A6.3 (EXTERIOR) FOR INSTALLATION.
- 3 6" SANITARY COVE TILE BASE. SEE DETAILS 4/A6.3 (INTERIOR) AND 6/A6.3 (EXTERIOR).
- 4 PROVIDE FLOOR TILE INSIDE WALK-IN COOLER (NO TILE OR BASE IN FREEZER). FLOAT FLOOR TILE IN COOLERS TO DRAIN TO KITCHEN. COORD. WITH COOLER WALL CONFIGURATION.
- 5 NO BASE TILE BEHIND WALK-IN COOLER/FREEZER.
- 6 ALIGN FLOOR TILE TRANSITION WITH FACE OF WALL.
- 7 FLOAT FLOOR TILE FOR FLUSH TRANSITION.
- 8 START POINT FOR FLOOR TILE.
- 9 METAL BASE IN COOLER; SEE SCOPE OF WORK. SEE DETAIL 1/A6.3.
- 10 REFER TO STRUCT DRAWINGS FOR CONC FLOOR SLOPES AROUND FLOOR DRAINS.
- 11 STEP UP AT FREEZER THRESHOLD.
- 12 SANITARY TILE BASE IN RESTROOMS.
- 13 INSTALL FLOOR TILE WITH OFFSET NO MORE THAN 33% OR INSTALL IN A STRAIGHT STACK BOND.

**NOT USED** **D**

**FINISH NOTES** **C**

**KEY NOTES** **B**

**FREDERICK J. GOGLIA**  
 ARCHITECT, NCARB, FIDI  
 1950 CRAIG ROAD, SUITE 300  
 ST. LOUIS, MO 63146  
 PH (314) 455-2400 FAX (314) 455-2800  
 www.rjg.com

CONTRACT DATE: 11/17/20  
 BUILDING TYPE: ENDEAVOR MED 40  
 PLAN VERSION: SEPT 2020  
 BRAND DESIGNER: 200109  
 SITE NUMBER: 297222  
 STORE NUMBER: 003717  
 ARCVISION: 200188

**TACO BELL**  
 6151 HWY 278 NW  
 COVINGTON, GA 30014



**FLOOR FINISH PLAN**  
**A7.0**