


WWW.DIline.com

**DESIGNER NOTE:**  
 WHEN A FIRE ALARM SYSTEM IS REQUIRED BY THE AHJ  
 USE THE FOLLOWING:  
 MANUFACTURER: HONEYWELL  
 SYSTEM: SILENT KNIGHT FARENHYT  
 MODEL: IFP-100



**REFLECTED CEILING PLAN** 1/4"=1'-0" **A**

Order Plans @

CEILING SYMBOL LEGEND		D
	1'-0" LED TROFFER	EXTERIOR WALL FIXTURE
	2'-0" x 4'-0" LED LIGHT FIXTURE	
	DOWNLIGHT @ WALK-IN (BY WALK-IN MFR.)	SPEAKER - CENTER ON CEILING TILE
	PENDANT FIXTURE	
	DOWNLIGHT - CENTER ON CEILING TILE	12" EXHAUST FAN
	EMERGENCY LIGHT	
	EXIT LIGHT (WALL MOUNTED)	HVAC RETURN GRILLE
	EXIT LIGHT (CEILING MOUNTED)	
	OCCUPANCY SENSOR CEILING MOUNTED	HVAC SUPPLY DIFFUSER
	BACK DOOR SECURITY STROBE LIGHT	

**DIMENSIONS:**  
 A. ALL DIMENSIONS ARE TO FACE OF FINISH U.O.N.

**CEILING FINISHES:**  
 A. REFER TO ROOM FINISH SCHEDULE (SHT A7.2) FOR CLG. FINISHES.

**SUSPENDED CEILING:**  
 A. ACOUSTICAL PANEL INSTALLATION: INSTALL ACOUSTICAL PANELS WITH EDGES IN CLOSE CONTACT WITH METAL SUPPORTS AND IN TRUE ALIGNMENT.  
 B. ALLOWABLE VARIATIONS FROM FLAT AND LEVEL SURFACE: 1/8" IN 10'-0" MAX.  
 C. ALLOWABLE VARIATIONS FROM PLUMB OF GRID MEMBERS: AS CAUSED BY ECCENTRIC LOADS, 2" MAX.  
 D. INSTALL SYSTEM AFTER MAJOR ABOVE CLG. WORK IS COMPLETE. COORD. LOCATIONS OF HANGERS WITH RELATED WORK.  
 E. SEE SPECS FOR ADDITIONAL INFORMATION.

**GYPSUM BOARD CEILING:**  
 A. SUBSTRATE SHALL BE 1/2" THICK GYP. BD.  
 B. ACOUSTICAL SEALANT: APPLY TO GYP. BD. PANELS AS INDICATED IN SPECS.  
 GYP. BD. FINISHING AND DECORATING. REFER TO DWGS FOR TEXTURE AND FINISHES.

**ELECTRICAL:**  
 A. SEE ELECT. DWGS. FOR FIXTURE SCHED.

- (1) CEILING GRID STARTING POINT.
- (2) BULKHEAD @ 8'-0" A.F.F.
- (3) NON-INSULATED BUNDLED SYRUP LINES FOR DRINK SYSTEM. SEE SCOPE OF WORK SEE DETAIL 17/A6.4.
- (4) 6" DIA PVC STUB THROUGH CEILING. SEE DETAIL 10/A6.4 & 11/A6.4
- (5) HOOD
- (6) FOR ROUGH FRAMING OPENINGS SEE AIR DEVICE SCHED. (TYP. ALL RESTROOMS).
- (7) DRIVE THRU CANOPY.
- (8) ROOF HATCH SEE 7/A6.0
- (11) VERTICAL DOWNSPOUT
- (12) SPEAKER - CENTER ON CEILING TILE (WHERE APPLICABLE).
- (15) UTILITY CHASE BY 3RD PARTY VENDOR TO CEILING.
- (16) EMERGENCY DUAL HEAD FIXTURE. SEE ELECTRICAL DRAWINGS.
- (17) SECURITY STROBE LIGHT, REFER TO ELECT. DWGS.
- (18) FAN COIL FOR WALK-IN.
- (20) ALERT LIGHT BOX FOR 3-COMP POWER SOAK MOUNTED AT C.L. OF BOX 7'-11" AFF
- (21) 30" X 30" ACCESS OPENING IN REAR WALL ABOVE CEILING. FINISH WITH GYP. BD.
- (24) INSTALL GRAPHIC PER ARTWORK SCHEDULE ON ALCOVE SOFFIT.
- (26) STAINLESS STEEL SYRUP CHASE ON WALL. SEE DETAIL 19/A6.4.
- (27) WATER INLET CHASE FOR CHEESE MELTER SCREWED TO HEATED AIR SCREEN

**KEY NOTES** **B**

**REFLECTED CEILING PLAN NOTES** **C**

CONTRACT DATE: 11/17/20  
 BUILDING TYPE: ENDEAVOR MED 40  
 PLAN VERSION: SEPT 2020  
 BRAND DESIGNER: 200109  
 SITE NUMBER: 297222  
 STORE NUMBER: 003717  
 ARCVISION: 200188

**TACO BELL**  
 8151 HWY 278 NW  
 COWINGTON, GA 30014



**REFLECTED  
 CEILING  
 PLAN**

**A7.1**