

REVISIONS	BY

**FREELAND and KAUFFMAN, INC.**  
 Engineers • Landscape Architects  
 209 West Stone Avenue  
 Greenville, South Carolina 29609  
 864-233-5497

**NO SET  
 NOT FOR  
 CONSTRUCTION**



**CALIBER COLLISION**  
 1233 E. BUTLER ROAD  
 GREENVILLE, SC 29607  
 CROSS DEVELOPMENT CC FIVE FORKS, LLC.  
 4336 MARSH RIDGE  
 CARROLLTON, TX 75010  
 TEL: (214) 614-8252

DRAWN	EAC
CHECKED	TMB
DATE	01/04/2021
SCALE	

DRAWING  
**R7**

### STANDARD PAVEMENT MARKINGS

FOR ARROWS & ONLY(S)

RIGHT OR LEFT TURN MARKINGS APPLICATION

STORAGE = 100 FT TO 150 FT

REFERENCES

SIGNING AND MARKING ENGINEER

**SCDOT**  
 DESIGN STANDARDS OFFICE  
 955 PARK STREET  
 COLUMBIA, SC 29201  
 STANDARD DRAWING  
 625-410-00

### PAVEMENT MARKING TYPICAL

#### LINE PATTERNS AND RAISED MARKER PLACEMENT

IDENTIFICATION KEY FOR RAISED MARKERS:

- WHITE SQUARE: MONODIRECTIONAL
- BLACK SQUARE: BIDIRECTIONAL
- ALL SQUARES ARE 4" X 4" UNLESS NOTED OTHERWISE

REFERENCES

SIGNING AND MARKING ENGINEER

**SCDOT**  
 DESIGN STANDARDS OFFICE  
 955 PARK STREET  
 COLUMBIA, SC 29201  
 STANDARD DRAWING  
 PAVEMENT MARKING TYPICAL  
 LINE PATTERNS AND RAISED MARKER PLACEMENT  
 630-205-00

### PAVEMENT MARKING TYPICAL

#### RAISED MARKER PLACEMENT & DETAIL

NOTES

- ALL RAISED PAVEMENT MARKINGS ARE TO BE SURFACE MOUNTED.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.
- RAISED PAVEMENT MARKINGS ARE USED TO SPURVEY CURB AND GUTTER PAVEMENT MARKINGS TO THE PAVEMENT SURFACE.

REFERENCES

SIGNING AND MARKING ENGINEER

**SCDOT**  
 DESIGN STANDARDS OFFICE  
 955 PARK STREET  
 COLUMBIA, SC 29201  
 STANDARD DRAWING  
 PAVEMENT MARKING TYPICAL  
 RAISED MARKER PLACEMENT & DETAIL  
 630-105-00

### PAVEMENT MARKING TYPICAL

#### DIAGONAL MARKINGS FOR TRANSITION FROM 2 LANES TO FIVE LANES

DETAIL OF MARKINGS

REFERENCES

STATE TRAFFIC OPERATIONS ENGINEER

**SCDOT**  
 DESIGN STANDARDS OFFICE  
 955 PARK STREET  
 COLUMBIA, SC 29201  
 STANDARD DRAWING  
 TRANSITION DIAGONAL MARKINGS  
 625-405-00

OFF-SITE ROADWAY - LAYOUT & STRIPING DETAILS