



- GENERAL NOTES:  
1. SPACING BETWEEN DOUBLE LINES SHALL BE EQUAL TO THE LINE WIDTH.  
2. EDGE LINES SHALL BE PLACED A MINIMUM OF 4 INCHES FROM THE NORMAL EDGE OF PAVEMENT.  
3. CONTRAST MARKINGS FOR SKIP STRIPING SHALL BE AS SHOWN IN DETAIL T-118.

DEPARTMENT OF TRANSPORTATION STATE OF GEORGIA	
CONSTRUCTION DETAILS PAVEMENT MARKING PLACEMENT NON-LIMITED ACCESS ROADWAY	
NO SCALE	JANUARY 2000
DESIGNED _____ DRAWN _____ TRACED _____ CHECKED _____	NUMBER T-IIA

Order Plans @ [www.LDLine.com](http://www.LDLine.com)

**INFRASTRUCTURE**  
CONSULTING & ENGINEERING  
4940 PEACHTREE INDUSTRIAL BLVD., SUITE 310  
NORCROSS, GEORGIA 30071

NOT TO SCALE

REVISION DATES		CONSTRUCTION DETAILS SR 18 BRIDGE REPLACEMENT @ LONG CANE CREEK TROUP COUNTY	
CHECKED:	DATE:	DRAWING No.	
BACKCHECKED:	DATE:	40-0019	
CORRECTED:	DATE:		
VERIFIED:	DATE:		