

TABLE NO. 1 ROUND PIPE - CONCRETE - CORRUGATED STEEL - CORRUGATED ALUMINUM
MINIMUM CLASS OF CONCRETE OR MINIMUM THICKNESS OF STEEL AND ALUMINUM

Table with columns: PIPE DIAMETER (INCHES), MINIMUM COVER (INCHES), HEIGHT OF FILL IN FEET ABOVE TOP OF PIPE (1-10 to 20+), PIPE TYPE, and PIPE DIAMETER (INCHES) 80-90. Rows include various pipe types like CONCRETE, STEEL 1, ALUM 1, etc., for diameters from 12 to 120 inches.

TABLE NO. 3 INFORMATION ONLY
COR. METAL THICKNESS EQUIVALENT GAGE

Table with columns: STATE, PROJECT NUMBER, SHEET NO., TOTAL SHEETS. Values: GA., 10300, 10, 10.

FOR CONDITIONS TO THE RIGHT OF THE HEAVY LINE, CLASS V CONCRETE PIPE REQUIRES IMPERFECT BACKFILL ACCORDING TO DETAIL "A" OR "B" ON SHEET 1 OF 3.

STEEL FOR ALUM 1 DENOTES CORRUGATION PROFILE 2 2/3" X 1/2"
STEEL 2 OR ALUM 2 DENOTES CORRUGATION PROFILE 3" X 1" (OR 5' X 1" FOR STEEL PIPE ONLY)

ALL STEEL AND ALUMINUM PIPE SHALL BE LOCK-SEAM OR WELDED-SEAM (HELICAL) CONSTRUCTION.
MINIMUM COVER VALUES APPLY TO HS-20 LIVE LOAD, MINIMUM COVER NEEDED FOR CONSTRUCTION VEHICLES MAY BE GREATER AND IS THE RESPONSIBILITY OF THE CONTRACTOR.

TRENCH CONSTRUCTION IS REQUIRED FOR CONDITIONS ON BOTH SIDES OF HEAVY LINE, SEE SHEET 3.
FOR CONDITIONS TO RIGHT OF HEAVY LINE, CONCRETE PIPE REQUIRES IMPERFECT BACKFILL ACCORDING TO SPECIFICATIONS AND THIS STANDARD.

TABLE VALUES FOR ALUMINUM CORRUGATED PIPE (OR ALUMINUM SPIRAL RIB PIPE) ARE COMPUTED BASED UPON ALCLAD ALLOY 3004-H34 HAVING MINIMUM YIELD STRENGTH, Fy=24,000 PSI. IF ALUMINUM PIPE IS OTHERWISE FURNISHED AS 3004-H32 (Fy=20,000 PSI), THE TABLE NO. ALLOWABLE FILL HEIGHTS SHALL BE ADJUSTED AS FOLLOWS:

- A. ALL MINIMUM COVER VALUES SHALL BE INCREASED BY 15 PERCENT. (EXAMPLE: 12 INCHES BECOMES 13.8 INCHES)
- B. ALL HEIGHT OF FILL VALUES SHALL BE DECREASED BY 15 PERCENT. (EXAMPLE: 35-40 FEET BECOMES 29.7-34.0 FEET)

Order Plans @ www.LDLine.com

DEPARTMENT OF TRANSPORTATION
STATE OF GEORGIA
STANDARD
CONCRETE & METAL PIPE CULVERTS
SHEET 2 OF 3
(FILL HEIGHTS FOR CONCRETE & CORRUGATED METAL PIPE)
NO SCALE
OCTOBER 24, 1998
NUMBER 10300

REVISION DATES

GEORGIA STANDARDS
SR 18 BRIDGE REPLACEMENT @ LONG CAME CREEK
TROUP COUNTY

Table with columns: CHECKED, BACKCHECKED, CORRECTED, VERIFIED, DATE, DRAWING No., 41-0002