



10/09/2020

PLUMBING FIXTURES

LEGEND		MOUNTING HEIGHT	SUPPLY			WASTE & VENT					FIXTURE		SUPPLY TRIM		SUPPLY/STOP		WASTE TRIM		RAP/FLOOR		MISC.		SEE FIXTURE SCHED NOTES		
MARK	DESCRIPTION		C.W.	H.W.	TEMPERED	FIX. OUTLET	TRAP	FIX. DRAIN	WASTE-MIN.	VENT-MIN.	INDIRECT	AIR GAP	AIR BREAK	MFR.	CAT. Nos.	MFR.	CAT. Nos.	MFR.	CAT. Nos.	MFR.	CAT. Nos.	MFR.		CAT. Nos.	
DF1	DRINKING FOUNTAIN/ WH/ BI-LEVEL/ ADA	27" TO BOTTOM OF LOW UNIT. 33 1/2" TO BOTTOM OF HIGH UNIT	1/2"			1-1/2"	1-1/2"	1-1/2"	1-1/2"	1-1/2"			H	116.662 AB.1	H	2167CC	E	2167CC	H	-	E	C8912CECO		1,3,5,13	
LV1	LAVATORY/ CT/ SO/ .5 GPM/ TMV/ ADA	34" TO RIM	1/2"	1/2"	1/2"	1-1/4"	1-1/2"	1-1/2"	1-1/2"	1-1/2"			A	116.662 AB.1	D	2165CCLK	E	2165CCLK	E	155AECO	E	8912CBECO		1,3,4,8,10,11	
LV2	LAVATORY/ WH/ SO/ .5 GPM/ TMV/ ADA	34" TO RIM	1/2"	1/2"	1/2"	1-1/4"	1-1/2"	1-1/2"	1-1/2"	1-1/2"			A	116.662 AB.1	D	2165CCLK	E	2165CCLK	E	155AECO	E	8912CBECO		1,3,4,8,10,11	
MB1	MOP BASIN/ FS/ 24"x24"x10" DEEP/ 2.0 GPM	42" TO FAUCET	1/2"	1/2"		3"	3"	3"	3"	1-1/2"			G	897-RCF	D	UNIT	D	UNIT	G	UNIT	-	ROUGH		2,6	
SK1	HAND WASHING SINK/ WH/ SS/ SO FAUCET/ 1.5 GPM/ TMV/ ADA	34" TO RIM	1/2"	1/2"	3/8"	1-1/4"	1-1/2"	1-1/2"	1-1/2"	1-1/2"			J	ELV2219SACC	K	-	E	2165CCLK	K	LK18	E	8912CBECO		1,3,4,10,11	
SK2	3 COMPARTMENT SINK/ FS/ SS/ 2.2 GPM/ TMV	-	1/2"	1/2"		-	-	-	-	-			J	MF3-2020-20L	D	445-DJ13ABCP	E	2165LK	-	-	-	-		12,14	
UR1	URINAL/ WH/ SO FV (BATTERY)/ 1.0 GPF/ ADA	17" TO LIP	3/4"			2"	INT	2"	2"	1-1/2"			A	6590.001	B	ROYAL 180 SMO-1.0-OR	B	-	A	-	A	-		1,3,13,15	
WB1	ICE MAKER OUTLET BOX/ 0.1 GPM	36" TO BOTTOM	1/2"										F	696-G1010MF	F	-	F	-	-	-	-	-			
WC1	WATER CLOSET/ WH/ SO FV (BATTERY)/ 1.6 GPF	15" TO RIM	1"			4"	INT	4"	4"	2"			A	2257.101	B	ROYAL 111 SMO-1.6-OR	B	-	A	-	A	-	C	1655SSCT	1,7,9
WC2	WATER CLOSET/ WH/ SO FV (BATTERY)/ 1.6 GPF/ ADA	17" TO RIM	1"			4"	INT	4"	4"	2"			A	2257.101	B	ROYAL 111 SMO-1.6-OR	B	-	A	-	A	-	C	1655SSCT	1,3,7,9,15

FIXTURE SCHEDULE NOTES:

1. VERIFY MOUNTING HEIGHT OF FIXTURE WITH ARCHITECTURAL PLANS PRIOR TO ROUGH-IN.
2. PROVIDE FIAT MODEL #832-AA HOSE AND BRACKET, FIAT MODEL #889-CC MOP BRACKET, FIAT MODEL #E-77-AA VINYL BUMPER GUARD, AND FIAT MODEL #MSG-11 WALL GUARDS. COORDINATE MOUNTING OF ACCESSORIES WITH ARCHITECT.
3. FIXTURE AND INSTALLATION SHALL CONFORM TO ADA REQUIREMENTS.
4. PROVIDE ASSE #1070 THERMOSTATIC MIXING VALVE SET TO DELIVER 105°F WATER TEMPERATURE.
5. PROVIDE OPTIONAL CANE APRON ELKAY #98324C FOR HIGH UNIT.
6. PROVIDE CHECK VALVES IN WATER SUPPLIES.
7. TOILET SEAT TO BE WHITE, COMMERCIAL GRADE, OPEN FRONT, ANTIMICROBIAL TYPE.
8. PROVIDE THRU WALL OR IN WALL BRACKET FOR CONCEALED ARM SUPPORT.
9. PROVIDE FOOT SUPPORT CARRIER WITH ADDITIONAL FOOT SUPPORT ROD LENGTH.
10. PROVIDE TRUEBRO #102 E-Z LAV GUARD.
11. COORDINATE ELECTRICAL REQUIREMENTS WITH ELECTRICAL CONTRACTOR.
12. EACH BASIN MUST INDEPENDENTLY AND DIRECTLY DRAIN TO FLOOR SINK PER NORTH CAROLINA PLUMBING CODE.
13. PROVIDE CHAIR CARRIER.
14. PROVIDE ASSE #1070 THERMOSTATIC MIXING VALVE SET TO DELIVER 115°F WATER TEMPERATURE.
15. FLUSH VALVE SENSORS FOR ADA FIXTURES ARE TO BE LOCATED ON THE ROOM WIDE AREA SIDE.

Order Plans @

WWW.LDILINE.COM

Lancaster County, South Carolina
Heath Springs Soccer Complex

200 Boyd Falls Road
Heath Springs, SC 29058

△ Revisions:

Proj. No.: 80703
Date: 10/09/2020

Sheet Name:
**PLUMBING
SCHEDULES**

P-601