

GENERAL NOTES:

- DIMENSIONS TO FLOOR DRAINS AND FLOOR SINKS ARE TO CENTER OF DRAINS, MEASURED FROM SUBSTRATE FACE OF EXTERIOR WALLS AND FACE OF STUD AT NEW INTERIOR WALLS.
- SEE 3/4"x10" FOR WALL BASE DETAILS.
- CONCRETE SLAB JOINT FILLER (EXPOSED CONCRETE AREAS); PROVIDE SEMI-RIGID POLYUREA JOINT FILLER AT ALL CONCRETE CONTROL JOINTS AND TOOLED JOINTS, SPAL PRO RS-88, COLOR: "TURKISH COFFEE"
- PROVIDE CONTINUOUS LATICRETE HYDRO BAN WATERPROOFING MEMBRANE UNDER ALL NEW TILE AREAS AND 12" UP WALL.
- SODA & BEER SLEEVES: PROVIDE GREY ELECTRICAL CONDUIT WITH FULL RADIUS SWEEPS WHERE SLEEVE COMES OUT OF FLOOR. SWEEPS TO BE COMPLETELY VERTICAL WHERE EXITING SLAB & CUT OFF 4" ABOVE SLAB. PLUMBER TO PROVIDE PVC CAP BEFORE LINES ARE PULLED SO THAT HOLES CAN BE CUT IN CAP AND LINES CAN BE PULLED THROUGH CAP AT INSTALL.
- FLOOR STAINING PROCESS:
 - APPLY (2) COATS AMERIPOLISH SURELOCK CONCRETE DYE, FOLLOW MFR. APPLICATION INSTRUCTIONS. REFER TO WEB LINK <http://www.ameripolish.com/TDS/AP-Surelock-TDS.pdf>
 - APPLY (2) COATS AMERIPOLISH SURELOCK STAIN PROTECTOR, FOLLOW MFR. APPLICATION INSTRUCTIONS. REFER TO WEB LINK <http://www.polishedconcretesolutions.com/template/images/msds/wb-stain-protector.pdf>


KEYNOTES:

- ALUMINUM THRESHOLD AT FLOOR TRANSITION.
- BEER SLEEVES: DASHED LINE INDICATES 6" UNDERSLAB SLEEVES FOR BEER LINES. SEE GENERAL NOTE #6.
- SODA SLEEVES: DASHED LINE INDICATES (1) 6" UNDERSLAB SLEEVE FOR SODA LINES. CONTROL POINTS INDICATE ROUTING TO AVOID COLUMN AND STAIR FOUNDATIONS. SEE GENERAL NOTE #6.
- FLOOR SINK, LOCATE AS DIMENSIONED.
- FLOOR DRAIN, LOCATE AS DIMENSIONED.
- FLOOR TRANSITION STRIP (TILE TO CONCRETE); SCHLUTER- RENO RAMP, "AERP 100 B65" (SATIN ANODIZED ALUMINUM).
- WALK-IN FREEZER BOX COMPARTMENT FURNISHED WITH INSULATED FLOOR. GC TO INSTALL KEC PROVIDED ALUMINUM DECKPLATE.
- 12" ALUMINUM DIAMOND PLATE THRESHOLD UNDER GARAGE DOOR. PROVIDE WITH "A" PROFILE, SEE 4 & 5/A410.
- CARPET TRANSITION STRIP: JOHNSONITE CTA-40-J (BLACK).
- 6" X 60" TRENCH DRAIN. SLOPE FLOOR 1/8"/FT TO DRAIN. ELEVATION OF DRAIN TO BE -3/32" AFF. LOCATE AS DIMENSIONED.
- 6" X 60" TRENCH DRAIN. SLOPE FLOOR 1/8"/FT TO DRAIN. ELEVATION OF DRAIN TO BE -3/8" AFF. LOCATE AS DIMENSIONED.
- LOCATE WATER LINE AS DIMENSIONED, SEE PLUMBING.

MATERIALS SCHEDULE SEE A600 FOR COMPLETE SCHEDULE

FINISH	DESCRIPTION	LOCATION	FINISH NO.	MFR	MFR NO.
BASE	QUARRY TILE BASE	KITCHEN	QB-1	DAL-TILE	-
	FLOOR TILE BASE	BAR	FB-1	DAL-TILE	STYLE: PAVER
	WOOD BASE	DINING/RESTROOMS	WB-1	CUSTOM	-
	METAL BASE	WALK-IN FREEZER	WB-4	SCHLUTER	DESIGNBASE-SL 3-1/8" TALL
CEILING	CEILING TILE	KITCHEN	ACT-1	USG	CLIMAPLUS #3260
	CEILING TILE	KITCHEN	ACT-2	USG	CLIMAPLUS #3270
FLOOR	SEALED CONCRETE	DINING	SC-1	-	-
	CARPET	DINING	CPT	TANDUS	STACK 9 04332
	QUARRY TILE	KITCHEN	QT-1	DAL-TILE	-
MILLWORK	BAR COUNTER	BAR	CTR-1	CUSTOM	-
	WAINSOT	DINING, RESTROOMS	PLAM-1	McNICHOLS	-
WALLS	WAINSOT	BAR	PLAM-2	-	-
	WOOD SIDING	BAR, DINING (SEE INTERIOR ELEVATIONS)	WW-1	-	-
	FIBERGLASS REINFORCED PLASTIC	KITCHEN	FRP-1	CRANE COMPOSITES	GLASBOARD-P (PIF)
MISC	FIBERGLASS REINFORCED PLASTIC	BAR AT BARTENDER SIDE ONLY	FRP-2	CRANE COMPOSITES	GLASBOARD-P (PIF)
	EXPANDED METAL	METAL SCREENS	MS-1	McNICHOLS	-
MISC	FABRIC	UPHOLSTERY, BOOTHS BACKS & SIDES	FAB1	KNOLL	ABACUS
	FABRIC	UPHOLSTERY, BOOTHS BACKS & SIDES	FAB2	ARCHITEX	SPRINKLE
	FABRIC	UPHOLSTERY, BOOTHS SEATS	FAB3	NASSIMI	CLASSIC

CONSULTANT:
JOHN SPONSELLER, ARCHITECT
 8025 W. 25TH PL.
 LAKEWOOD, CO 80214
 TEL: (303) 815-0161



GOOD TIMES RESTAURANTS, INC.
 141 Union Blvd., Suite 400
 Lakewood, CO 80228
 303-384-1430

BAD DADDY'S BURGER BAR "EASTCHASE"
 THE VENUE EASTCHASE
 NWC EASTCHASE PKWY & EASTCHASE LN.
 MONTGOMERY, AL 36117

Issue Record:
 4.23.2019 FOR PLAN REVIEW

Revisions:
 5.6.2019 WALK IN BOX
 7.1.2019 CANOPY REVS
 2.10.2021 TO GO REVS

Drawn:
DRAWN BY: JS, KC
 Checked:
CHECKED BY: JS
 Project No.
PROJECT#: 19-207

FLOOR FINISH PLAN

A125
 Date of Last Print:
 2.10.2021

1 FLOOR FINISH PLAN
 1/4" = 1'-0" NOTE: