

UTILITY LEGEND	
EX. OVERHEAD POWER	EX. SANITARY SEWER LINE (PER AS-BUILT INFO)
EX. OVERHEAD TELEPHONE	EX. STORM LINE (PER AS-BUILT INFO)
EX. OVERHEAD POWER/TELEPHONE	EX. SANITARY SEWER CLEANOUT (PER AS-BUILT INFO)
EX. UNDERGROUND TELEPHONE	EX. WATER VALVE (PER AS-BUILT INFO)
EX. UNDERGROUND POWER	P. WATER LINE
EX. SANITARY SEWER LINE	P. STORM LINE
EX. WATER LINE	EX. UNDERGROUND TELEPHONE
EX. GAS LINE	EX. SANITARY SEWER MANHOLE
EX. STORM LINE	EX. SANITARY SEWER GREASE TRAP
EX. SANITARY SEWER MANHOLE	EX. WATER VALVE
EX. SANITARY SEWER CLEANOUT	

STORM STRUCTURE TYPES:
 P.DI: PROPOSED GDOT STD. 1019A TYPE A
 EX.DI: EXISTING DROP INLET
 P.YI: PROPOSED GDOT STD. 1019A TYPE B
 P.STCO: PROPOSED STORM CLEANOUT

PIPE LEGEND:
 HOPE: HIGH-DENSITY POLYETHYLENE
 CMP: CORRUGATED METAL PIPE
 RCP: REINFORCED CONCRETE PIPE
 DIP: DUCTILE IRON PIPE

GENERAL GRADING NOTES:
 1. ALL CRITICAL SPOT GRADES ARE BOTTOM OF CURB ELEVATIONS UNLESS OTHERWISE SPECIFIED.
 2. NO SLOPES SHALL BE STEEPER THAN 2' HORIZONTAL TO 1' VERTICAL.
 3. VERTICAL DEPTH OF ALL DRY AND PRESSURIZED UTILITIES IS UNKNOWN. CONTRACTOR TO NOTIFY OWNER AND ENGINEER IMMEDIATELY IF ANY CONFLICTS ARE FOUND.
 4. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO ENSURE THAT THE BENCH MARKS AS SHOWN HAVE NOT BEEN DISTURBED FROM THEIR ORIGINAL POSITION AND ARE CHECKED AGAINST EXISTING FEATURE ELEVATIONS. IF A DISCREPANCY IS DISCOVERED, THE LAND SURVEYOR AND/OR ENGINEER SHOULD BE NOTIFIED IMMEDIATELY AND PRIOR TO GRADING ACTIVITIES.

SPOT ELEVATION LEGEND:
 FFE: FINISHED FLOOR ELEVATION
 TR: TOP OF RAMP
 BR: BOTTOM OF RAMP
 TS: TOP OF SIDEWALK
 TP: TOP OF PAVEMENT
 HP: HIGH POINT
 FOS: FINISHED GRADE ELEVATION
 TC: TOP OF CURB
 BC: BOTTOM OF CURB
 TW: TOP OF WALL ELEVATION AT EXISTING GRADE
 BW: BOTTOM OF WALL ELEVATION AT FINISHED GRADE
 EWI: ELEVATION OF SIDE WALL ELEVATION (AT FINISHED GRADE)
 BWO: BOTTOM OF SIDE WALL ELEVATION (AT FINISHED GRADE)

NOTE: SPOT ELEVATIONS ALONG WALL REPRESENT THE FINISHED GRADE ELEVATION ALONG THE FACE OF THE WALL, NOT THE ACTUAL BOTTOM OF THE WALL ELEVATION. THE CONTRACTOR SHOULD REFER TO THE WALL DESIGN PLANS, BY OTHERS, FOR TOP AND BOTTOM WALL ELEVATIONS DURING CONSTRUCTION.

STORMWATER MANAGEMENT NOTE:
 THE PROPOSED PROJECT LIES WITHIN THE SHOPS AT BELLS FERRY DEVELOPMENT. PER THE GRADING, PAVING AND DRAINAGE PLAN BY "DEVELOPMENT PLANNING & ENGINEERING, INC." DATED 09/15/2009; THE AREA WITHIN THE LIMITS OF THE PROJECT SITE SHOWN ON SHEET C-3.0 (0.98 ACRES OR 42,884 SF) WAS DESIGNED TO HAVE ±0.81 ACRES (±35,302 SF) OF IMPERVIOUS AREA & ±0.17 ACRES (±7,582 SF) OF PERVIOUS AREA. THE ACTUAL POST-DEVELOPED CONDITIONS FOR THE PROPOSED PROJECT WILL HAVE 0.77 ACRES (33,677 SF) OF IMPERVIOUS AREA & 0.21 ACRES (9,207 SF) OF PERVIOUS AREA. THE REDUCTION IN THE AMOUNT OF IMPERVIOUS AREAS (-0.04 ACRES) ALSO REDUCES THE RUNOFF CURVE NUMBER FROM 91 IN THE DESIGN TO 90 FOR THE PROPOSED PROJECT. THEREFORE, WATER QUALITY AND DETENTION ARE NOT REQUIRED FOR THIS PROJECT AT THIS TIME. ALL APPLICABLE STORMWATER MANAGEMENT WILL BE REQUIRED FOR ANY FUTURE DEVELOPMENT AT THIS SITE, INCLUDING THE AREA ALREADY URBANIZED. REFER TO THE HYDROLOGY REPORT FOR MORE INFORMATION.

NOTE: THE PROJECT LIMITS SHOWN HERE IS NOT THE PROJECT'S DISTURBED AREA. THE DISTURBED AREA FOR THE PROJECT IS 0.5 ACRES.



Rochester & Associates, Inc.
 425 Oak Street N.W. • Gainesville, Georgia 30601
 (770)718-0600 (770)718-9090 Fax • www.rochester-assoc.com

GRADING DETAIL FOR:
DOLLAR GENERAL WOODSTOCK
 LAND LOTS 882 & 883 OF THE 21ST STREET SECTION, CHEROKEE COUNTY, GEORGIA

NO.	DATE	DESCRIPTION	REVISIONS
A	2.11.2021	2ND - SUBMITTAL - COUNTY COMMENTS	

ANY CHANGES OR ALTERATIONS MADE TO THESE CONSTRUCTION DRAWINGS WITHOUT THE SIGNATURE OF THE DESIGNER SHALL BE VOID. THE SEAL SHOWING THE DESIGNER'S NAME AND LICENSE NUMBER WITH THIS PROJECT'S ORIGINAL DRAWINGS ARE KEPT ON FILE FOR VERIFICATION OF ANY CHANGES.

GRAPHIC SCALE: 0' 10' 20'

REGISTERED PROFESSIONAL ENGINEER
ALEN MARGAVICH
 2.11.2021

SHEET **C-3.2** OF **18**
 DATE: 12/30/2020
 SCALE: 1" = 10'
 JOB NO. 0215090.DWG
 DWG NO. 001.DWG
 DRAWN BY: PZL

GEORGIA811
 www.Georgia811.com

CHEROKEE COUNTY GRADING NOTES:

- THE ENTIRE STORMWATER MANAGEMENT SYSTEM, INCLUDING ALL CONVEYANCE, STORAGE, TREATMENT, FLOWRATES, ETC. WILL NEED TO BE ANALYZED BY A GEORGIA REGISTERED ENGINEER, USING AS-BUILT DATA PROVIDED BY A GEORGIA REGISTERED LAND SURVEYOR PRIOR TO SITE RELEASE/CERTIFICATE OF OCCUPANCY. CONTACT THE ENGINEERING DEPARTMENT AT 678-403-6074 OR BLMORGAN@CHEROKEEGA.COM FOR ADDITIONAL INFORMATION.
- A STORMWATER MAINTENANCE AGREEMENT IS REQUIRED FOR THIS PROJECT PRIOR TO THE FINAL PLAT SITE RELEASE/CERTIFICATE OF OCCUPANCY. A DRAFT COPY OF THE REQUIRED AGREEMENT CAN BE DOWNLOADED FROM: [HTTPS://WWW.CHEROKEEGA.COM/STORMWATER-MANAGEMENT_RESOURCES/DOCUMENT/MAINTENANCE_AGREEMENTUPDATED_7_20_2010.PDF](https://www.cherokeega.com/stormwater-management_resources/document/maintenance_agreementupdated_7_20_2010.pdf)
- THE STORMWATER MAINTENANCE AGREEMENT SHOULD BE SUBMITTED VIA E-MAIL OR ON CTTIVEW FOR PRELIMINARY REVIEW AND APPROVAL. PLEASE NOTE THAT EXHIBITS A, B, C, AND D MUST BE INCLUDED AND MUST BE CUSTOMIZED FOR THE PROJECT UNDER REVIEW. AFTER PRELIMINARY APPROVAL, THE ORIGINAL COMPLETE DOCUMENT SHOULD BE SUBMITTED TO THE ENGINEERING DEPARTMENT FOR SIGNATURE BY THE COUNTY ENGINEER AND NOTARIZED. THE AGREEMENT MUST THEN BE PICKED UP BY THE APPLICANT AND RECORDED WITH THE CHEROKEE COUNTY CLERK OF COURT (DEEDS AND RECORDS DEPARTMENT). DEEDS AND RECORDS ONLY ACCEPTS ORIGINAL DOCUMENTS WITH THE NOTARY SEAL, AND THEY MUST BE 8.5X11 OR 8.5X14. THE RECORDED DOCUMENT MUST BE RETURNED TO CHEROKEE COUNTY ENGINEERING DEPARTMENT PRIOR TO ISSUANCE OF A FINAL PLAT OR SITE RELEASE/CERTIFICATE OF OCCUPANCY.
- PER SECTION R401.3 OF THE 2012 INTERNATIONAL RESIDENTIAL CODE, THE ENTIRE LOT SHALL BE GRADED TO DRAIN SURFACE WATER AWAY FROM ALL FOUNDATION WALLS. THE GRADE SHALL FALL A MINIMUM OF 8 INCHES WITHIN THE FIRST 10 FEET, WHERE LOT LINES OR OTHER PHYSICAL BARRIERS PROHIBIT 8 INCHES OF FALL WITHIN 10 FEET. THE FINAL GRADE SHALL SLOPE AWAY FROM THE FOUNDATION AT A MINIMUM SLOPE OF 5 PERCENT AND THE WATER SHALL BE DIRECTED TO DRAINS OR SWALES TO ENSURE DRAINAGE AWAY FROM THE STRUCTURE. SWALES SHALL BE SLOPED AT A MINIMUM OF 2 PERCENT.
- IF UTILIZING INFILTRATION BMPs, A DENSE AND VIGOROUS VEGETATIVE COVER SHOULD BE ESTABLISHED OVER THE CONTRIBUTING PERVIOUS DRAINAGE AREAS BEFORE RUNOFF CAN BE ACCEPTED INTO THE FACILITY. OTHERWISE THE SEDIMENT FROM THE STORMWATER RUNOFF WILL CLOG THE PORES IN THE PLANTING MEDIA AND NATIVE SOILS.
- THERE ARE NO KNOWN WETLAND ON OR WITHIN 200' OF THE PROJECT'S DISTURBED AREA.
- THE HOMEOWNER'S ASSOCIATION IS RESPONSIBLE FOR THE MAINTENANCE OF ALL STORMWATER MANAGEMENT FACILITIES.
- THE PROPERTY OWNER WILL BE REQUIRED TO KEEP ALL DRAINAGE EASEMENTS OFF OF THE COUNTY RIGHT-OF-WAY FREE OF OBSTRUCTION IN SUCH A WAY AS TO ENSURE THE MAXIMUM DESIGNED FLOW AT ALL TIMES. THE PROPERTY OWNER SHALL NOT ALTER ANY DRAINAGE IMPROVEMENTS WITHOUT THE PRIOR WRITTEN APPROVAL FROM THE CHEROKEE COUNTY ENGINEERING DEPARTMENT.
- IT IS THE POLICY OF CHEROKEE COUNTY THAT DRAINAGE EASEMENTS ARE DEDICATED TO THE PUBLIC USE AND ARE NOT ACCEPTED BY CHEROKEE COUNTY FOR COUNTY MAINTENANCE AND ARE NOT CONSIDERED COUNTY PROPERTY. IT IS CHEROKEE COUNTY POLICY THAT NO COUNTY FORCES OR EQUIPMENT SHALL BE USED TO PERFORM CONSTRUCTION TO ANY DRAINAGE EASEMENT WITHIN CHEROKEE COUNTY, UNLESS SAID EASEMENT LIES WITHIN CHEROKEE COUNTY RIGHT-OF-WAY AND/OR SAID WORK IS NECESSARY TO PROTECT COUNTY RIGHT-OF-WAY PER POLICY ADOPTED JANUARY 14, 1997.
- CHEROKEE COUNTY SHALL NOT BE RESPONSIBLE FOR MAINTENANCE OF ANY PIPES, DITCHES, DETENTION PONDS, WATER QUALITY STRUCTURES, OR OTHER STRUCTURES WITHIN ANY DRAINAGE EASEMENT OUTSIDE THE COUNTY RIGHT-OF-WAY.