



ARCHITECTURAL GENERAL NOTES

1. PLAN DIMENSIONS SHOWN ARE TO FACE OF FRAMING MEMBERS, FACE OF MASONRY, FACE OF EXISTING WALL AND TO CENTERLINE OF COLUMNS.
2. ALL NOTES, DETAILS, AND FEATURES DRAWN AS APPLICABLE FOR ONE CONDITION ARE APPLICABLE TO SIMILAR CONDITIONS, WHETHER OR NOT SPECIFICALLY INDICATED.
3. LOCATE ALL INTERIOR DOOR FRAMES A DISTANCE OF 4" (FOUR) INCHES FROM THE THROAT RETURN TO THE CLOSEST ADJACENT PERPENDICULAR PARTITION, UON.
4. ALL ELEVATIONS ARE MEASURED FROM THE REFERENCE ELEVATION +0'-0", WHICH IS THE TOP OF THE FIRST FLOOR SLAB, UON.
5. DO NOT SCALE DRAWINGS TO DETERMINE DIMENSIONS OR SIZES OF BUILDING ELEMENTS.
6. ALL WOOD BLOCKING AND MISCELLANEOUS STEEL SHOWN IN DETAILS AND SECTIONS SHALL BE CONTINUOUS, UON.
7. USE FIRE-RETARDANT TREATED WOOD PRODUCTS FOR ALL CONCEALED WOOD BLOCKING, UON.
8. USE PRESERVATIVE-TREATED WOOD PRODUCTS FOR ALL WOOD BLOCKING IN CONTACT WITH EXTERIOR MASONRY OR CONCRETE WALLS, AND FOR ALL WOOD BLOCKING IN CONTACT WITH CONCRETE SLABS ON GRADE.
9. VERIFY ALL DIMENSIONS. BRING ANY DISCREPANCIES TO THE IMMEDIATE ATTENTION OF THE ARCHITECT.
10. PROVIDE WOOD OR METAL BLOCKING BEHIND GYPSUM BOARD AT THE FOLLOWING LOCATIONS:
 - A. ALL WALL-MOUNTED OR CEILING-MOUNTED DOOR STOPS, DOOR HOLD-OPEN DEVICES, AND OTHER HARDWARE.
 - B. ALL WALL-MOUNTED TOILET ACCESSORIES, AT GRAB BARS, PROVIDE BLOCKING CAPABLE OF RESISTING A MINIMUM LOAD OF 250 POUNDS APPLIED VERTICALLY OR HORIZONTALLY AT ANY POINT ON THE GRAB BAR.
 - C. ALL WALL-MOUNTED PLUMBING FIXTURES, INCLUDING BUT NOT LIMITED TO LAVATORIES, SINKS, URINALS, WATER CLOSETS, AND WATER COOLERS. PROVIDE BLOCKING CAPABLE OF RESISTING A MINIMUM LOAD OF 400 POUNDS APPLIED VERTICALLY AT ANY POINT ON THE PLUMBING FIXTURE.
 - D. ALL WALL-MOUNTED CABINETRY, SHELVING, AND SIMILAR ITEMS.
11. ALL MATERIALS USED IN THE PROJECT SHALL BE NEW AND PROVIDED BY THE CONTRACTOR, UON.
12. NOTIFY ARCHITECT OF ANY DISCREPANCY BETWEEN DRAWINGS, SPECIFICATIONS AND EXISTING CONDITIONS.
13. ALL NOTES, DETAILS, AND FEATURES DRAWN AS APPLICABLE FOR ONE CONDITION ARE APPLICABLE TO SIMILAR CONDITIONS, WHETHER OR NOT SPECIFICALLY INDICATED.

ARCHITECTURAL ABBREVIATIONS

&	AND	EA	EACH	KO	KICK OUT	SAFB	SOUND ATTENUATING FIRE BLANKETS
@	AT	EJ	EXPANSION JOINT	LE	LEAK	SF	SQUARE FEET
ACT	ACOUSTICAL CEILING TILE	ELEC	ELECTRIC	LEN	LENGTH	SIM	SIMILAR
ADJ	ADJUSTABLE, ADJUST	ELEV	ELEVATION	MTL	MATERIAL	SQ	SQUARE
AFF	ABOVE FINISH FLOOR	EOS	EDGE OF SLAB	MAX	MAXIMUM	SS	STAINLESS STEEL
AFS	ABOVE FINISH SLAB	EPS	EXPANDED POLYSTYRENE	MCH	MECHANICAL	STRUCT	STRUCTURAL
ALT	ALTERNATE	EQ	EQUAL	MFR	MANUFACTURER	STD	STANDARD
ALUM	ALUMINUM	EQUIP	EQUIPMENT	MIN	MINIMUM	STL	STEEL
APPROX	APPROXIMATE	EXIST	EXISTING	MISC	MISCELLANEOUS	SUSP	SUSPENDED
APC	ARCHITECTURAL PRECAST CONCRETE	EXP	EXPANSION / EXPANDED	MO	MASONRY OPENING	T & B	TOP & BOTTOM
BD	BOARD	EXT	EXTERIOR	MTG	MOUNTING	TD	TRENCH DRAIN
BLDG	BUILDING	FD	FLOOR DRAIN	MTL	METAL	THR	THRESHOLD
BLKG	BLOCKING	FEB	FIRE EXTINGUISHER BRACKET	NIC	NOT IN CONTRACT	TOC	TOP OF CONCRETE
BRG	BEARING	FEC	FIRE EXTINGUISHER CABINET	NO	NUMBER	TOW	TOP OF WALL
BUR	BUILT-UP ROOFING	FF	FINISH FLOOR	NOM	NOMINAL	TP	TOILET PARTITION
CL	CENTER LINE	FG	FIBERGLASS	NTS	NOT TO SCALE	TTL	TOTAL
CG	CORNER GUARD	FLR	FLOOR	OC	ON CENTER	UON	UNLESS OTHERWISE NOTED
CJ	CONTROL JOINT	FO	FACE OF	OD	OUTSIDE DIAMETER	VB	VINYL BASE
CLR	CLEAR	FRT	FIRE RETARDANT TREATED	OFCL	OWNER FURNISHED CONTRACTOR INSTALLED	VCT	VINYL COMPOSITION TILE
CLG	CEILING	GA	GAUGE	OFI	OWNER FURNISHED CONTRACTOR INSTALLED	VERT	VERTICAL
CMU	CONCRETE MASONRY UNIT	GALV	GALVANIZED	OFI	OWNER FURNISHED CONTRACTOR INSTALLED	VIF	VERIFY IN FIELD
CONC	CONCRETE	GC	GENERAL CONTRACTOR	OH	OPPOSITE HAND	VTR	VENT THRU ROOF
CONT	CONTINUOUS	GFRG	GLASS FIBER REINFORCED GYPSUM	OPNG	OPENING	W	WIDTH / WASHER
CT	CERAMIC TILE	GL	GLASS	OPP	OPPOSITE	WI	WITH
CT	CARPET	GWB	GYPSUM WALLBOARD	ORD	OVERFLOW ROOF DRAIN	W/O	WITHOUT
D	DEPTH / DRYER	GYP	GYPSUM	OTS	OPEN TO STRUCTURE	WC	WALLCOVERING
DBL	DOUBLE	HC	HANDICAPPED	PH	PANIC HARDWARE	WD	WOOD
DIA	DIAMETER	HDW	HARDWARE	PL	PLATE	WDW	WINDOW
DIA	DIAMETER	HWWD	HARDWOOD	PLM	PLASTIC LAMINATE	WO	WINDOW OPENING
DIAG	DIAGONAL	HM	HOLLOW METAL	PLYWD	PLYWOOD	WP	WORK POINT
DIM	DIMENSION	HORIZ	HORIZONTAL	PR	PAIR	WT	WEIGHT
DISP	DISPENSER	HT	HEIGHT	PTD	PAINTED	XPS	EXTRUDED POLYSTYRENE
DN	DOWN	HVAC	HEATING, VENTILATION, & AIR CONDITIONING	R	RADIUS		
DS	DOWNSPOUT	ID	INSIDE DIAMETER	RD	ROOF DRAIN		
DWG	DRAWING	INSUL	INSULATION	REF	REFRIGERATOR		
		INT	INTERIOR	REINF	REINFORCING		
		JT	JOINT	REQD	REQUIRED		
				RM	ROOM		
				RO	ROUGH OPENING		
				RWL	RAIN WATER LEADER		

MATERIAL LEGEND

	BRICK		INSULATION - RIGID
	CONCRETE		INSULATION - SPRAY FOAM
	CONCRETE MASONRY UNIT (CMU)		PLYWOOD / MDF
	EARTH		POROUS FILL
	GWB / PLASTER / GROUT / SPRAY FIREPROOFING		SPANDREL GLAZING
	INSULATION - BATT / LOOSE / BLANKET		WOOD BLOCKING / FRAMING - CONTINUOUS
	INSULATION - MINERAL WOOL		WOOD BLOCKING - INTERRUPTED

RATED PARTITION LEGEND

	ONE HALF HOUR FIRE RATING
	ONE HOUR FIRE RATING
	TWO HOUR FIRE RATING
	THREE HOUR FIRE RATING
	FOUR HOUR FIRE RATING
	SMOKE BARRIER (SB), SMOKE PARTITION (SP), OR PARTITION CAPABLE OF RESISTING THE PASSAGE OF SMOKE (S)

NOT ALL ABBREVIATIONS, SYMBOLS, AND LEGEND GRAPHICS LISTED ARE NECESSARILY USED ON THIS PROJECT. REFER TO DOCUMENTS FOR SPECIFIC INFORMATION.

RCP LEGEND

	SUPPLY GRILLE / RETURN GRILLE
	EXHAUST FAN
	LIGHT FIXTURE / EMERGENCY EGRESS LIGHT FIXTURE
	EXIT LIGHT / EXIT LIGHT W/ ARROW
	OCCUPANCY SENSOR
	CEILING MOUNTED RECEPTACLE
	CEILING MOUNTED SECURITY CAMERA
	SPRINKLER HEAD
	FIRE ALARM STROBE / FIRE ALARM HORN STROBE
	SMOKE DETECTOR
	SPEAKER / SPEAKER W/ STROBE
	CARBON MONOXIDE SENSOR
	HEAT SENSOR / PHOTO SENSOR
	EXPOSED CEILING
	CEILING HEIGHT
	ACCESS PANEL
	CEILING FAN
	2 x 2 ACOUSTICAL TILE LAY-IN CEILING
	GWB CEILING / SOFFIT
	METAL PANEL SOFFIT
	T&G WOOD CEILING

ARCHITECTURAL SYMBOLOGY

	NEW WORK KEYNOTE		DEMOLITION KEYNOTE
	WINDOW / LOUVER / CURTAIN WALL / STOREFRONT DESIGNATION		SPECIALTY ITEM DESIGNATION
	FLOOR DRAIN		REVISION TAG
	COLUMN GRID LINE		EXISTING COLUMN GRID LINE
	ROOM NAME / ROOM DESIGNATION		FIRST FLOOR ELEVATION DATUM
	DIRECTION OF SLOPE		ROOF SLOPE
	FIRE EXTINGUISHER CABINET		FIRE EXTINGUISHER BRACKET
	ACCESSIBLE BEDROOMS - MOBILITY FEATURES		ACCESSIBLE BEDROOMS - COMMUNICATION FEATURES
	ADJACENT AREA REFERENCE MATCHLINE		
	DETAIL, SECTION, ELEVATION TITLE		
	PLAN NORTH INDICATOR / TRUE NORTH INDICATOR		
	PLAN TITLE AND NORTH ARROW		
	DETAIL / ENLARGED PLAN		
	INTERIOR ELEVATION		
	EXTERIOR ELEVATION		
	BUILDING SECTION		
	DETAIL / WALL SECTION		
	DETAIL SECTION		
	DOOR NUMBER		
	PARTITION / WALL TYPE		

Order Plans

WWW.IDLINE.COM