


- FLOOR FRAMING PLAN NOTES:**
- FLOOR FRAMING SHALL BE AS FOLLOWS:
 - UNIT FLOOR FRAMING- SEE NOTES ON S4.1
 - BALCONY FRAMING- SEE NOTES ON S4.1
 - CORRIDOR, STORAGE, UTILITY ROOM & WALKWAY FLOOR FRAMING SHALL BE 18" DEEP PRE-ENGINEERED OPEN WEB TRUSSES @ 24" OC UNO
 - STAIR LANDING FRAMING SHALL BE AS FOLLOWS:
FLOOR LEVEL: 14" DEEP PRE-ENGINEERED OPEN WEB TRUSSES @ 24" OC
 - THE MIN NUMBER OF WALL STUDS AT BEARING POINTS SHALL BE (SEE BUILT-UP COL SCHEDULE ON S4.0 FOR ADD'L INFO).
BUILT-UP MULTI-PLY FLUSH BEAMS: SEE 13/S7.1 FOR ADDITIONAL INFORMATION (3 STUDS MIN)
GIRDER TRUSSES (GT): SHALL MATCH THE NUMBER OF PLYS OF THE GIRDER TRUSS (3 STUDS MIN) AND ON SEE JAMB/KING STUD SCHEDULE
 - THE CENTERLINE OF THE BEAM OR GT SHALL MATCH THE CENTERLINE OF THE SUPPORTING WALL STUDS.
 - ALL COL'S, INCLUDING STUD PARTS, MUST SIGN FLOOR TO FLOOR WITH SOLID BLOCKING OF THE SAME SECTION AND DIMENSIONS AS THE COL ABOVE, AT FLOOR CAVITY LOCATIONS. CONTINUE TO SUBSTRATE BEAM SUPPORT BELOW.
 - SEE S7.0 FOR ALLOWABLE PIPE & STUD PENETRATIONS.
 - SEE S7.0 FOR GENERAL SECTION OF SPRINKLER PIPE SUPPORT & METAL STAIR STRINGER CONNECTION
 - SEE ARCH DWGS FOR EXACT FINISHED FLOOR ELEVATIONS.
 - GENERAL NOTES FOR LUMBER SPECIES AND GRADE REQ'S.
SEE 18/S7.1 FOR ALL TRUSS TO BEAM CONNECTIONS.
ALL CONNECTOR TYPES REFER TO SIMPSON STRONG-TIE SPECIFICATIONS. SEE GENERAL NOTES FOR ADD'L INFO.
 - SEE S0.# SERIES FOR GENERAL NOTES
SEE S2.# SERIES FOR FLOOR FRAMING (STACK) PLANS
SEE S2.#X SERIES FOR FLOOR BRACING PLANS
SEE S3.# SERIES FOR ROOF FRAMING PLANS
SEE S4.0a-b FOR SHEARWALL/ANCHORAGE INFORMATION
SEE S4.0c FOR STUDWALL/BUILT UP COL SCHEDULE
SEE S4.# SERIES FOR INDIVIDUAL UNIT FRAMING WALLS
SEE S6.# SERIES FOR FOUNDATION/RETAINING WALL DETAILS
SEE S7.# SERIES FOR FLOOR FRAMING DETAILS
SEE S8.# SERIES FOR ROOF FRAMING DETAILS
SEE S9.# SERIES FOR MASONRY DETAILS
SEE S10.# SERIES FOR CLUB/FITNESS/VERANDA/
GARAGE/TRASH ENCLOSURE PLANS
SEE S10.#X SERIES FOR CLUB/FITNESS/VERANDA/
GARAGE/TRASH ENCLOSURE BRACING PLANS

- FLOOR FRAMING PLAN LEGEND**
- 210-2 INDICATES WOOD BEAM/HEADER DESIGNATION. SEE BEAM/HEADER SCHEDULE ON S4.0c FOR ADD'L INFO.
 - GT DENOTES GIRDER TRUSS LOCATION.
 - XXXXXX DENOTES CMU WALL. SEE GENERAL NOTES AND S9.1 FOR ADD'L INFO & DETAILS. SEE FDN PLAN FOR PLASTER DESIGNATIONS.
 - ⊗ DENOTES LOCATION OF MECH DUCT PENETRATION THRU CEILING. TRUSS SUPPLIER SHALL COORDINATE LOCATION OF TRUSSES W/PENETRATION. SEE ARCH DWGS FOR EXACT LOCATION.
 - 1-140 DENOTES UNIT STACK NUMBER. SEE S4.1 FOR ADD'L INFO.
 - BLDG NO. UNIT STACK NO.
 - DENOTES FLUSH BEAM WITH BOTTOM OF BEAM AT FLOOR TRUSS BEARING.
 - DENOTES HEADER WITHIN WALL FRAMING ABOVE OPENING
 - ⊥ DENOTES END OF MEMBER SUPPORTED BY A PRE-FAB METAL HANGER:
-FOR ALL FIREWALL HANGERS SEE NOTE 10 ON SHEET S0.1.
-FOR ALL TRUSS TO BEAM CONNECTIONS PROVIDE A TRUSS SERIES HANGER.
-ALL TRUSS TO TRUSS CONNECTIONS TO BE PROVIDED BY TRUSS SUPPLIER.

1
S2.1g
BUILDING 1 - 2nd FLOOR FRAMING PLAN
SCALE: 3/32" = 1'-0"



Project: 1928.00
CADD File:
Drawn By: AVG
Checked By: TQ
Permit Release:
May 15, 2020
Construction Release Set:
May 15, 2020
Revisions
No. Date Description

ASI / RFI Revisions
No. Date Description

Borough 33
an Apartment Community by
33 Broad MF, LLC
in Chattanooga, Tennessee

Drawing Title:
BUILDING 1 - 2nd
FLOOR FRAMING PLAN

S2.1a

ISSUED FOR CONSTRUCTION